

innova

simplicity



Split-System column

CCE

compact

Heat pump



R407C fluid



aesthetic



Airwell
Air Conditioning

The CCE 45 Split-System column is available in Heat pump version. The three-phase, 15,000 W capacity CCE 45RC is particularly suited for the air conditioning needs of tertiary premises such as offices, shops and restaurants. With its reduced footprint, clean lines and simplicity of use thanks to a control panel equipped with an LCD display, this product provides high levels of user comfort as well as being extremely easy to install.

- Scroll compressor.
- Multiple connection possibilities (left/right/rear/front) for easy installation and maintenance.
- High efficiency filtration system and ioniser as standard equipment for improved air quality.
- Equipped with a motorised vertical sweeping flap to provide evenly distributed blown air.
- Microprocessor management.
- Electronic regulation and programming.

Multi-function control panel

- Automatic Cooling/Heating regulation.
- 3 ventilation (FAN) speeds.
- Automatic ventilation.
- Night running (SLEEP).
- Dehumidification mode.
- Programming (TIMER).
- LCD display.



CCE 45 SERIES



Indoor Units

Heating capacity

Power input

kW

kW

15

4,57

Cooling capacity

Power input

Airflow (HS)

Acoustic power (min/max)

Dimensions (WxDxH)

Weight

kW

kW

m³/h

dB(A)

mm

kg

12,9

4,82

2 000

52/56

600x370x1900

70

Outdoor Units

Compressor type

Refrigerant

Operating limits Winter/Summer

Acoustic power

Weight

Dimensions (WxDxH)

dB(A)

kg

mm

GC 45 RC

Scroll

R407C

- 9°C/+ 43°C

69

95

900x340x970

Power supply 3N~400 V - 50 Hz

Fuse rating am

Power cable section (without heating)

Power supply side

Max. length/Max. height

Liquid pipe/Suction pipe

Electrical connections Ind./Out.

A

mm²

m

Inchs

mm²

10

5x1,5

Outdoor

40/20

3/8"-3/4"

6x1,5

(1) Nominal heating capacity: International conditions 20°C/12°C wet bulb – Outside air temperature: 7°C/6°C wet bulb.

(2) Nominal cooling capacity: International conditions (NF EN 255.2 / 814.2 standards) - 27°C/19°C wet bulb – Outside air temperature: 35°C/24°C wet bulb.



ACE
Marketing

ACE - 1 bis, av. du 8 mai 1945 - Saint-Quentin-en-Yvelines
F - 78284 Guyancourt Cedex
Fax : +33 (0) 1 39 44 11 55 - Tel. : +33 (0) 1 39 44 78 00
www.airwell.com



Your approved **Airwell**

