

DESCRIPTION

THE LVD-218 SERIES DLVA'S ARE AVAILABLE IN EXTENDED 70/75dB AND STANDARD 50dB DYNAMIC RANGE OVER THE FULL 2-18 GHz BANDWIDTH, WITH TRUE DC COUPLING. UNITS EMPLOY PLANAR DIODE DETECTORS AND INTEGRATED VIDEO CIRCUITRY FOR HIGH SPEED PERFORMANCE AND OUTSTANDING RELIABILITY. THE DLVA'S ARE OF SUPERIOR CONSTRUCTION USING STATE-OF-THE-ART MIC/MMIC TECHNOLOGY. THE SIZE IS 3.0" x 3.5" x 0.5".

FEATURES

- TRULY DC COUPLED
- WIDE BANDWIDTHS
- FAST RISE TIMES
- SHORT RECOVERY TIMES
- SUPERIOR ACCURACY
- EXTENDED DYNAMIC RANGE CAPABILITY
- MINIATURE SIZE
- 7.2 OZ WEIGHT

SPECIFICATIONS


- FREQUENCY RANGE 6 TO 18 GHz
- FREQUENCY FLATNESS ± 1.75 dB (± 1.5 dB TYPICAL)
- TSS -70dBm (-72dBm TYPICAL)
- VSWR 2.5:1
- DYNAMIC RANGE 80dB
- LOGGING RANGE -70 TO +10dBm
- LOG LINEARITY ± 1.75 dB (± 1.5 dB TYPICAL)
- LOG SLOPE 50mV/dB OR AS DESIRED
- LOG SLOPE ACCURACY $\pm 5\%$ MAXIMUM OF AVERAGE SLOPE
- LOG TEMPERATURE STABILITY ± 1.75 dB (± 1.5 dB TYPICAL)
- RISE TIME 30nS MAXIMUM, 20nS TYPICAL
- RECOVERY TIME 200nS TYPICAL, 300nS MAXIMUM
- VIDEO LOAD 50 OHMS (MINIMUM), OR AS DESIRED
- DC POWER (NO LOAD)
 - +V 9 TO 18V @ 350mA
 - V 9 TO 18V @ 200mA MAXIMUM
- SIZE 3.00" x 3.5" x 0.5"

AVAILABLE OPTIONS (SPECIFY)

- A01 EXTENDED 0.2 TO 20 GHz RF FREQUENCY RANGE
- A02 EXTENDED 0.5 TO 18 GHz RF FREQUENCY RANGE
- A03 FASTER RISE/RECOVERY TIMES
- A04 ALTERNATE LOG SLOPES
- A05 HIGH POWER RF CW/PEAK PROTECTION
- A06 EXTENDED LOGGING RANGE
- A07 OTHER VIDEO LOADS

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A	ORIGINAL RELEASE	11/22/92	<i>Jay</i>


MECHANICAL OUTLINE



- NOTES:
- 1) DIMENSIONS ARE IN INCHES
 - 2) TOLERANCES: X.XX ± 0.020
X.XXX ± 0.010
 - 3) WEIGHT: 7.2 OZ
 - 4) UNIT IS EPOXY SEALED

ENVIRONMENTAL RATINGS

- TEMPERATURE -54°C TO +85°C (OPERATING)
-65°C TO +100°C (STORAGE)
- HUMIDITY MIL-STD-202F, METHOD 103B COND. B
- SHOCK MIL-STD-202F, METHOD 213B COND. B
- VIBRATION MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE MIL-STD-202F, METHOD 107D COND. A

		AMERICAN MICROWAVE CORPORATION 7311G GROVE RD., FREDERICK, MD. 21701 TEL: (301) 662-4700 FAX: (301) 662-4938	
		PRODUCT FEATURE LVD-218-70/75 (OPTION 618) 6 TO 18 GHz, 70/75dB, TRULY DC-COUPLED DETECTOR LOG VIDEO AMPLIFIER	
APPROVALS DRAWN <i>Red</i> CHECKED <i>Me...</i>	DATE 11/22/92		