

SPECIFICATIONS:

- FREQUENCY: 0.5 GHz TO 18 GHz
- INSERTION LOSS: REFLECTIVE: 3.25db
ABSORPTIVE: 4.0db
- ISOLATION: 0.5 GHz TO 2 GHz: 60db
2 GHz TO 18 GHz: 70db
- VSWR: REFLECTIVE IN/OUT: 2.0:1
ABSORPTIVE IN/OUT: 2.0:1
ABSORPTIVE OUT/OFF: 2.0:1
- SPEED: RISE: 10ns TYPICAL, 15ns MAX.
FALL: 10ns TYPICAL, 15ns MAX.
DELAY ON: 75ns TYPICAL, 100ns MAX.
DELAY OFF: 75ns TYPICAL, 100ns MAX.
- POWER INPUT: (CW)+20dBm (STANDARD), +10 dBm (HIGH SPEED)
- SURVIVAL POWER: 1 WATT CW, 10 WATTS PEAK 1 usec
- CONTROL: TTL LOGIC "0"=ON "1"=OFF
- POWER SUPPLY: +5V @ 250 mA MAX.
-5V @ 75mA MAX.(REFLECTIVE)
100mA MAX.(ABSORPTIVE/NON-REFLECTIVE)

OPTIONS:

- INDEPENDENT CONTROL WITH SOLDER PIN STANDARD
- DEC-MP: 3 BIT DECODER WITH MULTIPIN
 - DEC-SP: 3 BIT DECODER WITH SOLDER PIN
 - MP-IND: INDEPENDENT CONTROL WITH MULTIPIN
 - 10M18: 10 MHz TO 18 GHz (INSERTION LOSS INCREASES BY 1.5db AT 10 MHz AND 0.5db AT 18 GHz)
 - 100M18: 100 MHz TO 18 GHz (INSERTION LOSS INCREASES BY 1.5db AT 100 MHz AND 0.5db AT 18 GHz)
 - 118: 1 GHz TO 18 GHz (NO CHANGE IN INSERTION LOSS)
 - 218: 2 GHz TO 18 GHz (NO CHANGE IN INSERTION LOSS)
 - 412: 4 GHz TO 12.4 GHz (NO CHANGE IN INSERTION LOSS)
 - 618: 6 GHz TO 18 GHz (NO CHANGE IN INSERTION LOSS)
 - 1218: 12 GHz TO 18 GHz (NO CHANGE IN INSERTION LOSS)
 - 100M20: 100 MHz TO 20 GHz (INSERTION LOSS INCREASES BY 1.5db AT 100 MHz AND 1.0db AT 20 GHz)
 - 220: 2 GHz TO 20 GHz (INSERTION LOSS INCREASES BY 1.0db AT 20 GHz)
 - 1020: 10 GHz TO 20 GHz (INSERTION LOSS INCREASES BY 1.0db AT 20 GHz)
 - B01: -12V POWER SUPPLIES
 - B02: -15V POWER SUPPLIES
 - B03: REVERSE LOGIC "1"=ON "0"=OFF
 - B04: DRIVERLESS, CURRENT CONTROLLED
 - B05: HIGH SPEED, TURNON/TURNOFF 25 nsec MAXIMUM WHEN APPLICABLE
 - B06: HIGH POWER - SPECIFY CW POWER, PEAK POWER, PULSE WIDTH, DUTY CYCLE, RF FREQUENCY AND BANDWIDTH
 - B07: CUSTOM DESIGNED PRODUCT- SPECIFY INITIALS OF CUSTOMER
 - B08: LOW VIDEO TRANSIENTS - SPECIFY VIDEO BANDWIDTH
 - B09: LOW INSERTION LOSS VERSION
 - B10: HIGHER ISOLATION VERSION

ENVIRONMENTAL RATINGS:

- TEMPERATURE: -55°C TO +85°C (OPERATING)
-65°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107D COND. A


NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS ARE IN INCHES

TOLERANCES:

- X.XX ±0.020
- X.XXX ±0.010

| REVISIONS | | | | |
|-----------|------|------------------|---------|----------|
| ZONE | REV. | DESCRIPTION | DATE | APPROVED |
| | | ORIGINAL RELEASE | 1/25/98 | |



NOTE:
DR=WITH DRIVER, REFLECTIVE
DT=WITH DRIVER, NON-REFLECTIVE/ABSORPTIVE

| | | | | |
|-----------|----------|---|------|--|
| PART NO. | | AMERICAN MICROWAVE CORPORATION FREDERICK, MARYLAND | | |
| APPROVALS | DATE | TITLE | | |
| DRAWN | 1/25/98 | OUTLINE DRAWING | | |
| CHECKED | 1/28/98 | MSNC-5DR/DT-04T-STANDARD | | |
| ISSUED | | REFLECTIVE OR NON-REFLECTIVE/ABSORPTIVE SOLID STATE SWITCH | | |
| SIZE | FSCM NO. | DWG NO. | REV. | |
| A | 60483 | 100-4303-1 | | |
| SCALE N/S | | SHEET 1 of 1 | | |