

**SPECIFICATIONS: SURFACE MOUNT - LOW WEIGHT**

- FREQUENCY: ..... 0.5 GHz TO 18 GHz
- INSERTION LOSS: ..... REFLECTIVE: 3.0db  
ABSORPTIVE: 3.5db
- ISOLATION: ..... 0.5 GHz TO 2 GHz: 60db  
2 GHz TO 18 GHz: 70db
- VSWR: ..... REFLECTIVE IN/OUT: 2.0:1  
ABSORPTIVE IN/OUT: 2.0:1  
ABSORPTIVE OUT/OFF: 2.0:1
- SPEED: ..... RISE: 10ns TYPICAL, 15ns MAX.  
FALL: 10ns TYPICAL, 15ns MAX.  
DELAY ON: 75ns TYPICAL, 100ns MAX.  
DELAY OFF: 75ns TYPICAL, 100ns MAX.
- POWER INPUT: ..... (CW)+20dBm (STANDARD), +10 dBm (HIGH SPEED)
- SURVIVAL POWER: ..... 1 WATT CW, 10 WATTS PEAK 1 usec
- CONTROL: ..... TTL LOGIC "0"=ON "1"=OFF
- WEIGHT: ..... 0.9 OUNCE
- POWER SUPPLY: ..... +5V @ 400 mA MAX.  
-5V @ 75mA MAX.(RELECTIVE)  
100mA MAX.(ABSORPTIVE/NON-REFLECTIVE)

**OPTIONS:**

- INDEPENDENT CONTROL WITH SOLDER PIN STANDARD
- DEC-SP ..... 3 BIT DECODER WITH SOLDER PIN
  - 10M18 ..... 10 MHz TO 18 GHz (INSERTION LOSS INCREASES BY 1.5db AT 10 MHz AND 0.5db AT 18 GHz)
  - 100M18 ..... 100 MHz TO 18 GHz (INSERTION LOSS INCREASES BY 1.5db AT 100 MHz AND 0.5db AT 18 GHz)
  - 118 ..... 1 GHz TO 18 GHz (NO CHANGE IN INSERTION LOSS)
  - 218 ..... 2 GHz TO 18 GHz (NO CHANGE IN INSERTION LOSS)
  - 412 ..... 4 GHz TO 12.4 GHz (NO CHANGE IN INSERTION LOSS)
  - 618 ..... 6 GHz TO 18 GHz (NO CHANGE IN INSERTION LOSS)
  - 1218 ..... 12 GHz TO 18 GHz (NO CHANGE IN INSERTION LOSS)
  - 100M20 ..... 100 MHz TO 20 GHz (INSERTION LOSS INCREASES BY 1.5db AT 100 MHz AND 1.0db AT 20 GHz)
  - 220 ..... 2 GHz TO 20 GHz (INSERTION LOSS INCREASES BY 1.0db AT 20 GHz)
  - 1020 ..... 10 GHz TO 20 GHz (INSERTION LOSS INCREASES BY 1.0db AT 20 GHz)
  - B01 ..... -12V POWER SUPPLIES
  - B02 ..... -15V POWER SUPPLIES
  - B03 ..... REVERSE LOGIC "1"=ON "0"=OFF
  - B04 ..... DRIVERLESS, CURRENT CONTROLLED
  - B05 ..... HIGH SPEED, TURNON/TURNOFF 25 nsec MAXIMUM WHEN APPLICABLE
  - B06 ..... HIGH POWER - SPECIFY CW POWER, PEAK POWER, PULSE WIDTH, DUTY CYCLE, RF FREQUENCY AND BANDWIDTH
  - B07 ..... CUSTOM DESIGNED PRODUCT- SPECIFY INITIALS OF CUSTOMER
  - B08 ..... LOW VIDEO TRANSIENTS - SPECIFY VIDEO BANDWIDTH
  - B09 ..... LOW INSERTION LOSS VERSION
  - B10 ..... HIGHER ISOLATION VERSION

**ENVIRONMENTAL RATINGS:**


- TEMPERATURE: ..... -55°C TO +85°C (OPERATING)  
-65°C TO +125°C (STORAGE)
- HUMIDITY: ..... MIL-STD-202F, METHOD 103B COND. B
- SHOCK: ..... MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: ..... MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: ..... MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: ..... MIL-STD-202F, METHOD 107D COND. A

ALL DIMENSIONS ARE IN INCHES

TOLERANCES:  
X.XX ±0.020  
X.XXX ±0.010

NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

REVISIONS			DATE	APPROVED
ZONE	REV.	DESCRIPTION		
	A	ORIGINAL RELEASE	7/28/97	



NOTE:

- DR=WITH DRIVER, REFLECTIVE
- DT=WITH DRIVER, NON-REFLECTIVE/ABSORPTIVE

PART NO.		AMERICAN MICROWAVE CORPORATION FREDERICK, MARYLAND	
APPROVALS	DATE	TITLE	
DRYAN	7/28/97	OUTLINE DRAWING	
CHECKED <i>L. Apple</i>	8/26/97	SMS-8DR/DT-025-STANDARD	
ISSUED		REFLECTIVE OR NON-REFLECTIVE/ABSORPTIVE	
		SURFACE MOUNT, SOLID STATE SWITCH	
SIZE	FSCM NO.	DWG NO.	REV.
A	60483	100-4198-1	A
SCALE	SHEET		1 of 1