

TIF8900

COMBUSTIBLE GAS DETECTOR



Features:

- Solid state sensor technology, long life and precision
- Broad band of combustible gas detection
- Sensitivity as low as 5 ppm
- Adjustable sensitivity
- Audible "Geiger counter" signal
- LED Leak Intensity Lights
- Automatic warm up
- Cordless operation
- Flexible 16" stainless probe for hard to reach places
- Rechargeable battery and charger included
- Rugged custom carrying case
- Made in the USA

Applications:

TIF8900 is the perfect tool to be used in a situation where a combustible gas, vapor or residue needs to be found.

- Gas lines and Pipes
- Exhaust and Fuel leaks
- Propane filling stations
- Fuel in marine bilges
- Heat Exchanger leaks
- Check manholes for safety
- Detect arson residue
- IAQ tests
- Liquid or gas fired heating systems



Engineered for Success



TIF8900

COMBUSTIBLE GAS DETECTOR



Voltage (Charger)	115V, 60Hz
Probe Length	15" (38cm)
Power Supply	(Two) 2.4V Ni-Cad Batteries
Battery Life	4 Hours/Charge
Operating Time	Instantaneous
Warm-up Time	30 seconds

Partial List of Detectable Compounds

Compound	Min. detectable concentration	Compound	Min. detectable concentration	
Acetylene	50 ppm	Methyl Chloride	5 ppm	
Iso-Butane (R600a)	500 ppm	Hydrogen Sulfide	5 ppm	
Methane	500 ppm	Acetone	50 ppm	
Ethane (R170)	500 ppm	Methanol	50 ppm	
Propane (R290)	500 ppm	Ammonia (R717)	20 ppm	
Ethylene	500 ppm	Gasoline	1 ppm	
Hydrogen	500 ppm	Chlorine	1 ppm	
Methyl Ether	500 ppm			
Vinyl Chloride	5 ppm			

Optional Accessories

Part Number

Cigarette lighter charger

TIF8805

Replacement Parts (supplied with product)	Part Number
Sensor	TIF8801
Rechargeable Ni-Cad batteries (2 each)	TIF8806A
115V battery charger	TIF8803A
220V battery charger	TIF8806B
Carrying Case	ATP-7038
Battery Cover	527690RED



TIF8805 12V Charger



TIF8806A: Ni-Cad Battery



ATP-7038: Carrying case



527690RED Battery cover



COMBUSTIBLE GAS DETECTOR

TIF8900





Miramar, Florida Ph: 954-499-5400 • Fax: 954-499-5418 • Toll Free: 1-800-327-5060 www.TIF.com