

Option Selection Guide

Notes: S= Standard	Model and Option Numbers												
	1073	1083	1084			1088	1092			1093			1094
Option Description	A	B	A	B	C	B	A	B	C	A	B	C	B
I/O													
Four Additional Configurable Outputs			03	03	03	03				03	03	03	
Parallel BCD Output			06	06	06	04							
BCD with Second RS-232 Port			17	17	17	17							
Second RS-232 Port			19	19	19	17A	19	19	19	19	19	19	S
Self-Monitor, IRIG-B Distribution System and Second RS-232 Port						18							
Out-of-Lock Relay 1 Form C (SPDT)			S	S	S	19	93	93	93	93	93	93	S
Fiber-Optic Output			20	20	20								
Four Configurable Fiber-Optic Outputs			20A	20A	20A	20A				20A	20A	20A	
COMTRADE Sample Rate Generator			23	23	23	23							
Frequency Measurement Capability		09											
Sine Wave Outputs (1M, 5M, 10M Hz)		xy											
8-Channel High-Drive IRIG-B Output			27	27	27	27				27	27	27	
Power System Time, Frequency and Phase Monitor			28	28	28	28				28	28	28	
Four Additional Outputs with Dry Contact and +25/50 Vdc			29	29	29	29				29	29	29	
Internal Network Time Protocol (NTP) Server			32	32	32	32				32	32	32	
IRIG-B Modulated Output			S	S	S	S	92	92	92	92	92	92	S
RS-422/485 Driver			S	S	S		94	94	94	94	94	94	S
Fiber-Optic Input	01												
Power													
Terminal Power Strip						07							
10 to 60 Vdc with Terminal Power Strip						08							
Surge Withstand & Terminal Strip (125 Vdc)						15A							
Surge Withstand & Terminal Strip (250 Vdc)						15B							
IEC-320 Power Inlet, 85 to 264 Vac, 110 to 275 Vdc	07	S	07	07	07	S				07	07	07	07
10 to 60 Vdc Power, Terminal Strip, Surge Withstand Capability	08		08	08	08					08	08	08	08
85 to 264 Vac, 110 to 275 Vdc Power Strip, SWC	10		10	10	10					10	10	10	10
Oscillator and Timing													
OCXO and 4 Additional Configurable Outputs						12							
General													
LCD Backlight				01	01	01		01			01	01	S
GPS Data Backup Battery		S	S	S	S	S	S	S	S	S	S	S	S
On/Off Switch	04		04	04		S				04	04		S
CE Mark/Label	S	S	S	S	S	S	S	S	S	S	S	S	S