



AVTECH ELECTROSYSTEMS LTD.

NANOSECOND WAVEFORM ELECTRONICS
SINCE 1975

P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-226-5772 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-226-2802 (Intl)

info@avtechpulse.com - <http://www.avtechpulse.com/>

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4

INSTRUCTIONS

MODEL AV-CTLX

TEST LOAD ADAPTER

FOR USE WITH AV-CLZ CABLES

SERIAL NUMBER: _____

WARRANTY

Avtech Electrosystems Ltd. warrants products of its manufacture to be free from defects in material and workmanship under conditions of normal use. If, within one year after delivery to the original owner, and after prepaid return by the original owner, this Avtech product is found to be defective, Avtech shall at its option repair or replace said defective item. This warranty does not apply to units which have been disassembled, modified or subjected to conditions exceeding the applicable specifications or ratings. This warranty is the extent of the obligation assumed by Avtech with respect to this product and no other warranty or guarantee is either expressed or implied.

TECHNICAL SUPPORT

Phone: 888-670-8729 (USA & Canada) or +1-613-226-5772 (Intl)

Fax: 800-561-1970 (USA & Canada) or +1-613-226-2802 (Intl)

E-mail: info@avtechpulse.com

World Wide Web: <http://www.avtechpulse.com>

TABLE OF CONTENTS

WARRANTY..... 2

TECHNICAL SUPPORT..... 2

TABLE OF CONTENTS..... 3

INTRODUCTION..... 4

SPECIFICATIONS..... 5

BASIC USAGE..... 6

Manual Reference: Z:\officefiles\instructword\lav-ctl\lav-ctlx,edition2.odt.
Last modified October 23, 2006.
Copyright © 2006 Avtech Electrosystems Ltd, All Rights Reserved.

INTRODUCTION

The AV-CTLX test load adapter allows a user to connect a soldered load to the end of a user-supplied AV-CLZ-type cable, which is used with a variety of Avtech pulse generators.

The AV-CTLX test load adapter consists of a female DB-37 connector to which a small circuit board (8 x 50 mm x 1/16") is soldered. Pins 1-19 of the connector are soldered to the top side of the board, and pins 20-37 are soldered to the bottom side.

The DB-37 connector will mate to the end of a user-supplied AV-CLZ-type cable. The user may solder a load between the two sides of the 8 x 50 mm circuit board, as desired.

The -ENC option provides an aluminum enclosure to surround the load devices, for safety purposes. This option is recommended when high voltages will be present on the load.

This adapter is intended for use in research, development, test and calibration laboratories by qualified personnel.

SPECIFICATIONS

Model:	AV-CTLX
Load resistance:	Open circuit (as supplied by factory). The user may install the desired resistance by soldering to the output circuit board.
Max. pulse current:	100A
Rise time:	< 5 ns
Maximum voltage:	Standard (open construction): 55V. With -ENC option (enclosed): 110V.
Connector:	DB-37 female. Pins 1-19 = signal, pins 20-37 = ground.
Temperature range:	+5°C to +40°C

BASIC USAGE

The basic mechanical connection scheme for the AV-CTLX is shown below:

