

# Test report

**322811-2TRFWL**

Date of issue: March 22, 2018

Applicant:

**Barrett Communications Pty Ltd**

Product:

**Barrett 4050 HF Transceiver**

Model:

**4050**

FCC ID:

**OW4-4050HF**

Specifications:

**FCC 47 CFR Part 87**

Aviation Services

#### Test location

---

Company name	Nemko Canada Inc.
Address	303 River Road
City	Ottawa
Province	Ontario
Postal code	K1V 1H2
Country	Canada
Telephone	+1 613 737 9680
Facsimile	+1 613 737 9691
Toll free	+1 800 563 6336
Website	www.nemko.com
Site number	FCC: CA2040; IC: 2040A-4 (3 m SAC)

Tested by	Kevin Rose, Wireless/EMC Specialist
Reviewed by	Andrey Adelberg, Senior Wireless/EMC Specialist
Date	March 22, 2018
Signature	

#### Limits of responsibility

---

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contain in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

#### Copyright notification

---

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.  
© Nemko Canada Inc.

## Table of contents

<b>Table of contents</b> .....	<b>3</b>
<b>Section 1. Report summary</b> .....	<b>4</b>
1.1 Applicant and manufacturer .....	4
1.2 Test specifications .....	4
1.3 Statement of compliance .....	4
1.4 Exclusions .....	4
1.5 Test report revision history .....	4
<b>Section 2. Summary of test results</b> .....	<b>5</b>
2.1 FCC Part 87 test results .....	5
<b>Section 3. Equipment under test (EUT) details</b> .....	<b>6</b>
3.1 Sample information .....	6
3.2 EUT information .....	6
3.3 Technical information .....	6
3.4 Product description and theory of operation .....	6
3.5 EUT exercise details .....	6
3.6 EUT setup diagram .....	7
3.7 EUT sub assemblies .....	7
<b>Section 4. Engineering considerations</b> .....	<b>8</b>
4.1 Modifications incorporated in the EUT .....	8
4.2 Technical judgment .....	8
4.3 Deviations from laboratory tests procedures .....	8
<b>Section 5. Test conditions</b> .....	<b>9</b>
5.1 Atmospheric conditions .....	9
5.2 Power supply range .....	9
<b>Section 6. Measurement uncertainty</b> .....	<b>10</b>
6.1 Uncertainty of measurement .....	10
<b>Section 7. Test equipment</b> .....	<b>11</b>
7.1 Test equipment list .....	11
<b>Section 8. Testing data</b> .....	<b>12</b>
8.1 FCC 87.131 Power and emissions .....	12
8.2 FCC 2.1047 Modulation characteristics .....	14
8.3 FCC 87.139(c) Emission limits, emission mask, bandwidth .....	17
8.4 FCC 87.141(d) Modulation requirements .....	21
8.5 FCC 87.139(c) Emission limits, conducted method .....	25
8.6 FCC 87.139(c) Emission limits, radiated method .....	29
8.7 FCC 87.133 Frequency stability .....	33
<b>Section 9. Block diagrams of test set-ups</b> .....	<b>34</b>
9.1 Radiated emissions set-up for frequencies below 1 GHz .....	34
9.2 Radiated emissions set-up for frequencies above 1 GHz .....	34
9.3 Frequency stability .....	35
9.4 Power limits, Modulation Characteristics, Emission limits, emission mask, bandwidth, Emission limits, conducted method .....	35

## Section 1. Report summary

---

### 1.1 Applicant and manufacturer

---

Company name	Barrett Communications Pty Ltd
Address	47 Discovery Drive, Bibra Lake
City	Perth
Province/State	Western Australia
Postal/Zip code	6163
Country	Australia

### 1.2 Test specifications

---

FCC 47 CFR Part 87	Aviation Services
--------------------	-------------------

### 1.3 Test methods

---

ANSI C63.26:2015	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services
------------------	---

### 1.4 Statement of compliance

---

In the configuration tested, the EUT was found compliant.

Testing was completed against all relevant requirements of the test standard. Results obtained indicate that the product under test complies in full with the requirements tested. The test results relate only to the items tested.

See "Summary of test results" for full details.

### 1.5 Exclusions

---

None

### 1.6 Test report revision history

---

Revision #	Details of changes made to test report
TRF	Original report issued

## Section 2. Summary of test results

---

---

### 2.1 FCC Part 87 test results

---

Part	Test description	Verdict
§87.131	Power and emissions	Pass
2.1047	Modulation characteristics	Reported
87.139(c)	Emission limits, emission mask, bandwidth	Pass
87.141(d)	Modulation requirements	Pass
87.139(c)	Emission limits, conducted method	Pass
87.139(c)	Emission limits, radiated method	Pass
87.133(c)	Frequency stability	Pass

Notes: None

## Section 3. Equipment under test (EUT) details

---

### 3.1 Sample information

---

Receipt date	February 8, 2017
Nemko sample ID number	1

### 3.2 EUT information

---

Product name	Barrett 4050 HF Transceiver
Model	4050 HF
Serial number	405010056

### 3.3 Technical information

---

Operating band	1.6–30 MHz
Test frequencies	2.182, 11.363, and 21.964 MHz
Modulation type	J3E and H3E
Occupied bandwidth (99 %)	2.7 kHz (J3E), 3 kHz (H3E)
Power requirements	13.8 Vdc for 125 Watt system and 24 Vdc for 150 Watt system.
Emission designator	2K70J3E, 3K00H3E
Antenna information	Various types with standard PL-259 connector

### 3.4 Product description and theory of operation

---

The Barrett 4050 Transceiver is a SDR based, 1000 channel HF SSB Transceiver with a frequency range of 1.6 to 30 MHz (250 kHz to 30 MHz in receive). The Barrett 4050 is designed using the latest technology including a high-resolution touch screen, IP connectivity, multi-language support, enhanced DSP noise reduction, secure digital voice, integrated GPS interface, ALE and advanced calling features.

### 3.5 EUT exercise details

---

The EUT was programmed for the low, mid, and high channels J3E used 400 and 1800 Hz input tone and H3E used 1500 Hz

### 3.6 EUT setup diagram

---



*Figure 3.6-1: Setup diagram*

### 3.7 EUT sub assemblies

---

*Table 3.7-1: EUT sub assemblies*

Description	Brand name	Model/Part number	Serial number
Power supply 13.8 VDC	Barrett	2022	202207554
Power supply 24 VDC	Barrett	4022	402410203

## Section 4. Engineering considerations

---

### 4.1 Modifications incorporated in the EUT

---

There were no modifications performed to the EUT during this assessment.

### 4.2 Technical judgment

---

None

### 4.3 Deviations from laboratory tests procedures

---

No deviations were made from laboratory procedures.



## Section 5. Test conditions

---

### 5.1 Atmospheric conditions

---

Temperature	15–30 °C
Relative humidity	20–75 %
Air pressure	860–1060 mbar

---

When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.

### 5.2 Power supply range

---

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages  $\pm 5\%$ , for which the equipment was designed.

## Section 6. Measurement uncertainty

---

### 6.1 Uncertainty of measurement

---

UKAS Lab 34 and TIA-603-B have been used as guidance for measurement uncertainty reasonable estimations with regards to previous experience and validation of data. Nemko Canada, Inc. follows these test methods in order to satisfy ISO/IEC 17025 requirements for estimation of uncertainty of measurement for wireless products.

Measurement uncertainty budgets for the tests are detailed below. Measurement uncertainty calculations assume a coverage factor of  $K = 2$  with 95% certainty.

Test name	Measurement uncertainty, dB
All antenna port measurements	0.55
Conducted spurious emissions	1.13
Radiated spurious emissions	3.78
AC power line conducted emissions	3.55

## Section 7. Test equipment

---

### 7.1 Test equipment list

---

*Table 7.1-1: Equipment list*

Equipment	Manufacturer	Model no.	Asset no.	Cal cycle	Next cal.
3 m EMI test chamber	TDK	SAC-3	FA002047	1 year	Dec. 1/17
Flush mount turntable	Sunol	FM2022	FA002082	—	NCR
Controller	Sunol	SC104V	FA002060	—	NCR
Antenna mast	Sunol	TLT2	FA002061	—	NCR
Active loop antenna (0.01–30 MHz)	Com-Power	AL-130	FA002674	1 year	June 21/18
Bilog antenna (20–3000 MHz)	Sunol	JB3	FA002108	1 year	April 28/17
Spectrum analyzer	Rohde & Schwarz	FSP	FA001920	1 year	Aug. 20/17
Spectrum analyzer	Rohde & Schwarz	FSU	FA001877	1 year	July. 15/17
50 Ω coax cable	Huber + Suhner	None	FA002074	1 year	April 26/17
50 Ω coax cable	Huber + Suhner	None	FA002830	1 year	July 29/17
Frequency counter	HP	5352B	FA001915	2 year	Apr.05/18

Note: NCR - no calibration required, VOU - verify on use

## Section 8. Testing data

---

### 8.1 FCC 87.131 Power and emissions

---

#### 8.1.1 Definitions and limits

Class of station	Frequency band/frequency	Authorized emission(s) <sup>2</sup>	Maximum power <sup>1</sup>
Aeronautical enroute and aeronautical fixed	HF	R3E, H3E, J3E, J7B, H2B, J2D	6 kW

<sup>1</sup>The power is measured at the transmitter output terminals and the type of power is determined according to the emission designator as follows:

- (i) Mean power (pY) for amplitude modulated emissions and transmitting both sidebands using unmodulated full carrier.
- (ii) Peak envelope power (pX) for all emission designators other than those referred to in paragraph (i) of this note.

<sup>2</sup>Excludes automatic link establishment.

#### 8.1.2 Test summary

---

Test date	February 21, 2017	Temperature	22 °C
Test engineer	Kevin Rose	Air pressure	1003 mbar
Verdict	Pass	Relative humidity	32 %

#### 8.1.3 Observations, settings and special notes

---

J3E – two tones at frequencies of 400 Hz and 1800 Hz, H3E one tone at a frequency of 1500 Hz

Test receiver settings:

Detector mode	Peak
Resolution bandwidth	>OBW
Video bandwidth	>RBW
Trace mode	Max Hold
Measurement time	Auto

8.1.4 Test data

*Table 8.1-1: results 125 W system operation*

Modulation	Frequency, MHz	RF output power, dBm	Limit, dBm	Margin, dB
J3E	2.182	49.79	67.78	17.99
J3E	11.363	50.09	67.78	17.69
J3E	21.964	50.02	67.78	17.76

*Table 8.1-2: results 125 W system operation*

Modulation	Frequency, MHz	RF output power, dBm	Limit, dBm	Margin, dB
H3E	2.182	49.56	67.78	18.22
H3E	11.363	49.85	67.78	17.93
H3E	21.964	49.86	67.78	17.92

*Table 8.1-3: results 150 W system operation*

Modulation	Frequency, MHz	RF output power, dBm	Limit, dBm	Margin, dB
J3E	2.182	51.23	67.78	16.55
J3E	11.363	51.59	67.78	16.19
J3E	21.964	51.44	67.78	16.34

*Table 8.1-4: results 150 W system operation*

Modulation	Frequency, MHz	RF output power, dBm	Limit, dBm	Margin, dB
H3E	2.182	51.25	67.78	16.53
H3E	11.363	51.45	67.78	16.33
H3E	21.964	51.31	67.78	16.47

## 8.2 FCC 2.1047 Modulation characteristics

---

### 8.2.1 Definitions and limits

---

(a) Voice modulated communication equipment. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz shall be submitted. For equipment required to have an audio low-pass filter, a curve showing the frequency response of the filter, or of all circuitry installed between the modulation limiter and the modulated stage shall be submitted.

(c) Single sideband and independent sideband radiotelephone transmitters which employ a device or circuit to limit peak envelope power. A curve showing the peak envelope power output versus the modulation input voltage shall be supplied. The modulating signals shall be the same in frequency as specified in paragraph (c) of §2.1049 for the occupied bandwidth tests.

### 8.2.2 Test summary

---

Test date	February 21, 2017	Temperature	22 °C
Test engineer	Kevin Rose	Air pressure	1003 mbar
Verdict	Pass	Relative humidity	32 %

### 8.2.3 Observations, settings and special notes

---

settings and special notes

Detector mode	
Resolution bandwidth	
Video bandwidth	
Trace mode	Peak

8.2.4 Test data




Figure 8.2-1: Modulation Characteristic 125 Watts




Figure 8.2-2: Modulation Characteristic 150 Watts



**Table 8.2-1: Modulation Characteristic results 150 Watts**

Hz	Watts
100	1.4
300	46
400	97
1000	145
2000	142
3000	1.9
4000	0.6
5000	0.2

**Table 8.2-2: Modulation Characteristic results 125 Watts**

Hz	Watts
100	1.3
300	45
400	86
1000	118
2000	117
3000	1.8
4000	0.9
5000	0.2

**Table 8.2-3: Modulation Limiting results 125 Watts**

2.182 MHz		11.363 MHz		21.964 MHz	
Input Audio,	Output power, Watts	Input Audio,	Output power, Watts	Input Audio,	Output power, Watts
0.01	0.04	0.01	0.05	0.01	0.05
0.02	0.2	0.02	0.3	0.02	0.2
0.04	2	0.04	3.5	0.04	1.5
0.05	4	0.05	7.6	0.05	3
0.07	14	0.07	24	0.07	9
0.1	45	0.1	67	0.1	33
0.15	112	0.15	114	0.15	106
0.2	123	0.2	119	0.2	114
0.3	123	0.3	118	0.3	118

**Table 8.2-4: Modulation Limiting results 150 Watts**

2.182 MHz		11.363 MHz		21.964 MHz	
Input Audio,	Output power, Watts	Input Audio,	Output power, Watts	Input Audio,	Output power, Watts
0.01	0.04	0.01	0.05	0.01	0.08
0.02	0.2	0.02	0.3	0.02	0.5
0.04	1.6	0.04	3	0.04	4
0.05	3.5	0.05	7	0.05	9
0.07	11	0.07	22	0.07	29
0.1	39	0.1	69	0.1	90
0.15	134	0.15	150	0.15	139
0.2	146	0.2	164	0.2	140
0.3	142	0.3	164	0.3	142



## 8.3 FCC 87.139(c) Emission limits, emission mask, bandwidth

---

### 8.3.1 Definitions and limits

---

(c) For aircraft station transmitters first installed after February 1, 1983, and for aeronautical station transmitters in use after February 1, 1983, and using H2B, H3E, J3E, J7B or J9W, the peak envelope power of any emissions must be attenuated below the peak envelope power of the transmitter (pX) as follows:

- 1) When the frequency is removed from the assigned frequency by more than 50 percent up to and including 150 percent of the authorized bandwidth of 3.0 kHz, the attenuation must be at least 30 dB.
- 2) When the frequency is removed from the assigned frequency by more than 150 percent up to and including 250 percent of the authorized bandwidth of 3.0 kHz, the attenuation must be at least 38 dB.
- 3) When the frequency is removed from the assigned frequency by more than 250 percent of the authorized bandwidth of 3.0 kHz for aircraft transmitters the attenuation must be at least 43 dB. For aeronautical station transmitters with transmitter power up to and including 50 watts the attenuation must be at least  $43 + 10 \log_{10} pX$  dB and with transmitter power more than 50 watts the attenuation must be at least 60 dB.

### 8.3.2 Test summary

---

Test date	February 21, 2017	Temperature	22 °C
Test engineer	Kevin Rose	Air pressure	1003 mbar
Verdict	Pass	Relative humidity	32 %


### 8.3.3 Observations, settings and special notes

---

Spectrum analyzer settings:


Detector mode	Peak
Resolution bandwidth	300 Hz or 30 Hz
Video bandwidth	RBW × 3
Trace mode	Max Hold

8.3.4 Test data




Date: 22.FEB.2017 15:51:43

Figure 8.3-1: Low channel Mask 125W 400 Hz and 1800 Hz




Date: 22.FEB.2017 15:53:54

Figure 8.3-2: Mid channel Mask 125W 400 Hz and 1800 Hz




Date: 22.FEB.2017 15:55:03

Figure 8.3-3: High channel Mask 125W 400 Hz and 1800 Hz




Date: 22.FEB.2017 20:06:47

Figure 8.3-4: Low channel Mask 125W 1500 Hz




Date: 22.FEB.2017 20:04:41

Figure 8.3-5: : Mid channel Mask 125W 1500 Hz




Date: 22.FEB.2017 20:02:58

Figure 8.3-6: High channel Mask 125W 1500 Hz




Date: 22.FEB.2017 16:53:32

Figure 8.3-7: Low channel Mask 150W 400 Hz and 1800 Hz




Date: 22.FEB.2017 16:53:00

Figure 8.3-8: Mid channel Mask 150W 400 Hz and 1800 Hz




Date: 22.FEB.2017 16:52:17

Figure 8.3-9: High channel Mask 150W 400 Hz and 1800 Hz




Date: 22.FEB.2017 19:05:00

Figure 8.3-10: Low channel Mask 150W 1500 Hz



Date: 22.FEB.2017 19:10:09

Figure 8.3-11: Mid channel Mask 150W 1500 Hz



Date: 22.FEB.2017 19:42:05

Figure 8.3-12: High channel Mask 150W 1500 Hz

## 8.4 FCC 87.141(d) Modulation requirements

---

### 8.4.1 Definitions and limits

---

(d) Single sideband transmitters must be able to operate in the following modes:

<b>Carrier mode</b>	<b>Level N(dB) of the carrier with respect to peak envelope power</b>
Full carrier (H3E)	$0 > N > -6$
Suppressed carrier (J3E)	Aeronautical stations $N < -40$ .

### 8.4.2 Test summary

---

Test date	February 21, 2017	Temperature	22 °C
Test engineer	Kevin Rose	Air pressure	1003 mbar
Verdict	Pass	Relative humidity	32 %


### 8.4.3 Observations, settings and special notes

---

Spectrum analyzer settings:


Detector mode	Peak
Resolution bandwidth	30 Hz
Video bandwidth	RBW × 3
Trace mode	Max Hold

8.4 Test data




Date: 22.FEB.2017 17:25:53

Figure 8.4-1: Low channel 125W 400 Hz and 1800 Hz 40 dB




Date: 22.FEB.2017 17:23:14

Figure 8.4-2: Mid channel 125W 400 Hz and 1800 Hz 40 dB




Date: 22.FEB.2017 17:22:06

Figure 8.4-3: High channel 125W 400 Hz and 1800 Hz 40 dB




Date: 22.FEB.2017 17:12:14

Figure 8.4-4: Low channel 150W 400 Hz and 1800 Hz 40 dB




Date: 22.FEB.2017 17:14:27

Figure 8.4-5: Mid channel 150W 400 Hz and 1800 Hz 40 dB




Date: 22.FEB.2017 17:18:50

Figure 8.4-6: High channel 125W 400 Hz and 1800 Hz 40 dB




Date: 22.FEB.2017 17:45:22

Figure 8.4-7: Low channel 125W 1500 Hz 6 dB




Date: 22.FEB.2017 18:45:39

Figure 8.4-8: Mid channel 125W 1500 Hz 6 dB




Date: 22.FEB.2017 18:46:51

Figure 8.4-9: High channel 125W 1500 Hz 6 dB




Date: 22.FEB.2017 18:52:34

Figure 8.4-10: Low channel 150W 1500 Hz 6 dB



Date: 22.FEB.2017 18:51:25

Figure 8.4-11: Mid channel 150W 1500 Hz 6 dB



Date: 22.FEB.2017 18:50:22

Figure 8.4-12: High channel 125W 1500 Hz 6 dB



## 8.5 FCC 87.139(c) Emission limits, conducted method

---

### 8.5.1 Definitions and limits

---

(c) For aircraft station transmitters first installed after February 1, 1983, and for aeronautical station transmitters in use after February 1, 1983, and using H2B, H3E, J3E, J7B or J9W, the peak envelope power of any emissions must be attenuated below the peak envelope power of the transmitter (pX) as follows:

- 4) When the frequency is removed from the assigned frequency by more than 50 percent up to and including 150 percent of the authorized bandwidth of 3.0 kHz, the attenuation must be at least 30 dB.
- 5) When the frequency is removed from the assigned frequency by more than 150 percent up to and including 250 percent of the authorized bandwidth of 3.0 kHz, the attenuation must be at least 38 dB.
- 6) When the frequency is removed from the assigned frequency by more than 250 percent of the authorized bandwidth of 3.0 kHz for aircraft transmitters the attenuation must be at least 43 dB. For aeronautical station transmitters with transmitter power up to and including 50 watts the attenuation must be at least  $43 + 10 \log_{10} pX$  dB and with transmitter power more than 50 watts the attenuation must be at least 60 dB.

### 8.5.2 Test summary

---

Test date	February 22, 2017	Temperature	22 °C
Test engineer	Kevin Rose	Air pressure	1003 mbar
Verdict	Pass	Relative humidity	32 %


### 8.5.3 Observations, settings and special notes

---

Spectrum analyzer settings:


Detector mode	Peak
Resolution bandwidth	10 kHz
Video bandwidth	RBW × 3
Trace mode	Max Hold

8.5.4 Test data




Date: 22.FEB.2017 21:37:34

Figure 8.5-1: Low channel Conducted Spurious 125W 1500 Hz




Date: 22.FEB.2017 21:39:28

Figure 8.5-2: Mid channel Conducted Spurious 125W 1500 Hz




Date: 22.FEB.2017 21:40:25

Figure 8.5-3: High channel Conducted Spurious 125W 1500 Hz




Date: 22.FEB.2017 22:09:02

Figure 8.5-4: Low channel Conducted Spurious 125W 1800 Hz and 400 Hz




Date: 22.FEB.2017 22:08:24

Figure 8.5-5: Mid channel Conducted Spurious 125W 1800 Hz and 400 Hz




Date: 22.FEB.2017 22:07:30

Figure 8.5-6: High channel Conducted Spurious 125W 1800 Hz and 400 Hz




Date: 22.FEB.2017 21:51:27

Figure 8.5-7: Low channel Conducted Spurious 150W 1500 Hz




Date: 22.FEB.2017 21:49:45

Figure 8.5-8: Mid channel Conducted Spurious 150W 1500 Hz




Date: 22.FEB.2017 21:48:39

Figure 8.5-9: High channel Conducted Spurious 150W 1500 Hz




Date: 22.FEB.2017 21:55:59

Figure 8.5-10: Low channel Conducted Spurious 150W 1800 Hz and 400 Hz



Date: 22.FEB.2017 21:57:38

Figure 8.5-11: Mid channel Conducted Spurious 150W 1800 Hz and 400 Hz



Date: 22.FEB.2017 21:58:31

Figure 8.5-12: High channel Conducted Spurious 150W 1800 Hz and 400 Hz

## 8.6 FCC 87.139(c) Emission limits, radiated method

---

### 8.6.1 Definitions and limits

---

- (1) When the frequency is removed from the assigned frequency by more than 50 percent up to and including 150 percent of the authorized bandwidth of 3.0 kHz, the attenuation must be at least 30 dB.
- (2) When the frequency is removed from the assigned frequency by more than 150 percent up to and including 250 percent of the authorized bandwidth of 3.0 kHz, the attenuation must be at least 38 dB.
- (c) For aircraft station transmitters first installed after February 1, 1983, and for aeronautical station transmitters in use after February 1, 1983, and using H2B, H3E, J3E, J7B or J9W, the peak envelope power of any emissions must be attenuated below the peak envelope power of the transmitter (pX) as follows:
- (3) When the frequency is removed from the assigned frequency by more than 250 percent of the authorized bandwidth of 3.0 kHz for aircraft transmitters the attenuation must be at least 43 dB. For aeronautical station transmitters with transmitter power up to and including 50 watts the attenuation must be at least 43 + 10 log<sub>10</sub> pX dB and with transmitter power more than 50 watts the attenuation must be at least 60 dB.

### 8.6.2 Test summary

---

Test date	February 22, 2017	Temperature	22 °C
Test engineer	Kevin Rose	Air pressure	1003 mbar
Verdict	Pass	Relative humidity	32 %


### 8.6.3 Observations, settings and special notes

---

Spectrum analyzer settings:


Detector mode	Peak
Resolution bandwidth	10 kHz
Video bandwidth	RBW × 3
Trace mode	Max Hold

8.6.4 Test data




Date: 27.APR.2017 03:49:42

Figure 8.6-1: Low channel Radiated Spurious 125W




Date: 27.APR.2017 03:03:49

Figure 8.6-2: Low channel Radiated Spurious 125W




Date: 27.APR.2017 03:48:39

Figure 8.6-3: Mid channel Radiated Spurious 125W




Date: 27.APR.2017 03:05:46

Figure 8.6-4: Mid channel Radiated Spurious 125W




Date: 27.APR.2017 03:46:58

Figure 8.6-5: High channel Radiated Spurious 125W




Date: 27.APR.2017 03:09:31

Figure 8.6-6: High channel Radiated Spurious 125W




Date: 27.APR.2017 03:37:11

Figure 8.6-7: Low channel Radiated Spurious 150W




Date: 27.APR.2017 03:19:07

Figure 8.6-8: Low channel Radiated Spurious 150W




Date: 27.APR.2017 03:38:08

Figure 8.6-9: Mid channel Radiated Spurious 150W




Date: 27.APR.2017 03:17:57

Figure 8.6-10: Mid channel Radiated Spurious 150W



Date: 27.APR.2017 03:40:07

Figure 8.6-11: High channel Radiated Spurious 150W



Date: 27.APR.2017 03:15:37

Figure 8.6-12: High channel Radiated Spurious 150W



## 8.7 FCC 87.133 Frequency stability

### 8.7.1 Definitions and limits

(c) For single-sideband transmitters, the tolerance is:  
 (1) All aeronautical stations on land: 10 Hz.

### 8.7.2 Test summary

Test date	February 21, 2017	Temperature	22 °C
Test engineer	Kevin Rose	Air pressure	1003 mbar
Verdict	Pass	Relative humidity	32 %

### 8.7.3 Observations, settings and special notes

1500 Hz tone was used during testing

### 8.7.4 Test data

**Table 8.7-1: Frequency drift measurement FCC Part 87 results 125 watt**


Test conditions	Frequency, Hz	Drift, Hz	Limit ±10 Hz
+50 °C, Nominal	11364384	-2	±10 Hz
+40 °C, Nominal	11364384	-2	±10 Hz
+30 °C, Nominal	11364385	-1	±10 Hz
+20 °C, +15 %	11364386	0	±10 Hz
+20 °C, Nominal	11364386	0	Reference
+20 °C, -15 %	11364386	0	±10 Hz
+10 °C, Nominal	11364387	1	±10 Hz
0 °C, Nominal	11364388	2	±10 Hz
-10 °C, Nominal	11364387	1	±10 Hz
-20 °C, Nominal	11364387	1	±10 Hz
-30 °C, Nominal	11364389	3	±10 Hz

**Table 8.7-2: Frequency drift measurement FCC Part 87. results 150 watt**


Test conditions	Frequency, Hz	Drift, Hz	Limit ±10 Hz
+50 °C, Nominal	11364384	-2	±10 Hz
+40 °C, Nominal	11364384	-2	±10 Hz
+30 °C, Nominal	11364385	-1	±10 Hz
+20 °C, +15 %	11364386	0	±10 Hz
+20 °C, Nominal	11364386	0	Reference
+20 °C, -15 %	11364386	0	±10 Hz
+10 °C, Nominal	11364387	1	±10 Hz
0 °C, Nominal	11364388	2	±10 Hz
-10 °C, Nominal	11364387	1	±10 Hz
-20 °C, Nominal	11364388	2	±10 Hz
-30 °C, Nominal	11364388	2	±10 Hz

## Section 9. Block diagrams of test set-ups

### 9.1 Radiated emissions set-up for frequencies below 1 GHz




### 9.2 Radiated emissions set-up for frequencies above 1 GHz



### 9.3 Frequency stability

---



### 9.4 Power limits, Modulation Characteristics, Emission limits, emission mask, bandwidth, Emission limits, conducted method

---

