SPECIFICATIONS: DWG, NO. SHEET REV **REVISIONS** 10-T-MT 10 WATT COAXIAL TERMINATION ZONE REV **DESCRIPTION** DATE **APPROVED** POWER RATING: 10 WATTS CW @ 40°C. A ECN #0185 12-23-97 12 WATTS CW @ 25°C. mes FREQUENCY RANGE & VSWR: DC TO 1GHz AT 1.10:1 MAX. 1GHz TO 4GHz AT 1.25:1 MAX. CONNECTOR TYPE: TNC-MALE IMPEDANCE: 50 OHMS, NOMINAL AMBIENT TEMPERATURE RANGE: -40°C TO +40°C OPERATING POSITION: ANY COOLANT: DRY (CONVECTION COOLED) FINISH: BLACK ANODIZED COOLING FIN, SILVER OR TRI-ALLOY PLATED CONNECTOR (2.15)NOMINAL SIZE: APPROX. 2.15" L X 2.30" DIA. (WITH TNC-TYPE MALE CONNECTOR) WEIGHT: APPROX. 3 OZ. 4 (2.00)(2.30)**←** (1.30) **→** UNLESS OTHERWISE SPECIFIED MILLIMETERS THIS DRAWING IS THE PROPERTY OF THE BIRD ELECTRONIC DIMENSIONS ARE IN INCHES .X= ±.4 .XX= ±.12 CORPORATION. THE DESIGNS AND SPECIFICATIONS DISCLOSED TOLERANCES ARE: Electronic Corporation HEREON ARE PROPRIETARY AND SHALL NOT BE REPRODUCED. NOR FRACTIONS DECIMALS **ANGLES** COPIED, NOR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF Cleveland (Solon) Ohio USA $.XX = \pm .010$ $.XXX = \pm .005$ ±1/64 ±30' APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT. DO NOT SCALE DRAWING **APPROVALS** DATE FINAL ASS'Y, TERMINATION MATERIAL DRAWN D.M.RINK 4-3-03 TNC-TYPE MALE, 10W CHECKED SIZE FSCM NO. DWG. NO. REV FINISH 10-T-MTAPPROVED 70998 MARKY 615-03 SCALE COMM CODE SHEET 1:1 LD1 1 OF 1 AUTOCAD