DWG. NO. REV SHEET **REVISIONS** 2-T-MB **SPECIFICATIONS:** ZONE **REV DESCRIPTION** DATE **APPROVED** POWER RATING: 2 WATTS MAX. @ 40°C. CHNG LABEL, FINISH ECN #0049 3-27-96 MEU 2.4 WATTS MAX. @ 25 C. CONNECTOR: BNC MALE FREQUENCY RANGE & VSWR: TO 1 GHz AT 1.10:1 MAX. 1 GHz TO 4 GHz AT 1.25:1 MAX. IMPEDANCE: 50 OHMS NOMINAL AMBIENT TEMPERATURE: RANGE: -40°C TO +40°C OPERATING POSITION: ANY COOLANT: DRY (CONVECTION COOLED) FINISH: SILVER OR TRI-ALLOY PLATED NOMINAL SIZE: APPROX. 1.75" L X Ø.700" WEIGHT: APPROX. 1.5 oz. (42 g) (ø.70) MODEL (UNLESS OTHERWISE SPECIFIED MILLIMETERS THIS DRAWING IS THE PROPERTY OF THE BIRD ELECTRONIC DIMENSIONS ARE IN INCHES .X= ±.4 .XX= ±.12 CORPORATION. THE DESIGNS AND SPECIFICATIONS DISCLOSED Electronic Corporation TOLERANCES ARE: HEREON ARE PROPRIETARY AND SHALL NOT BE REPRODUCED, NOR FRACTIONS DECIMALS Cleveland (Solon) Ohio USA **ANGLES** COPIED, NOR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF $.XX = \pm .010$ ±1/64 ± 30' APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT. $.XXX = \pm .005$ DO NOT SCALE DRAWING **APPROVALS** DATE FINAL ASS'Y/TERMINATION MATERIAL DRAWN 5-27-03 D.M.RINK BNC MALE, 2W CHECKED FSCM NO. DWG. NO. SIZE REV 2-T-MBFINISH 70998 APPROVED 66-03 MARKY SCALE COMM CODE SHEET 1:1 LD1 1 OF 1 **AUTOCAD**