1.4. **UNIT SPECIFICATIONS**

MODELS 6104, 6154, 6155, 6156 TERMALINE® WATTMETER

50 ohms nominal

VSWR 1.1:1 maximum across unit

frequency range

Connectors

Models 6104, 6154, 6156 Female N

Bird "QC" type female N

normally supplied

Load Power Rating

80 W continuous

Models 6154, 6155, 6156 150 W continuous

Power Scales Low Scale High Scale

(Black) (Red) 0-2 & 0-20 0-6 & 0-60

0-5 & 0-50 0-15 & 0-150

0-50 & 0-150

Frequency Range

25-1000 MHz 25-512 MHz

2-30 MHz

Accuracy

±5% of full scale

Model 6154 (512-1000 MHz) ±10% of full scale

Dimensions

9-5/8"L x 3-61/64"W x 6-3/8"H

(244.5 x 100 x 162 mm)

Models 6154, 6156 12-5/32"L x 3-61/64"W x

6-3/8"H

(309 x 100 x 162 mm)

12-27/32"L x 3-15/16"W x

6-11/32"H

(326 x 100 x 161 mm)



UNIT SPECIFICATIONS [CONT.]

Coolant Capacity	0.1 gal. (378.5 ml) approximate
Weight Model 6104 Models 6154, 6155, 6156	7 lb (3.2 kg) 8 lb (3.6 kg)
Operating Position Load Meter housing	Horizontal only Vertical or flat
Finish	Gray enamel

REPLACEMENT PARTS LIST [CONT.]

ITEM	QUANTITY	DESCRIPTION	PART NUMBER
_			
8	1	DC plug	7500-076
9	1	Meter mount shock strip	5-1066
10	1	Meter shock mount	4220-087
11	1	Crystal diode	7500-147
12	1	Toggle switch	5A2154
13	1	Handle	2400-017
14	1	Clamp band assembly	7500-254
15	1	DC cable (includes item 8)	4220-097-2
16	1	Diaphragm	2400-015
17	1	Diaphragm cap	2400-050
18	1	Chain & anchor assembly	6700-021
19	1	Bumper foot	5-049
20	2	Gasket	7500-153

NOTE - The resistor voltmeter assembly is only supplied factory-calibrated and includes crystal diode, chain and anchor assembly, and gaskets.

6.3. MODEL 6155

ITEM	QUANTITY	DESCRIPTION	PART NUMBER
1	1	RF section assembly	8130-015
2	1	Radiator assembly	2400-053
_		Element assembly	4271-070
3	0.1 gallon	Coolant	5-030
	(378.5ml)		1 pint container (473ml)
4	1	Slide switch	6155-004
5	1	Meter	2080-329
6	1	Radiator seal O-Ring	5-229
7	1	DC plug and cable assembly	4220-097-1
8	1	QC connector	See below*
9	1	Handle	2400-017
10	1	Clamp band assembly	7500-254
11	1	DC plug only	7500-076
12	1	Diaphragm	2400-015
13	1	Diaphragm cap	2400-050
14	4	Bumper feet	5-049