CHAPTER



WINGS



CHAPTER 57 WINGS

Subject/Page	Date	Subject/Page	Date	Subject/Page	Date
EFFECTIVE PAG	ES				
1	Apr 10/2008				
2	BLANK				
57–CONTENTS					
1	Apr 10/2007				
2	BLANK				
57-30-01					
1	Apr 10/2006				
2	BLANK				
57-40-01					
1	Apr 10/2006				
2	Apr 10/2006				
57-40-02					
1	Apr 10/2007				
2	Oct 10/2006				
3	Oct 10/2006				
4	Apr 10/2007				
57-50-01					
1	Apr 10/2006				
2	Apr 10/2006				
57-50-02					
1	Apr 10/2006				
2	BLANK				
57-50-03					
1	Apr 10/2006				
2	BLANK				
57-50-04					
1	Oct 10/2006				
2	Oct 10/2006				
3	Oct 10/2006				
4	BLANK				

A = Added, R = Revised, O = Overflow, D = Deleted

57-EFFECTIVE PAGES



TABLE OF CONTENTS

Subject	Title	Part No.
57-	WINGS	
57-30-01	SLING - RAKED WING TIP, INSTALLATION AND REMOVAL	A57004-1
57-40-01	LOCATING EQUIPMENT - WEDGE REPLACEMENT, INBOARD AND OUTBOARD LEADING EDGE SLAT	A57003-1
57-40-02	LUBRICATING EQUIPMENT - LEADING EDGE SLAT AUXILIARY ARM ROLLER BOLT	A57007-8
57-50-01	REPLACEMENT EQUIPMENT - OUTBOARD TRAILING EDGE FLAP	A57002-1
57-50-02	SOCKET ASSEMBLY - RETENTION NUT, MAIN LANDING GEAR ACTUATOR SUPPORT, WING	A57005-1
57-50-03	SPANNER WRENCH - SPECIAL NUT, INBOARD TRAILING EDGE MAIN FLAP	A57006-1
57-50-04	REMOVAL / INSTALLATION EQUIPMENT - MAIN LANDING GEAR BOTTLE PIN	A57008-1





PART NUMBER: A57004-1

NAME:

SLING - RAKED WING TIP, INSTALLATION AND REMOVAL

AIRPLANE MAINTENANCE: YES

COMPONENT MAINTENANCE: NO

USAGE & DESCRIPTION: The A57004-1 sling is used on 767-400 airplanes. A57004 is used for installation and removal of the raked wing tip. Refer to AMM 57-31-01 for complete usage instructions. A57004-1 consists of an A57004-2 sling assembly, four A57004-4 screws, two A57004-14 screws, all contained in a storage box.

WEIGHT: 19 lbs (8.6 kg)

DIMENSIONS: 12 x 12 x 15 inches (305 x 305 x 381 mm)





REPAIRABLE/REPLACEABLE PARTS			
ITEM NO.	PART NO.	NOMENCLATURE	VENDOR CODE
1	A57004-4	SCREW	
2	A57004-14	SCREW	

57-30-01 Apr 10/2006

Page 1



PART NUMBER: A57003-1

NAME: LOCATING EQUIPMENT - WEDGE REPLACEMENT, INBOARD AND OUTBOARD LEADING EDGE SLAT

AIRPLANE MAINTENANCE: NO

COMPONENT MAINTENANCE: YES

USAGE & DESCRIPTION: The A57003-1 locating equipment is used during component maintenance on all 767 airplanes. A57003 is used to locate the inboard and outboard slat trailing edge wedge position during replacement. For complete usage instructions see CMM 57-43-37, CMM 57-43-41, CMM 57-43-45, CMM 57-43-51, CMM 57-43-55 and CMM 57-43-61. A57003-1 consists of:

A57003-1			
QUANTITY	NOMENCLATURE	PART NUMBER	
2	INBOARD CLAMP BLOCK	A57003-2	
1	INBOARD LEFT HAND TOOL ASSEMBLY	A57003-3	
1	INBOARD RIGHT HAND TOOL ASSEMBLY	A57003-4	
1	OUTBOARD LEFT HAND TOOL ASSEMBLY	A57003-5	
1	OUTBOARD RIGHT HAND TOOL ASSEMBLY	A57003-6	
2	OUTBOARD CLAMP BLOCK	A57003-7	
1	STORAGE BOX		

WEIGHT:

31 lbs. (14 kg)

DIMENSIONS:

10 x 13 x 18 inches (254 x 330 x 457 mm)





767 ILLUSTRATED TOOL AND EQUIPMENT MANUAL



Inboard and Outboard Leading Edge Slat Wedge Replacement Locating Equipment Figure 1





PART NUMBER: A57007-8

NAME: LUBRICATING EQUIPMENT - LEADING EDGE SLAT AUXILIARY ARM ROLLER BOLT

AIRPLANE MAINTENANCE: YES

COMPONENT MAINTENANCE: NO

USAGE & DESCRIPTION: The A57007-8 lubricating equipment is used on all 767 airplanes. This tool is used to grease the bearing that fits around the leading edge slat auxiliary arm roller bolt. The A57007-3 cap and -9 fitting is used on the inboard auxiliary arm roller bolt. The A57007-5 cap and -10 fitting is used on the outboard auxiliary arm roller bolt. Refer to AMM 12-21-08, Service Letter 767-SL-57-037-B, and current A57007 drawing. The A57007-8 consists of the following:

A57007-8			
QUANTITY	NOMENCLATURE	PART NUMBER	
1	FITTING	A57007-9	
1	САР	A57007-3	
1	FITTING	A57007-10	
1	САР	A57007-5	
1	STORAGE BOX		

WEIGHT: 1.6 lbs (.72 kg)

DIMENSIONS:

NOTE:

2.7 x 2.7 x 2.0 inches (69 x 69 x 50 mm)

A57007-8 supersedes A57007-1.

57-40-02





Page 2 Oct 10/2006



767 ILLUSTRATED TOOL AND EQUIPMENT MANUAL





Lubricating Equipment - Leading Edge Slat Auxiliary Arm Roller Bolt Figure 2 (Sheet 1 of 2)







767 ILLUSTRATED TOOL AND EQUIPMENT MANUAL



(2 LOCATIONS)





A57007 T00L

Lubricating Equipment - Leading Edge Slat Auxiliary Arm Roller Bolt Figure 2 (Sheet 2 of 2)







PART NUMBER: A57002-1

NAME:

REPLACEMENT EQUIPMENT - OUTBOARD TRAILING EDGE FLAP

AIRPLANE MAINTENANCE: NO

COMPONENT MAINTENANCE: YES

USAGE & DESCRIPTION: The A57002-1 replacement equipment is used during component maintenance on all 767 airplanes. A57002 is used for replacing the wedge assembly of the outboard trailing edge flap. Refer to CMM 57-53-51 for complete usage instructions. A57002-1 consists of :

A57002-1			
QUANTITY	NOMENCLATURE	PART NUMBER	
1	RIGGING BAR ASSEMBLY	A57002-3	
1	RIGGING BAR ASSEMBLY	A57002-4	
1	RIGGING BAR ASSEMBLY	A57002-5	
1	RIGGING BAR ASSEMBLY	A57002-6	
1	RIGGING BAR ASSEMBLY	A57002-7	
10	WEDGE	A57002-14	
5	FEELER	A57002-15	
5	WEBBING ASSEMBLY	A57002-22	
2	STANDOFF ASSEMBLY	A57002-27	
2	STANDOFF ASSEMBLY	A57002-28	
2	STANDOFF ASSEMBLY	A57002-29	
1	STORAGE BOX		

WEIGHT:

20 lbs (9 kg)

DIMENSIONS:

5 x 15 x 45 inches (127 x 381 x 1143 mm)



Page 1 Apr 10/2006

٦

767 ILLUSTRATED TOOL AND EQUIPMENT MANUAL



Outboard Trailing Edge Flap Replacement Equipment Figure 1







PART NUMBER: A57005-1

NAME:	SOCKET ASSEMBLY - RETENTION NUT, MAIN LANDING GEAR ACTUATOR SUPPORT, WING
AIRPLANE MAINTENANCE:	NO
COMPONENT MAINTENANCE:	YES
USAGE & DESCRIPTION:	The A57005-1 socket assembly is used on all 767 airplanes. A57005 is used to remove and install the main landing gear actuator wing bearing retention nut. Refer to CMM 57-54-39 for complete usage instructions. A57005-1 consists of a A57005-2 socket assembly contained in a storage box.
WEIGHT:	4 lbs (1.8 kg)
DIMENSIONS:	3 x 7 x 7 inches (76 x 178 x 178 mm)



Wing Main Landing Gear Actuator Support Retention Nut Socket Assembly Figure 1





PART NUMBER: A57006-1

NAME:

SPANNER WRENCH - SPECIAL NUT, INBOARD TRAILING EDGE MAIN FLAP

AIRPLANE MAINTENANCE: NO

COMPONENT MAINTENANCE: YES

USAGE & DESCRIPTION: The A57006-1 spanner wrench is used during component maintenance on all 767 airplanes. A57006 is used for the removal and installation of the special nut on the inboard trailing edge main flap torque tube assembly. Refer to the current A57006 -1 drawing for complete usage instructions. A57006-1 consists of an A57006-2 spanner wrench contained in a storage box.

WEIGHT: 2 lbs (0.9 kg)

DIMENSIONS:

1 x 5 x 8 inches (25 x 127 x 203 mm)



Inboard Trailing Edge Main Flap, Special Nut, Spanner Wrench Figure 1





PART NUMBER: A57008-1

NAME:	REMOVAL / INSTALLATION EQUIPMENT - MAIN LANDING GEAR BOTTLE PIN
AIRPLANE MAINTENANCE:	YES
COMPONENT MAINTENANCE:	NO
USAGE & DESCRIPTION:	The A57008-1 removal and installation equipment is used on all 767 airplanes. This tool is a spanner wrench that is used to remove and install the main landing gear bottle pin (part number 113T1144). To remove the 113T1144 bottle pin, the tool is used in conjunction with a customer furnished breaker bar. To install the 113T1144 bottle pin, the tool is used in conjunction with a customer furnished torque wrench. Refer to AMM 57-54-06 and current A57008 drawing for additional instructions. The A57008-1 consists of the following:

A57008-1			
QUANTITY	NOMENCLATURE	PART NUMBER	
1	WRENCH ASSEMBLY	A57008-2	
1	BAR	A57008-4	
2	NUT	A57008-5	
2	WASHER	A57008-6	
1	STORAGE BOX		

WEIGHT:

6.4 lbs (2.9 kg)

DIMENSIONS:

3 x 4 x 26 inches (76 x 102 x 660 mm)



BOEING"

767 ILLUSTRATED TOOL AND EQUIPMENT MANUAL





Page 2 Oct 10/2006



767 ILLUSTRATED TOOL AND EQUIPMENT MANUAL



Main Landing Gear Strut Swivel Fitting Installation Figure 1 (Sheet 2 of 2)



