Océ 4700/CS4000 Series

Color Scanners for large format scan-to-file and copying

Professional scanning performance to complete your system



Océ Scanners	4715	4730	4770	4780	CS4040/ CS4050	CS4040/ CS4050 +upgr. kit 1	CS4040/ CS4050 +upgr. kit 2
Color scanning	No	No	Yes	Yes	Yes	Yes	Yes
Optical resolution (dpi)			288	400	400	400	400
Scanning resolution (dpi)	25-400	25-800	50-300	50-600	50-800	50-800	50-800
Total number of pixels	8,000	16,000	10,000	15,000	21,400	21,400	21,400
Number of sensors	1	2	2	3	4	4	4
Speed (at 400 dpi - 24 bit RGB)	-	-	-	-	0.8 ips	1.0 ips	1.3 ips
200 dpi - 24 bit RGB	2.4 ips	2.4 ips	1.4 ips	1.0 ips	1.6 ips	2.0 ips	2.6 ips
Sharpening /softening filters					no	yes	yes
ADL (Area Diffusion Logic)					no	no	yes
Media thickness - maximum	.12"	.12"	.12"	.12"	0.6"	0.6"	0.6"
Media width - maximum	40"	40"	40"	40"	51.5"	51.5"	51.5"
Width scan - maximum	36"	36"	36"	36"	40"/50"	40"/50"	40"/50"

General specifications

	ns		
Scanning modes color:	Full color RGB (24 bit), specified color (8 or 4 bit),	Scanning management	Viewing (graytone and black/white), histogram
e	index color (8 or 4 bit), Océ 4050 (36 bit) capture		analysis, format conversion, printing/plotting
monochrome:	Grayscale (8 bit), B&W (1 bit)	File formats	Over 50 input and output formats including TIFF,
Recalibration	Possible for special documents		JPEG, BMP, RLC
Scan length	Unlimited by scanner	Preset configurations	For automatic setup of scanning parameters
Light source	Stabilized fluorescent lamp	Batch scanning capability	With automatic naming of files
Optics	Apochromatic lenses	Deskewing	Horizontal alignment of skewed documents
Original loading	Automatic loading from front side	Despeckling	Removal of unwanted 'specks' (user definable)
0 0	(straight document path)	2D adaptive threshold	Optimum threshold level calculated for every pixel –
Automatic size recognition	All page sizes can be introduced anywhere across	-	removes unwanted background
U	the scanning width	Color extraction	Reduces 24 bit scan to 8 or 4 bit using customizable
Interface	Fast SCSI-2		look-up tables (color models only)
Color adjustment	3x3 Matrix multiplier, R,G & B Tone curves,	Viewing	Interactive on-the-fly viewer
2	White and Black points	Line enhancement	Thickens fine lines and emphasizes edges
Interface	Dual ultra fast SCSI-2	Multibuffering	Non-stop scanning for quality and productivity
Pedestal	Standard (desktop compatible)	Image processing	Contrast and brightness adjustment on gray tones
D	100 to 240 V, 50 to 60 Hz	Image manipulation	Mirroring, rotating, black/white reversing
Power requirements			
Power requirements CS4000 Series:		Leading edge elimination	Skips leading edge for optimum efficiency
CS4000 Series: Weight	143.3 pounds (65 kg)	Leading edge elimination	Skips leading edge for optimum efficiency
CS4000 Series: Weight	143.3 pounds (65 kg)	0 1	Skips leading edge for optimum efficiency ommendations
CS4000 Series:	143.3 pounds (65 kg)	Leading edge elimination	Skips leading edge for optimum efficiency ommendations Pentium III, 500 Mhz
CS4000 Series: Weight Dimensions (w × d × h,	143.3 pounds (65 kg)	Leading edge elimination	Skips leading edge for optimum efficiency ommendations Pentium III, 500 Mhz 256 Mb RAM
CS4000 Series: Weight Dimensions (w × d × h, 4700 Series: Weight	143.3 pounds (65 kg)) 61.4" × 18.3" × 7.3" 95 lbs. (43 kg)	Leading edge elimination	Skips leading edge for optimum efficiency ommendations Pentium III, 500 Mhz 256 Mb RAM 10 GB Hard Drive
CS4000 Series: Weight Dimensions (w × d × h, 4700 Series: Weight	143.3 pounds (65 kg)) 61.4" × 18.3" × 7.3"	Leading edge elimination	Skips leading edge for optimum efficiency ommendations Pentium III, 500 Mhz 256 Mb RAM 10 GB Hard Drive Video board - 8 Mb
CS4000 Series: Weight Dimensions (w × d × h, 4700 Series: Weight Dimensions (w × d × h, Output catch tray	143.3 pounds (65 kg)) 61.4" × 18.3" × 7.3" 95 lbs. (43 kg)) 48.4" × 24.8" × 39.8" optional for CS4000 Series	Leading edge elimination	Skips leading edge for optimum efficiency ommendations Pentium III, 500 Mhz 256 Mb RAM 10 GB Hard Drive Video board - 8 Mb Windows 95 or higher
CS4000 Series: Weight Dimensions (w × d × h, 4700 Series: Weight Dimensions (w × d × h, Output catch tray Océ Color Copy Soft	143.3 pounds (65 kg)) 61.4" × 18.3" × 7.3" 95 lbs. (43 kg)) 48.4" × 24.8" × 39.8" optional for CS4000 Series tware – Scan and Print On-The-Fly	Leading edge elimination	Skips leading edge for optimum efficiency ommendations Pentium III, 500 Mhz 256 Mb RAM 10 GB Hard Drive Video board - 8 Mb
CS4000 Series: Weight Dimensions (w × d × h, 4700 Series: Weight Dimensions (w × d × h, Output catch tray Océ Color Copy Sof Systems supported	143.3 pounds (65 kg)) 61.4" × 18.3" × 7.3" 95 lbs. (43 kg)) 48.4" × 24.8" × 39.8" optional for CS4000 Series tware – Scan and Print On-The-Fly Windows 95 and Windows NT 4.x	Leading edge elimination Minimum Color Rec	Skips leading edge for optimum efficiency ommendations Pentium III, 500 Mhz 256 Mb RAM 10 GB Hard Drive Video board - 8 Mb Windows 95 or higher Ethernet board
CS4000 Series: Weight Dimensions (w × d × h, 4700 Series: Weight Dimensions (w × d × h, Output catch tray Océ Color Copy Soft	143.3 pounds (65 kg)) 61.4" × 18.3" × 7.3" 95 lbs. (43 kg)) 48.4" × 24.8" × 39.8" optional for CS4000 Series tware – Scan and Print On-The-Fly Windows 95 and Windows NT 4.x Océ CS5000 Series, Océ 5350, Encad Novajet	Leading edge elimination	Skips leading edge for optimum efficiency ommendations Pentium III, 500 Mhz 256 Mb RAM 10 GB Hard Drive Video board - 8 Mb Windows 95 or higher Ethernet board SCSI cable, scanning software, manual and
CS4000 Series: Weight Dimensions (w × d × h, 4700 Series: Weight Dimensions (w × d × h, Output catch tray Océ Color Copy Sof Systems supported	143.3 pounds (65 kg)) 61.4" × 18.3" × 7.3" 95 lbs. (43 kg)) 48.4" × 24.8" × 39.8" optional for CS4000 Series tware – Scan and Print On-The-Fly Windows 95 and Windows NT 4.x Océ CS5000 Series, Océ 5350, Encad Novajet PRO600e, HP DesignJets 2000/2500, 3000/3500,	Leading edge elimination Minimum Color Rec	Skips leading edge for optimum efficiency ommendations Pentium III, 500 Mhz 256 Mb RAM 10 GB Hard Drive Video board - 8 Mb Windows 95 or higher Ethernet board
CS4000 Series: Weight Dimensions (w × d × h, 4700 Series: Weight Dimensions (w × d × h, Output catch tray Océ Color Copy Sof Systems supported Printers supported	143.3 pounds (65 kg)) 61.4" × 18.3" × 7.3" 95 lbs. (43 kg)) 48.4" × 24.8" × 39.8" optional for CS4000 Series tware – Scan and Print On-The-Fly Windows 95 and Windows NT 4.x Océ CS5000 Series, Océ 5350, Encad Novajet PRO600e, HP DesignJets 2000/2500, 3000/3500, 1050/1055	Leading edge elimination Minimum Color Rec	Skips leading edge for optimum efficiency ommendations Pentium III, 500 Mhz 256 Mb RAM 10 GB Hard Drive Video board - 8 Mb Windows 95 or higher Ethernet board SCSI cable, scanning software, manual and
CS4000 Series: Weight Dimensions (w × d × h, 4700 Series: Weight Dimensions (w × d × h, Output catch tray Océ Color Copy Soft Systems supported Printers supported Copy modes	143.3 pounds (65 kg)) 61.4" × 18.3" × 7.3" 95 lbs. (43 kg)) 48.4" × 24.8" × 39.8" optional for CS4000 Series tware – Scan and Print On-The-Fly Windows 95 and Windows NT 4.x Océ CS5000 Series, Océ 5350, Encad Novajet PRO600e, HP DesignJets 2000/2500, 3000/3500, 1050/1055 Map, line art, photo, black/white, user filter	Leading edge elimination Minimum Color Rec	Skips leading edge for optimum efficiency ommendations Pentium III, 500 Mhz 256 Mb RAM 10 GB Hard Drive Video board - 8 Mb Windows 95 or higher Ethernet board SCSI cable, scanning software, manual and
CS4000 Series: Weight Dimensions (w × d × h, 4700 Series: Weight Dimensions (w × d × h, Output catch tray Océ Color Copy Sof Systems supported Printers supported	143.3 pounds (65 kg)) 61.4" × 18.3" × 7.3" 95 lbs. (43 kg)) 48.4" × 24.8" × 39.8" optional for CS4000 Series tware – Scan and Print On-The-Fly Windows 95 and Windows NT 4.x Océ CS5000 Series, Océ 5350, Encad Novajet PRO600e, HP DesignJets 2000/2500, 3000/3500, 1050/1055 Map, line art, photo, black/white, user filter Automatic—using a different profile for each	Leading edge elimination Minimum Color Rec	Skips leading edge for optimum efficiency ommendations Pentium III, 500 Mhz 256 Mb RAM 10 GB Hard Drive Video board - 8 Mb Windows 95 or higher Ethernet board SCSI cable, scanning software, manual and
CS4000 Series: Weight Dimensions (w × d × h, 4700 Series: Weight Dimensions (w × d × h, Output catch tray Océ Color Copy Soft Systems supported Printers supported Copy modes Color calibration	143.3 pounds (65 kg)) 61.4" × 18.3" × 7.3" 95 lbs. (43 kg)) 48.4" × 24.8" × 39.8" optional for CS4000 Series tware – Scan and Print On-The-Fly Windows 95 and Windows NT 4.x Océ CS5000 Series, Océ 5350, Encad Novajet PRO600e, HP DesignJets 2000/2500, 3000/3500, 1050/1055 Map, line art, photo, black/white, user filter Automatic—using a different profile for each ink/media/machine combination	Leading edge elimination Minimum Color Rec	Skips leading edge for optimum efficiency ommendations Pentium III, 500 Mhz 256 Mb RAM 10 GB Hard Drive Video board - 8 Mb Windows 95 or higher Ethernet board SCSI cable, scanning software, manual and
CS4000 Series: Weight Dimensions (w × d × h, 4700 Series: Weight Dimensions (w × d × h, Output catch tray Océ Color Copy Soft Systems supported Printers supported Copy modes Color calibration Copy functions	143.3 pounds (65 kg)) 61.4" × 18.3" × 7.3" 95 lbs. (43 kg)) 48.4" × 24.8" × 39.8" optional for CS4000 Series tware – Scan and Print On-The-Fly Windows 95 and Windows NT 4.x Océ CS5000 Series, Océ 5350, Encad Novajet PRO600e, HP DesignJets 2000/2500, 3000/3500, 1050/1055 Map, line art, photo, black/white, user filter Automatic—using a different profile for each ink/media/machine combination Preview, cropping, scaling, paneling, archiving	Leading edge elimination Minimum Color Rec	Skips leading edge for optimum efficiency ommendations Pentium III, 500 Mhz 256 Mb RAM 10 GB Hard Drive Video board - 8 Mb Windows 95 or higher Ethernet board SCSI cable, scanning software, manual and
CS4000 Series: Weight Dimensions (w × d × h, 4700 Series: Weight Dimensions (w × d × h, Output catch tray Océ Color Copy Soft Systems supported Printers supported Copy modes Color calibration	143.3 pounds (65 kg)) 61.4" × 18.3" × 7.3" 95 lbs. (43 kg)) 48.4" × 24.8" × 39.8" optional for CS4000 Series tware – Scan and Print On-The-Fly Windows 95 and Windows NT 4.x Océ CS5000 Series, Océ 5350, Encad Novajet PRO600e, HP DesignJets 2000/2500, 3000/3500, 1050/1055 Map, line art, photo, black/white, user filter Automatic—using a different profile for each ink/media/machine combination	Leading edge elimination Minimum Color Rec	Skips leading edge for optimum efficiency ommendations Pentium III, 500 Mhz 256 Mb RAM 10 GB Hard Drive Video board - 8 Mb Windows 95 or higher Ethernet board SCSI cable, scanning software, manual and

Processing

Océ machines and materials are marketed by the Océ Group of companies in Australia, Austria, Belgium, Brazil, Brunei, China, Czech Republic, Denmark, Finland, France, Germany, Hong Kong, Hungary, Ireland, Italy, Luxembourg, Malaysia, Netherlands, Norway, Poland, Portugal, Singapore, South Africa, Spain, Sweden, Switzerland, Taiwan, Thailand, United Kingdom and United States. Océ cooperates with licensees or distributors in most other countries of the world.

Océ Scanning Software – functions performed on-the-fly



Océ-USA, Inc.

Océ Wide Format Printing Systems 5450 North Cumberland Avenue Chicago, Illinois 60656 1-800-714-4427 1-773-714-4076 Fax 1-773-714-4056 http://www.oceusa.com email info@oceusa.com

Prints within seconds of scanning

Océ-Canada Inc.

4711 Yonge Street, Suite 1100 Toronto, Ontario M2N6K8 1-800-668-1945 1-416-224-5600 email INFO@oce.ca

Printing for Professionals



© 2000 Océ Illustrations and specifications do not necessarily apply to the standard version of machines in all local markets. Technical specifications subject to change without notice.