

**Model:** iR2200/2800/3300

**Ref. No. :** FF-T01-L5-000002-02

**Date :** May 25, 2001

REVISED

FF-T01-L5-000002-01(May 17, 2001):

Correcting typographical errors and addition of information, ①×3 on p. 1

© Canon (UK) Limited

**Location:** System

**Subject:** Network Scan Function

**Reason:** This bulletin announces about network scan function.

### Detail:

- ① ➡ The network scan function enables iR2200/2800/3300 to serve as a scanner connected to a network.  
~~The network scan function automatically comes on when the machine has a network card. Whether the network scan function is on or off can be checked in service mode.~~  
The network scan function may be turned on or off in service mode. It is turned on at time of shipment from the factory.

Follow the service mode menu as follows:

COPIER>OPTION>USER>NW-SCAN

0: Network scan function is off.

1: Network scan function is on. Pressing the function key displays the PullScan screen.

- ① ➡ ~~Note that the function cannot be turned on or off in service mode.~~  
~~Printer models do not support the network scan function.~~  
The settings used in service mode will be retained after the power is turned off.  
The following shows if the scan function is enabled or disabled in relation to the presence and absence of a network card.

		Network card	
		Present	Absent
Service mode NW-SCAN	ON	Enabled	Disabled
	OFF	Disabled	Disabled

• Applicable firmware version

System (MN-CONT) Ver.06.01 or later

① ➡ ~~05.15~~