

**Test flames
accurately:
Go Digital !**

C.A 5260

**MULTIMETER/
THERMOMETER**



- " μ A" range for ionisation current
- Temperature measurement up to 1000°C
- Large back-lit display
- HOLD function
- Ergonomic function selector switch
- Comes with croc-clip, "K" thermocouple... etc.



**CHAUVIN
ARNOUX**

An instrument for use in the real world!

The C.A 5260 gives you the best in specialist multimeter design for HVAC&R* applications.


With its shock-proof casing surround, this instrument combines robustness with high performance, coming with all the necessary functions for flame testing, including measurement of temperature, voltage, current, continuity, capacitance, and resistance.

Its no surprise that specialists in the HVAC&R field are "hot" for this multimeter!

* heating, ventilation, air conditioning and refrigeration.

Setting the ionisation current on a gas-fired boiler.

The optimum combustion setting can be achieved by connecting the C.A 5260 to the flame detector and using the μA DC range.



Measurement of a starting capacitor value on a single-phase motor.

- The 40 μF range gives good resolution.
- The instrument is positioned with the back-stand in the shock-proof surround, making measurements extremely easy to read.



Measuring the temperature of an electric motor casing.

- Direct temperature reading from display in $^{\circ}\text{C}$ or $^{\circ}\text{F}$
- Measurement is via a traditional "K" type surface thermocouple (thermo-compensated mini-plug).

Technical specifications	
AC/DC Voltages Input impedance	5 ranges: 400 mV, 4 - 40 - 400 - 600 V 10 m Ω
AC/DC Currents Protection	2 ranges: 400 μA , and 4000 μA 0.1 A HRC fuse
Continuity Resistance Diode test	yes 6 ranges: 400 Ω - 4 - 40 - 400 k Ω - 4 - 40 M Ω yes
Capacitance	3 ranges: 40 μF - 400 μF - 4000 μF
Temperature (via "K" thermocouple)	-40 to 1000 $^{\circ}\text{C}$ / -40 to 2000 $^{\circ}\text{F}$
LCD	4000 cts (digit height: 15 mm)
Auto range Hold Min / Max Back-light	yes yes yes yes
Standards	IEC 1010-1 CAT III 600 V pollution level 2

To order

■ C.A 5260 P01.1967.32Z

Comes in blister style packaging complete with all its accessories :

- 1 set of 1.2 m flexible test probe leads (red / black)
- 1 croc-clip (red)
- 1 thermocouple adapter
- 1 user's manual in 5 languages
- 1 "K" thermocouple
- 1 x 9 V battery
- 1 certificate of verification

Accessories:

- Holster (220 x 180 x 75 mm) P01.2980.36
- Shoulder bag (240 x 230 x 70 mm) P01.2980.33
- Carrying case (270 x 230 x 65 mm) P01.2980.38

A vast range of IEC 1010 and IP2X safety accessories: brochure on demand



▶ Contact us for details of the numerous "K" thermocouples available



Your distributor

FRANCE

190, rue Championnet
75876 Paris Cedex 18
Tel : (33) 01 44 85 44 85
Fax : (33) 01 46 27 73 89

UNITED KINGDOM

Waldeck House - Waldeck Road
Maidenhead SL6 8BR
Tel 01628 788 888
Fax 01628 628 099

<http://www.chauvin-arnoux.com>

 CHAUVIN
ARNOUX