

3012 HF DATA MODEM

FEATURES AT A GLANCE



- High speed
- Easy to use
- Robust signalling
- Data terminal software
- Cost effective
- Reliable
- Addressing modes
- Advanced Automatic Link Establishment (ALE) ready
- Serial port protection
- Status indicators

The 3012 HF Data Modem provides a fast, reliable and cost-effective computer text and data communication capability for organisations operating in areas with little or no telecommunications infrastructure.

HIGH SPEED

The 3012 signalling protocol, designed to maximise performance over typical long-range channels, combines with internal data compression to give an effective data transfer speed of up to 6,000 bps.

EASY TO USE

The 3012 interface is based on the AT industry standard. This enables use with many commercial software applications. It can be integrated into these systems to provide automatic operation and data transfer, email, data logging and remote control applications.

ROBUST SIGNALLING

Advanced error control technology provides error-free point-to-point transmission. The modulation and coding systems incorporate specific design features that minimise or eliminate the problems of:

- multi-path delay
- selective fading
- frequency offset error
- dynamic range limitations
- protocol cross-linking

DATA TERMINAL SOFTWARE

With Codan's UUPlus™ *Email for HF* software, the 3012 facilitates transmission and reception of email-based messages, and point-to-point file transfer between HF stations.

UUPlus™ *Email for HF* is compatible with any email client application that uses internet protocols POP3 and SMTP, such as Outlook Express™, Eudora™, Netscape™ and Pegasus Mail™.

COST EFFECTIVE

HF transmissions are free to air, so data can be sent without any of the expensive call charges associated with satellite systems.

RELIABLE

All CODAN™ equipment is built to survive in extreme conditions and comes with full product support. A three year warranty is available to every registered user.

ADDRESSING MODES

The 3012 can be used for selective, group or broadcast transmissions.

Selective mode is used for point-to-point communication with a single station.

Group mode can send data to up to 99 specified stations.

Broadcast mode can transmit to all stations listening on a selected channel.

Error-free transmission is guaranteed for selective mode, but not for group or broadcast mode in difficult transmission conditions.

HOW IT WORKS

The 3012 interfaces directly with a data-capable HF SSB transceiver (see details in *Specifications –Associated Equipment*) and an IBM compatible computer, programmed with Codan UUPlus™ *Email for HF* software.

The 3012 emulates full-duplex operation so that once a link is established, the modem acts as a transparent RS232 link between the two stations.

SPECIFICATIONS

| | |
|--------------------------------|---|
| High-speed data mode | Selective repeat ARQ Protocol 2400 bps—16 channels QPSK modulation |
| Link establishment mode | Proprietary link establishment 80 baud CHIRP |
| Data compression | In-built data compression |
| Rate of data transfer | Up to 6000 bps (compressed) Up to 1475 bps (uncompressed) |
| Transceiver interface | 9600 baud RS232 TR.29 based AT port |
| Primary power | 13.5 V DC nominal (250 mA maximum current consumption) 10.5 to 15 V DC operating range |
| Temperature | 0°C to +55°C operating (–40°C to +60°C storage) |
| Size and weight | 210 mm W x 240 mm D x 65 mm H (including rear connectors); 1.8 kg |

ASSOCIATED EQUIPMENT

| | |
|---------------------------|--|
| HF SSB transceiver | For fixed or mobile stations: CODAN™ NGT™ AR / ASR / SR with Option F |
| HF SSB transceiver | For fixed or mobile stations: CODAN™ NGT™ AR / ASR / SR with Option F |
| Option CALM™ | To fit FED-STD-1045 ALE capability for NGT™ series Transceiver |
| Remote control | CODAN™ NGT™ Remote Control System |

CODAN™ and NGT™ are trademarks of Codan Limited. Other brand, product and company names mentioned in this document are trademarks or registered trademarks of their respective holders.

Values noted are typical. Equipment descriptions and specifications subject to change without notice or obligation.

ALE READY

When a CODAN™ transceiver is equipped with CODAN™ Automated Link Management (CALM™) or Automatic Link Establishment (ALE), the 3012 will provide automatic channel selection prior to sending data.

SERIAL PORT PROTECTION

The 3012 has a built in opto-isolation on its serial port, eliminating direct electrical connection between the controlling PC and the transceiver system.

INDICATORS

A front panel LED indicator shows presence of power and modem link status.

WHO CAN USE IT

The 3012 is designed for any organisation that needs to transfer information over a wide operation area, especially in remote regions or in areas where the usual telecommunications infrastructure is unreliable.

Being mobile, the 3012 can be used to transfer data that has been collected in the field. It can be set up to provide remote control and monitoring functions.

RADIO COMMUNICATIONS

12-20131-EN Issue 7 6/2012

T: +61 8 8305 0311 **F:** +61 8 8305 0411 **E:** sales@codanradio.com
Codan Limited 81 Graves Street Newton South Australia 5074 Australia

