

RC50-C HF EMAIL SOFTWARE

➤ FEATURES AT A GLANCE



- Adaptive data rates up to 19200 bit/s
- NATO interoperable
- Data encryption
- Compatible with CALM™/ALE
- Intranet/Internet gateway

Codan's RC50-C HF Email software provides fast, efficient, error free email capability over HF radio. Operating in conjunction with Codan's HF Transceivers and RM50 range of Data Modems, the software operates on a standard Windows™ PC using a single USB port with no specialised PC hardware requirements. When installed, the software runs in the background requiring no user interaction.

ADAPTIVE DATA RATES UP TO 19200 BIT/S

When used with a CODAN™ ISB capable Transceiver data rates up to 19200 bit/s are possible. Data rates are fully adaptive to suit the prevailing channel conditions ensuring the fastest possible data rate is used at all times. Inbuilt compression and industry leading data rates minimise station on-air time.

NATO INTEROPERABLE

Operator control via a standard POP3 email client and the use of STANAG 5066 ensures the system is interoperable with other manufacturer's systems.

DATA ENCRYPTION

Over the air transmissions can be encrypted using AES-256 bit encryption. Additionally, the RC50-C system has been designed to support customer defined third party email encryption software for full end-to-end email encryption.

SIMPLIFIED OPERATION USING CALM™ / ALE

The RC50-C HF Email software integrates with Codan's enhanced CALM™/ALE linking system, simplifying operation and ensuring the best available channel is chosen for each data session.

INTRANET / INTERNET GATEWAY

RC50-C can be configured as a gateway to connect with a wider Intranet/WAN providing a fully integrated field email service.



SPECIFICATIONS

STANAG 5066

V1.2 Annex F.12 Compressed File Transport Protocol (CFTP)

SUPPORTED WAVEFORMS

Modulation

Data Rates

MIL-STD-188-110A

Coded PSK

75, 150, 300, 600, 1200, 2400

Uncoded PSK

4800

MIL-STD-188-110B (serial tone)

Coded PSK/QAM

3200, 4800, 6400, 8000, 9600

MIL-STD-188-110B (Appendix F) *

Coded PSK/QAM

ISB: 9600, 12800, 16000, 19200

STANAG 4539

Coded PSK/QAM

75, 150, 300, 600, 1200, 2400

3200, 4800, 6400, 8000, 9600

Uncoded PSK/QAM

12800

STANAG 4285

Coded PSK

75, 150, 300, 600, 1200, 2400

Uncoded PSK

1200, 2400, 3600

STANAG 4415

Coded PSK

75

STANAG 4529

Coded PSK

75, 150, 300, 600, 1200

Uncoded PSK

600, 1200, 1800

DATA RATE CONTROL

Adaptive, controlled by BER measurements, ISB 75 to 19200 bit/s, SSB 75 to 9600 bit/s

DATA INTERFACE

USB2.0 or 2 x RS232 Serial

MINIMUM PC SYSTEM REQUIREMENTS

Windows™ XP Professional SP2 or Windows™ 2000 Professional SP4

Compatible with Windows™ 7

Intel Pentium IV 800 MHz or better

6 GB or more of free space for email storage

512 MB or more of RAM

CD-ROM drive

POP3 / SMTP compliant email client

Access to any commercial POP3 / SMTP compliant email server for internet connectivity

RECOMMENDED TRANSCEIVERS

Envoy™ X2

NGT™ SR, SRx, MR, ASR, AR

Manpack 2110, 2110M

* Requires an ISB capable Transceiver

Consult Codan for configuration options

CODAN™, Envoy™ and NGT™ are trademarks of Codan Limited. Other brand, product and company names mentioned in this document are trademarks or registered trademarks of their respective holders.

Values noted are typical. Equipment descriptions and specifications subject to change without notice or obligation.



www.codanradio.com

CODAN RADIO COMMUNICATIONS

12-20271-EN Issue 3 5/2014

Australia: +61 8 8305 0528

US: +1 585 419 9970

UK: +44 1252 717 272

Canada: +1 250 382 8268

Dubai: +971 44 53 72 01

sales@codanradio.com