

# Project 25 Compliance Assessment Program

## Summary Test Report

Codan Radio Communications UR-4E460-00-000

STR-Daniels-100001

Test Item Description	
<b>Manufacturer</b>	Codan Radio Communications
<b>Manufacturer Contact</b>	Allison McLennan
<b>Product Name</b>	MT-4E Receiver UR-4E460-00-000 (450-470 MHz)
<b>Installed Options:</b>	<b>Hardware</b> 50164.3 50154.3 50149.3 50037.1
	<b>Firmware</b> 2.1.1.D.S1.4
<b>Installed Vocoder</b>	Enhanced Full Rate

Test Description
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.2.1.1 – Project 25 Phase 1 Common Air Interface Performance Conventional Mode Operation Base Station/Repeaters

Laboratory Information	
<b>P25 CAP Laboratory Code</b>	P25CAP081016
<b>Date(s) of Test</b>	May 6, 2009 to May 16, 2009
<b>Date(s) of Issue</b>	May 16, 2009

Informative References	
<b>Date</b>	<b>Title</b>
March 2010	P25-CAB-CAI_TEST_REQ

<b>P25-CAB-CAI_TEST_REQ – March 2010, Section 2.2.1.1 – Project 25 Phase 1 Common Air Interface Performance Conventional Mode Operation Base Station/Repeaters</b>		<b>DTR-P25CAP81016-3008UT8</b>	
<b>RECEIVER TESTS (450 – 470 MHz)</b>			
<b>Test Case</b>	<b>Description</b>	<b>Requirement</b>	<b>Results</b>
2.1.4	Reference Sensitivity	≤ -113 dBm (Class B)	P
2.1.5	Faded Reference Sensitivity	≤ -105 dBm (Class B)	P
2.1.7	Adjacent Channel Rejection	≥ 60 dB (Class B)	P
2.1.8	Co-Channel Rejection	≤ 9 dB	P
2.1.9	Spurious Response Rejection	≥ 70 dB (Class B)	P
2.1.10	Intermodulation Rejection	≥ 70 dB (Class B)	P
2.1.11	Signal Displacement Bandwidth	≥ 1000 Hz	P
2.1.17	Late Entry Unsquench Delay		
	No Talk Group or Encryption	≤ 125 ms	P
	Talk Group Only	≤ 370 ms	P
	Encryption Only	≤ 370 ms	N/A2
	Both (on clear or encrypted channel)	≤ 460 ms	N/A2
2.1.18	Receiver Throughput Delay	≤ 125 ms	P
<b>TX TESTS (N/A)</b>			
<b>Test Case</b>	<b>Description</b>	<b>Requirement</b>	<b>Results</b>
2.2.8	Unwanted Emissions: Adjacent Channel Power Ratio	≥ 67 dB	N/A1
2.2.14	Transmitter Throughput Delay	≤ 125 ms	N/A1
2.2.15	Frequency Deviation for C4FM		N/A1
	High Level signal Deviation	2544 Hz ≤ f <sub>dev</sub> ≤ 3111 Hz	
	Low Level Signal Deviation	848 Hz ≤ f <sub>dev</sub> ≤ 1037 Hz	
2.2.16	Modulation Fidelity	≤ 10 % (Class B)	N/A1
2.2.18	Transient Frequency Behavior		N/A1
	Time Interval t1 = 10.0 ms	{Δf} ≤ 12.5 kHz	
	Time Interval t2 = 25.0 ms	{Δf} ≤ 6.25 kHz	
	Time Interval t3 = 10.0 ms	{Δf} ≤ 12.5 kHz	

<b>Test Case Result Definitions</b>	
<b>No Test Performed</b>	-
<b>Test Does Not Apply to the Test Object</b>	N/A
<b>Test Object Meets Requirements</b>	P (Pass)
<b>Test Object Does Not Meet Requirements</b>	F (Fail)
<b>Test Object is Inconclusive</b>	I (Inconclusive)

<b>Comments</b>
N/A1: UR-4E460 is a modular receiver and therefore P25-CAB-CAI_TEST_REQ –March 2010, Section 2.2.1.1 Transmitter tests are not applicable and not supported by this module. N/A2: Encryption Only and Both test cases not applicable as tested device not equipped for Encryption.

The information contained herein has been provided by the manufacturer of the product with permission to make the information publically available. The Department of Homeland Security (DHS) is making this information available as a public service; however, DHS IS PROVIDING THE INFORMATION "AS IS." DHS MAKES NO EXPRESS OR IMPLIED WARRANTIES AND SPECIFICALLY, DHS MAKES NO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THE ACCURACY OR USE OF THIS INFORMATION. Reference to any specific commercial products, processes, or services by trade name, trademark, manufacturer, or otherwise does not constitute an endorsement by or a recommendation from DHS.

**OMB NO:** 1640-0015

**EXPIRATION DATE:** 07/31/2015

**Burden Statement**

An agency may not conduct or sponsor information collection and a person is not required to respond to this information collection unless it displays a current valid Office of Management and Budget control number and an expiration date. The control number for this collection is 1640-0015 and this form will expire on 07/31/2015. The estimated average time to complete this for is 60 minutes per respondent. If you have any comments regarding the burden estimate you can write to Department of Homeland Security, Science and Technology Directorate, Washington, DC 20528.

DHS FORM 10056 – June 2009