



FieldMaxII-P

Laser Energy Meter

The FieldMax™II-P, a next-generation laser measurement system that replaces the original FieldMax, features a new PC host interface, LabVIEW drivers, an ActiveX DLL server component, analog output and expanded pyroelectric sensor capability. This combination of features makes FieldMaxII-P the most powerful and versatile laser meter in its price range.

The value of the FieldMaxII-P is strengthened by the broad range of pyroelectric sensors available. These sensors enable FieldMaxII-P to measure UV, visible and IR laser output from the nanojoule to the joule range, and to work with pulsed lasers with repetition rates of up to 300 Hz.

FieldMaxII-P features a large, easy-to-read backlit LCD and an intuitive user interface with front panel buttons to access all features for simple operation.

To facilitate laser tuning, FieldMaxII-P provides a unique tuning feature that is fast and effective. Statistics are supported, including max., min., mean, and standard deviation.

FieldMaxII-P features SmartProbe™ compatibility, which lets users store sensor responsivity, the serial number, and other important information in an EEPROM that automatically loads into the energy meter.

This general-purpose meter is designed to accommodate a broad range of users, including developers, production testers, service technicians and general scientific users, as well as laser-based instrumentation builders. For production test applications, a LabVIEW Instrument driver and ActiveX DLL server component facilitate the development of custom testing routines and simplify integration with other test equipment. Field service applications will benefit from the meter's small size, rechargeable battery pack (optional), and responsive tuning indicator for peaking laser output. For general laboratory use, the FieldMaxII offers versatility, accuracy, and easy access to statistics and features, such as wavelength compensation and attenuation correction.

FEATURES

- **Large, bright, backlit LCD display**
- **Digital accuracy with analog-like movement for laser tuning**
- **Works with pyroelectric sensors**
- **Measures energy up to 300 pps**
- **Intuitive button-driven user interface**
- **USB 1.1 interface with complete host control capability**
- **Analog output with selectable full-scale voltage (1, 2, and 5V)**
- **LabVIEW drivers, applications software, ActiveX DLL server components**
- **Portable AC/DC operation**
- **Rechargeable battery pack (optional)**
- **Compact, rugged enclosure with stand**

COMPATIBILITY

- **Pyroelectric sensors**



FieldMaxII-P

Laser Energy Meter

		FieldMaxII-P
Specifications	Max. Measurable Energy Pyroelectric	(sensor-dependent) 300.0J
	Min. Measurable Energy Pyroelectric	(sensor-dependent) 1 nJ (up to 18.3V input from sensor)
	Displayable Full-Scale Energy Ranges Pyroelectric	(sensor-dependent) 3,000 nJ to 300.0J (manual ranging)
	Measurement Resolution	0.1% of full-scale
	Max. Rep. Rate (pulsed energy measurement)	300 Hz (every pulse)
	Accuracy Digital Meter System	±1.0% of reading Meter accuracy + sensor accuracy
	Display	58 x 73 mm, fixed-segment LCD with backlight
	Digital Tuning Needle	100 ms time constant
	Statistical Analysis	Min., max., mean, and standard deviation
	Computer Interface	USB 1.1
	Analog Output	1V, 2V, 5V, 100 ohm source impedance
	Internal Trigger	2 to 20% of full-scale, selectable
	Instrument Power	90 to 260 VAC, 50/60 Hz, AC power adapter (incl.) Six 1.5V alkaline batteries (incl.) 7.2V, 750 mAh rechargeable battery pack (optional)
	Temperature Operating Storage	5°C to 40°C (41°F to 104°F) -20°C to 70°C (-4°F to 158°F)
	Regulations Met	CE
	Size (H x W x D)	200 x 100 x 40 mm (7.87 x 3.94 x 1.57 in.)
Weight (including batteries)	0.5 kg (1.1 lb.)	
Controls & Connections	Front Panel PWR/BL Hz ZERO STAT AVG WAVE ATTN AREA TRIG SETUP/LOCAL ARROW KEYS	Toggle power switch and backlight Display rep. rate Zero stats Display statistics: max., min., mean, standard deviation Engage averaging Enter wavelength and engage wavelength compensation Enter attenuation factor and engage attenuation Enter area and engage area correction to display J/cm ² Select trigger level from 2 to 20% of full scale Enters setup mode and accepts selections; cancels PC host control Manually control range Select STAT value (min., max., mean, standard deviation) Select and change numerical values
	Left Side Panel	Power jack connector
	Right Side Panel	USB connector DB-25 smart probe connector
	Part Number*	1072789

*Supplied with six alkaline AA batteries, power cord, AC power adapter, 6 ft. USB cable, user manual, soft carrying case, and certificate of calibration.



COHERENT, INC.

7470 SW Bridgeport Road
Portland, OR 97224-7286
phone (800) 343-4912
(971) 327-2700
(971) 327-2778
e-mail LMC.sales@Coherent.com
web www.Coherent.com

Japan +81 (3) 5635 8700
Benelux +31 (30) 280 6060
France +33 (0)1 6985 5145
Germany +49 (6071) 9680
Italy +39 (02) 34 530 214
UK +44 (1353) 658 833

Coherent follows a policy of continuous product improvement. Specifications are subject to change without notice.

Coherent offers a limited warranty for all FieldMaxII-P systems. For full details of this warranty coverage, please refer to the Service section at www.Coherent.com or contact your local Sales and Service Representative.

