

This section contains a grid of 150 small diagnostic tables, arranged in 10 columns and 15 rows. Each table is a small data set with multiple columns and rows, likely representing different printer settings or diagnostic results. The text within these tables is too small to read clearly but appears to be organized into structured data blocks.

A small table located in the bottom right corner of the page, containing a few rows of data.

B01

CO1

MAINDEC-11-DZLAE-B MACY11 27(1006) 01-MAR-77 14:45 PAGE 1  
02-FEB-77 15:08

.REM +

#### IDENTIFICATION

PRODUCT CODE: MAINDEC-11-DZLAE-B-D  
PRODUCT NAME: LA180 PRINTER DIAGNOSTIC  
DATE CREATED: MARCH 1977  
MAINTAINER: DIAGNOSTIC GROUP  
AUTHOR: ROBERT BAKER  
R. QUENNEVILLE

THE INFORMATION IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT CORPORATION. DIGITAL EQUIPMENT CORPORATION ASSUMES NO RESPONSIBILITY FOR ANY ERRORS THAT MAY APPEAR IN THIS DOCUMENT.

THE SOFTWARE DESCRIBED IN THIS DOCUMENT IS FURNISHED UNDER A LICENSE AND MAY ONLY BE USED OR COPIED IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE.

DIGITAL EQUIPMENT CORPORATION ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS SOFTWARE ON EQUIPMENT THAT IS NOT SUPPLIED BY DIGITAL.

COPYRIGHT (C) 1975, 1977 BY DIGITAL EQUIPMENT CORPORATION



TABLE OF CONTENTS

- 1.0 ABSTRACT
- 2.0 REQUIREMENTS
  - 2.1 EQUIPMENT
  - 2.2 STORAGE
  - 2.3 PRELIMINARY PROGRAMS
- 3.0 LOADING PROCEDURE & INITIALIZATION
- 4.0 STARTING PROCEDURES
- 5.0 OPERATING PROCEDURES
  - 5.1 SWITCH REGISTER CONTROLS
  - 5.2 CONSOLE TERMINAL KEYBOARD CONTROL
  - 5.3 DYNAMIC SOFTWARE SWITCH REGISTER CONTROL
  - 5.4 ERROR REPORTING
  - 5.5 INTERFACE CONTROL
- 6.0 TEST DESCRIPTIONS
  - 6.1 OPERATOR INTERVENTION TESTS
    - 6.1.1 TEST 00 - PARALLEL INTERFACE TESTS
    - 6.1.2 TEST 01 - TOP OF FORM SWITCH TEST
    - 6.1.3 TEST 02 - PRINT SPEED TIMING TEST
  - 6.2 PRINTING TESTS
    - 6.2.1 TEST 20 - DATA TRANSFER PATHS TEST
    - 6.2.2 TEST 21 - HEAD POSITIONING TEST
    - 6.2.3 TEST 22 - BACKSPACE TEST
    - 6.2.4 TEST 23 - CHARACTER GENERATOR TEST
    - 6.2.5 TEST 24 - NON-PRINTABLE CHARACTER TEST
    - 6.2.6 TEST 25 - BUFFER TEST
    - 6.2.7 TEST 26 - OVERPRINT TEST
    - 6.2.8 TEST 27 - MULTIPLE LINE FEED TEST
    - 6.2.9 TEST 30 - RIBBON FEED TEST
    - 6.2.10 TEST 31 - BELL TEST
  - 6.3 OPTION TESTS
    - 6.3.1 TEST 50 - SECONDARY CHARACTER SET
  - 6.4 MAINTENANCE AIDS
    - 6.4.1 TEST 60 - LIFE TEST
    - 6.4.2 TEST 61 - SCOPE DRIVE ROUTINE
    - 6.4.3 TEST 62 - LINE PRINT TEST
    - 6.4.4 TEST 63 - CHARACTER PRINT TEST
    - 6.4.5 TEST 64 - SELECTED PATTERN PRINT TEST

## 1.0 ABSTRACT

THE DIAGNOSTICS FOR THE LA180 PRINTER ARE DESIGNED TO EXERCISE ALL AREAS OF THE PRINTER, SIMULATING WORSE CASE CONDITIONS TO DETECT BOTH MECHANICAL AND ELECTRICAL FAULTS. ADDITIONAL FACILITIES WITHIN THE DIAGNOSTIC PROGRAM WILL AID IN ISOLATION OF ANY FAULT CONDITIONS DETECTED.

OPERATION OF THE DIAGNOSTIC PROGRAM WILL BE CONTROLLED FROM THE PROCESSOR SWITCH REGISTER OR FROM AN AVAILABLE CONSOLE DEVICE. THE OPERATOR WILL BE GIVEN AS MUCH CONTROL OVER THE OPERATION OF THE PROGRAM AS POSSIBLE WHILE TRYING TO KEEP THE CONTROL SCHEME SIMPLE.

THIS DIAGNOSTIC PROGRAM WAS DESIGNED TO RUN IN 4K OR LESS OF MEMORY AND TO BE COMPATIBLE WITH ACT AND XXDP.

## 2.0 REQUIREMENTS

### 2.1 EQUIPMENT

THIS DIAGNOSTIC WAS WRITTEN TO RUN ON ALL MODELS OF THE PDP-11 PROCESSOR WITH A LA180 PRINTER USING EITHER A STANDARD PARALLEL INTERFACE OR A KL11/DL11 SERIAL INTERFACE. MULTIPLE LA180'S, ON INDIVIDUAL INTERFACES, CAN BE RUN TOGETHER PROVIDING THEY ARE ON EITHER ALL SERIAL OR ALL PARALLEL INTERFACES, AND PROVIDING THEIR ADDRESS ASSIGNMENTS ARE CONTIGUOUS. THE PROGRAM WILL USE A STANDARD CONSOLE DEVICE, IF AVAILABLE, FOR OPERATOR INSTRUCTIONS AND ERROR REPORTING. IT IS SUGGESTED THAT A CONSOLE DEVICE BE USED WHEN RUNNING THIS DIAGNOSTIC BUT IT IS NOT REQUIRED IF THE CPU HAS A HARDWARE SWITCH REGISTER. IF ANY NON-STANDARD ADDRESSES ARE USED FOR EITHER THE LA180 OR THE CONSOLE DEVICE, CHANGE THE ADDRESSES IN THE COMMON TAG AREA OF THE PROGRAM (STARTING AT LOCATION 1100).

### 2.2 STORAGE

THIS PROGRAM USES MOST OF 4K OF MEMORY WITHOUT AFFECTING THE AREA USED BY THE ABSOLUTE LOADER.

### 2.3 PRELIMINARY PROGRAMS

ALL APPLICABLE PDP-11 DIAGNOSTICS SHOULD BE RUN SUCCESSFULLY ON THE PROCESSOR.

### 3.0 LOADING PROCEDURE & INITIALIZATION

LOAD THE LA180 DIAGNOSTIC PROGRAM FOLLOWING NORMAL PROCEDURES.

IF A HARDWARE SWITCH REGISTER DOES NOT EXIST OR ALL SWITCHES ARE PLACED UP BEFORE STARTING THE DIAGNOSTIC, THE PROGRAM WILL USE THE CONTENTS OF LOCATION 176 AS THE VALUE OF THE SWITCHES. THEREFORE, WHEN USING THE SOFTWARE SWITCH REGISTER BE SURE TO LOAD LOCATION 176 WITH THE DESIRED SWITCH VALUE BEFORE STARTING THE PROGRAM. REFER TO SECTION 5.3 FOR DETAILS ON DYNAMIC SOFTWARE SWITCH REGISTER CONTROL.

REFER TO SECTION 5.5 FOR INTERFACE CONTROL INFORMATION.

REFER TO THE TEST ADDRESS TABLE IN THE PROGRAM LISTING FOR DETAILS ON CHANGING THE PRINTING TEST SEQUENCE OR DELETING TESTS FROM THE DIAGNOSTIC.

### 4.0 STARTING PROCEDURES

STARTING ADDRESSES:

200 = GENERAL START:  
RUN OPERATOR INTERVENTION TESTS THEN ENTER PRINTING TEST SEQUENCE. FOR USE ON SINGLE-PARALLEL INTERFACE ONLY.

600 = RESTART:  
ENTER PRINTING TEST SEQUENCE DIRECTLY SKIPPING OPERATOR INTERVENTION TESTS.

604 = GO DIRECTLY TO CONSOLE TERMINAL KEYBOARD CONTROL - SELECT TEST.

STARTING AT 200 WILL RUN THE ENTIRE DIAGNOSTIC PACKAGE. THE PROGRAM WILL FIRST EXECUTE THE OPERATOR INTERVENTION TESTS AND THEN ENTER THE PRINTING TEST SEQUENCE WHERE IT WILL LOOP CONTINUOUSLY. STARTING AT 600 (THE RESTART) WILL SKIP THE OPERATOR INTERVENTION TESTS AND ENTER THE PRINTING TEST SEQUENCE DIRECTLY. STARTING AT 604 WILL CAUSE THE PROGRAM TO GO DIRECTLY TO CONSOLE KEYBOARD CONTROL IF A CONSOLE DEVICE EXISTS, OTHERWISE, THE PROGRAM WILL HALT WAITING FOR A TEST SELECTION FROM THE SWITCH REGISTER. ALSO, BY PLACING THE HALT AND SELECT TEST SWITCH UP (1) BEFORE STARTING THE DIAGNOSTIC, THE DIAGNOSTIC WILL HALT WAITING FOR A TEST SELECTION FROM THE SWITCH REGISTER AFTER INITIALIZATION OF THE PROGRAM.

TO START THE DIAGNOSTIC PROGRAM: SET THE DESIRED STARTING ADDRESS IN THE SWITCH REGISTER AND DEPRESS LOAD ADDRESS. SET THE SWITCH REGISTER OPTIONS AS DESIRED (SEE SECTION 5.1), AND DEPRESS START. THE DIAGNOSTIC PROGRAM WILL NOW RUN IN THE MANNER SELECTED.

## 5.0 OPERATING PROCEDURES

## 5.1 SWITCH REGISTER CONTROLS

THE FOLLOWING, BASIC CONTROL FUNCTIONS ARE AVAILABLE THROUGH THE USE OF THE SWITCH REGISTER. IF A HARDWARE SWITCH REGISTER DOES NOT EXIST OR ALL SWITCHES WERE SET UP BEFORE STARTING THE DIAGNOSTIC, THE PROGRAM WILL USE THE CONTENTS OF LOCATION 176 AS THE VALUE OF THE SWITCH REGISTER. REFER TO SECTION 5.3 FOR DETAILS ON SSR CONTROL.

<u>SWITCH</u>	<u>POSITION</u>	<u>FUNCTION</u>
15	1 (UP) 0 (DWN)	STOP ON ERROR CONTINUE ON ERROR
14	1 (UP) 0 (DWN)	LOOP ON TEST NORMAL OPERATION
13	1 (UP) 0 (DWN)	INHIBIT ERROR TYPEOUT NORMAL OPERATION
11		MANUAL TIMING - OVER ALL PRINT SPEED TIMING
10	1 (UP) 0 (DWN)	BELL ON ERROR NORMAL OPERATION
09	1 (UP) 0 (DWN)	SINGLE CHAR - SCOPE ROUTINE FULL LINES
08	1 (UP) 0 (DWN)	HALT & SELECT TEST NORMAL OPERATION
07-00		* COLUMNS AT START UP.
05-00		TEST SELECTION DURING DIAG.
06-00		CHAR SELECTION FOR SCOPE ROUTINE

## 5.1.1 SWITCH 15 - STOP ON ERROR

WITH THIS SWITCH UP (1), THE PROGRAM WILL HALT OR WAIT FOR A KEYBOARD ON ANY DETECTED ERROR. WHEN DOWN (0), THE PROGRAM WILL CONTINUE ON ERROR IF POSSIBLE.

## 5.1.2 SWITCH 14 - LOOP ON TEST

WITH THIS SWITCH UP (1), THE PROGRAM WILL CONTINUE TO LOOP ON THE CURRENT TEST UNTIL THIS SWITCH IS PLACED DOWN (0). AFTER RETURNING THIS SWITCH TO THE DOWN (0) POSITION, THE TEST WILL CONTINUE NORMAL OPERATION AT THE COMPLETION OF THE CURRENT TEST. THUS, WHENEVER THIS SWITCH IS DOWN (0), THE PROGRAM WILL CONTINUE NORMAL OPERATION.

## 5.1.3 SWITCH 13 - INHIBIT ERROR TYPEOUT

WHENEVER THIS SWITCH IS IN THE UP (1) POSITION, ERROR TYPEOUTS WILL NOT OCCUR.

## 5.1.4 SWITCH 11 - MANUAL TIMING

THIS SWITCH WILL BE USED TO MANUALLY TIME THE OVERALL PRINT SPEED OF THE LA180 PRINTER IF A CLOCK OPTION DOES NOT EXIST.

## 5.1.5 SWITCH 10 - BELL ON ERROR

PLACING THIS SWITCH UP (1) WILL CAUSE THE CONSOLE (IF AVAILABLE) TO RING A BELL WHENEVER AN ERROR CONDITION IS DETECTED IN THE LA190 PRINTER.

## 5.1.6 SWITCH 9 - SINGLE CHAR/FULL LINES CHAR

THIS SWITCH WILL BE USED TO SELECT WHETHER TO SEND ONLY A SINGLE CHARACTER OR FULL LINES OF CHARACTERS TO THE LA190 PRINTER DURING TEST 61 ONLY.



## 5.1.7 SWITCH 8 - HALT &amp; SELECT TEST

THE PROGRAM WILL HALT WHENEVER THIS SWITCH IS PLACED IN THE UP (1) POSITION. AT THAT TIME, SET THE DESIRED TEST NUMBER IN THE PROPER POSITION IN THE PROCESSOR SWITCH REGISTER.

TO START THE NORMAL TEST SEQUENCE WITH THE SELECTED TEST, PLACE THE HALT AND SELECT TEST SWITCH DOWN (0) THEN DEPRESS THE CONTINUE SWITCH.

TO RUN A SELECTED TEST ONCE AND HALT, LEAVE THE HALT AND SELECT TEST SWITCH UP (1) AND DEPRESS CONTINUE. THE PROGRAM WILL EXECUTE ONE COMPLETE PASS OF THE SELECTED TEST, THEN HALT WAITING FOR ANOTHER TEST SELECTION. TO HALT THE PROGRAM DURING EXECUTION OF THE SELECTED TEST, PLACE THE HALT & SELECT TEST SWITCH DOWN (0) AT ANY TIME. THE PROGRAM WILL HALT AT THE COMPLETION OF THE CURRENT OPERATION AND WAIT FOR ANOTHER TEST SELECTION.

## 5.1.8 SELECTION OF NUMBER OF COLUMNS

THESE SWITCHES WILL BE USED WHEN THE PROGRAM IS FIRST STARTED TO INPUT THE DESIRED, MAXIMUM NUMBER OF COLUMNS THE DIAGNOSTIC IS TO TEST. THE NUMBER SET MUST BE IN OCTAL AND BE EQUAL TO OR GREATER THAN 2 AND LESS THAN OR EQUAL TO 132(10). IF THE SWITCHES ARE NOT SET WITHIN THESE SET LIMITS, THE PROGRAM WILL DEFAULT TO TESTING 132(10) COLUMNS. THUS, LEAVING THESE SWITCHES DOWN (000) THE PROGRAM WILL AUTOMATICALLY TEST THE FULL 132(10) COLUMNS.

## 5.1.9 TEST SELECTION

THESE SWITCHES WILL BE USED TO SELECT A DESIRED TEST WHENEVER THE HALT AND SELECT TEST SWITCH IS USED TO HALT THE DIAGNOSTIC PROGRAM.

## 5.2 CONSOLE TERMINAL - KEYBOARD CONTROL

WHENEVER A CONSOLE TERMINAL IS DETERMINED TO BE AVAILABLE BY THE PROGRAM, THE DIAGNOSTIC WILL BE CAPABLE OF BEING CONTROLLED FROM THE KEYBOARD OF THE CONSOLE DEVICE. TYPING A RUBOUT (DEL) ON THE CONSOLE KEYBOARD AT ANY TIME WILL CAUSE THE PROGRAM TO STOP AND PRINT THE FOLLOWING MESSAGE ON THE CONSOLE DEVICE:

SELECT TEST #:

TYPE ANY LEGAL TEST NUMBER FOLLOWED BY ONE OF THE FOLLOWING CONTROL CHARACTERS AND A CARRIAGE RETURN:

CHARACTER -----	FUNCTION -----
. (PERIOD)	RUN TEST ONCE & RETURN TO TEST SELECTION
L	LOOP ON SELECTED TEST
S	START SEQUENCE WITH SELECTED TEST

THE L AND S MAY BE EITHER UPPER OR LOWER CASE BUT TEST NUMBERS MUST ALWAYS BE ENTERED AS 2 DIGIT NUMBERS.

TO RESET THE DESIRED MAXIMUM NUMBER OF COLUMNS, TYPE A CONTROL-C (↑C) ON THE CONSOLE TERMINAL KEYBOARD AT ANY TIME, THE FOLLOWING MESSAGE WILL BE TYPED ON THE CONSOLE DEVICE:

# COLUMNS =

TYPE IN THE DESIRED NUMBER OF COLUMNS (IN DECIMAL) ON THE CONSOLE KEYBOARD FOLLOWED BY A CARRIAGE-RETURN. IF THE SELECTED NUMBER IS LESS THAN 2 OR GREATER THAN 132(10) THE MESSAGE WILL BE REPEATED AND YOU MUST REENTER THE NUMBER OF COLUMNS. WHEN A CORRECT NUMBER IS ENTERED, THE PROGRAM WILL THEN ASK FOR A TEST SELECTION AS DESCRIBED PREVIOUSLY IN THIS SECTION.

TO CHANGE THE NUMBER OF COLUMNS WHEN WAITING FOR A TEST SELECTION, TYPE A CONTROL-C FOLLOWED BY A CARRIAGE RETURN. WHILE INPUTTING A TEST SELECTION OR COLUMN NUMBER THE RUBOUT (DEL) KEY MAY BE USED TO DELETE INCORRECT ENTRIES. AT ALL TIMES SWITCH REGISTER CONTROL WILL STILL BE EFFECTIVE, EVEN IF USING CONSOLE TERMINAL KEYBOARD CONTROL.

### 5.3 DYNAMIC SOFTWARE SWITCH REGISTER CONTROL

WHENEVER A CONSOLE TERMINAL IS AVAILABLE AND A HARDWARE SWITCH REGISTER IS NOT AVAILABLE (OR ALL SWITCHES WERE UP WHEN THE PROGRAM WAS STARTED), THE PROGRAM WILL RECOGNIZE THE FOLLOWING DYNAMIC SOFTWARE SWITCH REGISTER CONTROL:

TYPING A CONTROL-G (BEL) AT ANY TIME DURING PROGRAM EXECUTION, EXCEPT WHEN WAITING FOR A TEST OR COLUMN NUMBER SELECTION, WILL CAUSE THE DIAGNOSTIC TO STOP THE CURRENT TEST AND TYPE THE FOLLOWING MESSAGE ON THE CONSOLE DEVICE:

SWR = XXXXXX NEW =

WHERE XXXXXX IS THE CURRENT CONTENTS OF THE SOFTWARE SWITCH REGISTER (SSR) IN OCTAL. THE SOFTWARE CONTROL ROUTINE WILL THEN AWAIT OPERATOR ACTION. THE OPERATOR IS THEN REQUIRED TO TYPE ONE OR MORE OF THE LEGAL CHARACTERS 1) 0-7, 2) LINE FEED <LF>, 3) CARRIAGE RETURN <CR>, OR 4) CONTROL-U (^U). NO CHECK IS MADE FOR CHARACTER LEGALITY. IF THE INPUT CHARACTER IS NOT A LF, CR, OR ^U IT IS ASSUMED TO BE AN OCTAL DIGIT AND WILL BE ECHOED AS THE DIGIT THAT IS GOING TO BE STORED IN THE SWITCH SETTING.

TO CHANGE THE CONTENTS OF THE SSR THE OPERATOR SIMPLY TYPES THE NEW DESIRED VALUE IN OCTAL, LEADING ZEROS NEED NOT BE TYPED. AND TERMINATES THE INPUT STRING WITH A <CR> OR <LF> DEPENDING ON THE PROGRAM ACTION DESIRED AS DESCRIBED BELOW. THE INPUT VALUE WILL BE TRUNCATED TO THE LAST 6 DIGITS TYPED. AT LEAST ONE DIGIT MUST BE TYPED PRIOR TO THE TERMINATOR BEFORE A CHANGE TO THE SSR WILL OCCUR.

WHEN THE INPUT STRING IS TERMINATED WITH A <CR> THE DIAGNOSTIC WILL CONTINUE EXECUTION FROM THE POINT AT WHICH IT WAS INTERRUPTED. IF A <CR> IS THE ONLY THING TYPED, THE PROGRAM WILL CONTINUE WITHOUT CHANGING THE SSR. IF A <LF> IS USED TO TERMINATE THE INPUT STRING, THE PROGRAM WILL THEN ASK FOR A TEST SELECTION AS DESCRIBED IN SECTION 5.2.

IF A ^U IS TYPED AT ANY POINT IN THE INPUT STRING PRIOR TO THE TERMINATOR, THE INPUT VALUE WILL BE DISREGARDED AND THE PROMPT MESSAGE WILL BE REPRINTED.

#### 5.4 ERROR REPORTING ON PARALLEL INTERFACE

IF A CONSOLE TERMINAL EXISTS AND THE INHIBIT ERROR TYPEOUT SWITCH IS DOWN (0) WHENEVER AN ERROR IS DETECTED THE FOLLOWING ERROR MESSAGE WILL BE PRINTED ON THE CONSOLE DEVICE:

TEST #XX, PC=XXXXXX, ERROR #XXX, MESSAGE >>>>>>>>>

THE ERROR MESSAGE INDICATES THE TEST NUMBER, THE LOCATION WHERE THE ERROR OCCURRED, THE ERROR NUMBER, AND THE TYPE OF ERROR THAT OCCURRED. FOR ADDITIONAL INFORMATION ON ANY ERROR CONDITION, REFER TO THE PROGRAM LISTING.

WHENEVER A CONSOLE TERMINAL IS NOT AVAILABLE THE HALT ON ERROR SWITCH SHOULD BE USED. AFTER AN ERROR OCCURS AND THE PROGRAM HALTS, EXAMINE THE CONTENTS OF \$ERRPC TO FIND THE ADDRESS WHERE THE ERROR OCCURRED AND \$ITEMB TO FIND THE ERROR NUMBER. THE TEST NUMBER WILL BE LOCATED IN EITHER THE HARDWARE OR SOFTWARE DISPLAY DEPENDING ON CPU TYPE. THEN REFER TO THE PROGRAM LISTING TO DETERMINE THE TYPE OF ERROR THAT OCCURRED AND TO FIND ANY ADDITIONAL INFORMATION REGARDING THAT ERROR. IF NEEDED, THE ERROR MESSAGES ARE LOCATED NEAR THE END OF THE PROGRAM LISTING.

#### 5.5 INTERFACE CONTROL

THIS DIAGNOSTIC, WHEN INITIALLY LOADED, IS PRECONDITIONED TO TEST A SINGLE LA180 ON A PARALLEL INTERFACE ADDRESSED AS 177510. THE DIAGNOSTIC CAN BE CONDITIONED TO RUN ON SERIAL INTERFACES BY DEPOSITING ANY NON-ZERO QUANTITY INTO LOCATION SERSW OR BY SELECTING AND RUNNING TEST 77. THE DIAGNOSTIC CAN BE RECONDITIONED TO RUN ON PARALLEL INTERFACES BY DEPOSITING ALL ZEROS INTO LOCATION SERSW OR BY SELECTING AND RUNNING TEST 76. THE NUMBER OF INTERFACES TO BE DRIVEN IS CONTROLLED BY THE QUANTITY IN LOCATION NUMLP. THE VALUE IN THIS LOCATION IS PRESET TO 1 AND SHOULD BE CHANGED IF MORE THAN 1 UNIT IS TO BE TESTED. THE ADDRESS OF THE LOWEST ADDRESSED PARALLEL INTERFACE (IF ANY) SHOULD BE DEPOSITED INTO LOCATION FSTPAD. THIS VALUE HAS BEEN PRESET TO 177510. THE ADDRESS OF THE LOWEST ADDRESSED SERIAL INTERFACE (IF ANY) SHOULD BE DEPOSITED INTO LOCATION FSTSAD. THIS VALUE HAS BEEN PRESET TO 175610.

#### 6.0 TEST DESCRIPTIONS

##### 6.1 OPERATOR INTERVENTION TESTS

THIS SERIES OF TESTS CONSISTS OF ALL TESTS NORMALLY EXECUTED WHICH COULD POSSIBLE REQUIRE OPERATOR INTERVENTION. THESE TESTS ARE EXECUTED ONLY ONCE EACH WHEN THE DIAGNOSTIC IS FIRST STARTED JP. A DETAILED DESCRIPTION OF EACH TEST FOLLOWS:

## 6.1.1 TEST 00 - INTERFACE &amp; CONTROL TESTS

THIS TEST IS DESIGNED AS A COMMAND DECODE AND CONTROL PARALLEL-INTERFACE TEST AND INCLUDES CHECKOUT OF THE PRINTER INTERRUPT FACILITY. MANUAL INTERVENTION IS REQUIRED TO TEST THE VARIOUS TESTABLE ERROR (NON-READY) CONDITIONS OF THE PRINTER. OPERATOR INSTRUCTIONS WILL BE PRINTED ON THE CONSOLE DEVICE IF AVAILABLE THEN THE PROGRAM WILL WAIT FOR THE OPERATOR TO COMPLETE THE ACTION. DEPRESS THE SPACE BAR ON THE CONSOLE KEYBOARD OR THE CONTINUE SWITCH ON THE CPU IF NO CONSOLE DEVICE IS AVAILABLE TO TEST THE NEXT CONDITION WHEN READY. IF ANY ERROR CONDITION EXISTS OR ANY NON-EXPECTED RESULTS ARE ENCOUNTERED, AN ERROR MESSAGE WILL BE PRINTED ON THE CONSOLE DEVICE IF AVAILABLE. (REFER TO SECTION 5.3 ON ERROR REPORTING.)

POWER SHOULD BE OFF ON THE LA180 BEFORE STARTING THIS TEST. THE PROGRAM WILL FIRST TEST THAT THE ERROR BIT IS SET AND THE PRINTER IS NOT READY WITH POWER OFF. AN INSTRUCTION WILL THEN ASK FOR THE PRINTER POWER TO BE TURNED ON. TURN POWER ON AND MAKE SURE THERE IS PAPER IN THE PRINTER AND THE PRINTER IS OFF LINE. THE DIAGNOSTIC WILL AGAIN CHECK THAT THE ERROR BIT IS SET AND THE PRINTER IS NOT READY. AN INSTRUCTION ON THE CONSOLE DEVICE WILL NEXT INFORM THE OPERATOR TO TURN THE LA180 ON LINE. THE PROGRAM WILL NOW CHECK THAT THE ERROR BIT IS CLEAR AND THE PRINTER IS READY. THE NEXT PRINTED INSTRUCTION WILL HAVE THE OPERATOR FORCE A PAPER OUT CONDITION BY OPENING THE PAPER FEED TRACTORS AND REMOVING THE PAPER FROM THE PRINTER. THE DIAGNOSTIC WILL CHECK THAT THE ERROR BIT IS SET AND PRINTER IS NOT READY. THE LAST INSTRUCTION WILL ASK TO RESTORE THE PRINTER TO ON-LINE BY RE-INSERTING PAPER AND CLEARING THE ERROR CONDITION. MAKE SURE THE PRINTER IS SET TO ON-LINE BEFORE CONTINUING. THE PROGRAM WILL TEST TO SEE IF THE ERROR BIT IS CLEARED AND THE PRINTER IS READY.

THE LAST HALF OF THIS TEST WILL BE PERFORMED AUTOMATICALLY WITHOUT FURTHER MANUAL INTERVENTION REQUIRED. THE DIAGNOSTIC WILL ISSUE A RESET INSTRUCTION AND SEE THAT THE ERROR BIT IS CLEAR AND THE PRINTER IS READY. A CARRIAGE RETURN WILL BE LOADED TO THE PRINTER TO SEE IF LOADING THE CHARACTER BUFFER WILL CLEAR THE READY BIT. THE TEST WILL THEN CHECK THAT THE ERROR BIT IS CLEAR AND THE PRINTER READY BIT DOES SET WITHIN A REASONABLE AMOUNT OF TIME. THE FINAL TEST WILL CHECK THAT THE PRINTER WILL NOT INTERRUPT ABOVE PRIORITY LEVEL 3 AND WILL INTERRUPT AT ALL PRIORITY LEVELS BELOW LEVEL 4.

### 6.1.2 TEST 01 - TOP OF FORM SWITCH TEST

THIS TEST CHECKS ALL POSITIONS OF THE TOP OF FORM SWITCH. THE PROGRAM WILL PRINT INSTRUCTIONS FOR THE NEXT SETTING OF THE TOP OF FORM SWITCH ON THE CONSOLE TERMINAL (IF AVAILABLE) AND THEN WAIT FOR THE OPERATOR TO COMPLETE THE ACTION. AFTER SETTING THE SWITCH, DEPRESS THE SPACE BAR OF THE CONSOLE DEVICE (OR CONTINUE ON THE PROCESSOR IF NO CONSOLE DEVICE EXISTS) TO TEST THAT SWITCH POSITION. AFTER CHECKING ALL POSITIONS, THE PRINTER OUTPUT CAN BE VISUALLY VERIFIED. A LINE OF ALL DASHES IS PRINTED AS A STARTING POINT AND THEN LINES ARE PRINTED TO INDICATE THE PROPER SPACING (IN INCHES) FROM THE PREVIOUS LINE TO THAT LINE.

EXAMPLE:

```
-----  

----- 4.0 INCH FORM FEED -----
```

### 6.1.3 TEST 02 - PRINT SPEED TIMING TEST

THIS TEST IS DESIGNED TO TIME THE LA180 FOR ONE FULL MINUTE WHILE A SWIRL PATTERN IS PRINTED TO THE SELECTED MAXIMUM NUMBER OF COLUMNS. IF A LINE CLOCK OR A PROGRAMMABLE CLOCK OPTION IS DETERMINED TO BE AVAILABLE BY THE PROGRAM, IT WILL BE USED TO AUTOMATICALLY TIME THE PRINTER. WHEN NEITHER CLOCK OPTION IS AVAILABLE, MANUAL TIMING WILL BE USED AND OPERATING INSTRUCTIONS WILL BE TYPED ON THE CONSOLE DEVICE IF IT IS AVAILABLE. WHICHEVER METHOD OF TIMING IS USED, AT THE END OF ONE FULL MINUTE THE APPROXIMATE PRINT SPEED WILL BE PRINTED ON THE LA180 AND ALSO ON THE CONSOLE DEVICE (IF AVAILABLE). REMEMBER, THE PRINT SPEED IS DIRECTLY RELATED TO THE NUMBER OF COLUMNS BEING PRINTED. ALSO, THE CONTENTS OF ONE LOCATION IN MEMORY WILL HAVE TO BE CHANGED IF THE LINE FREQUENCY IS 50 HZ. AND A CLOCK OPTION IS BEING USED FOR TIMING.

## 6.2 PRINTING TESTS

THESE TESTS ARE DESIGNED AS A TEST OF THE PRINTING MECHANISM AND THE ASSOCIATED CONTROL LOGIC. AT THE BEGINNING OF EACH TEST, A TEST HEADER WILL INDICATE THE TEST NUMBER BEING EXECUTED. THE TEST PROGRAM CONTINUALLY MONITORS FOR PROPER OPERATION OF THE LINE PRINTER AFTER EACH PRINTER OPERATION HAS BEEN COMPLETED, THROUGH THE PRINTER "READY" LINE AND THE SETTING OF THE "DEMAND" FLAG. IT SHOULD BE NOTED, HOWEVER, THAT THE "DEMAND" RETURN FROM THE PRINTER IS CONDITIONAL UPON THE PRINTER "READY". SINCE THE PROCESSOR CAN ONLY DETECT THE CURRENT CONDITION OF THE "READY" AND "DEMAND" RETURN LINES IT IS NECESSARY TO EXAMINE THE PRINT PATTERNS PRODUCED BY THE VARIOUS TEST ROUTINES. EACH PATTERN HAS BEEN CHOSEN FOR EASE OF VISUAL VERIFICATION. DETAILED DESCRIPTIONS OF EACH TEST PATTERN APPEARS IN THE DESCRIPTION OF THE FOLLOWING TEST ROUTINES.





6.2.4 TEST 23 - CHARACTER GENERATOR TEST

THIS TEST CHECKS THE SPACE ALL 94 PRINTABLE CHARACTERS (ASCII CODES 040 TO 176) BY PRINTING A SINGLE LINE, 30 CHARACTERS LONG, OF EACH CHARACTER.

EXAMPLE:

```
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
.
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
BBBBBBBBBBBBBBBBBBBBBBBBBBBBBB
```

6.2.5 TEST 24 - NON-PRINTABLE CHARACTER TEST

THIS TEST IS DESIGNED TO TEST THE LA180 HANDLING OF NON-PRINTABLE CHARACTERS AND TO EXERCISE THE FULL RANGE OF THE CHARACTER STORAGE BUFFER. THE TEST PATTERN PRODUCED WILL BE A 30 LINE SWIRL PATTERN, CONSISTING OF FULL LINES OF THE ENTIRE PRINTABLE CHARACTER SET. IF THIS TEST IS LOOPED ON, THE PATTERN WILL CONTINUE A FULL SWIRL, RATHER THAN ONLY 30 LINES AND THEN REPEATING. AS THE SWIRL PATTERN IS PRODUCED, THE GROUP OF PRINTABLE CHARACTERS WILL BE SHIFTED (IN INCREMENTS DEPENDING ON THE NUMBER OF COLUMNS BEING TESTED) THROUGH THE FULL RANGE OF THE CHARACTER BUFFER, STARTING AT THE END OF THE BUFFER. NON-PRINTABLE CHARACTERS WILL BE USED TO FILL THE CHARACTER BUFFER BEFORE AND AFTER THE GROUP OF PRINTABLE CHARACTERS, FOR EACH PRINTED LINE. ALL NON-PRINTABLE CHARACTERS HAVING NO CONTROL FUNCTION WITHIN THE LA180 WILL BE USED.

EXAMPLE:

```
!"#$%&'()*+,-./0123456789:;<=>?@ABC....
!"#$%&'()*+,-./0123456789:;<=>?@ABCD....
!"#$%&'()*+,-./0122456789:;<=>?@ABCDE....
```

6.2.6 TEST 25 - BUFFER TEST

THIS TEST IS DESIGNED TO TEST THE CHARACTER STORAGE BUFFER IN THE LA180 FOR PROPER OPERATION. THIS TEST WILL PRODUCE FOUR LINES OF PRINT WITH 2 BLANK LINES BETWEEN THE FIRST AND SECOND LINES. THE LINES PRINTED WILL ALSO SERVE AS A CHECK OF PRINTING THE CORRECT COLUMN WIDTH. THE PATTERNS ARE DESCRIBED FOR 132 COLUMNS BUT WILL BE SHORTENED ACCORDINGLY FOR NARROWER TEST WIDTHS. BEFORE THE FIRST LINE IS STORED, 16 E'S WILL BE LOADED INTO THE BUFFER. THEN A RUBOUT (177) WILL BE SENT TO CHECK THAT A RUBOUT WILL CLEAR THE BUFFER. BEFORE EACH OF THE LAST THREE LINES IS PRINTED AND BEFORE THE BLANK LINES BETWEEN THE FIRST AND SECOND PRINTED LINES, THE CHARACTER BUFFER WILL BE FILLED WITH ALL E'S. THUS, AN E PRINTED ANYWHERE IN THE TEST PATTERN INDICATES AN ERROR.



6.2.8 TEST 27 - MULTIPLE LINE FEED TEST

THIS TEST CHECKS THE LINE FEED CAPABILITY OF THE PRINTER BY SENDING VARIOUS GROUPS OF LINE FEEDS INTERSPACED WITH REFERENCE LINES. THE NUMBER PRINTED AT THE LEFT MARGIN OF THE REFERENCE LINE INDICATES THE NUMBER OF LINE FEEDS THAT FOLLOW. EACH LINE WILL CONTAIN A STRING OF DASHES AS REFERENCE POINTS FOR MEASURING, THE FIRST AND LAST BEING 132 CHARACTERS LONG (MAXIMUM) AND THE MIDDLE LINES BEING 30 CHARACTERS LONG.

EXAMPLE:

```
01-----  
02-----  
  
04-----  
  
08-----  
  > 7 BLANK LINES  
16-----  
  > 15 BLANK LINES  
32-----  
  > 31 BLANK LINES  
00-----
```

## 6.2.9 TEST 30 - RIBBON FEED TEST

THIS TEST CHECKS THE RIBBON FEED MECHANISM BY PRINTING A SINGLE COLUMN OF 24 LINES OF X'S DOWN THE LEFT HAND MARGIN OF THE PAGE. VISUALLY CHECK FOR PROPER OPERATION OF THE RIBBON FEED MECHANISM DURING THIS TEST.

EXAMPLE:

```
X  
X  
X  
.  
.  
X  
X  
X
```

## 6.2.10 TEST 31 - BELL TEST

THIS TEST IS DESIGNED TO CHECK THE BELL CODE LOGIC AND THE TIMING SEQUENCE OF THE MICRO LOGIC. THE TEST WILL PRINT "BELL TEST" INTERSPACED WITH BELL CODES BETWEEN CHARACTERS AND THE FOLLOWING CARRIAGE RETURN AND LINE FEED FUNCTIONS. A TOTAL OF FIVE BELLS WILL BE SOUNDED. THIS TEST WILL ALSO AUDIBLY INDICATE AN END OF A COMPLETE PASS THROUGH THE PRINTING TEST SEQUENCE.

EXAMPLE:

```
<BEL> BELL <BEL> <SP> TEST <BEL> <CR>  
<BEL> <LF> <BEL> <CR>
```

### 6.3 OPTION TESTS

#### 6.3.1 TEST 50 - SECONDARY CHARACTER SET OPTION

THIS TEST IS DESIGNED TO EXERCISE THE SECONDARY CHARACTER SET OPTION, TESTING THE ABILITY TO SELECT EITHER CHARACTER SET UNDER SOFTWARE CONTROL FROM THE CPU, AND ALSO TESTING THAT THE CORRECT CHARACTERS ARE PRINTED WITHIN EACH SET.

A NUMBER IS PRINTED AT THE LEFT MARGIN INDICATING WHICH CHARACTER SET IS BEING PRINTED. #1 INDICATES THE PRIMARY SET AND #2 INDICATES THE SECONDARY (APL) SET. FOLLOWING THE NUMBER THE APPROPRIATE CHARACTER SET, DISTINGUISHED BY THE ABSENCE OR PRESENCE OF THE 8TH BIT IN EACH CHARACTER, IS PRINTED IN ITS ENTIRETY.

IF LESS THAN 98 COLUMNS ARE BEING TESTED, ADDITIONAL LINE(S) WILL BE PRINTED TO COMPLETE EACH CHARACTER SET.

#### EXAMPLE:

```
#1= !"#$%&'()*...ETC..PRIMARY CHARACTER SET...
#2= !"#$%&'()*...ETC..SECONDARY CHARACTER SET...
```



## 6.4 MAINTENANCE AIDS

THESE TESTS ARE PROVIDED AS ADDITIONAL DEBUGGING AND EXERCISING AIDS FOR THE LA180 PRINTER. A DETAILED DESCRIPTION OF EACH TEST FOLLOWS.

## 6.4.1 TEST 60 - LIFE TEST

THIS TEST RUNS CONTINUOUSLY AND IS RUN AS AN INDIVIDUAL, SPECIAL TEST, AND IS NOT PART OF THE STANDARD PRINTING TEST SEQUENCE. THIS TEST PRINTS 2 LINES OF EACH PRINTABLE CHARACTER AND THEN REPEATS CONTINUOUSLY. THE SECOND LINE OF EACH CHARACTER IS OVERPRINTED 4 TIMES TO CONSERVE PAPER. AT THE COMPLETION OF EACH PASS THROUGH THE ENTIRE PRINTABLE CHARACTER SET, THE PASS COUNT WILL BE PRINTED ON THE LA180.

TIME FOR A COMPLETE PASS, WITH 132 COLUMNS IS APPROXIMATELY 10 MINUTES.

## EXAMPLE:

```
AAAAAAAAAAAAAAAAAAAA  
AAAAAAAAAAAAAAAAAAAA  
BBBBBBBBBBBBBBBBBB  
BBBBBBBBBBBBBBBBBB
```

## 6.4.2 TEST 61 - SCOPE DRIVE ROUTINE

THE PURPOSE OF THIS TEST IS TO PROVIDE THE OPERATOR WITH A SHORT BUT COMPREHENSIVE SCOPE DRIVER ROUTINE FOR USE IN TROUBLE SHOOTING THE PRINTER AND INTERFACE CONTROL LOGIC WITH AN OSCILLOSCOPE.

DEPENDING ON THE SETTING OF THE SINGLE CHAR/FULL LINE SWITCH OF THE SWITCH REGISTER (SWITCH 09) THIS TEST WILL EITHER CONTINUALLY SEND WHATEVER CHARACTER IS SET IN THE SWITCH REGISTER TO THE LINE PRINTER, OR ONLY SEND IT ONCE AND HALT. WHEN CONTINUOUSLY SENDING CHARACTERS, A LINE FEED WILL BE INSERTED AFTER THE MAXIMUM COLUMN COUNT IS REACHED TO PRINT THE LINE. WHEN SENDING SINGLE CHARACTERS, DEPRESS CONTINUE TO SEND THE CHARACTER SET IN THE SWITCH REGISTER. TO RESUME SENDING CONTINUOUS CHARACTERS, PLACE THE SINGLE CHAR/FULL LINE CONTROL SWITCH DOWN, SET THE DESIRED CHARACTER, AND DEPRESS CONTINUE. TO STOP SENDING CONTINUOUSLY PLACE THE SINGLE CHAR/FULL LINE SWITCH UP AND THE PROGRAM WILL HALT WAITING FOR A CHARACTER SELECTION. WHEN SENDING INDIVIDUAL CHARACTERS OR IF SENDING NON-PRINTABLE CHARACTERS, NO LINE FEEDS OR CARRIAGE RETURNS WILL BE INSERTED BY THE PROGRAM.

## 6.4.3 TEST 62 - LINE PRINT TEST

THIS TEST CONTINUOUSLY PRINTS FULL LINES OF WHATEVER CHARACTER IS TYPED ON THE CONSOLE KEYBOARD. TO CHANGE CHARACTERS, RESELECT THIS TEST AND TYPE ANOTHER CHARACTER. AN ERROR MESSAGE WILL BE PRINTED ON THE LA180 IF THIS TEST IS SELECTED AND A CONSOLE TERMINAL DOES NOT EXIST.

## 6.4.4 TEST 63 - CHARACTER PRINT TEST

THIS TEST LOADS WHATEVER CHARACTER IS TYPED ON THE CONSOLE KEYBOARD TO THE LA180, CHARACTER BY CHARACTER. ALL TYPED CHARACTERS ARE ECHOED TO THE CONSOLE DEVICE AS THEY ARE LOADED TO THE LA180. EXTRA CARRIAGE RETURNS OR LINE FEEDS ARE ECHOED TO THE CONSOLE DEVICE TO AVOID OVERPRINTING LINES. IF THIS TEST IS SELECTED AND A CONSOLE TERMINAL DOES NOT EXIST AN ERROR MESSAGE WILL BE PRINTED ON THE LA180.

## 6.4.5 TEST 64 - SELECTED PATTERN PRINT TEST

THIS TEST REPEATEDLY LOADS THE LA180 PRINTER BUFFER WITH A STRING OF DATA RESIDING IN STORAGE. THIS STRING IS ESTABLISHED BY TYPING ON THE CONSOLE KEYBOARD AND TERMINATING THE STRING BY DEPRESSING EITHER CTL-A OR CTL-B. PRINTING THEN BEGINS AUTOMATICALLY. PRINTING CAN BE INTERRUPTED BY DEPRESSING CTL-SPACE WHEREUPON A NEW PATTERN CAN BE ENTERED. IF CTL-A OR CTL-B IS THE FIRST KEY DEPRESSED, PRINTING OF THE INTERRUPTED PATTERN WILL RESUME.

IF A PATTERN OF CHARACTERS IS TO BE REPEATED OVER AND OVER (ON A SINGLE LINE) IT IS ONLY NECESSARY TO ENTER THE PATTERN ONCE AND THEN DEPRESS CTL-B. EXAMPLE: IF ABC(SP)(CTL-B) IS ENTERED, EACH LINE PRINTED WILL BE ABC ABC ABC ABC ETC., (TO MAXIMUM NUMBER OF SPECIFIED COLUMNS).

NOTE THAT NO PRINT COMMAND CODE (LF, CR, OR FF) IS USED WHEN ENTERING PATTERNS TO BE REPEATED BY CTL-B.

OPTIONALLY PRINT COMMANDS CAN BE ENTERED INTO THE CHARACTER STRING TO OBTAIN ALMOST ANY DESIRED SEQUENCE OF ACTIONS. SUCH A STRING SHOULD BE TERMINATED BY DEPRESSING CTL-A ONLY.

NOTE THAT THE STRING IS STORED AT THE END OF ALL DIAGNOSTIC CODING THEREBY ALLOWING IT TO BE OPEN-ENDED IN LENGTH (UP TO THE MEMORY LIMIT).

TO STOP PRINTING AND ENTER A NEW STRING DEPRESS CTL-SPACE. TO SELECT A NEW TEST DEPRESS DELETE/RUBOUT. TO CHANGE THE NUMBER OF COLUMNS DEPRESS CTL-C.

MAINDEC-11-DZLAE-B MACY11 27(1006) 01-MAR-77 14:45 PAGE 21  
 DZLAEB.P11 28-FEB-77 15:08

.ENABLE ABS,AMA

```

: TITLE MAINDEC-11-DZLAE-B
:* COPYRIGHT (C) 1977
:* DIGITAL EQUIPMENT CORP.
:* MAYNARD, MASS. 01754
:*
:* PROGRAM BY ROBERT BAKER
:*
:* THIS PROGRAM WAS ASSEMBLED USING THE PDP-11 MAINDEC SYSMAC
:* PACKAGE (MAINDEC-11-DZQAC-C3), JAN 19, 1977.
:*

```

.SBTTL OPERATIONAL SWITCH SETTINGS

```

:*
:* SWITCH USE
:* -----
:* 15 HALT ON ERROR
:* 14 LOOP ON TEST
:* 13 INHIBIT ERROR TYPEOUTS
:* 12 MANUAL TIMING
:* 10 BELL ON ERROR
:* 9 SNGL CHAR/FULL LINE - SCOPE ROUTINE
:* 8 HALT & SELECT TEST
:*
:* 07--00 * COLUMNS AT START UP
:*
:* 05--00 TEST * SELECTION
:*
:* 06--00 CHAR SELECTION FOR SCOPE ROUTINE

```

```

:*** SET ALL SWITCHES UP BEFORE STARTING THE PROGRAM TO USE THE
: SOFTWARE SWITCH REGISTER CONTROL. MAKE SURE LOCATION 000176
: CONTAINS THE DESIRED SWITCH SETTINGS BEFORE STARTING.

```

## .SBTTL BASIC DEFINITIONS

```

001100      ;*INITIAL ADDRESS OF THE STACK POINTER *** 1100 ***
            STACK= 1100
            .EQUIV EMT,ERROR      ;;BASIC DEFINITION OF ERROR CALL
            .EQUIV IOT,SCOPE     ;;BASIC DEFINITION OF SCOPE CALL

;*MISCELLANEOUS DEFINITIONS
000011      HT= 11              ;;CODE FOR HORIZONTAL TAB
000012      LF= 12              ;;CODE FOR LINE FEED
000015      CR= 15              ;;CODE FOR CARRIAGE RETURN
000200      CRLF= 200           ;;CODE FOR CARRIAGE RETURN-LINE FEED
177776      PS= 177776         ;;PROCESSOR STATUS WORD
            .EQUIV PS,PSW
177774      STKLMT= 177774     ;;STACK LIMIT REGISTER
177772      PIRQ= 177772       ;;PROGRAM INTERRUPT REQUEST REGISTER
177570      DSWR= 177570       ;;HARDWARE SWITCH REGISTER
177570      ODISP= 177570      ;;HARDWARE DISPLAY REGISTER

;*GENERAL PURPOSE REGISTER DEFINITIONS
000000      R0= %0             ;;GENERAL REGISTER
000001      R1= %1             ;;GENERAL REGISTER
000002      R2= %2             ;;GENERAL REGISTER
000003      R3= %3             ;;GENERAL REGISTER
000004      R4= %4             ;;GENERAL REGISTER
000005      R5= %5             ;;GENERAL REGISTER
000006      R6= %6             ;;GENERAL REGISTER
000007      R7= %7             ;;GENERAL REGISTER
000006      SP= %6             ;;STACK POINTER
000007      PC= %7             ;;PROGRAM COUNTER

;*PRIORITY LEVEL DEFINITIONS
000000      PR0= 0             ;;PRIORITY LEVEL 0
000040      PR1= 40            ;;PRIORITY LEVEL 1
000100      PR2= 100           ;;PRIORITY LEVEL 2
000140      PR3= 140           ;;PRIORITY LEVEL 3
000200      PR4= 200           ;;PRIORITY LEVEL 4
000240      PR5= 240           ;;PRIORITY LEVEL 5
000300      PR6= 300           ;;PRIORITY LEVEL 6
000340      PR7= 340           ;;PRIORITY LEVEL 7

;*"SWITCH REGISTER" SWITCH DEFINITIONS
100000      SW15= 100000
040000      SW14= 40000
020000      SW13= 20000
010000      SW12= 10000
004000      SW11= 4000
002000      SW10= 2000
001000      SW09= 1000
000400      SW08= 400
000200      SW07= 200
000100      SW06= 100
000040      SW05= 40
000020      SW04= 20
000010      SW03= 10
000004      SW02= 4

```

000002  
000001

SW01= 2  
SW00= 1  
.EQUIV SW09,SW9  
.EQUIV SW08,SW8  
.EQUIV SW07,SW7  
.EQUIV SW06,SW6  
.EQUIV SW05,SW5  
.EQUIV SW04,SW4  
.EQUIV SW03,SW3  
.EQUIV SW02,SW2  
.EQUIV SW01,SW1  
.EQUIV SW00,SW0

100000  
040000  
020000  
010000  
004000  
002000  
001000  
000400  
000200  
000100  
000040  
000020  
000010  
000004  
000002  
000001

.\*DATA BIT DEFINITIONS (BIT00 TO BIT15)

BIT15= 100000  
BIT14= 40000  
BIT13= 20000  
BIT12= 10000  
BIT11= 4000  
BIT10= 2000  
BIT09= 1000  
BIT08= 400  
BIT07= 200  
BIT06= 100  
BIT05= 40  
BIT04= 20  
BIT03= 10  
BIT02= 4  
BIT01= 2  
BIT00= 1  
.EQUIV BIT09,BIT9  
.EQUIV BIT08,BIT8  
.EQUIV BIT07,BIT7  
.EQUIV BIT06,BIT6  
.EQUIV BIT05,BIT5  
.EQUIV BIT04,BIT4  
.EQUIV BIT03,BIT3  
.EQUIV BIT02,BIT2  
.EQUIV BIT01,BIT1  
.EQUIV BIT00,BIT0

000004  
000010  
000014  
000014  
000014  
000020  
000024  
000030  
000034  
000060  
000064  
000240

.\*BASIC "CPU" TRAP VECTOR ADDRESSES

ERRVEC= 4 ; TIME OUT AND OTHER ERRORS  
RESVEC= 10 ; RESERVED AND ILLEGAL INSTRUCTIONS  
TBITVEC=14 ; "T" BIT  
TRIVEC= 14 ; TRACE TRAP  
BPTVEC= 14 ; BREAKPOINT TRAP (BPT)  
IOTVEC= 20 ; INPUT/OUTPUT TRAP (IOT) \*\*SCOPE\*\*  
PWRVEC= 24 ; POWER FAIL  
EMTVEC= 30 ; EMULATOR TRAP (EMT) \*\*ERROR\*\*  
TRAPVEC=34 ; "TRAP" TRAP  
TKVEC= 60 ; TTY KEYBOARD VECTOR  
TPVEC= 64 ; TTY PRINTER VECTOR  
PIRQVEC=240 ; PROGRAM INTERRUPT REQUEST VECTOR

000015  
000012  
000014  
000200

CR=15  
LF=12  
FF=14  
CRLF=200

\*\*\*\*\*  
.SBTTL TRAP CATCHER

000000

. =0  
;\*ALL UNUSED LOCATIONS FROM 4 - 776 CONTAIN A ".+2,HALT"  
;\*SEQUENCE TO CATCH ILLEGAL TRAPS AND INTERRUPTS  
;\*LOCATION 0 CONTAINS 0 TO CATCH IMPROPERLY LOADED VECTORS

000174  
000175

. =174  
DISPREG: .WORD 0 ;:SOFTWARE DISPLAY REGISTER  
SWREG: .WORD 0 ;:SOFTWARE SWITCH REGISTER

.SBTTL ACT11 HOOKS

\*\*\*\*\*  
;HOOKS REQUIRED BY ACT11

000046  
000052

000200 \$SVPC=. ;SAVE PC  
000046 . =46  
005322 \$ENDAD ;:1)SET LOC.46 TO ADDRESS OF \$ENDAD IN .SEJP  
000052 . =52  
020000 .WORD 20000 ;:2)SET LOC.52 TO 20000  
000200 .=\$SVPC ;: RESTORE PC



;;\*\*\*\*\*

```

000030          . = 30
000030 007744   $ERROR          ;EMT - ERROR HANDLER
000032 000000   0
000100          . = 100
000100 ^06566   LKSRV          ;KW11-L INTERRUPT
000102 000000   0
000104 006556   DCI            ;KW11-P INTERRUPT
000106 000000   0

```

;;\*\*\*\*\*

.SBTTL STARTING ADDRESSES

```

000200          . = 200
000200 000137 001174   JMP      START          ;GENERAL START
000600          . = 600
000600 000137 001210   JMP      RESTRT         ;RESTART - NO INTERACTIVE TESTS
000604 000137 001220   JMP      CONTRL        ;GO TO KEYBOARD CONTROL
                                ;WILL DEFAULT TO SWITCH REG
                                ;IF CONSOLE DEVICE DOES NOT EXIST

```

;;\*\*\*\*\*

.SBTTL COMMON TAGS

```

001100          . = 1100
001100 177560   TKS:          ;TTY KYBD STATUS REG. ADDRESS
001102 177562   TKB:          ;TTY KYBD BUFFER REG. ADDRESS
001104 177564   TPS:          ;TTY PRINTER STATUS REG. ADDRESS
001106 177566   TPB:          ;TTY PRINTER BUFFER REG. ADDRESS

```

```

.EQUIV TKS,$TKS
.EQUIV TKB,$TKB
.EQUIV TPS,$TPS
.EQUIV TPB,$TPB

```

001110	000000	LPKS:	0	;	THE FOLLOWING 4 LOCATIONS ARE INITIALIZED
				;	BY THE PROGRAM
				;	LINE PRINTER KBD STATUS REG ADDRESS
				;	(IF SERIAL INTERFACE)
				;	BIT 6 = INTERRUPT ENABLE
001112	000000	LPKB:	0	;	LINE PRINTER KBD BUFFER REG ADDRESS
001114	000000	LPS:	0	;	LINE PRINTER STATUS REG. ADDRESS
				;	BIT 15 = ERROR (IF PARALLEL INTERFACE)
				;	BIT 7 = READY
				;	BIT 6 = INTERRUPT ENABLE
001116	000000	LPB:	0	;	LINE PRINTER DATA BUFFER REG. ADDRESS
				;	BITS 0-6 = ASCII CHAR BUFFER
				;	BITS 7-15 = NOT USED
001120	000000	SERSW:	0	;	SERIAL SWITCH. THE PRESENCE OF ANY 1-BITS
				;	IN THIS WORD WILL INDICATE THAT
				;	SERIAL-INTERFACED LA180'S ARE TO BE TESTED.
				;	DEFAULT IS ALL 0'S = PARALLEL INTERFACE.
001122	000001	NUMLP:	1	;	THE NUMBER OF LA180'S WHICH THIS
				;	DIAGNOSTIC WILL ATTEMPT TO TEST.
				;	DEFAULT = 1
001124	175610	FSTSAD:	175610	;	FIRST LA180 ADDRESS TO BE USED IF INTERFACE-
				;	TYPE INDICATED IN LOCATION SERSW IS SERIAL.
001126	177510	FSTPAD:	177510	;	FIRST LA180 ADDRESS TO BE USED IF INTERFACE-
				;	TYPE INDICATED IN LOCATION SERSW IS PARALLEL.
001130	000000	ACTFST:	0	;	ACTUAL FIRST ADDRESS BEING USED
				;	DURING PROGRAM EXECUTION. INITIALIZED BY PROGRAM ITSELF
001132	000000	LPCTR:	0	;	LP COUNTER (USED BY PROGRAM ONLY)
001134	172540	PLKS:	172540	;	KL11-P CLOCK STATUS REG. ADDRESS
001136	172542	CSBR:	172542	;	KL11-P COUNT SET ADDRESS
001140	177546	LKS:	177546	;	KW11-L CLOCK STATUS REG. ADDRESS
001142	177570	SWR:	.WORD 177570	;	SW REG ADDRESS
001144	177570	DISPLAY:	.WORD 177570	;	DISPLAY ADDR

001146 000000  
001150 000204  
001152 000  
001153 000  
001154 000  
  
001155 000

\$STNM: .WORD 0  
WIDTH: .WORD 132.  
STRONE: .BYTE 0  
TRONE: .BYTE 0  
TLOOP: .BYTE 0  
  
CKFLAG: .BYTE 0

; TEST NUMBER  
; NUMBER OF COLUMNS  
; RUN TEST ONCE FLAG (SW REG CTL)  
; RUN TEST ONCE FLAG (KYBD CTL)  
; LOOP ON TEST FLAG (KYBD CTL)  
  
; CLOCK OPTION FLAG  
; 0 = NONE AVAILABLE  
; +1 = KL11-L  
; -1 = KL11-P

001156 000207  
001160 077  
001161 015  
001162 000012  
  
001164 000015  
001166 000014

\$BELL: .ASCIZ <207>  
\$QUES: .ASCII /?/  
\$CRLF: .ASCII <15>  
\$LF: .ASCIZ <12>  
  
\$^: .ASCIZ <15>  
\$F: .ASCIZ <14>

; BELL CODE  
; QUESTION MARK  
; CARRIAGE RETURN - LINE FEED  
; LINE FEED  
  
; CARRIAGE RETURN ONLY  
; FORM FEED

.EVEN

\*\*\*\*\*  
; THE FOLLOWING LOCATIONS ARE USED BY THE TTY TYPE ROUTINES  
; SET THE FILL CHARACTERS AS REQUIRED FOR VARIOUS CONSOLE TERMINALS  
; THE TERMINAL AVAILABLE FLAG WILL BE SET BY THE PROGRAM.

001170 000  
001171 002  
001172 012  
001173 000

\$NULL: .BYTE 0  
\$FILLS: .BYTE 2  
\$FILLC: .BYTE 12  
\$TPFLG: .BYTE 0

; NULL CHARACTER FOR FILLS  
; NUMBER OF FILLER CHARACTERS REQUIRED  
; INSERT FILL CHARACTERS AFTER LINE FEED  
; TERMINAL UNAVAILABLE FLAG  
; BIT <07> = 1 = UNAVAILABLE

.EVEN

::\*\*\*\*\*

.SBTTL PROGRAM INITIALIZATION

```

001174 005037 001146 000046 START: CLR $STSTM ;SET TEST NUMBER TO ZERO
001200 023737 000042 000046 CMP @#42,@#46 ;CHECK IF IN ACT QUICK VERIFY
;SKIP MANUAL INTERVENTION TESTS IF YES
001206 001007 000020 001146 RESTR: BNE STARTX ;INITIALIZE
001210 012737 000020 001146 MOV #20,$STSTM ;SET TEST NUMBER TO 20
001216 000403 000020 001146 BR STARTX ;INITIALIZE
001220 012737 177777 001146 CONTRL: MOV #-1,$STSTM ;SET CONTROL FLAG
001226 012737 177570 001142 STARTX: MOV #177570,SWR ;INITIALIZE SWR CONTROL
001234 013737 001142 001144 MOV SWR,DISPLAY
.SBTTL INITIALIZE THE COMMON TAGS
001242 012706 001100 MOV #STACK,SP ;;SETUP THE STACK POINTER
;;INITIALIZE A FEW VECTORS
001246 012737 013060 000034 MOV #STRAP,@TRAPVEC ;;TRAP VECTOR FOR TRAP CALLS
001254 012737 000340 000036 MOV #340,@TRAPVEC+2;LEVEL 7
001262 012737 013210 000024 MOV #SPWRDN,@PWRVEC ;;POWER FAILURE VECTOR
001270 012737 000340 000026 MOV #340,@PWRVEC+2 ;LEVEL 7
001276 005037 005336 005300 CLR $PASS ;CLEAR THE PASS COUNT
001302 013737 005306 005300 MOV $ENDCT,$EOPCT ;SETUP END-OF-PROGRAM COUNTER
;;SIZE FOR A HARDWARE SWITCH REGISTER. IF NOT FOUND OR IT IS
;;EQUAL TO A "-1", SETUP FOR A SOFTWARE SWITCH REGISTER.
001310 013746 000004 000004 MOV @ERRVEC,-(SP) ;SAVE ERROR VECTOR
001314 012737 001350 000004 MOV #64$,@ERRVEC ;SET UP ERROR VECTOR
001322 012737 177570 001142 MOV #DSWR,SWR ;SETUP FOR A HARDWARE SWICH REGISTER
001330 012737 177570 001144 MOV #DDISP,DISPLAY ;AND A HARDWARE DISPLAY REGISTER
001336 022777 177777 177576 CMP #-1,@SWR ;TRY TO REFERENCE HARDWARE SWR
001344 001012 000004 000004 BNE 66$ ;BRANCH IF NO TIMEOUT TRAP OCCURRED
;AND THE HARDWARE SWR IS NOT = -1
001346 000403 000004 000004 BR 65$ ;BRANCH IF NO TIMEOUT
001350 012716 001356 000004 64$: MOV #65$,(SP) ;SET UP FOR TRAP RETURN
001354 000002 000002 000002 RTI
001356 012737 000176 001142 65$: MOV #SWREG,SWR ;;POINT TO SOFTWARE SWR
001364 012737 000174 001144 MOV #DISPREG,DISPLAY
001372 012637 000004 000004 66$: MOV (SP)+,@ERRVEC ;;RESTORE ERROR VECTOR
001376 017700 177540 000004 MOV @SWR,R0 ;GET SWITCHES
001402 005200 000004 000004 INC R0 ;CHECK IF ALL SWITCHES ARE UP
001404 001006 000004 000004 BNE 6$ ;CONTINUE IF NOT
001406 012737 000176 001142 MOV #SWREG,SWR ;IF UP, SET SOFTWARE SWITCH CONTROL
001414 012737 000174 001144 MOV #DISPREG,DISPLAY
001422 017700 177514 000004 6$: MOV @SWR,R0 ;GET SW REG
001426 042700 177400 000004 BIC #177400,R0 ;SAVE BITS 0-7
001432 020027 000204 000004 CMP R0,#132. ;TEST # COLUMNS
001436 003003 000004 000004 BGT 2$ ;TOO BIG, DEFAULT TO 132(10)
001440 020027 000002 000002 1$: CMP R0,#2. ;TEST # COLUMNS
001444 103002 000002 000002 BHIS 3$ ;BRANCH IF OK
001446 012700 000204 000002 2$: MOV #132.,R0 ;DEFAULT TO 132(10)
001452 010037 001150 000002 3$: MOV R0,WIDTH ;SAVE # COLUMNS
001456 105037 001154 000002 CLRB TLOOP ;RESET FLAGS
001462 105037 001152 000002 CLRB STRONE
001466 105037 001153 000002 CLRB TRONE
001472 005037 011660 000002 CLR SVTST
001476 000401 000002 000002 BR 10$ ;REPLACE THIS INSTRUCTION WITH NOP (234)

```

```

001500 000424          BR      20$          ;TO SKIP CLOCK TIMINGS
001502 012737 000002 000006 10$:  MOV      #RTI,2#6      ;SET TRAP RETURN
001510 012737 000006 000004      MOV      #6,2#4
001516 112737 177777 001155      MOVB    #-1,CKFLAG      ;SET CLOCK FLAG FOR KW11-P
001524 000261          SEC          ;SET C-BIT
001526 105777 177402          TSTB    2PLKS          ;KW11-P AVAILABLE?
001532 103011          BCC     30$          ;YES, CHECK FOR CONSOLE TERMINAL
001534 112737 000001 001155      MOVB    #1,CKFLAG      ;SET CLOCK FLAG FOR KW11-L
001542 000261          SEC          ;SET C-BIT
001544 105777 177370          TSTB    2LKS          ;KW11-L AVAILABLE?
001550 103002          BCC     30$          ;YES, CHECK FOR CONSOLE TERMINAL
001552 105037 001155          CLRB    CKFLAG        ;CLEAR CLOCK AVAILABLE FLAG - NONE THERE
001556 004737 001764 30$:  JSR     PC,QUO1      ;INITILIZE ACTFST AND SELECT DRIVER
001562 112737 177777 001173      MOVB    #-1,$STPFLG    ;SET CONSOLE UNAVAILABLE FLAG
001570 000261          SEC          ;SET C-BIT
001572 105777 177302          TSTB    2TKS          ;CONSOLE TERMINAL THERE?
001576 103402          BCS     4$          ;NO, BRANCH
001600 105037 001173          CLRB    $STPFLG      ;YES, CLEAR CONSOLE UNAVAILABLE FLAG
001604 103002 4$:  BCC     5$          ;CONTINUE IF CONSOLE
001606 104414 015225          PRINT  ,NCMSG        ;PRINT NO CONSOLE MESSAGE
001612 005037 000006 5$:  CLR     2#6          ;RESET TRAP VECTOR HALTS
001616 005037 000004          CLR     2#4
001622 004737 002032          JSR     PC,QUO2      ;TYPE INTF. MISC. IF CONSOLE

.SBTTL TYPE PROGRAM NAME
::TYPE THE NAME OF THE PROGRAM IF FIRST PASS
001626 005227 177777          INC     #-1          ;:FIRST TIME?
001632 001022          BNE     67$          ;:BRANCH IF NO
001634 022737 005322 000042      CMP     #SENDAD,2#42 ;:ACT-11?
001642 001416          BEQ     67$          ;:BRANCH IF YES
001644 104401 001652          TYPE   ,68$        ;:TYPE ASCIZ STRING
001650 000413          BR     67$          ;:GET OVER THE ASCIZ
::68$: .ASCIZ <CRLF>#MAINDEC-11-DZLAE-B#<CRLF>
67$:
001700          TST     $STNM        ;WANT CONTROL NOW?
001700 005737 001146          BGE     11$          ;NO, CONTINUE
001704 002005          TSTB    $STPFLG      ;TERMINAL THERE?
001706 105737 001173 15$:  BMI     13$          ;NO, DEFAULT TO SW REG CONTROL
001712 100406          JMP     KYBDST       ;YES, GO TO KYBD CONTROL
001714 000137 007442          BIT     #SW8,2SWR    ;WANT TEST SELECTION?
001720 032777 000400 177214 11$:  BEQ     12$          ;NO, CHECK TEST #
001726 001402          JMP     SELECT       ;YES, GO TO TEST SELECTION HALT
001730 000137 006752 13$:  MOV     $STNM,RO     ;GET TEST NUMBER
001734 013700 001146 12$:  ASL     RO          ;SET POINTER
001740 006300          TST     TAT(RO)     ;CHECK IF TEST IN TABLE
001742 005760 013356          BGT     14$          ;BRANCH IF IN TABLE
001746 003004          BLT     15$          ;END OF SEQUENCE, SELECT TEST
001750 002756          INC     $STNM        ;INCREMENT TEST NUMBER
001752 005237 001146          BR     11$          ;CHECK NEXT TEST NUMBER IN TABLE
001756 000760          JMP     2TAT(RO)    ;GO TO TEST
001760 000170 013356 14$:

```

```

001764 005737 001120      QUC1:  TST      SERSW      ; IS SERIAL SWITCH SET?
001770 001407              BEQ      80$      ; ZEROS=NO=PARALLEL=BRANCH
001772 013737 001124 001130      MOV      FSTPAD,ACTFST ; SET ADDRESS OF 1ST SERIAL INTF.
002000 012737 011206 011042      MOV      #SLOAD,LDPTR+2 ; SWITCH TO SERIAL LOADER
002006 000406              BR       90$      ; GET AROUND NEXT 2 INSTRS
002010 013737 001126 001130      MOV      FSTPAD,ACTFST ; SET ADDRESS OF 1ST PARALLEL INTF.
002016 012737 011044 011042      MOV      #PLOAD,LDPTR+2 ; SWITCH TO PARALLEL LOADER
002024 004737 011316      JSR      PC,RSTADR   ; ADDRESS 1ST LINE PRINTER
002030 000207              RTS      PC        ; RETURN

002032 105737 001173      QUC2:  TSTB     $TFPLG    ; IS THERE A CONSOLE TERMINAL?
002036 100430              BMI     78$      ; BRANCH IF NONE
002040 104401 002176      TYPE    ,74$     ; CRLF CONSOLE
002044 005737 001120      TST     $ERSW    ; IS SERIAL SWITCH SET?
002050 001476              BEQ     77$      ; ZEROS=NO=PARALLEL=BRANCH
002052 104401 002122      TYPE    ,71$     ; SERIAL
002056 104401 002132      70$:   TYPE    ,72$     ; INTERFACED LA180 TEST, CRLF
002062 104401 002161      TYPE    ,73$     ; # LA180'S =
002066 013746 001122      MOV     NUMLP,-(SP) ; PUT # OF LP'S ONTO STACK
002072 104405      TYPDS   ; TYPE # OF LP'S BEING TESTED
002074 104401 002176      TYPE    ,74$     ; CRLF
002100 104401 002200      TYPE    ,75$     ; FIRST PRINTER'S ADDRESS IS
002104 013746 001130      MOV     ACTFST,-(SP) ; PUT VALUE ONTO STACK
002110 104403      TYPOS   ; TYPE OCTAL ADDRESS
002112      .BYTE  6
002113      .BYTE  1
002114 104401 002176      TYPE    ,74$     ; CRLF
002120 000207      78$:   RTS      PC        ; EXIT
002122 042523 044522 046101      71$:   .ASCIZ  /SERIAL /
002130 000040
002132 047111 042524 043122      72$:   .ASCIZ  /INTERFACED LA180 TEST/<<CRLF>
002140 041501 042105 046040
002146 030501 030070 052040
002154 051505 100124      000
002161      043 046040 030501      73$:   .ASCIZ  /# LA180'S = /
002166 030070 051447 036440
002174 000040
002176 000200      74$:   .ASCIZ  <CRLF>
002200 044506 051522 020124      75$:   .ASCIZ  /FIRST PRINTER'S ADDRESS IS /
002206 051120 047111 042524
002214 023522 020123 042101
002222 051104 051505 020123
002230 051511 000040
002234 040520 040522 046114      76$:   .ASCIZ  /PARALLEL /
002242 046105 000040      .EVEN

002246 104401 002234      77$:   TYPE    ,76$     ; PARALLEL
002252 000701              BR      70$      ; CONTINUE
  
```



\*\*\*\*\*

.SBTTL OPERATOR INTERVENTION TESTS

////////////////////////////////////

:TEST0 - INTERFACE AND CONTROL TESTS (PARALLEL INTF ONLY)

:TEST ERROR AND READY BITS, PRINTER OFF LINE - POWER OFF

////////////////////////////////////

002254 005737 001120  
002260 001402  
002262 000137 006644  
002266 104401 015567  
002272 104421  
002274 104420  
002276 005777 176612  
002302 100402  
002304 104001  
002306 000772  
002310 105777 176600  
002314 100002  
002316 104002  
002320 000765

TEST0: TST SERSW ; IS PARALLEL INTF INDICATED?  
BEQ 29\$ ; BRANCH IF YES  
JMP EXIT ; OTHERWISE EXIT TEST  
29\$: TYPE, TOMSG0 ; TYPE INSTRUCTIONS  
HOLD ; WAIT FOR OPERATOR  
28\$: CHECK ; CHECK FOR CONTROL  
TST 2LPS ; CHECK FOR ERROR CONDITION  
BMI 1\$ ; OK, ERROR SET  
ERROR 1 ; ERROR CLEAR, POWER OFF  
BR 23\$ ; RETEST  
1\$: TSTB 2LPS ; CHECK READY  
BPL 2\$ ; OK, READY NOT SET  
ERROR 2 ; READY SET, POWER OFF  
BR 28\$ ; RETEST

////////////////////////////////////

:TEST ERROR AND READY BITS, PRINTER OFF LINE - POWER ON

////////////////////////////////////

002322 104401 015626  
002326 104421  
002330 104420  
002332 005777 176556  
002336 100402  
002340 104003  
002342 000772  
002344 105777 176544  
002350 100002  
002352 104004  
002354 000765

2\$: TYPE, TOMSG1 ; TYPE INSTRUCTION - TURN POWER ON  
HOLD ; WAIT FOR OPERATOR  
3\$: CHECK ; CHECK FOR CONTROL  
TST 2LPS ; CHECK ERROR  
BMI 4\$ ; OK, ERROR SET  
ERROR 3 ; ERROR CLEAR, PRINTER OFF LINE  
BR 3\$ ; RETEST  
4\$: TSTB 2LPS ; CHECK READY  
BPL 5\$ ; OK, READY NOT SET  
ERROR 4 ; READY SET, PRINTER OFF LINE  
BR 3\$ ; RETEST

////////////////////////////////////

:TEST ERROR AND READY BITS, PRINTER ON LINE

////////////////////////////////////

002356 104401 015651  
002362 104421  
002364 104420  
002366 005777 176522  
002372 100002

5\$: TYPE, TOMSG2 ; TYPE INSTRUCTION, TURN ON LINE  
HOLD ; WAIT FOR OPERATOR  
6\$: CHECK ; CHECK FOR CONTROL  
TST 2LPS ; CHECK ERROR  
BPL 7\$ ; OK, ERROR CLEAR

```

002374 104005          ERROR      5          ;ERROR SET, PRINTER ON LINE
002376 000772          BR          6$         ;RETEST
002400 105777 176510 7$:  TSTB      2LPS      ;CHECK READY
002404 100402          BMI          8$         ;OK, READY SET
002406 104006          ERROR      6          ;READY CLEAR, PRINTER ON LINE
002410 000765          BR          6$         ;RETEST

```

;//

;TEST PAPER OUT SWITCH

;//

```

002412 104401 015705 9$:  TYPE      ,TOMSG3    ;TYPE INSTRUCTION, PAPER OUT
002416 104421          HOLD          ;WAIT FOR OPERATOR
002420 104420          CHECK         ;CHECK CONTROL
002422 012777 000012 176466 MOV          #12,2LPB   ;SEND LF
002430 005777 176460 9$:  TST        2LPS      ;CHECK FOR ERROR CONDITION
002434 100402          BMI          10$        ;OK, ERROR SET
002436 104007          ERROR      7          ;ERROR CLEAR, PAPER OUT ERROR
002440 000767          BR          9$         ;RETEST
002442 105777 176446 10$: TSTB      2LPS      ;CHECK READY
002446 100002          BPL          11$        ;OK, READY CLEAR
002450 104010          ERROR      10         ;READY SET, PAPER OUT, ON LINE
002452 000762          BR          9$         ;RETEST

```

;//

;TEST ABILITY TO CLEAR ERROR CONDITION

;//

```

002454 104401 015737 11$: TYPE      ,TOMSG4    ;TYPE INSTRUCTION, RESET & ON LINE
002460 104421          HOLD          ;WAIT FOR OPERATOR
002462 104420          CHECK         ;CHECK FOR CONTROL
002464 005777 176424 12$: TST        2LPS      ;CHECK ERROR
002470 100002          BPL          13$        ;OK, ERROR CLEAR
002472 104011          ERROR      11         ;ERROR DID NOT CLEAR
002474 000772          BR          12$        ;RETEST
002476 105777 176412 13$: TSTB      2LPS      ;CHECK READY
002502 100402          BMI          14$        ;OK, READY SET
002504 104012          ERROR      12         ;READY NOT SET
002506 000773          BR          13$        ;RETEST

```

;//

;CHECK ERROR & READY BITS AFTER RESET INSTRUCTION

;//

```

002510 104420          CHECK         ;CHECK CONTROL
002512 000005          RESET        ;CLEAR WORLD
002514 005777 176374 14$: TST        2LPS      ;CHECK ERROR
002520 100002          BPL          15$        ;OK, ERROR CLEAR
002522 104013          ERROR      13         ;ERROR BIT SET AFTER RESET INSTR.
002524 000771          BR          14$        ;RETEST

```

```

002526 104420
002530 000005
002532 105777 176356
002536 100402
002540 104014
002542 000771
15$: CHECK ;CHECK CONTROL
      RESET ;CLEAR WORLD
      TSTB @LPS ;CHECK READY
      BMI 16$ ;OK, READY SET
      ERROR 14 ;READY BIT CLEAR AFTER RESET INSTR.
      BR 15$ ;RETEST

```

;/;;/

;CHECK THAT LOADING CHAR BUFFER RESETS READY BIT  
;AND PRINTER DOES GO BACK READY.

;/;;/

```

002544 104420
002546 005005
002550 012777 000015 176340
002556 105777 :76332
002562 100002
002564 104015
002566 000766
002570 005777 176320
002574 100002
002576 104016
002600 000761
002602 105777 176306
002606 100404
002610 005205
002612 001366
002614 104017
002616 000752
16$: CHECK ;CHECK CONTROL
      CLR R5 ;CLEAR TIME OUT COUNTER
      MOV #15,@LPS ;LOAD CARRIAGE RETURN INTO BUFFER
      TSTB @LPS ;CHECK READY
      BPL 17$ ;OK, READY CLEAR
      ERROR 15 ;READY BIT NOT CLEAR WHEN CHAR LOADED
      BR 16$ ;RETEST
17$: TST @LPS ;CHECK ERROR
      BPL 18$ ;OK, ERROR CLEAR
      ERROR 16 ;ERROR BIT SET AFTER CHAR LOAD
      BR 16$ ;RETEST
18$: TSTB @LPS ;PRINTER STILL BUSY
      BMI 19$ ;NO, NEXT TEST
      INC R5 ;YES, INC TIMER
      BNE 17$ ;WAIT FOR FLAG
      ERROR 17 ;NO, TOO LONG
      BR 16$ ;RETEST

```

;/;;/

;CHECK INTERRUPT LEVEL OF PRINTER  
;PRINTER SHOULD BE AT LEVEL 4  
;  
;TEST THAT PRINTER WILL NOT INTERRUPT ABOVE LEVEL 3

;/;;/

```

002620 012705 000340
002624 104420
002626 012737 002730 000200
002634 012737 000340 000202
002642 005777 176246
002646 100002
002650 104020
002652 000764
002654 105777 176234
002660 100402
002662 104021
002664 000757
002666
002666 010546
002670 012746 002676
19$: MOV #PR7,R5 ;SET FIRST LEVEL
20$: CHECK ;CHECK CONTROL
      MOV #23$,200 ;SET INTERRUPT RETURN
      MOV #PR7,202 ;SET PRIORITY 7 ON INTERRUPT
      TST @LPS ;CHECK FOR ERROR
      BPL 21$ ;OK, ERROR CLEAR
      ERROR 20 ;ERROR BIT SET
      BR 20$ ;RETEST
21$: TSTB @LPS ;CHECK READY
      BMI 22$ ;OK, READY SET
      ERROR 21 ;READY BIT NOT SET
      BR 20$ ;RETEST
22$: MOV R5,-(SP) ;:PUT NEW PS ON STACK
      MOV #E4,-(SP) ;:PUT NEW PC ON STACK

```

```

002674 000002          RTI          ;;POP NEW PC AND PS
002676 052777 000100 176210 64$:  BIS      #BIT6,2LPS  ;SET PRINTER INT. ENABLE
002704 000240          NOP          ;DELAY
002706 042777 000100 176200  BIC      #BIT6,2LPS  ;CLEAR PRINTER INT. ENABLE
002714 162705 000040          SUB      #40,R5      ;SET NEXT LEVEL
002720 020527 000140          CMP      R5,#PR3     ;LEVEL 3?
002724 001404          BEQ      24$      ;YES, CONTINUE NEXT TEST
002726 000736          BR       20$      ;NO, TEST THIS LEVEL

002730 022626 23$:  CMP      (SP)+,(SP)+  ;RESTORE STACK
002732 104022          ERROR    22      ;INTERRUPT ABOVE LEVEL 3
002734 000733          BR       20$      ;RETEST

;//////////////////////////////////////
;TEST ABILITY OF PRINTER TO INTERRUPT AT ALL PRIORITY LEVELS BELOW 4
;//////////////////////////////////////

002736 104420          24$:  CHECK          ;CHECK FOR CONTROL
002740 012737 003024 000200  MOV      #27$,200    ;SET INTERRUPT RETURN
002745 005777 176142          TST      2LPS        ;CHECK FOR ERROR
002752 100002          BPL      25$        ;OK, ERROR CLEAR
002754 104020          ERROR    20      ;ERROR BIT SET
002756 000767          BR       24$        ;RETEST
002760 105777 176130 25$:  TSTB     2LPS        ;CHECK READY
002764 100402          BMI      26$        ;OK, READY SET
002766 104021          ERROR    21      ;READY CLEAR
002770 000762          BR       24$        ;RETEST
002772 010546          26$:  MOV      R5,-(SP)    ;;PUT NEW PS ON STACK
002774 012746 003002          MOV      #65$,-(SP) ;;PUT NEW PC ON STACK
003000 000002          RTI          ;;POP NEW PC AND PS
003002 052777 000100 176104 65$:  BIS      #BIT6,2LPS  ;SET PRINTER INTR. ENABLE
003010 000240          NOP          ;DELAY
003012 042777 000100 176074  BIC      #BIT6,2LPS  ;CLEAR PRINTER INTR. ENABLE
003020 104023          ERROR    23      ;NO INTERRUPT BELOW LEVEL 4
003022 000745          BR       24$        ;RETEST

003024 042777 000100 176062 27$:  BIC      #BIT6,2LPS  ;CLEAR PRINTER INTR. ENABLE
003032 022626          CMP      (SP)+,(SP)+  ;RESET STACK
003034 162705 000040          SUB      #40,R5      ;SET NEXT LEVEL
003040 002336          BGE      24$        ;RETEST IF NOT DONE ALL LEVELS
003042 012737 000137 000200  MOV      #137,200    ;RESET INSTRUCTIONS AT 200-202
003050 012737 001174 000202  MOV      #START,202
003056 005046          CLR      -(SP)      ;;PUT NEW PS ON STACK
003060 012746 003066          MOV      #66$,-(SP) ;;PUT NEW PC ON STACK
003064 000002          RTI          ;;POP NEW PC AND PS
003066 000137 006644 66$:  JMP      EXIT      ;EXIT TEST
  
```

K03

MAINDEC-11-DZLAE-B MACY11 27(1006) 01-MAR-77 14:45 PAGE 35  
DZLAE8.P:1 28-FEB-77 15:08

OPERATOR INTERVENTION TESTS

:/...../  
:TEST1 - TOP OF FORM SWITCH TEST  
:/...../

003072 104413  
003074 012705 003204  
003100 012701 000036  
003104 012700 000055  
003110 104416  
003112 104414 001164  
003116 104401 016035  
003122 010537 003130  
003126 104401  
003130 000000  
003132 104401 016067  
003136 104421  
003140 104420  
003142 104414 001166  
003146 104414 015777  
003152 010537 003160  
003156 104414  
003160 000000  
003162 104414 016006  
003166 022525  
003170 005715  
003172 001351  
003174 104414 001162  
003200 000137 006644

TEST1: PRTHDR  
MOV #45,R5  
MOV #30,R1  
MOV #55,R0  
MLOAD  
PRINT ,SCR  
3\$: TYPE ,T1MSG3  
MOV R5,1\$  
TYPE  
1\$: .WORD 0  
TYPE ,T1MSG4  
HOLD  
CHECK  
PRINT ,SFF  
PRINT ,T1MSG1  
MOV R5,2\$  
PRINT  
2\$: .WORD 0  
PRINT ,T1MSG2  
CMP (R5)+,(R5)+  
TST (R5)  
BNE 3\$  
PRINT ,SLF  
JMP EXIT  
4\$: .ASCIZ / 3 /  
.ASCIZ /3.5/  
.ASCIZ / 4 /  
.ASCIZ /5.5/  
.ASCIZ / 6 /  
.ASCIZ / 7 /  
.ASCIZ / 8 /  
.ASCIZ /8.5/  
.ASCIZ /11 /  
.ASCIZ /12 /  
.ASCIZ /14 /  
.WORD 0

:PRINT TEST HEADER  
:SET TABLE POINTER  
:SET CHAR COUNT  
:SET DASH CHAR  
:LOAD DASHED LINE  
:PRINT LINE  
:TYPE INSTRUCTIONS  
:SET SWITCH SETTING FOR MSG  
:FINISH INSTRUCTIONS  
:WAIT FOR OPERATOR  
:CHECK FOR CONTROL  
:ISSUE FORM FEED  
:PRINT REFERENCE LINE  
:SET FORM FEED LENGTH FOR MSG  
:FINISH MSG  
:INC TABLE POINTER  
:CHECK TABLE TO SEE IF DONE TEST  
:FINISH TEST  
:ADVANCE PAPER WHEN DONE  
:EXIT TEST  
:FORM FEED SWITCH SETTINGS  
:END OF TABLE

003204 031440 000040  
003210 027063 000065  
003214 032040 000040  
003220 027065 000065  
003224 033040 000040  
003230 033440 000040  
003234 034040 000040  
003240 027070 000065  
003244 030461 000040  
003250 031061 000040  
003254 032061 000040  
003260 000000

:/

;TEST2 - PRINT SPEED TIMING

;A SWIRL PATTERN IS PRINTED FOR ONE FULL MINUTE  
;WHILE THE NUMBER OF LINES PRINTED IS COUNTED.  
;TIMING WILL BE DONE BY KW11-L/KW11-P CLOCK OTION IF EITHER AVAILABLE.  
;OTHERWISE, MANUAL TIMING WILL BE USED TO OBTAIN APPROX. PRINT TIMINGS.

;IF A HARDWARE SWITCH REGISTER IS NOT AVAILABLE, THIS TEST  
;CANNOT BE RUN WITHOUT A CLOCK OPTION BEING AVAILABLE. THE  
;PROGRAM WILL AUTOMATICALLY SKIP THIS TEST IF IT CANNOT BE RUN.

:/

003262	104413			TEST2:	PRTHDR		;PRINT TEST HEADER
003264	012737	003500	006610		MOV #SPD,TORTN		;SET TIME OUT RETURN
003272	005004				CLR R4		;CLEAR LINE COUNT
003274	105737	001155			TSTB CKFLAG		;TEST CLOCK FLAG
003300	001417				BEQ 4\$		;NONE THERE, MANUAL TIMING
003302	002407				BLT 1\$		;KW11-P
003304	013737	006612	006606		MOV MINCNT,CNTR		;SET KW11-L CLOCK COUNT
003312	012777	000100	175620		MOV #BIT6,PLKS		;ENABLE CLOCK INTERRUPT
003320	000427				BR T2SP		;START PRINTING
003322	013777	006612	175606	1\$:	MOV MINCNT,ACSBR		;SET CLOCK COUNT
003330	012777	000105	175576		MOV #105,PLKS		;START CLOCK
003336	000420				BR T2SP		;START PRINTING
003340	023727	001142	177570	4\$:	CMP SWR,#177570		;CLECK SW REG ADR
003346	001406				BEQ 2\$		
003350	104414	016134			PRINT .T2EM		;CONTINUE IF HARDWARE
003354	104401	016134			TYPE .T2EM		;PRINT ERRORS MMSG
003360	000137	006644			JMP EXIT		;EXIT TEST
003364	104401	015253		2\$:	TYPE ,MANMSG		;PRINT INSTRUCTIONS
003370	032777	010000	175544	3\$:	BIT #SW12,SWR		;SW12 UP?
003376	001774				BEQ 3\$		;NO, WAIT FOR START
003400	012702	000041		T2SP:	MOV #41,R2		;SET START CHAR
003404	010200			1\$:	MOV R2,R0		;SET CHAR
003406	013701	001150		2\$:	MOV WIDTH,R1		;SET COLUMN COUNT
003412	104415			3\$:	LOAD		;LOAD CHAR
003414	005301				DEC R1		;DEC CHAR COUNT
003416	001407				BEQ 4\$		;BRANCH IF DONE LINE
003420	005200				INC R0		;NEXT CHAR
003422	020027	000177			CMP R0,#177		;CHECK CHAR
003426	001371				BNE 3\$		;OK, CONTINUE
003430	012700	000040			MOV #40,R0		;SET CHAR = SPACE
003434	000766				BR 3\$		;CONTINUE
003436	104414	001162		4\$:	PRINT \$LF		;PRINT LINE
003442	005204				INC R4		;INC LINE COUNT
003444	105737	001155			TSTB CKFLAG		;USING CLOCK TIMING?
003450	001006				BNE 5\$		;YES, BYPASS MANUAL TIMING
003452	032777	010000	175462		BIT #SW12,SWR		;SW12 DOWN?
003460	001002				BNE 5\$		;NO, CONTINUE
003462	000137	003500			JMP SPD		;YES, EXIT PRINTING ROUTINE
003466	005202			5\$:	INC R2		;INC START CHAR
003470	020227	000177			CMP R2,#177		;CHECK IT

003474 001343  
003476 000740

BNE 1\$ ;OK, CONTINUE  
BR 12SP ;RESET START CHAR

;/;;/

;ROUTINE TO PRINT/TYPE MEASURED PRINT SPEED FOR TEST 2.

;/;;/

003500 012700 000177  
003504 104415  
003506 104401 015470  
003512 104414 015470  
003516 105737 001155  
003522 001004  
003524 104401 015511  
003530 104414 015511  
003534  
003534 010446  
003536 004737 012650  
003542 104417  
003544 010446  
003546 104405  
003550 104414 015522  
003554 104401 015522  
003560 013746 001150  
003564 104405  
003566 104401 015551  
003572 013746 001150  
003576 004737 012650  
003602 104417  
003604 104414 015551  
003610 000137 006644

SPD: MOV #177,R0 ;SET RUBOUT CHAR  
LOAD ;CLEAR CHAR BUFFER  
TYPE PRSP1 ;START MMSG  
PRINT ,PRSP1  
TSTB CKFLAG ;USING CLOCK?  
BNE 1\$ ;YES, BRANCH  
TYPE ,PRSP2 ;ADD WORD "APPROXIMATELY" TO MMSG  
PRINT ,PRSP2  
  
1\$: MOV R4,-(SP) ;PUSH R4 ON STACK  
JSR PC,\$SB20 ;CONVERT #  
CNLOAD ;LOAD #  
MOV R4,-(SP) ;PUSH R4 ON STACK  
TYPDS ;TYPE #  
PRINT ,PRSP3 ;LOAD MORE OF MMSG  
TYPE ,PRSP3  
MOV WIDTH,-(SP) ;#COLUMNS ON STACK  
TYPDS ;TYPE #  
TYPE ,PRSP4 ;TYPE END OF MMSG  
MOV WIDTH,-(SP) ;# COLUMNS ON STACK AGAIN  
JSR PC,\$SB20 ;CONVERT #  
CNLOAD ;LOAD #  
PRINT ,PRSP4 ;PRINT MMSG ON LA180  
JMP EXIT ;EXIT TEST

.SBTTL PRINTING TESTS

;/;;

;TEST20 - DATA TRANSFER PATHS TEST  
;THIS TEST PRINTS 16 LINES OF ALTERNATING \*'S AND U'S IN A CHECKERBOARD  
;PATTERN

;/;;

003614 104413  
003616 012703 052452  
003622 012702 000020  
003626 010300  
003630 013701 001150  
003634 104415  
003636 000300  
003640 005301  
003642 001374  
003644 000303  
003646 104414 001162  
003652 005302  
003654 001364  
003656 000137 006644

TEST20: PRTHDR ;PRINT TEST HEADER  
MOV #\*\*U,R3 ;SET FIRST CHAR PAIR  
MOV #16,R2 ;SET LINE COUNT  
1\$: MOV R3,R0 ;SET CHAR PAIR  
MOV WIDTH,R1 ;SET COLUMN COUNT  
2\$: LOAD CHAR ;LOAD CHAR  
SWAB R0 ;SET NEXT CHAR  
DEC R1 ;DEC COLUMN COUNT  
BNE 2\$ ;FINISH LINE  
SWAB R3 ;SET NEXT LINE START CHAR  
PRINT \$LF ;PRINT LINE  
DEC R2 ;DEC LINE COUNT  
BNE 1\$ ;FINISH TEST  
JMP EXIT ;EXIT WHEN DONE



;/;;;

;TEST21 - HEAD POSITIONING TEST

;THIS TEST PRINTS A SINGLE LINE OF ALTERNATING O'S AND SPACES  
;THEN FILLS IN THE SPACES WITH X'S ONE AT A TIME.

;/;;;

003662	104413	
003664	013701	001150
003670	012700	000060
003674	104415	
003676	005301	
003700	001405	
003702	012700	000040
003706	104415	
003710	005301	
003712	001366	
003714	104414	001164
003720	012702	000002
003724	012700	000040
003730	010201	
003732	005301	
003734	104416	
003736	012700	000130
003742	104415	
003744	104414	001164
003750	062702	000002
003754	020237	001150
003760	101761	
003762	104414	001162
003766	000137	006644

TEST21:	PRTHDR		;PRINT TEST HEADER
	MOV	WIDTH,R1	;SET COLUMN COUNT
1\$:	MOV	#60,R0	;SET CHAR
	LOAD		;LOAD CHAR
	DEC	R1	;DEC CHAR COUNT
	BEQ	2\$	;PRINT LINE WHEN LOADED
	MOV	#40,R0	;SET SPACE CHAR
	LOAD		;LOAD SPACE
	DEC	R1	;DEC CHAR COUNT
	BNE	1\$	;FINISH LINE
2\$:	PRINT	,SCR	;PRINT LINE
	MOV	#2,R2	;SET FIRST CHAR COUNT
3\$:	MOV	#40,R0	;SET SPACE CHAR
	MOV	R2,R1	;GET CHAR COUNT
	DEC	R1	;SUBTRACT ONE
	MLOAD		;LOAD SPACES
	MOV	#'X,R0	;SET X CHAR
	LOAD		;LOAD X
	PRINT	,SCR	;PRINT LINE
	ADD	#2,R2	;ADD 2 TO CHAR COUNT
	CMP	R2,WIDTH	;DONE LINE?
	BLOS	3\$	;NO, FINISH LINE
	PRINT	,\$LF	;YES, ADVANCE PAPER
	JMP	EXIT	;EXIT TEST

:/

:TEST22 - BACKSPACE TEST

:2 LINES OF X'S INTERSPACED WITH DASHES WILL BE PRINTED BY PRINTING A SLASH,  
:EXECUTING A BACKSPACE, AND THEN PRINTING A BACKSLASH TO  
:COMPLETE EACH X CHAR.  
:A MAXIMUM OF 127 COLUMNS WILL BE PRINTED BY THIS TEST.

:/

003772 104413  
003774 012702 000002  
004000 013701 001150  
004004 020127 000177  
004010 003402  
004012 012701 000177  
004016 104414 004054  
004022 005301  
004024 001405  
004026 012700 000055  
004032 104415  
004034 005301  
004036 001367  
004040 104414 001162  
004044 005302  
004046 001354  
004050 00C:37 00E944  
  
004054 004057 000134

```
TEST22: PRTHDR          ;PRINT TEST HEADER
          MOV           #2,R2          ;SET LINE COUNT
1$:      MOV           WIDTH,R1       ;SET COLUMN COUNT
          CMP           R1,#127.      ;CHECK # COLUMNS
          BLE           2$           ;GREATER THAN 127?
          MOV           #127.,R1      ;YES, SET TO 127
2$:      PRINT         ,10$          ;LOAD SLASH-BS-BACKSLASH
          DEC           R1           ;DEC CLOUMN COUNT
          BEQ           3$           ;PRINT LINE IF DONE
          MOV           #55,R0        ;SET ASCII OF DASH
          LOAD          ;LOAD DASH CHAR
          DEC           R1           ;DEC COLUMN COUNT
          BNE           2$           ;FINISH LINE
3$:      PRINT         ,LF          ;PRINT LINE
          DEC           R2           ;DEC LINE COUNT
          BNE           1$           ;FINISH TEST
          JMP           EXIT         ;EXIT TEST

10$:     .ASCIZ <57><10><134>
          .EVEN
```

004

```

////////////////////////////////////////
:TEST23 - CHARACTER GENERATOR TEST
:THIS TEST PRINTS A SINGLE LINE (30 CHARACTERS LONG) OF EACH PRINTABLE CHAR
:PRECEDED BY A LINE OF ALL SPACES
////////////////////////////////////////

```

```

004060 104413
004062 012700 000040
004066 012701 000036
004072 104416
004074 104414 001162
004100 005200
004102 020027 000177
004106 001367
004110 000137 006644

```

```

TEST23: PRTHDR          ;PRINT TEST HEADER
          MOV          #40,R0    ;SET FIRST CHAR
1$:      MOV          #30.,R1   ;SET CHAR COUNT
          MLOAD        ;LOAD LINE
          PRINT        ;PRINT LINE
          INC          R0        ;SET NEXT CHAR
          CMP          R0,#177  ;CHAR = RUBOUT?
          BNE         1$        ;NO, FINISH TEST
          JMP          EXIT      ;EXIT TEST

```

;///  
:TEST24 - NON-PRINTABLE CHARACTER TEST  
:THIS TEST PRINTS A 30 LINE SWIRL PATTERN WITH NON-PRINTABLE CHARACTERS  
:LOADED BEFORE AND AFTER THE PRINTING CHARACTERS TO TEST ALL AREAS OF THE  
:CHARACTER BUFFER IN THE LA180. IF THIS TEST IS LOOPED ON, THE SWIRL  
:PATTERN WILL CONTINUE, 30 LINES PRINTED EACH TIME THE TEST IS LOOPED.  
:///

004114 104413  
004116 012702 000041  
004122 012705 000036  
004126 013701 001150  
004132 012703 000377  
004136 160103  
004140 005004  
004142 162703 000035  
004146 002402  
004150 005204  
004152 000773  
004154 005003  
004156 1F2701 000377  
004162 005401  
004164 160301  
004166 004737 004320  
004172 013701 001150  
004176 010200  
004200 104415  
004202 005301  
004204 001407  
004206 005200  
004210 020027 000177  
004214 001371  
004216 012700 000040  
004222 000766  
004224 010301  
004226 004737 004320  
004232 104414 001162  
004236 005305  
004240 003015  
004242 105737 001154  
004246 001006  
004250 002777 040000 174664  
004256 001002  
004260 000137 006644  
004264 012705 000036  
004270 005003  
004272 000401  
004274 060403  
004276 013701 001150  
004302 005202  
004304 020227 000177  
004310 001322  
004312 012702 000041

TEST24: PRTHOR  
MOV #41,R2  
MOV #30,R5  
MOV WIDTH,R1  
MOV #255,R3  
SUB R1,R3  
CLR R4  
2\$: SUB #29,R3  
BLT 3\$  
INC R4  
BR 2\$  
3\$: CLR R3  
4\$: SUB #255,R1  
NEG R1  
SUB R3,R1  
JSR PC,10\$  
MOV WIDTH,R1  
MOV R2,R0  
5\$: LOAD R1  
DEC R1  
BEQ 6\$  
INC R0  
CMP R0,#177  
BNE 5\$  
MOV #40,R0  
BR 5\$  
6\$: MOV R3,R1  
JSR PC,10\$  
PRINT \$LF  
DEC R5  
BGT 8\$  
TSTB TLOOP  
BNE 7\$  
BIT #SW14,2SWR  
BNE 7\$  
JMP EXIT  
7\$: MOV #30,R5  
CLR R3  
BR 9\$  
8\$: ADD R4,R3  
9\$: MOV WIDTH,R1  
INC R2  
CMP R2,#177  
BNE 4\$  
MOV #41,R2

;PRINT TEST HEADER  
;SET START CHAR  
;SET LINE COUNT  
;GET COLUMN COUNT  
;SET BUFFER SIZE  
;SUBTRACT COLUMNS COUNT  
;CLEAR CHAR INC COUNT  
;DIVIDE NON-PRINT CHAR COUNT BY 29  
  
;R4 = NON-PRINT CHAR INC COUNT  
  
;CLEAR NON-PRINT CHAR COUNT 2ND BLOCK  
;CALCULATE # NON-PRINT CHARS, 1ST BLOCK  
  
;LOAD 1ST BLOCK OF NON-PRINT CHARS  
;SET # PRINTABLE CHARS (COLUMN COUNT)  
;SET FIRST PRINT CHAR  
;LOAD PRINTABLE CHAR  
;DEC CHAR COUNT  
;BRANCH IF DONE PRINTABLE CHARS  
;NEXT CHAR  
;CHECK CHAR  
;OK - CONTINUE  
;RESET CHAR = SPACE  
;CONTINUE  
;SET # NON-PRINT CHARS, 2ND BLOCK  
;LOAD 2ND BLOCK NON-PRINT CHARS  
;PRINT LINE  
;DEC LINE COUNT  
;CONTINUE TEST  
;LOOP ON TEST?  
;YES, INITIALIZE  
;LOOP ON TEST?  
;YES, INITIALIZE  
;EXIT TEST  
;RESET LINE COUNT  
;CLEAR NON-PRINT CHAR COUNT  
;CONTINUE SWIRL  
;INC NON-PRINT CHAR COUNT, 2ND BLOCK  
;RESET COLUMN COUNT  
;INC START CHAR  
;CHECK START CHAR  
;OK, CONTINUE  
;RESET START CHAR

004316 000717

BR 4\$

;CONTINUE

;/;;/

;ROUTINE TO LOAD NON-PRINTABLE CHARACTERS FOR TEST 24.

;/;;/

004320 005701  
004322 001430  
004324 005000  
004326 104415  
004330 005301  
004332 003424  
004334 005200  
004336 020027 000007  
004342 001774  
004344 020027 000010  
004350 001771  
004352 020027 000012  
004356 001766  
004360 020027 000014  
004364 001763  
004366 020027 000015  
004372 001760  
004374 020027 000040  
004400 001751  
004402 000751  
004404 000207

10\$: TST R1 ;TEST CHAR COUNT  
BEQ 14\$ ;RETURN IF ZERO  
11\$: CLR RO ;SET FIRST NON-PRINT CHAR  
12\$: LOAD ;LOAD CHAR  
DEC R1 ;DEC CHAR COUNT  
BLE 14\$ ;RETURN IF DONE  
13\$: INC RO ;NEXT CHAR  
CMP RO,#7 ;CHAR = BELL ?  
BEQ 13\$ ;YES, NEXT CHAR  
CMP RO,#10 ;CHAR = BS?  
BEQ 13\$ ;YES, NEXT CHAR  
CMP RO,#12 ;CHAR = LF?  
BEQ 13\$ ;YES, NEXT CHAR  
CMP RO,#14 ;CHAR = FF?  
BEQ 13\$ ;YES, NEXT CHAR  
CMP RO,#15 ;CHAR = CR?  
BEQ 13\$ ;YES, NEXT CHAR  
CMP RO,#40 ;CHAR = SPACE?  
BEQ 11\$ ;YES, RESET CHAR  
BR 12\$ ;CONTINUE  
14\$: RTS PC ;RETURN

G04

//

;TEST25 - BUFFER TEST

;THIS TEST CHECKS THE CHARACTER BUFFER OF THE LA180 WHILE PRINTING  
;FOUR LINES OF NUMBERS (WITH 2 BLANK LINES BETWEEN THE FIRST AND SECOND  
;LINE). THESE LINES CAN BE USED TO CHECK THE PROPER PRINTING WIDTH.  
;ANY E PRINTED INDICATES AN INCORRECT LOAD OR BUFFER ACTION.

//

004406 104413  
004410 012701 000020  
004414 012700 000105  
004420 104416  
004422 012700 000177  
004426 104415  
004430 005002  
004432 013701 001150  
004436 012700 000061  
004442 104415  
004444 005301  
004446 001414  
004450 005202  
004452 020227 000144  
004456 002771  
004460 012700 000063  
004464 020227 000202  
004470 002764  
004472 012700 000062  
004476 000761  
004500 104414 001162  
004504 012701 000400  
004510 012700 000105  
004514 104416  
004516 104414 001162  
004522 012701 000376  
004526 012700 000105  
004532 104416  
004534 012700 000177  
004540 104415  
004542 104414 001162  
004546 012701 000400  
004552 012700 000105  
004556 104416  
004560 013701 001150  
004564 012700 000060  
004570 005002  
004572 104415  
004574 005301  
004576 001407  
004600 005202  
004602 020227 000143  
004606 002771  
004610 012700 000061  
004614 000766

TEST25: PRTHDR ;PRINT TEST HEADER  
MOV #16, R1 ;SET CHAR COUNT  
MOV #'E,R0 ;SET E CHAR  
MLOAD ;LOAD BUFFER  
MOV #177,R0 ;SET RUBOUT CHAR  
LOAD ;CLEAR BUFFER  
CLR R2 ;CLEAR CHAR COUNT  
MOV WIDTH,R1 ;SET COLUMN COUNT  
MOV #61,R0 ;SET CHAR  
1\$: LOAD ;LOAD CHAR  
DEC R1 ;DEC COLUMN COUNT  
BEQ 2\$ ;PRINT LINE WHEN LOADED  
INC R2 ;INC CHAR COUNT  
CMP R2,#100. ;DONE ONES?  
BLT 1\$ ;NO, CONTINUE  
MOV #63,R0 ;SET NEXT CHAR  
CMP R2,#130. ;DONE 3'S?  
BLT 1\$ ;NO, CONTINUE  
MOV #62,R0 ;YES, SET NEXT CHAR  
BR 1\$ ;CONTINUE LOADING CHARACTERS  
2\$: PRINT \$LF ;PRINT LINE  
MOV #256,R1 ;SET CHAR COUNT  
MOV #'E,R0 ;SET E CHAR  
MLOAD ;LOAD BUFFER  
PRINT \$LF ;PRINT BLANK LINE  
MOV #254,R1 ;SET CHAR COUNT  
MOV #'E,R0 ;SET E CHAR  
MLOAD ;LOAD BUFFER  
MOV #177,R0 ;SET RUBOUT CHAR  
LOAD ;CLEAR BUFFER  
PRINT \$LF ;BLANK LINE  
MOV #256,R1 ;SET CHAR COUNT  
MOV #'E,R0 ;SET E CHAR  
MLOAD ;LOAD BUFFER  
MOV WIDTH,R1 ;SET COLUMN COUNT  
MOV #60,R0 ;SET CHAR  
CLR R2 ;CLEAR CHAR COUNT  
3\$: LOAD ;LOAD CHAR  
DEC R1 ;DEC COLUMN COUNT  
BEQ 4\$ ;PRINT LINE WHEN LOADED  
INC R2 ;INC CHAR COUNT  
CMP R2,#99. ;DONE ZEROS?  
BLT 3\$ ;NO, CONTINUE  
MOV #61,R0 ;YES, SET NEXT CHAR  
BR 3\$ ;CONTINUE

004616	104414	001162	4\$:	PRINT	\$LF	:PRINT LINE
004622	012701	000400		MOV	#256,R1	:SET CHAR COUNT
004626	012700	000105		MOV	#E,R0	:SET E CHAR
004632	104416			MLOAD		:LOAD BUFFER
004634	012700	000177		MOV	#177,R0	:SET RUBOUT CHAR
004640	104415			LOAD		:CLEAR BUFFER
004642	012700	000060		MOV	#60,R0	:SET CHAR
004646	012702	000011		MOV	#9,R2	:SET GROUP COUNT
004652	013701	001150		MOV	WIDTH,R1	:SET CHAR COUNT
004656	104415		5\$:	LOAD		:LOAD CHAR
004660	005302			DEC	R2	:DEC GROUP COUNT
004662	001010			BNE	7\$	:FINISH GROUP
004664	005200			INC	R0	:SET NEXT CHAR
004666	020027	000072		CMP	R0,#72	:GOOD CHAR?
004672	103402			BLO	6\$	:YES, CONTINUE
004674	012700	000060		MOV	#60,R0	:NO, RESET CHAR TO ZERO
004700	012702	000012	6\$:	MOV	#10,R2	:RESET GROUP COUNT
004704	005301		7\$:	DEC	R1	:DEC CHAR COUNT
004706	001363			BNE	5\$	:FINISH LINE
004710	104414	001162		PRINT	\$LF	:PRINT LINE
004714	012701	000400		MOV	#256,R1	:SET CHAR COUNT
004720	012700	000105		MOV	#E,R0	:SET E CHAR
004724	104416			MLOAD		:LOAD BUFFER
004726	012700	000061		MOV	#61,R0	:SET CHAR
004732	013701	001150		MOV	WIDTH,R1	:SET CHAR COUNT
004736	104415		8\$:	LOAD		:LOAD CHAR
004740	005200			INC	R0	:SET NEXT CHAR
004742	020027	000072		CMP	R0,#72	:GOOD CHAR?
004746	103402			BLO	9\$	:YES, CONTINUE
004750	012700	000060		MOV	#60,R0	:RESET CHAR
004754	005301		9\$:	DEC	R1	:DEC CHAR COUNT
004756	001367			BNE	8\$	:FINISH LINE
004760	104414	001162		PRINT	\$LF	:PRINT LINE
004764	000137	006644		JMP	EXIT	:EXIT TEST

:/

:TEST26 - OVERPRINT TEST  
:THIS TEST PRINTS FOUR LINES OF ALTERNATING CHARACTERS AND SPACES  
:IN A CHECKERBOARD PATTERN. EACH LINE IS OVERPRINTED TWICE.

:/

004770 104413  
004772 012703 005050  
004776 012702 000003  
005002 011300  
005004 001417  
005006 013701 001150  
005012 104415  
005014 000300  
005016 005301  
005020 001374  
005022 005302  
005024 001403  
005026 104414 001164  
005032 000763  
005034 104414 001162  
005040 005723  
005042 000755  
005044 000137 006644  
  
005050 020105  
005052 040040  
005054 020115  
005056 021440  
005060 000000

TEST26: PRTHDR  
MOV #6\$ R3  
1\$: MOV #3 R2  
2\$: MOV (R3),R0  
BEQ 5\$  
MOV WIDTH,R1  
3\$: LOAD  
SWAB R0  
DEC R1  
BNE 3\$  
DEC R2  
BEQ 4\$  
PRINT ,SCR  
BR 2\$  
4\$: PRINT ,SLF  
TST (R3)+  
BR 1\$  
5\$: JMP EXIT  
  
6\$: .ASCII /E /  
.ASCII /Q /  
.ASCII /M /  
.ASCII /# /  
.WORD 0

:PRINT TEST HEADER  
:SET TABLE POINTER  
:SET OVERPRINT COUNT  
:GET CHAR PAIR  
:EXIT IF DONE TEST  
:SET COLUMN COUNT  
:LOAD CHAR  
:SET NEXT CHAR  
:DEC COLUMN COUNT  
:FINISH LINE  
:DEC OVERPRINT COUNT  
:BRANCH IF DONE OVERPRINT  
:PRINT LINE  
:CONTINUE  
:PRINT LINE  
:INC TABLE POINTER  
:PRINT NEXT LINE  
:EXIT TEST  
  
:END OF TABLE



J04

;/;;/;  
;TEST27 - MULTIPLE LINE FEED TEST  
;NUMBER PRINTED INDICATES NUMBER OF LINE FEEDS FOLLOWING THAT LINE.  
;DASHED REFERENCE LINES ARE PRINTED TO AID IN CHECKING PROPER  
;LINE FEEDS.  
;/;;/;

005062 104413  
005064 012703 005170  
005070 111346  
005072 004737 012650  
005076 104417  
005100 121327 000001  
005104 101406  
005106 012701 000035  
005112 121327 000010  
005116 101411  
005120 000407  
005122 013701 001150  
005126 020127 000036  
005132 103002  
005134 012701 000036  
005140 005301  
005142 012700 000055  
005146 104416  
005150 111301  
005152 113700 001162  
005156 104416  
005160 105723  
005162 003342  
005164 000137 006644

TEST27: PRTHDR ;PRINT TEST HEADER  
MOV #55,R3 ;SET TABLE POINTER  
1\$: MOVB (R3),-(SP) ;NUMBER ONTO STACK  
JSR PC,\$5B20 ;CONVERT #  
CNLOAD ;LOAD NUMBER  
CMPB (R3),#1 ;TEST #  
BLOS 2\$ ;PRINT FULL DASH LINE IF J OF 1  
MOV #29,R1 ;SET DASH LENGTH  
CMPB (R3),#8. ;CHECK #  
BLOS 4\$ ;2 4 OR 8 - PRINT 29 DASHES  
BR 3\$ ;16 OR 32 - PRINT 28 DASHES  
2\$: MOV WIDTH,R. ;SET CHAR COUNT  
CMP R1,#30. ;CHECK IT  
BHIS 3\$ ;OK CONTINUE  
MOV #30.,R1 ;SET TO 30  
3\$: DEC R1 ;SUBTRACT ONE  
4\$: MOV #55,R0 ;SET DASH CHAR  
MLOAD ;LOAD DASH LINE  
MOVB (R3),R1 ;SET LF COUNT  
MOVB \$LF,R0 ;SET LF CHAR  
MLOAD ;LOAD LF'S  
TSTB (R3)+ ;INC TABLE POINTER  
BGT 1\$ ;FINISH TEST  
JMP EXIT ;EXIT TEST

005170 001 002 004 5\$: .BYTE 1,2,4,8.,16.,32.,0  
005173 010 020 040  
005176 000

005200 .EVEN

K04

;/;;/

;TEST30 - RIBBON FEED TEST

; THIS TEST PRINTS A SINGLE COLUMN OF 24 LINES OF X'S DOWN THE LEFT  
; HAND MARGIN OF THE PAGE.

;/;;/

005200 104413  
005202 012701 000030  
005206 104414 005222  
005212 005301  
005214 001374  
005216 000137 006644

TEST30: PRTHDR ;PRINT TEST HEADER  
MOV #24.,R1 ;SET LINE COUNT  
1\$: PRINT 2\$ ;PRINT X - LF  
DEC R1 ;DEC LINE COUNT  
BNE 1\$ ;FINISH TEST  
JMP EXIT ;EXIT TEST

005222 005130 000  
005226

2\$: .ASCIZ /X/<12>  
.EVEN

;/;;/

;TEST31 - BELL TEST

; THIS TEST WILL SOUND 5 BELLS WHILE PRINTING "BELL TEST"

;/;;/

005226 104413  
005230 104414 005240  
005234 000137 005262

TEST31: PRTHDR ;PRINT TEST HEADER  
PRINT 1\$ ;DO TEST  
JMP \$EOP ;EXIT TEST

005240 041007 046105 003514  
005246 052040 051505 003524  
005254 003415 003412 000015

1\$: .ASCIZ <7>/BELL/<7>/ TEST/<7><15><7><12><7><15>

.EVEN

.SBTTL END OF PASS ROUTINE

\*\*\*\*\*  
\*INCREMENT THE PASS NUMBER (\$PASS)  
\*IF THERES A MONITOR GO TO IT  
\*IF THERE ISN'T JUMP TO EXIT

005262				\$EOP:	NOP			
005262	000240				INC	\$PASS	:: INCREMENT THE PASS NUMBER	
005264	005237	005336			BIC	#100000,\$PASS	:: DON'T ALLOW A NEG. NUMBER	
005270	042737	100000	005336		DEC	(PC)+	:: LOOP?	
005276	005327			\$EOPCT:	.WORD	1		
005300	000001				BGT	\$DOAGN	:: YES	
005302	003013				MOV	(PC)+,a(PC)+	:: RESTORE COUNTER	
005304	012737			\$ENDCT:	.WORD	1		
005306	000001				\$EOPCT			
005310	005300			\$GET42:	MOV	a#42,R0	:: GET MONITOR ADDRESS	
005312	013700	000042			BEQ	\$DOAGN	:: BRANCH IF NO MONITOR	
005316	001405				RESET		:: CLEAR THE WORLD	
005320	000005			\$ENDAD:	JSR	PC,(R0)	:: GO TO MONITOR	
005322	004710				NOP		:: SAVE ROOM	
005324	000240				NOP		:: FOR	
005326	000240				NOP		:: ACT11	
005330	000240			\$DOAGN:				
005332					JMP	a(PC)+	:: RETURN	
005334	000137			\$RTNAD:	.WORD	EXIT		
005336	006644			\$PASS:	.WORD	0	:: NUMBER OF PASSES	
005336	000000							



;\*\*\*\*\*

.SBTTL MAINTENANCE AIDS

;/

;TEST60 - LIFE TEST

;THIS TEST PRINTS 2 FULL LINES OF EACH PRINTABLE CHARACTER  
;THE SECOND LINE IS OVERPRINTED 4 TIMES TO CONSERVE PAPER  
;AT THE END OF EACH PASS THROUGH THE ENTIRE PRINTABLE CHARACTER  
;SET, THE PASS COUNT WILL BE PRINTED ON THE LAIBO.

;/

005540 005037 005652  
005544 104413  
005546 012700 000041  
005552 013701 001150  
005556 104416  
005560 104414 001162  
005564 012702 000005  
005570 013701 001150  
005574 104416  
005576 104414 001164  
005602 005302  
005604 001371  
005606 104414 001162  
005612 005200  
005614 020027 000177  
005620 001354  
005622 005237 005652  
005626 104414 015102  
005632 013746 005652  
005636 004737 012650  
005642 104417  
005644 104414 001162  
005650 000735  
005652 000000

TEST60: CLR PASCNT ;CLEAR PASS COUNT  
1\$: PRTHDR ;PRINT TEST HEADER, FEED BLANK LINES  
MOV #41,R0 ;SET FIRST CHAR  
2\$: MOV WIDTH,R1 ;SET COLUMN COUNT  
MLOAD ;LOAD LINE  
PRINT \$LF ;PRINT LINE  
MOV #5,R2 ;SET OVERPRINT COUNT  
3\$: MOV WIDTH,R1 ;SET COLUMN COUNT  
MLOAD ;LOAD LINE  
PRINT \$CR ;PRINT LINE  
DEC R2 ;DEC OVERPRINT COUNT  
BNE 3\$ ;FINISH OVERPRINT  
PRINT \$LF ;ADVANCE PAPER  
INC R0 ;SET NEXT CHAR  
CMP R0,#177 ;TEST CHAR  
BNE 2\$ ;OK, CONTINUE  
INC PASCNT ;INC PASS COUNT  
PRINT PASMMSG ;LOAD PASS COUNT MESSG  
MOV PASCNT,-(SP) ;PUSH PASCNT ON STACK  
JSR PC,\$SB20 ;CONVERT #  
CNLOAD ;LOAD #  
PRINT \$LF ;PRINT MESSG  
BR 1\$ ;START NEXT PASS  
PASCNT: .WORD 0 ;PASS COUNT

;/;;/

:TEST61 - SCOPE DRIVE ROUTINE

:THIS TEST WILL LOAD A CHARACTER SET IN SWITCH REGISTER BITS 0-6  
:IF SWITCH 9 IS DOWN, FULL LINES WILL BE LOADED & PRINTED (LF).  
:IF SWITCH 9 IS UP, THE CHAR WILL BE LOADED ONCE AND THE PROGRAM  
:WILL HALT. NO LINE FEEDS OR CARRIAGE RETURNS WILL BE SENT BY THE  
:PROGRAM.

;/;;/

005654 104413  
005656 000422  
005660 013701 001150  
005664 017700 173252  
005670 042700 177600  
005674 104415  
005676 020027 000015  
005702 001410  
005704 020027 000012  
005710 001405  
005712 020027 000040  
005716 103404  
005720 005301  
005722 000402  
005724 013701 001150  
005730 032777 001000 173204  
005736 001402  
005740 000000  
005742 000750  
005744 005701  
005746 003346  
005750 001403  
005752 012700 000177  
005756 104415  
005760 104414 001162  
005764 000735

TEST61: PRTHDR  
BR 11\$  
10\$: MOV WIDTH,R1  
1\$: MOV \$SWR,R0  
BIC #177,R0  
LOAD  
CMP R0,#15  
BEQ 11\$  
CMP R0,#12  
BEQ 11\$  
CMP R0,#40  
BLO 12\$  
DEC R1  
BR 12\$  
11\$: MOV WIDTH,R1  
12\$: BIT \$SW9,\$SWR  
BEQ 2\$  
HALT  
BR 1\$  
2\$: TST R1  
BGT 1\$  
BEQ 3\$  
MOV #177,R0  
LOAD  
3\$: PRINT \$LF  
BR 10\$

:PRINT TEST HEADER  
:CHECK SWITCH REG FIRST  
:SET COLUMN COUNT  
:GET CHARACTER  
:MASK UNWANTED BITS  
:LOAD CHAR  
:CHAR = CR?  
:YES, RESET COLUMN COUNT  
:CHAR = LF?  
:YES, RESET COLUMN COUNT  
:NON-PRINTABLE CHAR?  
:YES, DON'T DEC COLUMN COUNT  
:DEC COLUMN COUNT  
:CONTINUE  
:RESET COLUMN COUNT  
:TEST SWITCH 9  
:PRINT FULL LINE  
:ONE CHAR - HALT  
:GET NEXT CHAR  
:TEST COLUMN COUNT  
:CONTINUE IF NOT DONE LINE  
:LOADED MORE THAN WIDTH?  
:YES, CLEAR BUFFER  
:PRINT LINE, ADVANCE PAPER  
:CONTINUE

////////////////////////////////////

;TEST62 - LINE PRINT TEST

; THIS TEST PRINTS FULL LINES CONTINUOUSLY OF WHATEVER CHARACTER  
; IS TYPED ON THE CONSOLE KEYBOARD. TO CHANGE CHARACTERS, RESELECT  
; THIS TEST. AN ERROR MESSG WILL BE PRINTED IF THIS TEST IS SELECTED  
; AND A CONSOLE TERMINAL DOES NOT EXIST.

////////////////////////////////////

005766 104413  
005770 105737 001173  
005774 100473  
005776 104401 015205  
006002 105777 173072  
006006 100375  
006010 104420  
006012 017700 173064  
006016 010046  
006020 004737 010344  
006024 012746 000200  
006030 004737 010344  
006034 013701 001150  
006040 104416  
006042 104414 001162  
006046 000772

TEST62: PRTHDR ;PRINT TEST HEADER  
TSTB \$TFPLG ;CHECK IF TERMINAL EXISTS  
BMI TERR ;EXIT IF NONE  
TYPE TCHAR ;TYPE INSTR  
2\$: TSTB JTKS ;WAIT FOR KYBD FLAG  
BPL 2\$  
CHECK ;CHECK CHAR FOR CONTROL  
MOV JTKB,RC ;GET CHAR  
MOV RO,-(SP) ;CHAR ONTO STACK  
JSR PC,\$TYPEC ;ECHO CHAR  
MOV #CALF,-(SP) ;SEND CR-LF  
JSR PC,\$TYPEC  
1\$: MOV WIDTH,R1 ;SET COLUMN COUNT  
MLOAD ;LOAD LINE  
PRINT \$LF ;PRINT LINE  
BR 1\$ ;CONTINUE

////////////////////////////////////

:TEST63 - CHARACTER PRINT TEST

: THIS TEST LOADS WHATEVER CHARACTER IS TYPED ON THE CONSOLE KEYBOARD  
: TO THE LA180, CHARACTER BY CHARACTER.  
: IF THIS TEST IS SELECTED AND A CONSOLE TERMINAL DOES NOT EXIST,  
: AN ERROR MESSAGE WILL BE PRINTED.

////////////////////////////////////

006050 104413  
006052 105737 001173  
006056 100442  
006060 104401 015205  
006064 104401 001161  
006070 105777 173004  
006074 100375  
006076 104420  
006100 017700 172776  
006104 010046  
006106 004737 010344  
006112 104415  
006114 020027 000015  
006120 001003  
006122 012746 000012  
006126 000413  
006130 020027 000012  
006134 001003  
006136 012746 000015  
006142 000405  
006144 020027 000014  
006150 001347  
006152 012746 000200  
006156 004737 010344  
006162 000742

TEST63: PRTHDR ;PRINT TEST HEADER  
TSTB \$TFPLG ;CHECK IF TERMINAL EXISTS  
BMI TERR ;EXIT IF NONE  
TYPE ,TCHAR ;TYPE INSTR  
TYPE \$CRLF ;SEND CR-LF  
1\$: TSTB \$TKS ;WAIT FOR KYBD FLAG  
BPL \$S ;WAIT FOR FLAG  
CHECK ;CHECK CHAR FOR CONTROL  
MOV \$TKB,RO ;GET CHAR  
MOV RO,-(SP) ;CHAR ONTO STACK  
JSR PC,\$TYPEC ;ECHO CHAR  
LOAD ;LOAD CHAR  
CMP RO,#CR ;SEND LF AFTER CR  
BNE \$S  
MOV #LF,-(SP)  
BR \$S  
2\$: CMP RO,#LF ;SEND CR AFTER LF  
BNE \$S  
MOV #CR,-(SP)  
BR \$S  
3\$: CMP RO,#FF ;SND CRLF AFTER FF  
BNE \$S  
MOV #CRLF,-(SP)  
4\$: JSR PC,\$TYPEC  
BR \$S ;CONTINUE

006164 104414 015225  
006170 000137 006752

TERR: PRINT NCMMSG ;PRINT NO CONSOLE MESS  
JMP SELECT ;RETURN TO SELECT TEST (HALT)



```

:////////////////////
:TEST 64 -      SELECTED PATTERN PRINT TEST
:1) TYPE DESIRED CHARACTERS INCLUDING, WHERE APPROPRIATE, LA180
:   PRINT COMMANDS (IE., LF OR CR OR FF). TERMINATE STRING BY
:   TYPING CTL-A. PRINTING WILL BEGIN.
:OR
:2) TYPE A DESIRED PATTERN (TO BE AUTOMATICALLY REPEATED UNTIL
:   PREVIOUSLY SPECIFIED # OF COLUMNS HAS BEEN FILLED).
:   DO NOT INSERT ANY PRINT COMMANDS. TERMINATE PATTERN BY TYPING
:   CTL-B. AFTER PROPAGATING THE PATTERN TO THE PROPER # OF COLUMNS
:   AN LF PRINT COMMAND WILL BE INSERTED AND PRINTING WILL BEGIN.
:TO STOP PRINTING AND ENTER A NEW PATTERN TYPE CTL-SPACE.
:TO SELECT A NEW TEST TYPE DELETE/RUBOUT.
:TO CHANGE # OF COLUMNS TYPE CTL-C.
:////////////////////

```

```

006174 104413
006176 105737 001173
006202 100770
006204 104401 015415
006210 104401 015464
006214 012701 016174
006220 012700 000177
006224 104415
006226 195777 172646
006232 100375
006234 104420

006236 017700 172640
006242 042700 177600
006246 022700 000001
006252 001435
006254 022700 000002
006260 001440
006262 010046
006264 004737 010344
006270 005726
006272 110021
006274 020027 000015
006300 001003
006302 012746 000012
006306 000413
006310 020027 000012
006314 001003
006316 012746 000015
006322 000405
006324 020027 000014
006330 001336
006332 012746 000200
006336 004737 010344

```

```

TEST64: PRTHDR      ;PRINT TEST HEADER
          TSTB      $TPFLG ;CHECK IF CONSOLE TERMINAL EXISTS
          BMI      TERR    ;EXIT IF NONE
          TYPE     ,T64MSG ;TYPE BRIEF INSTRS
ACCEPT:  TYPE     ,TWOBEL ;RING CONSOLE BELL TWICE
          MOV      #TABLE4,R1 ;SET POINTER LEFTMOST IN TABLE
          MOV      #177,R0
          LOAD     ;RESET PRINTER BUFFER POINTER.
2$:      TSTB      3TKS
          BPL      2$
          CHECK
          ;WAIT FOR CONSOLE KBD FLAG
          ;CHECK FOR KBD CONTROL CHARACTERS
          ;AND CHECK SWITCHES ALSO.
          ;SAME CHAR TO R0
          ;STRIP UNWANTED BITS
          MOV      3TKB,R0
          BIC      #177600,R0
          CMP      #1,R0
          BEQ      CTLA    ;BRANCH IF CONTROL A
          CMP      #2,R0
          BEQ      CTLB    ;BRANCH IF CONTROL B
          MOV      R0,-(SP) ;CHAR ONTO STACK
          JSR     PC,$TYPEC ;ECHO CHARACTER TO CONSOLE
          TST     (SP)+    ;ADJUST STACK
          MOVB    R0,(R1)+ ;CHAR TO PRINT TABLE
          CMP     R0,#CR   ;SEND LF AFTER CR (TO CONSOLE)
          BNE     4$
          MOV     #LF,-(SP)
          BR      8$
4$:      CMP     R0,#LF
          BNE     6$
          MOV     #CR,-(SP)
          BR      8$
6$:      CMP     R0,#FF
          BNE     2$
          MOV     #CRLF,-(SP) ;SEND CRLF AFTER FF (TO CONSOLE)
          JSR     PC,$TYPEC ;CONTINUE ACCEPTING PATTERN
9$:

```

006342	005726			TST	(SP)+		:ADJUST STACK
006344	000730			BR	25		:CONTINUE ACCEPTING PATTERN
006346	022701	016174		CTLA:	CMP	#TABL64,R1	:IF POINTER IS LEFTMOST
006352	001445				BEQ	PRPAT	:RESUME PRINTING PREVIOUS PATTERN
006354	010137	006512			MOV	R1,ENDADR	:CURRENT POINTER TO ENADR
006360	000442				BR	PRPAT	:GO PRINT NEW PATTERN
006362	022701	016174		CTLB:	CMP	#TABL64,R1	:IF POINTER IS LEFTMOST
006366	001437				BEQ	PRPAT	:RESUME PRINTING PREVIOUS PATTERN
006370	162701	016174			SUB	#TABL64,R1	:GET PATTERN LENGTH INTO R1
006374	013737	001150	006506		MOV	WIDTH,COLCTR	:GET # OF COLUMNS INTO COUNTER
006402	010137	006510			MOV	R1,CHACTR	:GET # OF CHARS INTO COUNTER
006406	062701	016174			ADD	#TABL64,R1	:RE-ESTABLISH POINTER
006412	012702	016174			MOV	#TABL64,R2	:ESTABLISH SECONDARY POINTER
006416	163737	006510	006506		SUB	CHACTR,COLCTR	:REMAINING COLUMNS INTO COLCTR
006424	112221			PROPAT:	MOVB	(R2)+(R1)+	:PROPAGATE PATTERN TO # OF SPECIFIED COLUMNS
006426	005337	006506			DEC	COLCTR	
006432	003001				BGT	15	
006434	000407				BR	DUNCOL	
006436	005337	006510		15:	DEC	CHACTR	
006442	001401				BEQ	DUNPAT	
006444	000767				BR	PROPAT	
006446	012702	016174		DUNPAT:	MOV	#TABL64,R2	:RE-ADDRESS PATTERN
006452	000764				BR	PROPAT	
006454	112721	000012		DUNCOL:	MOVB	#LF,(R1)+	:INSERT LA180 PRINT COMMAND
006460	010137	006512			MOV	R1,ENDADR	
006464	000400				BR	PRPAT	:GO PRINT REPEATED PATTERN
006466	012701	016174		PRPAT:	MOV	#TABL64,R1	:SET POINTER LEFTMOST
006472	112100			15:	MOVB	(R1)+,R0	
006474	104415				LOAD		:LOAD CHAR (FROM R0) TO LA180
006476	020137	006512			CMP	R1,ENDADR	:ALSO CHK CONSOLE KBD AND CPL SW
006502	001771				BEQ	PRPAT	:END OF TABLE DATA?
006504	000772				BR	15	:YES, PRINT IT OVER.
							:NO, CONTINUE LOADING LA180 BUFFER
006506	000000			COLCTR:	0		:COLUMN COUNTER
006510	000000			CHACTR:	0		:CHARACTER COUNTER
006512	016240			ENDADR:	#TABL64+44		:HOLDS ENDING ADDR+1 OF PRINT DATA.
006514	005037	001120		TEST76:	CLR	SERSW	:CLEAR SWITCH (TO PARALLEL)
006520	004737	001764			JSR	PC,QUO1	:INITILIZE ACTFST AND SELECT DRIVER
006524	004737	002032			JSR	PC,QUO2	:TYPE INTF MISC IF CONSOLE
006530	000137	006644			JMP	EXIT	:EXIT TEST.
006534	012737	052525	001120	TEST77:	MOV	#52525,SERSW	:SET SWITCH (TO SERIAL)
006542	004737	001764			JSR	PC,QUO1	:INITILIZE ACTFST AND SELECT DRIVER
006546	004737	002032			JSR	PC,QUO2	:TYPE INTF MISC IF CONSOLE
006552	000137	006644			JMP	EXIT	:EXIT TEST

;/;;/

.SBTTL CLOCK INTERRUPT SERVICE ROUTINES

;/;;/

```

006556 004737 006614 DCI: JSR PC,SRDCI ;DISABLE KW11-P INTERRUPT
006562 000177 000022 JMP JORTN ;TIME OUT RETURN

006566 005337 006606 LKSRV: DEC CNTR ;DEC TIME COUNT
006572 001401 BEQ IS ;TIME OUT?
006574 000002 RTI ;NO RETURN
006576 004737 006614 IS: JSR PC,SRDCI ;DISABLE KW11-L INTERRUPT
006602 000177 000002 JMP JORTN ;TIME OUT RETURN

006606 000000 CNTR: .WORD 0 ;KW11-L TIMING COUNT
006610 000000 JORTN: .WORD 0 ;TIME OUT RETURN ADDRESS

006612 007020 MINCNT: .WORD 7020 ;60 HZ LINE FREQ. MINUTE COUNT
;SET TO 5670(8) FOR 50 HZ. LINE FREQ.

```

;/;;/

;SUBROUTINE TO DISABLE CLOCK OPTION INTERRUPTS

;/;;/

```

006614 105737 001155 SRDCI: TSTB CKFLAG ;CHECK CLOCK OPTION FLAG
006620 001410 BEQ 2$ ;RETURN IF NONE
006622 002404 BLT IS ;BRANCH IF KW11-P
006624 042777 000100 172306 BIC #BIT6,2LKS ;DISABLE KW11-L INTERRUPT
006632 000403 BR 2$ ;RETURN
006634 042777 000100 172272 IS: BIC #BIT6,2PLKS ;DISABLE KW11-P INTERRUPT
006642 000207 2$: RTS PC

```



\*\*\*\*\*

.SBTTL ROUTINES TO SELECT DESIRED TEST

////////////////////////////////////

;ROUTINE TO SELECT TEST FROM SW REG, BITS 0-5

////////////////////////////////////

```

006752 004737 006614      SELECT: JSR      PC,SRDCI      ;CLEAR CLOCK INTER
006756 105037 001152      CLR      CLRB      STRONE     ;CLEAR PROGRAM CONTROL FLAGS
006762 105037 001153      CLR      CLRB      TRONE     ;
006766 105037 001154      CLR      CLRB      TLOOP    ;
006772 004737 007140      JSR      PC,KYBDF     ;CHECK IF KYBD FLAG
006776 000000 1$:      HALT              ;NO KYBD FLAG - HALT
                                ;WAIT FOR OPERATOR TO SELECT TEST
                                ;PRESS CONTINUE WHEN READY
                                ;CHECK SWB
007000 032777 000400 172134  BIT      #SWB,2SWR     ;WANT TO RUN TEST ONCE & HALT
007006 001403 2$:      BEQ      2$              ;YES, SET FLAG
007010 112737 177777 001152  MOV     #-1,STRONE   ;NO, CHECK SW REG
007016 017700 172120  MOV     2SWR,RO      ;MASK BITS 0-5
007022 042700 177700  BIC     #1C77,RO    ;SAVE TEST NUMBER
007026 010037 001146  MOV     RO,$TSTNM   ;SET TABLE POINTER
007032 006300  ASL     RO          ;CHECK IF TEST IS IN TABLE
007034 005760 013356  TST     TAT(RO)     ;NOT THERE, GET NEW SELECTION
007040 003744  BLE     SELECT      ;RESET STACK
007042 012706 001100  MOV     #STACK,SP   ;GO TO SELECTED TEST
007046 00C170 013356  JMP     2TAT(RO)

```

////////////////////////////////////

;ROUTINE TO CHECK FOR KYBD OR SW REG CONTROL  
;CALL: CHECK

////////////////////////////////////

```

007052 004737 007140      $CHECK: JSR      PC,KYBDF     ;CHECK FOR KYBD FLAG
007056 010046  MOV     RO,-(SP)    ;PUSH RO ON STACK
007060 005000  CLR     RO          ;CLEAR RO
007062 032777 000400 172052  BIT     #SWB,2SWR   ;CHECK SWB
007070 001401 1$:      BEQ      1$              ;BRANCH IF SW DOWN
007072 005300  DEC     RO          ;SET FLAG IF UP
007074 123700 001152  CMPB   STRONE,RO   ;CHANGE IN SWITCH?
007100 001402 2$:      BEQ      2$              ;NO, RETURN (CHANGE TO 0402 TO DISABLE SW B)
007102 000137 006752  JMP     SELECT      ;YES, SELECT TEST (HALT)
007106 3$:      MOV     (SP)+,RO    ;POP STACK INTO RO
007106 012600  RTI                    ;RETURN
007110 000002

```

;/;;/

;ROUTINE TO WAIT FOR OPERATOR ACTION

;/;;/

007112	105737	001173	\$HOLD:	TSTB	\$TPFLG	:	TERMINAL THERE?
007116	100002			BPL	1\$	:	BRANCH IF YES
007120	000000			HALT		:	HALT IF NO
007122	000405			BR	2\$	:	RETURN ON CONTINUE SWITCH
007124	104401	015144	1\$:	TYPE	WTMSG	:	TYPE WAIT MMSG
007130	105777	171744	3\$:	TSTB	2TKS	:	KYBD FLAG?
007134	100375			BPL	3\$	:	NO WAIT FOR FLAG
007136	000002		2\$:	RTI		:	RETURN

;/;;/

;ROUTINE TO CHECK FOR KEYBOARD FLAGS  
;WHEN LOOKING FOR CONTROL FROM THE CONSOLE DEVICE KEYBOARD  
;CALL: JSR PC,KYBDF

;/;;/

007140	105737	001173	KYBDF:	TSTB	\$TPFLG	:	TERMINAL THERE?
007144	100527			BMI	1\$	:	NO, EXIT
007146	105777	171726		TSTB	2TKS	:	FLAG SET?
007152	100124			BPL	1\$	:	NO - EXIT
007154	104406		2\$:	RDCHR		:	FLAG SET - READ CHAR
007156	023727	001142	000176	CMP	SWR, #SWREG	:	USING HARDWARE SW REG?
007164	001101			BNE	4\$	:	BRANCH IF YES
007166	022716	000007		CMP	#7, (SP)	:	CHAR = BEL <007>?
007172	001076			BNE	4\$	:	BRANCH IF NOT
007174	005726		5\$:	TST	(SP)+	:	RESET STACK
007176	005037	007436		CLR	20\$	:	CLEAR NEW SW SETTING
007202	005037	007440		CLR	30\$	:	CLEAR INPUT FLAG
007206	104401	015122		TYPE	DSMSG1	:	TYPE MMSG
007212	013746	000176		MOV	SWREG, -(SP)	:	PUSH SWREG ON STACK
007216	104402			TYPOC		:	TYPE IT
007220	104401	015132		TYPE	DSMSG2	:	TYPE MORE OF MMSG
007224	104406		9\$:	RDCHR		:	READ CHAR
007226	021627	000025		CMP	(SP), #25	:	CHAR = CONTROL-U ?
007232	001003			BNE	10\$	:	BRANCH IF NOT
007234	104401	012242		TYPE	\$CNTLU	:	ECHO CONTROL-U
007240	000755			BR	5\$	:	RESTART ROUTINE
007242	021627	000015		CMP	(SP), #CR	:	CHAR = CR?
007246	001011		10\$:	BNE	7\$	:	BRANCH IF NOT
007250	104401	001161		TYPE	\$CRLF	:	ECHO CR-LF
007254	005737	007440		TST	30\$	:	CHECK INPUT FLAG
007260	001460			BEQ	6\$	:	LEAVE SW SETTINGS ALONE IF NO INPUT
007262	013737	007436	000176	MOV	20\$, SWREG	:	SET NEW SW REG
007270	000454			BR	6\$	:	RETURN TO TEST
007272	021627	000012		CMP	(SP), #LF	:	CHAR = LF?
007276	001011		7\$:	BNE	8\$	:	BRANCH IF NOT
007300	104401	001161		TYPE	\$CRLF	:	ECHO CR-LF
007304	005737	007440		TST	30\$	:	CHECK INPUT FLAG

007310	001477			BEQ	TSEL					
007312	013737	007436	000176	MOV	20\$,SWREG					; LEAVE SW SETTINGS ALONE IF NO INPUT
007320	000473			BR	TSEL					; SET NEW SW REG
007322	042716	177770		8\$: BIC	#1C7,(SP)					; GO TO TEST SELECT (VIA KEYBOARD)
007326	062716	000060		ADD	#60,(SP)					; MASK DIGIT
007332	004737	010344		JSR	PC,\$TYPEC					; MAKE ASCII
007336	042716	177770		BIC	#1C7,(SP)					; PRINT DIGIT
007342	006337	007436		ASL	20\$					; MASK DIGIT
007346	006337	007436		ASL	20\$					; SHIFT SWITCH SETTINGS FOR NEW ONE
007352	006337	007436		ASL	20\$					
007356	062637	007436		ADD	(SP)+,20\$					; ADD NEW SWITCH
007362	005237	007440		INC	30\$					; SET INPUT FLAG
007366	000716			BR	9\$					; CONTINUE
007370	022716	000177		4\$: CMP	#177,(SP)					; CHAR = RUBOUT?
007374	001001			BNE	3\$					; NO, CHECK AGAIN
007376	000444			BR	TSEL					; YES, GET TEST SELECTION (VIA KEYBOARD)
007400	022716	000003		3\$: CMP	#3,(SP)					; CHAR = CNTL C ?
007404	001416			BEQ	KYBDST					; YES, GET # COLUMNS
007406	005716			TST	(SP)					; IS CODE = NUL, IE., CTL-SPACE?
007410	001004			BNE	6\$					; BRANCH IF NOT
007412	022737	000064	001146	CMP	#64,\$STSTM					; IS THIS TEST 64 ?
007420	001402			BEQ	11\$					; BRANCH IF YES
007422	005726			6\$: TST	(SP)+					; RESET STACK
007424	000207			1\$: RTS	PC					; NO, RETURN
007426	012706	001100		11\$: MOV	#STACK,SP					; FIX STACK
007432	000137	006210		JMP	ACCEPT					; TO WITHIN TEST 64
007436	000000			20\$: .WORD	0					; SW SETTING INPUT
007440	000000			30\$: .WORD	0					; INPUT FLAG

;/;;/

:ROUTINE TO SET NUMBER OF COLUMNS FROM CONSOLE DEVICE KYBD

;/;;/

007442 004737 006614  
 007446 104401 014751  
 007452 104410  
 007454 012605  
 007456 020527 000204  
 007462 003003  
 007464 020527 000002  
 007470 103005  
 007472 104401 001160  
 007476 104401 001161  
 007502 000763  
 007504 010537 001150

KYBDST: JSR PC,SRDCI ;CLEAR CLOCK INTER  
 TYPE ,COLUMN ;TYPE COLUMNS MESSAGE  
 2\$: RDEEC ;GET # COLUMNS  
 MOV (SP)+,R5 ;POP STACK INTO R5  
 CMP R5,#132. ;TEST SIZE OF NUMBER  
 BGT 1\$ ;TOO BIG, GET AGAIN  
 CMP R5,#2 ;TEST SIZE AGAIN  
 BHIS 3\$ ;BRANCH IF OK  
 1\$: TYPE ,SQUES ;INPUT ERROR - TYPE QUESTION MARK  
 TYPE ,SCLRF  
 BR 2\$ ;GET INPUT AGAIN  
 3\$: MOV R5,WIDTH ;OK, SAVE # COLUMNS

;/;;/

:ROUTINE TO FETCH TEST # FROM CONSOLE KEYBOARD  
 AND DETERMINE TEST ACTION  
 TEST NUMBER MUST BE OCTAL, FOLLOWED BY ONE OF THE  
 FOLLOWING CONTROL CHARACTERS:

PERIOD . = RUN TEST ONCE AND SELECT NEXT TEST  
 L = LOOP ON SELECTED TEST  
 S = START TEST SEQUENCE WITH SELECTED TEST

;/;;/

007510 004737 006614  
 007514 105037 001153  
 007520 105037 001154  
 007524 105037 001152  
 007530 104401 014767  
 007534 104407  
 007536 012605  
 007540 112500  
 007542 042700 177600  
 007546 022700 000003  
 007552 001733  
 007554 020027 000060  
 007560 103461  
 007562 020027 000067  
 007566 101061  
 007570 042700 177770  
 007574 006300  
 007576 006300  
 007600 006300  
 007602 112501  
 007604 042701 177600  
 007610 020127 000060

TSEL: JSR PC,SRDCI ;CLEAR CLOCK INTER  
 CLRB TRONE ;CLEAR PROGRAM CONTROL FLAGS  
 CLRB TLOOP  
 CLRB STRONE  
 TYPE ,SELTST ;TYPE SELECT TEST MESSG  
 5\$: RDLIN ;GET TEST SELECTION  
 MOV (SP)+,R5 ;POP STACK INTO R5  
 MOVB (R5)+,R0 ;SET TEST # IN R0  
 BIC #C177,R0  
 CMP #3,R0 ;CHECK IF CHAR = CNTL-C  
 BEQ KYBDST ;GET # COLUMNS IF CNTL-C  
 CMP R0,#60 ;CHECK IF OCTAL NUMBER  
 BLO 4\$ ;NOT OCTAL - INPUT ERRO  
 CMP R0,#67 ;NOT OCTAL - INPUT ERROR  
 BHI 4\$ ;NOT OCTAL - INPUT ERROR  
 BIC #C7,R0 ;OK - STORE DIGIT  
 ASL R0  
 ASL R0  
 ASL R0  
 MOVB (R5)+,R1 ;GET SECOND DIGIT  
 BIC #C177,R1 ;CHECK IF AN OCTAL DIGIT  
 CMP R1,#60



MOS

MAINDEC-11-DZLAE-B MACY11 27(1006) 01-MAR-77 14:45 PAGE 63  
 DZLAE.B.P11 28-FEB-77 15:08 ROUTINES TO SELECT DESIRED TEST

Address	Offset	Code	Label	Instruction	Comment
007614	103446			BLO 4\$	; NOT OCTAL - INPUT ERROR
007616	020127	000067		CMP R1,#67	
007622	101043			BHI 4\$	; NOT OCTAL - INPUT ERROR
007624	042701	177770		BIC #1C7,R1	; OK - MASK DIGIT
007630	060100			ADD R1,R0	; MAKE COMPLETE TEST NUMBER
007632	010037	001146		MOV R0,\$STNM	; SAVE TEST NUMBER
007636	006300			ASL R0	; SET TABLE POINTER
007640	005760	013356		TST TAT(R0)	; CHECK IF TEST IS IN TABLE
007644	003432			BLE 4\$	; NOT IN TABLE, GET NEW SELECTION
007646	112501			MOVB (R5)+,R1	; GET CONTROL CHAR
007650	042701	177600		BIC #1C177,R1	; MASK BITS
007654	020127	000056		CMP R1,#56	; CHAR = PERIOD?
007660	001004			BNE 1\$	; NO, CONTINUE CHECK
007662	112737	177777	001153	MOVB #-1,TRONE	; YES, SET FLAG
007670	000414			BR 3\$	; CONTINUE
007672	042701	000040	1\$:	BIC #BITS,R1	; MASK BIT 5 (ALLOW UPPER OR LOWER CASE)
007676	022701	000114		CMP #'L,R1	; CHAR = L?
007702	001004			BNE 2\$	; NO, CONTINUE
007704	112737	177777	001154	MOVB #-1,TLOOP	; YES, SET FLAG
007712	000403			BR 3\$	; CONTINUE
007714	022701	000123	2\$:	CMP #'S,R1	; CHAR = S?
007720	001004			BNE 4\$	; NO, INPUT ERROR
007722	012706	001100	3\$:	MOV #STACK,SP	; RESET STACK
007726	000170	013356		JMP @TAT(R0)	; ALL OK - GO TO SELECTED TEST
007732	104401	001160	4\$:	TYPE .SQUES	; INPUT ERROR
007736	104401	001161		TYPE .SCP_F	; PRINT QUESTION MARK
007742	000674			BR 5\$	; GET NEW INPUT

;;\*\*\*\*\*

.SBTTL ERROR HANDLER ROUTINE

; THIS ROUTINE WILL SAVE THE ERROR NUMBER AND THE ADR OF THE ERROR CALL  
 ; AND GO TO REPORT ON ERROR  
 ; THE SWITCH OPTIONS PROVIDED BY THIS ROUTINE ARE:

SW15 = 1 HALT ON ERROR  
 SW13 = 1 INHIBIT ERROR TYPEOUTS  
 SW10 = 1 BELL ON ERROR

; CALL ERROR N ; ERROR = EMT & N = ERROR ITEM NUMBER

007744	013777	001146	171172	\$ERROR: MOV	\$STNM, \$DISPLAY;	DISPLAY TEST NUMBER AND ERROR FLAG
007752	032777	002000	171162	BIT	#BIT10, \$SWR	; BELL ON ERROR?
007760	001402			BEG	1\$	; NO - SKIP
007762	104401	001156		TYPE	\$BELL	; RING BELL
007766	011637	01004C		1\$: MOV	(SP), \$ERRPC	; GET ADDRESS OF ERROR INSTRUCTION
007772	162737	000002	010040	SUB	#2, \$ERRPC	
010000	117737	000034	010042	MOVB	\$ERRPC, \$ITEMB	; STRIP AND SAVE THE ERROR ITEM CODE
010006	032777	020000	171126	BIT	#BIT13, \$SWR	; SKIP TYPEOUTS IF SET
010014	001004			BNE	2\$	; SKIP TYPEOUTS
010016	004737	010044		JSR	PC REPORT	; GO TO REPORT ROUTINE
010022	104401	001161		TYPE	\$CRLF	
010026	005777	171110		2\$: TST	\$SWR	; HALT ON ERROR IF SET
010032	100001			BPL	3\$	; SKIP IS CONTINUE
010034	104421			HOLD		; DYNAMIC HALT
010036	000002			3\$: RTI		; RETURN
010040	000000			\$ERRPC: .WORD	0	; LAST ERROR INSTRUCTION EXECUTED
010042	000000			\$ITEMB: .WORD	0	; ITEM CODE

;;

ERROR REPORT ROUTINE

ERROR MESSAGE WILL USE THE FOLLOWING FORM:

TEST #XX, PC=XXXXXX, ERROR #XXX, MESSAGE >>>>>>>>>>

;;

010044 105737 001173  
 010050 100435  
 010052 010046  
 010054 104401 015044  
 010060 013746 001146  
 010064 104403  
 010066 002  
 010067 001  
 010070 104401 015054  
 010074 013746 010040  
 010100 104402  
 010102 104401 015063  
 010106 013746 010042  
 010112 104403  
 010114 003  
 010115 001  
 010116 104401 015076  
 010122 013700 010042  
 010126 006300  
 010130 016037 013554 010140  
 010136 104401  
 010140 000000  
 010142 012600  
 010144 000207

REPORT:	TSTB	\$TPFLG	; TERMINAL EXIT?
	BMI	2\$	; NO, EXIT
	MOV	RO, -(SP)	; PUSH RO ON STACK
	TYPE	\$TSTNC	; TYPE FIRST PART OF ERROR MESC
	MOV	\$TSTNM, -(SP)	; PUSH \$TSTNM ON STACK
	TYPOS		; TYPE TEST NUMBER
	.BYTE	2	; TWO DIGITS MAX.
	.BYTE	1	; TYPE LEADING ZEROS
	TYPE	PCMSG	; TYPE PART OF ERROR MESC
	MOV	\$ERRPC, -(SP)	; PUSH \$ERRPC ON STACK
	TYPOC		; TYPE ERROR PC
	TYPE	ERR	; TYPE MORE OF ERROR MESC
	MOV	\$ITEMB, -(SP)	; PUSH \$ITEMB ON STACK
	TYPOS		; TYPE ERROR NUMBER
	.BYTE	3	; 3 DIGITS MAX.
	.BYTE	1	; TYPE LEADING ZEROS
	TYPE	ERRS	; TYP SPACES
	MOV	\$ITEMB, RO	; GET ERROR NUMBER
	ASL	RO	; SET TABLE POINTER
	MOV	EMAT-2(RO), 1\$	; SET ERROR MESSAGE ADR
	TYPE		; TYPE ERROR MESC
1\$:	.WORD	0	
	MOV	(SP)+, RO	; POP STACK INTO RO
2\$:	RTS	PC	; RETJRN

.SBTTL SAVE AND RESTORE RO-R5 ROUTINES

```

*****
*SAVE RO-R5
*CALL:
*   SAVREG
*UPON RETURN FROM $SAVREG THE STACK WILL LOOK LIKE:
*
*TOP---(+16)
* +2---(+18)
* +4---R5
* +6---R4
* +8---R3
*+10---R2
*+12---R1
*+14---R0

```

```

010146
010146 010046
010150 010146
010152 010246
010154 010346
010156 010446
010160 010546
010162 016646 000022
010166 016646 000022
010172 016646 000022
010176 016646 000022
010202 000002

```

```

$SAVREG:
MOV RO,-(SP)      ;; PUSH RO ON STACK
MOV R1,-(SP)     ;; PUSH R1 ON STACK
MOV R2,-(SP)     ;; PUSH R2 ON STACK
MOV R3,-(SP)     ;; PUSH R3 ON STACK
MOV R4,-(SP)     ;; PUSH R4 ON STACK
MOV R5,-(SP)     ;; PUSH R5 ON STACK
MOV 22(SP),-(SP) ;; SAVE PS OF MAIN FLOW
MOV 22(SP),-(SP) ;; SAVE PC OF MAIN FLOW
MOV 22(SP),-(SP) ;; SAVE PS OF CALL
MOV 22(SP),-(SP) ;; SAVE PC OF CALL
RTI

```

```

010204
010204 012666 000022
010210 012666 000022
010214 012666 000022
010220 012666 000022
010224 012605
010226 012604
010230 012603
010232 012602
010234 012601
010236 012600
010240 000002

```

```

*RESTORE RO-R5
*CALL:
*   RESREG
$RESREG:
MOV (SP)+,22(SP) ;; RESTORE PC OF CALL
MOV (SP)+,22(SP) ;; RESTORE PS OF CALL
MOV (SP)+,22(SP) ;; RESTORE PC OF MAIN FLOW
MOV (SP)+,22(SP) ;; RESTORE PS OF MAIN FLOW
MOV (SP)+,R5     ;; POP STACK INTO R5
MOV (SP)+,R4     ;; POP STACK INTO R4
MOV (SP)+,R3     ;; POP STACK INTO R3
MOV (SP)+,R2     ;; POP STACK INTO R2
MOV (SP)+,R1     ;; POP STACK INTO R1
MOV (SP)+,R0     ;; POP STACK INTO R0
RTI

```

::\*\*\*\*\*

.SBTTL TYPE ROUTINE

;ROUTINE TO TYPE ASCIZ MESSAGES, MESSAGE MUST TERMINATE WITH A 0 BYTE.  
;THE ROUTINE WILL INSERT A NUMBER OF NULL CHARACTERS AFTER A LINE FEED.  
;NOTE1: \$NULL CONTAINS THE CHARACTER TO BE USED AS THE FILLER CHARACTER  
;NOTE2: \$FILLS CONTAINS THE NUMBER OF FILLER CHARACTERS REQUIRED.  
;NOTE3: \$FILLC CONTAINS THE CHARACTER TO FILL AFTER.

;CALL:

			TYPE	MESADR	MESADR IS ADDRESS OF FIRST CHAR IN ASCIZ STRING
010242	105737	001173	\$TYPE: TSTB	\$TPFLG	: IS THERE A CONSOLE TERMINAL?
010246	100407		BMI	3\$	: BRANCH IF NO CONSOLE TERMINAL
010250	010046		1\$: MOV	RO, -(SP)	: SAVE RO
010252	017600	000002	MOV	2\$(SP), RO	: GET ADR OF ASCIZ STRING
010256	112046		2\$: MOVB	(RO)+, -(SP)	: PUSH CHARACTER TO BE TYPED ONTO STACK
010260	001005		BNE	4\$	: BR IF IT ISN'T THE TERMINATOR
010262	005726		TST	(SP)+	: IF TERMINATOR, POP IT OFF STACK
010264	012600		MOV	(SP)+, RO	: RESTORE RO
010266	062716	000002	3\$: ADD	2, (SP)	: ADJUST RETURN PC
010272	000002		RTI		: RETURN
010274	122716	000200	4\$: CMPB	#CRLF, (SP)	: BRANCH IF NOT <CRLF>
010300	001004		BNE	5\$	
010302	005726		TST	(SP)+	: POP <CR><LF> EQUIV
010304	104401	001161	TYPE,	\$CRLF	: TYPE CR-LF
010310	000762		BR	2\$	: GET NEXT CHAR
010312	004737	010344	5\$: JSR	PC, \$TYPEC	: GO TYPE CHAR
010316	123726	001172	6\$: CMPB	\$FILLC, (SP)+	: IS IT TIME FOR FILLER CHARS?
010322	001355		BNE	2\$	: IF NO GO GET NEXT CHAR
010324	013746	001170	MOV	\$NULL, -(SP)	: GET # FILLER CHARS NEEDED
					: AND THE NULL CHAR
010330	105366	000001	7\$: DECB	1(SP)	: DOES A NULL NEED TO BE TYPED?
010334	002770		BLT	6\$	: BR IF NO - GO POP THE NULL OFF OF STACK
010336	004737	010344	JSR	PC, \$TYPEC	: GO TYPE NULL
010342	000772		BR	7\$	: LOOP
010344	105777	170534	\$TYPEC: TSTB	2\$TPS	: WAIT UNTIL CONSOLE PRINTER IS READY
010350	100375		BPL	\$TYPEC	
010352	116677	000002 170526	MOVB	2(SP), 2\$TPB	: LOAD CHAR TO BE TYPED INTO DATA REG.
010360	000207		RTS	PC	: RETURN

CONVERT BINARY TO DECIMAL AND TYPE ROUTINE

.SBTTL CONVERT BINARY TO DECIMAL AND TYPE ROUTINE

```

;*****
;THIS ROUTINE IS USED TO CHANGE A 16-BIT BINARY NUMBER TO A 5-DIGIT
;SIGNED DECIMAL (ASCII) NUMBER AND TYPE IT. DEPENDING ON WHETHER THE
;NUMBER IS POSITIVE OR NEGATIVE A SPACE OR A MINUS SIGN WILL BE TYPED
;BEFORE THE FIRST DIGIT OF THE NUMBER. LEADING ZEROS WILL ALWAYS BE
;REPLACED WITH SPACES.
;CALL:

```

```

; *      MOV      NUM,-(SP)      ;:PUT THE BINARY NUMBER ON THE STACK
; *      TYPDS                    ;:GO TO THE ROUTINE

```

```

010362          $TYPDS:
010362 010046      MOV      R0,-(SP)      ;:PUSH R0 ON STACK
010364 010146      MOV      R1,-(SP)      ;:PUSH R1 ON STACK
010366 010246      MOV      R2,-(SP)      ;:PUSH R2 ON STACK
010370 010346      MOV      R3,-(SP)      ;:PUSH R3 ON STACK
010372 010546      MOV      R5,-(SP)      ;:PUSH R5 ON STACK
010374 012746 020200  MOV      #20200,-(SP) ;:SET BLANK SWITCH AND SIGN
010400 016605 000020  MOV      20(SP),R5 ;:GET THE INPUT NUMBER
010404 100004      BPL      1$ ;:BR IF INPUT IS POS.
010406 005405      NEG      R5 ;:MAKE THE BINARY NUMBER POS.
010410 112766 000055 000001  MOVB   #'-,1(SP) ;:MAKE THE ASCII NUMBER NEG.
010416 005000      CLR      R0 ;:ZERO THE CONSTANTS INDEX
010420 012703 010576      MOV      #$DBLK,R3 ;:SETUP THE OUTPUT POINTER
010424 112723 000040      MOVB   #' ,(R3)+ ;:SET THE FIRST CHARACTER TO A BLANK.
010430 005002      CLR      R2 ;:CLEAR THE BCD NUMBER
010432 016001 010566      MOV      $DTBL(R0),R1 ;:GET THE CONSTANT
010436 160105      SUB      R1,R5 ;:FORM THIS BCD DIGIT
010440 002402      BLT      4$ ;:BR IF DONE
010442 005202      INC      R2 ;:INCREASE THE BCD DIGIT BY 1
010444 000774      BR      3$
010446 060105      4$:  ADD      R1,R5 ;:ADD BACK THE CONSTANT
010450 005702      TST      R2 ;:CHECK IF BCD DIGIT=0
010452 001002      BNE      5$ ;:FALL THROUGH IF 0
010454 105716      TSTB   (SP) ;:STILL DOING LEADING 0'S?
010456 100407      BMI      7$ ;:BR IF YES
010460 106316      5$:  ASLB   (SP) ;:MSD?
010462 103003      BCC      6$ ;:BR IF NO
010464 116663 000001 177777  MOVB   1(SP),-1(R3) ;:YES--SET THE SIGN
010472 052702 000060      6$:  BIS      #'0,R2 ;:MAKE THE BCD DIGIT ASCII
010476 052702 000040      7$:  BIS      #' ,R2 ;:MAKE IT A SPACE IF NOT ALREADY A DIGIT
010502 110223      MOVB   R2,(R3)+ ;:PUT THIS CHARACTER IN THE OUTPUT BUFFER
010504 005720      TST   (R0)+ ;:JUST INCREMENTING
010506 020027 000010      CMP   R0,#10 ;:CHECK THE TABLE INDEX
010512 002746      BLT   2$ ;:GO DO THE NEXT DIGIT
010514 003002      BGT   8$ ;:GO TO EXIT
010516 010502      MOV   R5,R2 ;:GET THE LSD
010520 000764      BR   6$ ;:GO CHANGE TO ASCII
010522 105726      8$:  TSTB   (SP)+ ;:WAS THE LSD THE FIRST NON-ZERO?
010524 100003      BPL   9$ ;:BR IF NO
010526 116663 177777 177776  MOVB   -1(SP),-2(R3) ;:YES--SET THE SIGN FOR TYPING
010534 105013      9$:  CLRB   (R3) ;:SET THE TERMINATOR
010536 012605      MOV   (SP)+,R5 ;:POP STACK INTO R5
010540 012603      MOV   (SP)+,R3 ;:POP STACK INTO R3
010542 012602      MOV   (SP)+,R2 ;:POP STACK INTO R2

```

MAINDEC-11-DZLAE-8 MACY11 27(1006) 01-MAR-77 14:45 PAGE 69  
DZLAE8.P11 28-FEB-77 15:08

CONVERT BINARY TO DECIMAL AND TYPE ROUTINE

```

010544 012601      MOV      (SP)+,R1      ;;POP STACK INTO R1
010546 012600      MOV      (SP)+,R0      ;;POP STACK INTO R0
010550 104401 010576 TYPE      $DBLK      ;;NOW TYPE THE NUMBER
010554 016666 000002 000004 MOV      2(SP),4(SP)    ;;ADJUST THE STACK
010562 012616      MOV      (SP)+,(SP)
010564 000002      RTI                          ;;RETURN TO USER
010566 023420      $DTBL: 10000.
010570 001750      1000.
010572 000144      100.
010574 000012      10.
010576 000004      $DBLK: .BLKW 4

```

.SBTTL BINARY TO OCTAL (ASCII) AND TYPE

```

*****
: THIS ROUTINE IS USED TO CHANGE A 16-BIT BINARY NUMBER TO A 6-DIGIT
: OCTAL (ASCII) NUMBER AND TYPE IT.
: $TYPOS---ENTER HERE TO SETUP SUPPRESS ZEROS AND NUMBER OF DIGITS TO TYPE
: CALL:
:   MOV     NUM,-(SP)      ;; NUMBER TO BE TYPED
:   TYPOS   ;; CALL FOR TYPEOUT
:   .BYTE  N              ;; N=1 TO 5 FOR NUMBER OF DIGITS TO TYPE
:   .BYTE  M              ;; M=1 OR 0
:                               ;; 1=TYPE LEADING ZEROS
:                               ;; 0=SUPPRESS LEADING ZEROS

```

```

: $TYPON---ENTER HERE TO TYPE OUT WITH THE SAME PARAMETERS AS THE LAST
: $TYPOS OR $TYPOC

```

```

: CALL:
:   MOV     NUM,-(SP)      ;; NUMBER TO BE TYPED
:   TYPON   ;; CALL FOR TYPEOUT

```

```

: $TYPOC---ENTER HERE FOR TYPEOUT OF A 16 BIT NUMBER

```

```

: CALL:
:   MOV     NUM,-(SP)      ;; NUMBER TO BE TYPED
:   TYPOC   ;; CALL FOR TYPEOUT

```

```

010606 017646 000000          $TYPOS: MOV     2(SP),-(SP)      ;; PICKUP THE MODE
010612 116637 000001 011031  MOVB   1(SP), $OFILL  ;; LOAD ZERO FILL SWITCH
010620 112537 011033          MOVB   (SP)+, $OMODE+1 ;; NUMBER OF DIGITS TO TYPE
010624 062716 000002          ADD     #2, (SP)      ;; ADJUST RETURN ADDRESS
010630 000406          BR     $TYPON
010632 112737 000001 011031  $TYPOC: MOVB   #1, $OFILL  ;; SET THE ZERO FILL SWITCH
010640 112737 000006 011033  MOVB   #6, $OMODE+1  ;; SET FOR SIX(6) DIGITS
010646 112737 000005 011030  $TYPON: MOVB   #5, $OCNT  ;; SET THE ITERATION COUNT
010654 010346          MCV   R3, -(SP)      ;; SAVE R3
010656 010446          MOV   R4, -(SP)      ;; SAVE R4
010660 010546          MOV   R5, -(SP)      ;; SAVE R5
010662 113704 011033          MOVB   $OMODE+1, R4 ;; GET THE NUMBER OF DIGITS TO TYPE
010666 005404          NEG   R4
010670 062704 000006          ADD   #6, R4          ;; SUBTRACT IT FOR MAX. ALLOWED
010674 110437 011032          MOVB   R4, $OMODE    ;; SAVE IT FOR USE
010700 113704 011031          MOVB   $OFILL, R4    ;; GET THE ZERO FILL SWITCH
010704 016605 000012          MOV   12(SP), R5    ;; PICKUP THE INPUT NUMBER
010710 005003          CLR   R3            ;; CLEAR THE OUTPUT WORD
010712 006105          1$: ROL   R5          ;; ROTATE MSB INTO "C"
010714 000404          BR   3$
010716 006105          2$: ROL   R5          ;; FORM THIS DIGIT
010720 006105          ROL   R5
010722 006105          ROL   R5
010724 010503          MOV   R5, R3
010726 006103          3$: ROL   R3          ;; GET LSB OF THIS DIGIT
010730 105337 011032          JECB  $OMODE        ;; TYPE THIS DIGIT
010734 100016          BPL   7$            ;; BR IF NO
010736 042703 177770          BIC   #177770, R3   ;; GET RID OF JUNK
010742 001002          BNE   4$            ;; TEST FOR 0
010744 005704          TST  R4            ;; SUPPRESS THIS 0
010746 001403          BEQ  5$            ;; BR IF YES

```



```

010750 005204
010752 052703 000060
010756 052703 000040
010762 110337 011026
010766 104401 011026
010772 105337 011030
010776 003347
011000 002402
011002 005204
011004 000744
011006 012605
011010 012604
011012 012603
011014 016666 000002 000004
011022 012616
011024 000002
011026 000
011027 000
011030 000
011031 000
011032 000000
  
```

```

4$: INC R4
   BIS #'C,R3
5$: BIS #' R3
   MOV R3,8$
   TYPE 8$
7$: DECB $OCNT
   BGT 2$
   BLT 6$
   INC R4
   BR 2$
6$: MOV (SP)+,R5
   MOV (SP)+,R4
   MOV (SP)+,R3
   MOV 2(SP),4(SP)
   MOV (SP)+,(SP)
   RTI
8$: .BYTE 0
   .BYTE 0
$OCNT: .BYTE 0
$OFILL: .BYTE 0
$OMODE: .WORD 0
  
```

```

:: DON'T SUPPRESS ANYMORE 0'S
:: MAKE THIS DIGIT ASCII
:: MAKE ASCII IF NOT ALREADY
:: SAVE FOR TYPING
:: GO TYPE THIS DIGIT
:: COUNT BY 1
:: BR IF MORE TO DO
:: BR IF DONE
:: INSURE LAST DIGIT ISN'T A BLANK
:: GO DO THE LAST DIGIT
:: RESTORE R5
:: RESTORE R4
:: RESTORE R3
:: SET THE STACK FOR RETURNING
:: RETURN
:: STORAGE FOR ASCII DIGIT
:: TERMINATOR FOR TYPE ROUTINE
:: OCTAL DIGIT COUNTER
:: ZERO FILL SWITCH
:: NUMBER OF DIGITS TO TYPE
  
```

```

011034 004737 011316
011040 000137 000000
  
```

```

$LOAD: JSR PC,RSTADR
$LDPTR: JMP 0
  
```

```

: RESTORE ADDRESSING TO FIRST PRINTER
: SWITCH TO EITHER PARALLEL OR
: SERIAL SINGLE-CHARACTER LOADER.
: THIS SWITCH IS SET UP BY THE PROGRAM
: AT STARTUP PER THE CONTENTS OF SERSW WORD.
  
```

::\*\*\*\*\*

.SBTTL ROUTINES TO LOAD CHARACTERS TO LA190

://

:ROUTINE TO LOAD SINGLE CHARACTERS TO LA180 PRINTER  
:USING THE STANDARD PARALLEL INTERFACE  
:CALL: MOV CHAR,RO ;PUT CHAR IN RO  
:LOAD

:IF PRINTER DOES NOT GO READY WITHIN 9 TO 32 SECONDS  
:(DEPENDING ON CPU AND MEMORY TYPE) THE DIAGNOSTIC WILL  
:INDICATE AN ERROR - ERROR #24 - NOT READY.

://

011044	104420			PLOAD:	CHECK		:CHECK FOR CONTROL
011046	012737	000040	C11140		MOV	#40,6\$	:SET DELAY LOOP COUNT
011054	005777	170034			TST	2LPS	:CHECK FOR ERROR CONDX
011060	100002				BPL	1\$	:BRANCH IF OK
011062	104024				ERROR	24	:PRINTER ERROR BEFORE LOAD
011064	000423				BR	4\$	:EXIT
011066	005037	011136		1\$:	CLR	5\$	:CLEAR DELAY COUNT
011072	005237	011136		2\$:	INC	5\$	:INC COUNT
011076	001005				BNE	3\$	:COUNTINUE
011100	005337	C11140			DEC	6\$	:DEC DELAY LOOP COUNT
011104	001370				BNE	1\$	:WAIT IF NOT READY
011106	104025				ERROR	25	:ERROR, PRINTER NOT READY
011110	000411				BR	4\$	:EXIT
011112	105777	167776		3\$:	TSTB	2LPS	:CHECK FOR PRINTER READY
011116	100365				BPL	2\$	:WAIT FOR READY
011120	110077	167772			MCVB	RO,2LFB	:LOAD CHAR
011124	005777	167764			TST	2LPS	:TEST FOR ERROR CONDX AGAIN
011130	100001				BPL	4\$	:BRANCH IF OK
011132	104026				ERROR	26	:PRINTER ERROR AFTER LOAD
011134	000402			4\$:	BR	NXTADR	:DOES ANOTHER PRINTER REQUIRE LOADING ALSO?
011136	000000			5\$:	.WORD	0	:DELAY COUNTER
011140	000040			6\$:	.WORD	32.	:DELAY LOOP COUNTER

011142	005337	001132		NXTADR:	DEC	LPCTR	:DECREMENT LINE PRINTER COUNTER
011146	003416				BLE	10\$	:BR IF COUNT IS ZERO OR LESS (TO EXIT)
011150	062737	000010	001110		ADD	#10.LPKS	:ADDRESS NEXT CONTIGUOUS LINE PRINTER
011156	062737	000010	001112		ADD	#10.LPKB	
011164	062737	000010	001114		ADD	#10.LPS	
011172	062737	000010	001116		ADD	#10.LPB	
011200	000177	177636			JMP	2LDPTR+2	:GO LOAD SAME CHARACTER TO NEXT PRINTER
011204	000002			10\$:	RTI		:USING SAME LOADER. :RETURN, SINGLE CHARACTER LOAD IS :COMPLETE (TO ALL PRINTERS).

;/;;/

:ROUTINE TO LOAD SINGLE CHARACTERS TO THE LA180 PRINTER  
:USING THE SERIAL INTERFACE.  
:CALL: MOV CHAR,RO ;PUT CHAR IN RO  
: LOAD

;/;;/

011206	105777	167676		SLOAD:	TSTB	2LPKS	;CHECK FOR PRINT KBD INPUT
011212	100031				BPL	2\$	;BRANCH IF NONE
011214	017737	167672	011314		MOV	2LPKB,10\$	;READ PRINTER KEYBOARD CHARACTER
011222	042737	177600	011314		BIC	#177600,10\$	;STRIP EXCESS BITS
011230	023727	011314	000023		CMP	10\$,#23	;IS CHARACTER XOFF?
011236	001017				BNE	2\$	;NO, SO BRANCH
011240	104420			3\$:	CHECK		;YES, CHECK FOR OPERATOR INTERVENTION
011242	105777	167642			TSTB	2LPKS	;CHECK FOR MORE PRINTER KBD INPUT
011246	100374				BPL	3\$	;NONE, WAIT FOR EXPECTED XON
011250	017737	167636	011314		MOV	2LPKB,10\$	;READ PRINTER KEYBOARD CHARACTER
011256	042737	177600	011314		BIC	#177600,10\$	;STRIP EXCESS BITS
011264	023727	011314	000021		CMP	10\$,#21	;IS CHARACTER XON?
011272	001362				BNE	3\$	;NO, WAIT SOME MORE.
011274	000404				BR	4\$	;YES, GO DIRECTLY TO LOAD A CHARACTER
011276	104420			2\$:	CHECK		;CHECK FOR OPERATOR INTERVENTION
011300	105777	167610			TSTB	2LPS	;IS PRINTER READY?
011304	100340				BPL	SLOAD	;NO, START CHECKS OVER
011306	110077	167604		4\$:	MOVB	RO,2LPB	;YES, LOAD CHARACTER
011312	000713				BR	NXTADR	;GO LOAD SAME CHARACTER TO NEXT PRINTER
							;USING SAME LOADER.
011314	000000			10\$:	.WORD	0	;LA180 KEYBOARD CHARACTER STORAGE.

011316	013737	001130	001110	RSTADR:	MOV	ACTFST,LPKS	;SET PRINTER KBD STATUS REG ADDRESS
011324	013737	001110	001112		MOV	LPKS,LPKB	
011332	062737	000002	001112		ADD	#2,LPKB	;SET PRINTER KBD BUFFER ADDRESS
011340	013737	001112	001114		MOV	LPKB,LPS	
011346	062737	000002	001114		ADD	#2,LPS	;SET PRINTER STATUS REG ADDRESS
011354	013737	001114	001116		MOV	LPS,LPB	
011362	062737	000002	001116		ADD	#2,LPB	;SET PRINTER BUFFER ADDRESS
011370	013737	001122	001132		MOV	NUMLP,LPCR	;PUT # OF LP'S INTO A COUNTER.
011376	000207				RTS	PC	;RETURN

K06

MAINDEC-11-DZLAE-B MACY11 27(1006) 01-MAR-77 14:45 PAGE 74  
 DZLAEB.P11 28-FEB-77 15:08

ROUTINES TO LOAD CHARACTERS TO LA180

;/;;/

;ROUTINE TO LOAD MULTIPLE CHARACTERS (NOT ASCIZ/ASCII STRINGS)  
 ;WILL LOAD CHAR ONCE IF COUNT = 0  
 ;PUT CHARACTER COUNT IN R1 (POSITIVE)  
 ;PUT ASCII CHARACTER IN R0  
 ;CALL: MLOAD

;/;;/

011400 104415  
 011402 005301  
 011404 003375  
 011406 000002

\$MLOAD: LOAD ;LOAD CHAR  
 .DEC R1 ;DEC COUNT  
 BGT \$MLOAD ;FINISH LOAD  
 RTI ;RETURN

;/;;/

;ROUTINE TO LOAD CONVERTED NUMBERS AND SUPPRESS LEADING ZEROS  
 ;IF ALL DIGITS ARE ZERO, ROUTINE WILL PRINT A SINGLE ZERO  
 ;ENTER WITH ADDRESS OF ASCIZ STRING ON STACK  
 ;CALL: CNLOAD

;/;;/

011410  
 011410 010046  
 011412 010146  
 011414 010246  
 011416 005002  
 011420 016601 000012  
 011424 112100  
 011426 001410  
 011430 005702  
 011432 001004  
 011434 020027 000060  
 011440 001771  
 011442 005202  
 011444 104415  
 011446 000766  
 011450 005702  
 011452 001003  
 011454 012700 000060  
 011460 104415  
 011462  
 011462 012602  
 011464 012601  
 011466 012600  
 011470 016666 000002 000004  
 011476 012616  
 011500 000002

\$CNLD:  
 MOV R0,-(SP) ;;PUSH R0 ON STACK  
 MOV R1,-(SP) ;;PUSH R1 ON STACK  
 MOV R2,-(SP) ;;PUSH R2 ON STACK  
 CLR R2  
 1\$: MOV 12(SP),R1 ;GET ADR  
 MOVB (R1)+,R0 ;GET CHAR  
 BEQ 3\$ ;RETURN WHEN DONE  
 TST R2 ;DONE LEADING ZEROS?  
 BNE 2\$ ;YES, LOAD CHAR  
 CMP R0,#60 ;NO, CHECK THIS CHAR  
 BEQ 1\$ ;SKIP IF ZERO  
 INC R2 ;SET FLAG IF NON-ZERO  
 2\$: LOAD ;LOAD CHAR  
 BR 1\$ ;CONTINUE  
 3\$: TST R2 ;ALL CHARS ZERO?  
 BNE 4\$ ;NO, EXIT  
 MOV #60,R0 ;YES, LOAD ZERO  
 LOAD  
 4\$: MOV (SP)+,R2 ;;POP STACK INTO R2  
 MOV (SP)+,R1 ;;POP STACK INTO R1  
 MOV (SP)+,R0 ;;POP STACK INTO R0  
 MOV 2(SP),4(SP) ;ADJUST STACK  
 MOV (SP)+,(SP)  
 RTI ;RETJRN

//

: ROUTINE TO PRINT ASCIZ STRINGS ON LA180 PRINTER  
: STRING MUST BE TERMINATED BY NULL BYTE  
: CALL: PRINT  
: MESAOR  
:

//

011502  
011502 010046  
011504 010146  
011506 017601 000004  
011512 112100  
011514 001407  
011516 120027 000200  
011522 001002  
011524 012700 000012  
011530 104415  
011532 000767  
011534  
011534 012601  
011536 012600  
011540 062716 000002  
011544 000002

\$PRINT:  
MOV RO, -(SP) ;: PUSH RO ON STACK  
MOV R1, -(SP) ;: PUSH R1 ON STACK  
MOV 24(SP), R1 ;: GET ADDRESS OF ASCIZ STRING  
1\$: MOVB (R1)+, RO ;: GET CHAR  
BEQ 2\$ ;: BRANCH IF TERMINATOR (NULL)  
CMPB RO, #CRLF ;: CHECK IF CRLF CODE  
BNE 3\$ ;: BRANCH IF NOT  
MOV #LF, RO ;: YES, DO LF ONLY  
3\$: LOAD ;: LOAD CHAR  
BR 1\$ ;: GET NEXT CHAR  
2\$: MOV (SP)+, R1 ;: POP STACK INTO R1  
MOV (SP)+, RO ;: POP STACK INTO RO  
ADD #2, (SP) ;: ADJUST RETURN PC  
RTI ;: RETURN

M06

MAINDEC-11-DZLAE-B MACY11 27(1006) 01-MAR-77 14:45 PAGE 76  
 DZLAE8.P11 28-FEB-77 15:J8 ROUTINES TO LOAD CHARACTERS TO LA180

;/;;/

.SBTTL PRINT TEST HEADER

;THE NUMBER OF COLUMNS WILL ALSO BE PRINTED FOR TEST 25 ONLY  
 ;CALL: PRTHDR

;/;;/

011546				SPRHDR:	CLR	-(SP)	::PUT NEW PS ON STACK
011546	005045				MOV	#645,-(SP)	::PUT NEW PC ON STACK
011550	012746	011556			RTI		::POP NEW PC AND PS
011554	000002			645:			
011556					MOV	#177,R0	::SET RUBOUT CHAR
011556	012700	000177			LOAD		::CLEAR LA180 CHAR BUFFER
011562	104415				CMP	\$TSTNM,SVTST	::CHECK IF PRINTED THIS # LAST
011564	023737	001146	011660		BEG	3\$	::YES, PRINT BLANK LINE & EXIT
011572	001427				MOV	\$TSTNM,SVTST	::NO, STORE NEW #
011574	013737	001146	011660		PRINT	TSTNO	::LOAD TEST # MMSG
011602	104414	015011			MOV	\$TSTNM,-(SP)	::PUSH \$TSTNM ON STACK
011606	013746	001146			JSR	PC,\$SB20	::CONVERT #
011612	004737	013024			CNLOAD		::LOAD NUMBER
011616	104417				PRINT	.\$LF	::PRINT LINE
011620	104414	001162			CMP	\$TSTNM,#25	::IS THIS TEST 25?
011624	023727	001146	000025		BNE	3\$	::NO, SKIP COLUMN MMSG
011632	001007				MOV	WIDTH,-(SP)	::PUT # COLUMNS ON STACK
011634	013746	001150			JSR	PC,\$SB20	::CONVERT #
011640	004737	012650			CNLOAD		::LOAD NUMBER
011644	104417				PRINT	.\$COLMN	::LOAD CLOUMN MMSG
011646	104414	015031		3\$:	PRINT	.\$LF	::BLANK LINE
011652	104414	001162		4\$:	RTI		::RETURN
011656	000002						
011660	000000			SVTST:	.WORD	0	::SAVE TEST NUMBER

.SBTTL TTY INPUT ROUTINE

\*\*\*\*\*  
:ENABL LSB

.DSABL LSB

\*\*\*\*\*  
:THIS ROUTINE WILL INPUT A SINGLE CHARACTER FROM THE TTY

:\*CALL:

:\* RDCHR ;: INPUT A SINGLE CHARACTER FROM THE TTY  
:\* RETURN HERE ;: CHARACTER IS ON THE STACK  
:\* ;: WITH PARITY BIT STRIPPED OFF  
:\*

011662 011646  
011664 016666 000004 000002  
011672 105777 167202  
011676 100375  
011700 117766 167176 000004  
011706 042766 177600 000004  
011714 026627 000004 000023  
011722 001013  
011724 105777 167150  
011730 100375  
011732 117746 167144  
011736 042716 177600  
011742 022627 000021  
011746 001366  
011750 000750  
011752 026627 000004 000140  
011760 002407  
011762 026627 000004 000175  
011770 003003  
011772 042766 000040 000004  
012000 000002

\$RDCHR: MOV (SP), -(SP)  
MOV 4(SP), 2(SP)  
1\$: TSTB 2\$TKS  
BPL 1\$  
MOV 2\$TKB, 4(SP)  
BIC #177, 4(SP)  
CMP 4(SP), #23  
BNE 3\$  
2\$: TSTB 2\$TKS  
BPL 2\$  
MOV 2\$TKB, -(SP)  
BIC #177, (SP)  
CMP (SP)+, #21  
BNE 2\$  
BR 1\$  
3\$: CMP 4(SP), #140  
BLT 4\$  
CMP 4(SP), #175  
BGT 4\$  
BIC #40, 4(SP)  
4\$: RTI

:: PUSH DOWN THE PC  
: : SAVE THE PS  
: : WAIT FOR  
: : A CHARACTER  
: : READ THE TTY  
: : GET RID OF JUNK IF ANY  
: : IS IT A CONTROL-S?  
: : BRANCH IF NO  
: : WAIT FOR A CHARACTER  
: : LOOP UNTIL ITS THERE  
: : GET CHARACTER  
: : MAKE IT 7-BIT ASCII  
: : IS IT A CONTROL-G?  
: : IF NOT DISCARD IT  
: : YES, RESUME  
: : IS IT UPPER CASE?  
: : BRANCH IF YES  
: : IS IT A SPECIAL CHAR?  
: : BRANCH IF YES  
: : MAKE IT UPPER CASE  
: : GO BACK TO USER

\*\*\*\*\*  
:THIS ROUTINE WILL INPUT A STRING FROM THE TTY

:\*CALL:

:\* RDLIN ;: INPUT A STRING FROM THE TTY  
:\* RETURN HERE ;: ADDRESS OF FIRST CHARACTER WILL BE ON THE STACK  
:\* ;: TERMINATOR WILL BE A BYTE OF ALL 0'S  
:\*

012002 010346  
012004 005046  
012006 012703 012236  
012012 022703 012242  
012016 101456  
012020 104406  
012022 112613  
012024 122713 000177  
012030 001022  
012032 005716  
012034 001007  
012036 112737 000134 012234

\$RDLIN: MOV R3, -(SP)  
CLR -(SP)  
1\$: MOV #TTYIN, R3  
2\$: CMP #TTYIN+4, R3  
BLOS 4\$  
RDCHR  
MOV (SP)+, (R3)  
10\$: CMPB #177, (R3)  
BNE 5\$  
TST (SP)  
BNE 6\$  
MOV #', 9\$

:: SAVE R3  
: : CLEAR THE RUBOUT KEY  
: : GET ADDRESS  
: : BUFFER FULL?  
: : BR IF YES  
: : GO READ ONE CHARACTER FROM THE TTY  
: : GET CHARACTER  
: : IS IT A RUBOUT  
: : BR IF NO  
: : IS THIS THE FIRST RUBOUT?  
: : BR IF NO  
: : TYPE A BACK SLASH

012044	104401	012234			TYPE	95		
012050	012716	177777			MOV	-1,(SP)	;;	SET THE RUBOUT KEY
012054	005303		65:		DEC	R3	;;	BACKUP BY ONE
012056	020327	012236			CMP	R3,#STTYIN	;;	STACK EMPTY?
012062	103434				BLO	45	;;	BR IF YES
012064	111337	012234			MOV	(R3),95	;;	SETUP TO TYPEOUT THE DELETED CHAR.
012070	104401	012234			TYPE	95	;;	GO TYPE
012074	000746				BR	25	;;	GO READ ANOTHER CHAR.
012076	005716		55:		TST	(SP)	;;	RUBOUT KEY SET?
012100	001406				BEQ	75	;;	BR IF NO
012102	112737	000134	012234		MOV	#'\,95	;;	TYPE A BACK SLASH
012110	104401	012234			TYPE	95		
012114	005016				CLR	(SP)	;;	CLEAR THE RUBOUT KEY
012116	122713	000025		75:	CMP	#25,(R3)	;;	IS CHARACTER A CTRL U?
012122	001003				BNE	85	;;	BR IF NO
012124	104401	012242			TYPE	,SCNTLU	;;	TYPE A CONTROL "U"
012130	000726				BR	15	;;	GO START OVER
012132	122713	000022		85:	CMP	#22,(R3)	;;	IS CHARACTER A "TR"?
012136	001011				BNE	35	;;	BRANCH IF NO
012140	105013				CLRB	(R3)	;;	CLEAR THE CHARACTER
012142	104401	001161			TYPE	,SCRLF	;;	TYPE A "CR" & "LF"
012146	104401	012236			TYPE	,STTYIN	;;	TYPE THE INPUT STRING
012152	000717				BR	25	;;	GO PICKUP ANOTHER CHARACTER
012154	104401	001160		45:	TYPE	,SQUES	;;	TYPE A '?'
012160	000712				BR	15	;;	CLEAR THE BUFFER AND LOOP
012162	111337	012234		35:	MOV	(R3),95	;;	ECHO THE CHARACTER
012166	104401	012234			TYPE	95		
012172	122723	000015			CMP	#15,(R3)+	;;	CHECK FOR RETURN
012176	001305				BNE	25	;;	LOOP IF NOT RETURN
012200	105063	177777			CLRB	-1(R3)	;;	CLEAR RETURN (THE 15)
012204	104401	001162			TYPE	,SLF	;;	TYPE A LINE FEED
012210	005726				TST	(SP)+	;;	CLEAN RUBOUT KEY FROM THE STACK
012212	012603				MOV	(SP)+,R3	;;	RESTORE R3
012214	011646				MOV	(SP),-(SP)	;;	ADJUST THE STACK AND PUT ADDRESS OF THE
012216	016666	000004	000002		MOV	4(SP),2(SP)	;;	FIRST ASCII CHARACTER ON IT
012224	012766	012236	000004		MOV	#STTYIN,4(SP)		
012232	000002				RTI		;;	RETURN
012234	000			95:	.BYTE	0	;;	STORAGE FOR ASCII CHAR. TO TYPE
012235	000				.BYTE	0	;;	TERMINATOR
012236	000004				.BLKB	4	;;	RESERVE 4 BYTES FOR TTY INPUT
012242	052536	005015	000		SCNTLU:	.ASCIZ /↑U<<15><12>	;;	CONTROL "U"
012247	136	006507	000012		SCNTLG:	.ASCIZ /↑G<<15><12>	;;	CONTROL "G"
012254	005015	053523	020122		SMSWR:	.ASCIZ <15><12>/SWR = /		
012262	020075	000						
012265	040	047040	053505		\$MNEW:	.ASCIZ / NEW =		
012272	036440	000040						



READ A DECIMAL NUMBER FROM THE TTY

.SBTTL READ A DECIMAL NUMBER FROM THE TTY

\*\*\*\*\*  
\*THIS ROUTINE WILL READ A DECIMAL (ASCII) NUMBER FROM THE TTY AND  
\*CHANGE IT TO BINARY. IF TOO MANY CHARACTERS OR ANY ILLEGAL CHARACTERS  
\*ARE READ A "?" FOLLOWED BY A CARRIAGE RETURN-LINE FEED WILL BE TYPED.  
\*THE COMPLETE NUMBER MUST BE RETYPED. THE INPUT IS TERMINATED BY THE  
\*USER TYPING A CARRIAGE RETURN. THE RANGE OF THE INPUT NUMBER IS  
\*POSITIVE 32767 TO NEGATIVE 32768.

\*CALL:  
\* RDDEC ;:READ A DECIMAL NUMBER  
\* RETURN HERE ;:NUMBER IS ON TOP OF THE STACK

```

012276 011646          000004 000002 $RDDEC: MOV      (SP), -(SP) ;: PROVIDE SPACE FOR
012300 016666          000004 000002      MOV      4(SP), 2(SP) ;: THE INPUT NUMBER
012306 010046          000004 000002      MOV      R0, -(SP) ;: PUSH R0 ON STACK
012310 010146          000004 000002      MOV      R1, -(SP) ;: PUSH R1 ON STACK
012312 010246          000004 000002      MOV      R2, -(SP) ;: PUSH R2 ON STACK
012314 104407          000004 000002 1$:  RDLIN ;: READ AN ASCII LINE
012316 012600          000004 000002      MOV      (SP)+, R0 ;: ADDRESS OF 1ST CHAR.
012320 010037          012444      MOV      R0, 6$ ;: SAVE IN CASE OF BAD INPUT
012324 005046          000004 000002      CLR      -(SP) ;: CLEAR DATA WORD
012326 005002          000004 000002      CLR      R2 ;: SIGN SET POSITIVE
012330 122710          000055      CMPB    #'-, (R0) ;: SEE IF A MINUS SIGN WAS TYPED
012334 001001          000055      BNE     2$ ;: BR IF NO MINUS SIGN
012336 112002          000055      MOVB   (R0)+, R2 ;: SAVE FOR LATER USE
012340 112001          000055 2$:  MOVB   (R0)+, R1 ;: PICKUP THIS CHARACTER
012342 001424          000055      BEQ    3$ ;: GET OUT IF ZERO
012344 122701          000060      CMPB   #'0, R1 ;: MAKE SURE THIS CHARACTER
012350 003032          000060      BGT    5$ ;: IS A DIGIT BETWEEN 0 & 9
012352 122701          000071      CMPB   #'9, R1
012356 002427          000071      BLT    5$
012360 032716          170000      BIT    #'C7777, (SP) ;: DON'T LET NUMBER GET TO BIG
012364 001024          000071      BNE     5$ ;: BR IF NUMBER WOULD OVERFLOW
012366 006316          000071      ASL    (SP) ;: *2
012370 011646          000071      MOV    (SP), -(SP) ;: SAVE FOR LATER
012372 006316          000071      ASL    (SP) ;: *4
012374 006316          000071      ASL    (SP) ;: *8
012376 062616          000071      ADD    (SP)+, (SP) ;: *10
012400 102416          000060      BVS    5$ ;: OVERFLOW ISN'T ALLOWED
012402 162701          000060      SUB    #'0, R1 ;: STRIP AWAY THE ASCII JUNK
012406 060116          000060      ADD    R1, (SP) ;: ADD IN THIS DIGIT
012410 102412          000060      BVS    5$ ;: OVERFLOW ISN'T ALLOWED
012412 000752          000060      BR     2$ ;: LOOP
012414 005702          000060 3$:  TST    R2 ;: CHECK IF NUMBER IS NEG
012416 001401          000060      BEQ    4$ ;: BR IF NO
012420 005416          000060      NEG    (SP) ;: YES--NEGATE THE NUMBER
012422 012666          000012 4$:  MOV    (SP)+, 12(SP) ;: SAVE THE RESULT
012426 012602          000012      MOV    (SP)+, R2 ;: POP STACK INTO R2
012430 012601          000012      MOV    (SP)+, R1 ;: POP STACK INTO R1
012432 012600          000012      MOV    (SP)+, R0 ;: POP STACK INTO R0
012434 000002          000012      RTI ;: RETURN

012436 005726          000012 5$:  TST    (SP)+ ;: CLEAN PARTIAL NUMBER FROM STACK
012440 105010          000012      CLRB   (R0) ;: SET A TERMINATOR

```

007

MAINDEC-11-DZLAE-B MACY11 27(1006) 01-MAR-77 14:45 PAGE 80  
DZLAE8.P11 28-FEB-77 15:08 READ A DECIMAL NUMBER FROM THE TTY

012442 104401  
012444 000000  
012446 104401 001160  
012452 000720

6\$: TYPE .WORD 0  
TYPE \$QUES  
BR 1\$

:::TYPE THE INPUT UP TO BAD CHAR.  
:::POINTER GOES HERE  
:::"?" "CR" &"LF"  
:::TRY AGAIN

# E07

MAINDEC-11-DZLAE-B    MACY11 27(1006)    01-MAR-77 14:45 PAGE 81  
 DZLAE.B.P11    28-FEB-77 15:38

DOUBLE LENGTH BINARY TO DECIMAL ASCII CONVERT ROUTINE

.SBTTL DOUBLE LENGTH BINARY TO DECIMAL ASCII CONVERT ROUTINE

```

:*****
:*THIS ROUTINE WILL CONVERT A 32-BIT BINARY NUMBER TO AN UNSIGNED
:*DECIMAL (ASCII) NUMBER. THE SIGN OF THE BINARY NUMBER MUST BE
:*POSITIVE.
:*CALL

```

```

:*      MOV      #PNTR,-(SP)      ;; POINTER TO LOW WORD OF BINARY NUMBER
:*      JSR      PC,@#$DB2D
:*      RETURN
;; THE FIRST ADDRESS OF ASCII
;; IS ON THE STACK

```

012454	104411		\$DB2D:	SAVREG	;; SAVE REGISTERS
012456	016602	000002		MOV 2(SP),R2	;; PICKUP THE DATA POINTER
012462	012700	012634		MOV #\$DECVL,R0	;; GET ADDRESS OF "\$DECVL" STRING
012466	010066	000002		MOV R0,2(SP)	;; PUT ADDRESS OF ASCII STRING ON STACK
012472	012201			MOV (R2)+,R1	;; PICKUP THE BINARY NUMBER
012474	012202			MOV (R2)+,R2	
012476	012737	000012	012552	MOV #10,4\$	;; SET UP TO DO 10 CONVERSIONS
012504	012704	012564		MOV \$TNPWR,R4	;; ADDRESS OF TEN POWER
012510	012705	012566		MOV \$TNPWR+2,R5	
012514	005003		1\$:	CLR R3	;; CLEAR PARTIAL
012516	161401		2\$:	SUB (R4),R1	;; SUBTRACT TEN POWER
012520	005602			SBC R2	
012522	161502			SUB (R5),R2	
012524	002402			BLT 3\$	;; BR IF TEN POWER TOO LARGE
012526	005203			INC R3	;; ADD 1 TO PARTIAL
012530	000772			BR 2\$	;; LOOP
012532	062401		3\$:	ADD (R4)+,R1	;; RESTORE SUBTRACTED VALUE
012534	005502			ADC R2	
012536	062402			ADD (R4)+,R2	
012540	022525			CMP (R5)+,(R5)+	;; MOVE TO NEXT TEN POWER
012542	052703	000060		BIS #0,R3	;; CHANGE PARTIAL TO ASCII
012546	110320			MOVB R3,(R0)+	;; SAVE IT
012550	005327			DEC (PC)+	;; DONE?
012552	000000		4\$:	.WORD 0	
012554	001357			BNE 1\$	;; BR IF NO
012556	105020			CLRB (R0)+	;; TERMINATOR
012560	104412			RESREG	;; RESTORE REGISTERS
012562	000207			RTS PC	;; RETURN
012564	145000		\$TNPWR:	145000	;; 1.0E09
012566	035632			35632	
012570	160400			160400	;; 1.0E08
012572	002765			2765	
012574	113200			113200	;; 1.0E07
012576	000230			230	
012600	041100			041100	;; 1.0E06
012602	000017			17	
012604	103240			103240	;; 1.0E05
012606	000001			1	
012610	023420			23420	;; 1.0E04
012612	000000			0	
012614	001750			1750	;; 1.0E03
012616	000000			0	
012620	000144			144	;; 1.0E02

MAINDEC-11-DZLAE-B MACY11 27(1006) 01-MAR-77 14:45 PAGE 82  
 DZLAEB.P11 28-FEB-77 15:08 DOUBLE LENGTH BINARY TO DECIMAL ASCII CONVERT ROUTINE

012622 000000  
 012624 000012  
 012626 000000  
 012630 000001  
 012632 000000  
 012634 000014

0  
 12 ::1.0E01  
 0  
 1 ::1.0E00  
 0

\$DECVL: .BLKB 12. ;;RESERVE STORAGE FOR ASCII STRING

.SBTTL SINGLE LENGTH BINARY TO DECIMAL ASCII ROUTINE

::\*\*\*\*\*  
 :;THIS ROUTINE WILL CONVERT A 16-BIT UNSIGNED BINARY NUMBER TO AN  
 :;UNSIGNED DECIMAL ASCII NUMBER.

:;\*CALL  
 :;\* MOV NUMBER, -(SP) ;;PUT BINARY NUMBER ON THE STACK  
 :;\* JSR PC, @#\$SB2D ;;CALL  
 :;\* RETURN ;;ADDRESS OF THE 1ST ASCII CHAR. IS ON THE STACK

012650 016637 000002 012700  
 012656 012746 012700  
 012662 004737 012454  
 012666 062716 000005  
 012672 012666 000002  
 012676 000207  
 012700 000000 000000

\$SB2D: MOV 2(SP), 1\$ ;;SAVE BINARY NUMBER  
 MOV #1\$, -(SP) ;;SET POINTER  
 JSR PC, @#\$SB2D ;;CALL DOUBLE LENGTH CONVERT  
 ADD #5, (SP) ;;ONLY ALLOW FIVE CHARACTERS  
 MOV (SP)+, 2(SP) ;;PICKUP POINTER  
 RTS PC ;;RETURN  
 1\$: .WORD 0,0

DOUBLE LENGTH BINARY TO OCTAL ASCII CONVERT ROUTINE

.SBTTL DOUBLE LENGTH BINARY TO OCTAL ASCII CONVERT ROUTINE

```

;*****
;THIS ROUTINE WILL CONVERT A 32-BIT UNSIGNED BINARY NUMBER TO AN
;UNSIGNED OCTAL ASCII NUMBER.
;CALL
;*      MOV      #PNTR, -(SP)      ;; POINTER TO LOW WORD OF BINARY NUMBER
;*      JSR      PC, @#$DB20      ;; CALL THE ROUTINE
;*      RETURN                      ;; THE ADDRESS OF THE FIRST ASCII CHAR. IS ON THE STACK
    
```

012704	104411		\$DB20:	SAVREG		;; SAVE ALL REGISTERS
012706	016601	000002		MOV	2(SP), R1	;; PICKUP THE POINTER TO LOW WORD
012712	012705	013023		MOV	#\$OCTVL+13., R5	;; POINTER TO DATA TABLE
012715	012704	000014		MOV	#12., R4	;; DO ELEVEN CHARACTERS
012722	012703	177770		MOV	#107, R3	;; MASK
012726	012100			MOV	(R1)+, R0	;; LOWER WORD
012730	012101			MOV	(R1)+, R1	;; HIGH WORD
012732	005002			CLR	R2	;; TERMINATOR
012734	110245		1\$:	MOVB	R2, -(R5)	;; PUT CHARACTER IN DATA TABLE
012736	010002			MOV	R0, R2	;; GET THIS DIGIT
012740	005304			DEC	R4	;; COUNT THIS CHARACTER
012742	003007			BGT	3\$	;; BR IF NOT THE LAST DIGIT
012744	001405			BEQ	2\$	;; BR IF IT IS THE LAST DIGIT
012746	005205			INC	R5	;; ALL DIGITS DONE-ADJUST POINTER FOR FIRST
012750	010566	000002		MOV	R5, 2(SP)	;; ASCII CHAR. & PUT IT ON THE STACK
012754	104412			RESREG		;; RESTORE ALL REGISTERS
012756	000207			RTS	PC	;; RETURN TO USER
012760	006203		2\$:	ASR	R3	;; POSITION THE MASK FOR THE LAST DIGIT
012762	006001		3\$:	ROR	R1	;; POSITION THE BINARY NUMBER FOR
012764	006000			ROR	R0	;; THE NEXT OCTAL DIGIT
012766	006001			ROR	R1	
012770	006000			ROR	R0	
012772	006001			ROR	R1	
012774	006000			ROR	R0	
012776	040302			BIC	R3, R2	;; MASK OUT ALL JUNK
013000	062702	000060		ADD	#'0, R2	;; MAKE THIS CHAR. ASCII
013004	000753			BR	1\$	;; GO PUT IT IN THE DATA TABLE
013006	000016		\$OCTVL:	.BLKB	14.	;; RESERVE DATA TABLE

.SBTTL SINGLE LENGTH BINARY TO OCTAL ASCIZ ROUTINE

;;\*\*\*\*\*  
;;\*THIS ROUTINE WILL CONVERT A 16-BIT UNSIGNED BINARY NUMBER TO AN  
;;\*UNSIGNED OCTAL ASCIZ NUMBER.

;;\*CALL  
;;\* MOV NUMBER, -(SP) ;;PUT BINARY NUMBER ON THE STACK  
;;\* JSR PC, @\$\$SB20 ;;CALL  
;;\* RETURN ;;ADDRESS OF 1ST ASCIZ CHAR. IS ON THE STACK

013024	016637	000002	013054	\$\$SB20:	MOV	2(SP), 1\$	;;SAVE THE BINARY NUMBER
013032	012746	013054			MOV	*1\$, -(SP)	;;SET POINTER
013036	004737	012704			JSR	PC, @\$\$SB20	;;CALL DOUBLE LENGTH CONVERT ROUTINE
013042	062716	000005			ADD	*5, (SP)	;;ONLY ALLOW SIX CHARACTERS
013045	012666	000002			MOV	(SP)+, 2(SP)	;;PICKUP POINTER
013052	000207				RTS	PC	;;RETURN
013054	000000	000000		1\$:	.WORD	0,0	

.SBTTL TRAP DECODER

```

;*****
;THIS ROUTINE WILL PICKUP THE LOWER BYTE OF THE "TRAP" INSTRUCTION
;AND USE IT TO INDEX THROUGH THE TRAP TABLE FOR THE STARTING ADDRESS
;OF THE DESIRED ROUTINE. THEN USING THE ADDRESS OBTAINED IT WILL
;GO TO THAT ROUTINE.
    
```

```

013060 016646 000002 $TRAP: MOV 2(SP),-(SP) ;; ASSUME THE STATUS OF
013064 042716 000020 BIC #20,(SP) ;; THE CALLER--DO NOT ALLOW
013070 012746 013076 MOV #1$,-(SP) ;; T-BIT TRAPS
013074 000002 RTI ;; SET THE NEW STATUS
013076 010046 1$: MOV R0,-(SP) ;; SAVE R0
013100 016600 000002 MOV 2(SP),R0 ;; GET TRAP ADDRESS
013104 005740 TST -(R0) ;; BACKUP BY 2
013106 111000 MOV#B (R0),R0 ;; GET RIGHT BYTE OF TRAP
013110 022700 000044 CMP #$TERM,R0 ;; CHECK FOR OUT OF BOUNDS
013114 003002 BGT .+6 ;; BR IF OK
013116 000000 HALT ;; OUT OF BOUNDS
013120 000776 BR .-2 ;; HANGUP
013122 006300 ASL R0 ;; POSITION FOR INDEXING
013124 016000 013144 MOV $TRPAD(R0),R0 ;; INDEX TO TABLE
013130 000200 RTS R0 ;; GO TO ROUTINE
    
```

;;THIS IS USE TO HANDLE THE "GETPRI" MACRO

```

013132 011646 000004 000002 $TRAP2: MOV (SP),-(SP) ;; MOVE THE PC DOWN
013134 016666 MOV 4(SP),2(SP) ;; MOVE THE PSW DOWN
013142 000002 RTI ;; RESTORE THE PSW
    
```

.SBTTL TRAP TABLE

```

;THIS TABLE CONTAINS THE STARTING ADDRESSES OF THE ROUTINES CALLED
;BY THE "TRAP" INSTRUCTION.
    
```

```

: ROUTINE
: -----
013144 013132 $TRPAD: .WORD $TRAP2
013146 010242 $TYPE ;;CALL=TYPE TRAP+1(104401) TTY TYPEOUT ROUTINE
013150 010632 $TYPOC ;;CALL=TYPOC TRAP+2(104402) TYPE OCTAL NUMBER (WITH LEADING ZEROS)
013152 010606 $TYPOS ;;CALL=TYPOS TRAP+3(104403) TYPE OCTAL NUMBER (NO LEADING ZEROS)
013154 010646 $TYPON ;;CALL=TYPON TRAP+4(104404) TYPE OCTAL NUMBER (AS PER LAST CALL)
013156 010362 $TYPDS ;;CALL=TYPDS TRAP+5(104405) TYPE DECIMAL NUMBER (WITH SIGN)

013160 011662 $RDCHR ;;CALL=RDCHR TRAP+6(104406) TTY TYPEIN CHARACTER ROUTINE
013162 012002 $RDLIN ;;CALL=RDLIN TRAP+7(104407) TTY TYPEIN STRING ROUTINE
013164 012276 $RDDEC ;;CALL=RDDEC TRAP+10(104410) READ A DECIMAL NUMBER FROM TTY
013166 010146 $$AVREG ;;CALL=SAVREG TRAP+11(104411) SAVE R0-R5 ROUTINE
013170 010204 $RESREG ;;CALL=RESREG TRAP+12(104412) RESTORE R0-R5 ROUTINE
013172 011546 $PRHDR ;;CALL=PRTHOR TRAP+13(104413) PRINT TEST HEADER
013174 011502 $PRINT ;;CALL=PRINT TRAP+14(104414) PRINT ROUTINE
013176 011034 $LOAD ;;CALL=LOAD TRAP+15(104415) LOAD CHAR ROUTINE
013200 011400 $MLOAD ;;CALL=MLOAD TRAP+16(104416) MULTIPLE CHAR LOAD
013202 011410 $CNLD ;;CALL=CNLOAD TRAP+17(104417) LOAD CONVERTED NUMBER
    
```

J07

MAINDEC-11-DZLAE-B MACY11 27(1006) 01-MAR-77 14:45 PAGE 86  
DZLAEB.P11 28-FEB-77 15:08 TRAP TABLE

013204 007052  
013206 007112  
000044

\$CHECK ::CALL=CHECK  
\$HOLD ::CALL=HOLD  
\$TERM=-\$TRPAD

TRAP+20(104420) CHECK FOR KYBD OR SW REG CONTROL  
TRAP+21(104421) WAIT FOR OPERATOR ACTION



.SBTTL POWER DOWN AND UP ROUTINES

```

*****
: POWER DOWN ROUTINE
013210 012737 013350 000024 $PWRDN: MOV $SILLUP, @#PWRVEC ;; SET FOR FAST UP
013216 012737 000340 000026 MOV #340, @#PWRVEC+2 ;; PRIO:7
013224 010046 MOV R0, -(SP) ;; PUSH R0 ON STACK
013226 010146 MOV R1, -(SP) ;; PUSH R1 ON STACK
013230 010246 MOV R2, -(SP) ;; PUSH R2 ON STACK
013232 010346 MOV R3, -(SP) ;; PUSH R3 ON STACK
013234 010446 MOV R4, -(SP) ;; PUSH R4 ON STACK
013236 010546 MOV R5, -(SP) ;; PUSH R5 ON STACK
013240 017746 165676 MOV @SWR, -(SP) ;; PUSH @SWR ON STACK
013244 010637 013354 MOV SP, $SAVR6 ;; SAVE SP
013250 012737 013262 000024 MOV $PWRUP, @#PWRVEC ;; SET UP VECTOR
013256 000000 HALT
013260 000776 BR .-2 ;; HANG UP

```

```

*****
: POWER UP ROUTINE
013262 012737 013350 000024 $PWRUP: MOV $SILLUP, @#PWRVEC ;; SET FOR FAST DOWN
013270 013706 013354 MOV $SAVR6, SP ;; GET SP
013274 005037 013354 CLR $SAVR6 ;; WAIT LOOP FOR THE TTY
013300 005237 013354 1$: INC $SAVR6 ;; WAIT FOR THE INC
013304 001375 BNE 1$ ;; OF WORD
013306 012677 165630 MOV (SP)+, @SWR ;; POP STACK INTO @SWR
013312 012605 MOV (SP)+, R5 ;; POP STACK INTO R5
013314 012604 MOV (SP)+, R4 ;; POP STACK INTO R4
013316 012603 MOV (SP)+, R3 ;; POP STACK INTO R3
013320 012602 MOV (SP)+, R2 ;; POP STACK INTO R2
013322 012601 MOV (SP)+, R1 ;; POP STACK INTO R1
013324 012600 MOV (SP)+, R0 ;; POP STACK INTO R0
013326 012737 013210 000024 MOV $PWRDN, @#PWRVEC ;; SET UP THE POWER DOWN VECTOR
013334 012737 000340 000026 MOV #340, @#PWRVEC+2 ;; PRIO:7
013342 104401 TYPE PWRMSG ;; REPORT THE POWER FAILURE
013344 015215 $PWRMG: .WORD PWRMSG ;; POWER FAIL MESSAGE POINTER
013346 000002 RTI
013350 000000 $SILLUP: HALT ;; THE POWER UP SEQUENCE WAS STARTED
013352 000776 BR .-2 ;; BEFORE THE POWER DOWN WAS COMPLETE
013354 000000 $SAVR6: 0 ;; PUT THE SP HERE

```

////////////////////////////////////

.SBTTL TEST ADDRESS TABLE

;THE PRINTING TEST SEQUENCE STARTS WITH TEST20  
;TO REMOVE A TEST FROM THE PROGRAM -  
;DEPOSIT ZERO FOR THE TEST ADDRESS IN THIS TABLE  
;A MINUS ONE (-1) IN THE TABLE INDICATES THE END OF THE PRINTING SEQUENCE

////////////////////////////////////

013356 002254  
013360 003072  
013362 003262  
013364 000000  
013366 000000  
013370 000000  
013372 000000  
013374 000000  
013376 000000  
013400 000000  
013402 000000  
013404 000000  
013406 000000  
013410 000000  
013412 000000  
013414 000000  
013416 003614  
013420 003662  
013422 003772  
013424 004060  
013426 004114  
013430 004406  
013432 004770  
013434 005062  
013436 005200  
013440 005226  
013442 177777  
013444 000000  
013446 000000  
013450 000000  
013452 000000  
013454 000000  
013456 000000  
013460 000000  
013462 000000  
013464 000000  
013466 000000  
013470 000000  
013472 000000  
013474 000000  
013476 005340  
013500 000000  
013502 000000  
013504 000000  
013506 000000

TAT: TEST0  
TEST1  
TEST2  
0 ;TEST3  
0 ;TEST4  
0 ;TEST5  
0 ;TEST6  
0 ;TEST7  
0 ;TEST10  
0 ;TEST11  
0 ;TEST12  
0 ;TEST13  
0 ;TEST14  
0 ;TEST15  
0 ;TEST16  
0 ;TEST17  
TEST20  
TEST21  
TEST22  
TEST23  
TEST24  
TEST25  
TEST26  
TEST27  
TEST30  
TEST31  
-1 ;TEST32  
0 ;TEST33  
0 ;TEST34  
0 ;TEST35  
0 ;TEST36  
0 ;TEST37  
0 ;TEST40  
0 ;TEST41  
0 ;TEST42  
0 ;TEST43  
0 ;TEST44  
0 ;TEST45  
0 ;TEST46  
0 ;TEST47  
TEST50  
0 ;TEST51  
0 ;TEST52  
0 ;TEST53  
0 ;TEST54

013510	000000	0	;TEST55
013512	000000	0	;TEST56
013514	000000	0	;TEST57
013516	005540	TEST60	
013520	005654	TEST61	
013522	005766	TEST62	
013524	006050	TEST63	
013526	006174	TEST64	
013530	000000	0	;TEST65
013532	000000	0	;TEST66
013534	000000	0	;TEST67
013536	000000	0	;TEST70
013540	000000	0	;TEST71
013542	000000	0	;TEST72
013544	000000	0	;TEST73
013546	000000	0	;TEST74
013550	000000	0	;TEST75
013552	006514	TEST76	
013554	006534	TEST77	

;/;;;

.SBTTL ERROR MESSAGE ADDRESS TABLE

;/;;;

013556	013632	EMAT: ERR1
013560	013661	ERR2
013562	013706	ERR3
013564	013744	ERR4
013566	014000	ERR5
013570	014033	ERR6
013572	014070	ERR7
013574	014117	ERR10
013576	014144	ERR11
013600	014170	ERR12
013602	014232	ERR13
013604	014266	ERR14
013606	014324	ERR15
013610	014360	ERR16
013612	014414	ERR17
013614	014451	ERR20
013616	014503	ERR21
013620	014537	ERR22
013622	014573	ERR23
013624	014632	ERR24
013626	014671	ERR25
013630	014713	ERR26

;/;;;

.SBTTL ERROR MESSAGES

;/;;;

013632	051105	047522	020122	ERR1:	.ASCIZ /ERROR CLEAR, POWER OFF/
013640	046103	040505	026122		
013646	050040	053517	051105		
013654	047440	043106	000		
013661	122	040505	054504	ERR2:	.ASCIZ /READY SET, POWER OFF/
013666	051440	052105	020054		
013674	047520	042527	020122		
013702	043117	000106			
013706	051105	047522	020122	ERR3:	.ASCIZ /ERROR CLEAR, PRINTER OFF LINE/
013714	046103	040505	026122		
013722	050040	044522	052116		
013730	051105	047440	043106		
013736	046040	047111	000105		
013744	042522	042101	020131	ERR4:	.ASCIZ /READY SET, PRINTER OFF LINE/
013752	042523	026124	050040		
013760	044522	052116	051105		
013766	047440	043106	046040		
013774	047111	000105			
014000	051105	047522	020122	ERR5:	.ASCIZ /ERROR SET, PRINTER ON LINE/
014006	042523	026124	050040		
014014	044522	052116	051105		
014022	047440	020116	044514		
014030	042516	000			
014033	122	040505	054504	ERR6:	.ASCIZ /READY CLEAR, PRINTER ON LINE/
014040	041440	042514	051101		
014046	020054	051120	047111		
014054	042524	020122	047117		
014062	046040	047111	000105		
014070	051105	047522	020122	ERR7:	.ASCIZ /ERROR CLEAR, PAPER OUT/
014076	046103	040505	026122		
014104	050040	050101	051105		
014112	047440	052125	000		
014117	122	040505	054504	ERR10:	.ASCIZ /READY SET, PAPER OUT/
014124	051440	052105	020054		
014132	040520	042520	020122		
014140	052517	000124			
014144	051105	047522	020122	ERR11:	.ASCIZ /ERROR DID NOT CLEAR/
014152	044504	020104	047516		
014160	020124	046103	040505		
014166	000122				
014170	042522	042101	020131	ERR12:	.ASCIZ /READY NOT SET AFTER ERROR CLEARED.
014176	047516	020124	042523		
014204	021124	043101	042524		
014212	020122	051105	047522		
014220	020122	046103	040505		
014226	042522	000104			
014232	051105	047522	020122	ERR13:	.ASCIZ /ERROR SET AFTER RESET INSTR/
014240	042523	020124	043101		
014246	042524	020122	042522		
014254	042523	020124	047111		

014262	052123	000122		
014266	042522	042101	020131	ERR14: .ASCIZ /READY CLEAR AFTER RESET INSTR/
014274	046103	040505	020122	
014302	043101	042524	020122	
014310	042522	042523	020124	
014316	047111	052123	000122	
014324	042522	042101	020131	ERR15: .ASCIZ /READY SET AFTER CHAR LOADED/
014332	042523	020124	043101	
014340	042524	020122	044103	
014346	051101	046040	040517	
014354	042504	000104		
014360	051105	047522	020122	ERR16: .ASCIZ /ERROR SET AFTER CHAR LOADED/
014366	042523	020124	043101	
014374	042524	020122	044103	
014402	051101	046040	040517	
014410	042504	000104		
014414	042522	042101	020131	ERR17: .ASCIZ /READY NEVER SET, CHAR LOADED/
014422	042516	042526	020122	
014430	042523	026124	041440	
014436	040510	020122	047514	
014444	042 1	042105	000	
014451	105	051122	051117	ERR20: .ASCIZ /ERROR SET, INTERRUPT TEST/
014456	051440	052105	020054	
014464	047111	042524	051122	
014472	050125	020124	042524	
014500	052123	000		
014503	122	040505	054504	ERR21: .ASCIZ /READY CLEAR, INTERRUPT TEST/
014510	041440	042514	051101	
014516	020054	047111	042524	
014524	051122	050125	020124	
014532	042524	052123	000	
014537	120	044522	052116	ERR22: .ASCIZ /PRINTER INTER ABOVE LEVEL 3/
014544	051105	044440	052116	
014552	051105	040440	047502	
014560	042526	046040	053105	
014566	046105	031440	000	
014573	116	020117	051120	ERR23: .ASCIZ /NO PRINTER INTER BELOW LEVEL 4/
014600	047111	042524	020122	
014606	047111	042524	020122	
014614	042502	047514	020127	
014622	042514	042526	020114	
014630	000064			
014632	051120	047111	042524	ERR24: .ASCIZ /PRINTER ERROR BEFORE CHAR LOAD/
014640	020122	051105	047522	
014646	020122	042502	047506	
014654	042522	041440	040510	
014662	020122	047514	042101	
014670	000			
014671	120	044522	052116	ERR25: .ASCIZ /PRINTER NOT READY/
014676	051105	047040	052117	
014704	051040	040505	054504	
014712	000			
014713	120	044522	052116	ERR26: .ASCIZ /PRINTER ERROR AFTER CHAR LOAD/
014720	051105	042440	051122	
014726	051117	040440	052106	
014734	051105	041440	040510	

014742 020122 047514 042101  
014750 000

;/;;;  
.SBTTL PROGRAM MESSAGES  
;/;;;

014751	200	020043	047503	COLUMN: .ASCIZ <CRLF># COLUMNS = /
014756	052514	051715	020123	
014764	020075	000		
014767	200	042523	042514	SELTST: .ASCIZ <CRLF>/SELECT TEST # /
014774	052103	052040	051505	
015002	020124	020043	020040	
015010	000			
015011	012	052012	051505	TSTNO: .ASCIZ <LF><LF>/TEST NUMBER /
015016	020124	052516	041115	
015024	051105	020040	000	
015031	040	041440	046117	COLMN: .ASCIZ / COLUMNS/<LF>
015036	046525	051516	000012	
015044	052200	051505	020124	ETSTNO: .ASCIZ <CRLF>/TEST #/
015052	000043			
015054	020054	050040	036503	PCMSG: .ASCIZ /, PC= /
015062	000			
015063	054	020040	051105	ERR: .ASCIZ /, ERROR #/
015070	047522	020122	000043	
015076	020054	000040		ERRS: .ASCIZ /, /

015102	042412	042116	047440	PRMSG: .ASCIZ <LF>/END OF PASS #/
015110	020106	040520	051523	
015116	020040	000043		
015122	051600	051127	036440	DSMSG1: .ASCIZ <CRLF>/SWR = /
015130	000040			
015132	020040	047040	053505	DSMSG2: .ASCIZ / NEW = /
015140	036440	000040		
015144	040527	052111	047111	WTMSG: .ASCIZ /WAITING. TYP SPACE TO CONTINUE/<CRLF>
015152	026107	020040	054524	
015160	020120	050123	041501	
015166	020105	047524	041440	
015174	047117	044524	052516	
015202	100105	000		
015205	103	040510	020122	TCHAR: .ASCIZ /CHAR = /
015212	020075	000		
015215	200	047520	042527	PWRMSG: .ASCIZ <CRLF>/POWER/<CRLF>
015222	100122	000		
015225	012	047516	041440	NCMSG: .ASCIZ <LF>/NO CONSOLE TERMINAL/<LF>
015232	047117	047523	042514	
015240	052040	051105	044515	
015246	040516	005114	000	
015253	120	044522	052116	MANMSG: .ASCII /PRINT SPEED MANUAL TIMING/<CRLF>
015260	051440	042520	042105	
015266	046440	047101	040525	
015274	020114	044524	044515	
015302	043516	200		
015305	120	052125	051440	.ASCII /PUT SWITCH 12 UP TO START TIMING/<CRLF>
015312	044527	041524	020110	
015320	031061	052440	020120	
015326	047524	051440	040524	
015334	052122	052040	046511	
015342	047111	100107		
015346	052520	020124	053523	.ASCIZ /PUT SWITCH 12 DOWN AT END OF 1 MINUTE/<CRLF>
015354	052111	044103	030440	
015362	020062	047504	047127	
015370	040440	020124	047105	
015376	020104	043117	030440	
015404	046440	047111	052125	
015412	100105	000		
015415	105	052116	051105	T64MSG: .ASCIZ /ENTER PATTERN PER LISTING OR DOCUMENT<CRLF>
015422	050040	052101	042524	
015430	047122	050040	051105	
015436	046040	051511	044524	
015444	043516	047440	020122	
015452	047504	052503	042515	
015460	052116	000200		
015464	003407	000200		TWOBEL: .ASCIZ <7><7><CRLF>
015470	050200	044522	052116	PRSP1: .ASCIZ <CRLF>/PRINT SPEED IS /
015476	051440	042520	042105	
015504	044440	020123	000	
015511	101	050120	047522	PRSP2: .ASCIZ /APPROX. /
015516	027130	000040		
015522	020040	044514	042516	PRSP3: .ASCIZ / LINES/<57>/MINUTE . WITH
015530	027523	044515	052516	
015536	042524	026040	053440	
015544	052111	020110	000	

MAINDEC-11-DZLAE-B  
DZLAEB.P11 28-FEB-77

MACY11 27(1006)  
15:08

01-MAR-77 14:45 PAGE 94  
PROGRAM MESSAGES

015551	040	041440	040510	PRSP4: .ASCIZ / CHARS/⟨57⟩/LINE/⟨CRLF⟩
015556	051522	046057	047111	
015564	100105	000		
015567	124	051125	020116	TOMSG0: .ASCIZ /TURN POWER OFF & SET OFF LINE/⟨CRLF⟩
015574	047520	042527	020122	
015602	043117	020106	020046	
015610	042523	020124	043117	
015616	020106	044514	042516	
015624	000200			
015626	045517	020054	052524	TOMSG1: .ASCIZ /OK, TURN POWER ON/⟨CRLF⟩
015634	047122	050040	053517	
015642	051105	047440	100116	
015650	000			
015651	117	026113	051440	TOMSG2: .ASCIZ /OK, SET PRINTER TO ON-LINE/⟨CRLF⟩
015656	052105	050040	044522	
015664	052116	051105	052040	
015672	020117	047117	046055	
015700	047111	100105	000	
015705	117	026113	052040	TOMSG3: .ASCIZ /OK, TRY PAPER OUT SWITCH/⟨CRLF⟩
015712	054522	050040	050101	
015720	051105	047440	052125	
015726	051440	044527	041524	
015734	100110	000		
015737	117	026113	051040	TOMSG4: .ASCIZ /OK, RESTORE PRINTER TO ON-LINE/⟨CRLF⟩
015744	051505	047524	042522	
015752	050040	044522	052116	
015760	051105	052040	020117	
015766	047117	046055	047111	
015774	100105	000		
015777	055	026455	026455	TIMSG1: .ASCIZ /----- /
016004	000040			
016006	044440	041516	020110	TIMSG2: .ASCIZ / INCH FORM FEED -----/⟨CR⟩
016014	047506	046522	043040	
016022	042505	020104	026455	
016030	026455	006455	000	
016035	123	052105	043040	TIMSG3: .ASCIZ /SET FORM FEED SWITCH TO /
016042	051117	020115	042506	
016050	042105	051440	044527	
016056	041524	020110	047524	
016064	020040	000		
016067	040	044440	041516	TIMSG4: .ASCIZ / INCHES & DEPRESS TOF RESET SWITCH/⟨CRLF⟩
016074	042510	020123	020046	
016102	042504	051120	051505	
016110	020123	047524	020106	
016116	042522	042523	020124	
016124	03523	052111	044103	
016132	000200			
016134	047516	046440	052105	T2EM: .ASCIZ NO METHOD OF TIMING AVAILABLE/⟨CRLF⟩
016142	047510	020104	043117	
016150	052040	046511	047111	
016156	020107	053101	044501	
016164	040514	046102	100105	
016172	000			
016174				.EVEN



F08

MA:INDEC-11-DZLAE-B MACY11 27(1006) 01-MAR-77 14:45 PAGE 95  
CZLAEB.P11 28-FEB-77 15:08 PROGRAM MESSAGES

016174	047531	020125	047506
016202	043522	052117	052040
016210	020117	047105	042524
016216	020122	040504	040524
016224	020073	052103	026514
016232	050123	041501	005105
016240	000		

TABL64: .ASCIZ /YOU FORGOT TO ENTER DATA; CTL-SPACE/<LF>

:OPEN-ENDED TABLE FOR TEST 64 DATA.

00000:

.ENC

ACCEPT	006210	EMAT	013556	NXTADR	011142	STRONE	00:152	TEST64	006174
ACTEST	001:30	EMTVEC=	000030	PASCNT	005652	SVTST	011660	TEST76	006514
BIT0	= 000001	ENDADR	006512	PASMSG	015102	SWR	001142	TEST77	006534
BIT00	= 000001	ERR	015063	PCMSG	015054	SWREG	000176	TKB	001102
BIT01	= 000002	ERRS	015076	PIRQ	= 177772	SWO	= 000001	TKS	001100
BIT02	= 000004	ERRVEC=	000004	PIRQVE=	000240	SW00	= 000001	TKVEC =	000060
BIT03	= 000010	ERR1	013632	PLKS	001134	SW01	= 000002	TLOOP	001154
BIT04	= 000020	ERR10	014117	PLOAD	011044	SW02	= 000004	TORTN	006610
BIT05	= 000040	ERR11	014144	PRINT =	104414	SW03	= 000010	TPB	001106
BIT06	= 000100	ERR12	014170	PROPAT	006424	SW04	= 000020	TPS	001104
BIT07	= 000200	ERR13	014232	PRPAT	006466	SW05	= 000040	TPVEC =	000064
BIT08	= 000400	ERR14	014266	PRSP1	015470	SW06	= 000100	TRAPVE=	000034
BIT09	= 001000	ERR15	014324	PRSP2	015511	SW07	= 000200	TRONE	001153
BIT1	= 000002	ERR16	014360	PRSP3	015522	SW08	= 000400	TRTVEC=	000014
BIT10	= 002000	ERR17	014414	PRSP4	015551	SW09	= 001000	TSEL	007510
BIT11	= 004000	ERR2	013661	PRTHDR=	104413	SW1	= 000002	TSTNO	015011
BIT12	= 010000	ERR20	014451	PRTSET	005442	SW10	= 002000	TWOBEL	015464
BIT13	= 020000	ERR21	014503	PRO	= 000000	SW11	= 004000	TYPDS =	104405
BIT14	= 040000	ERR22	014537	PR1	= 000040	SW12	= 010000	TYPE	= 104401
BIT15	= 100000	ERR23	014573	PR2	= 000100	SW13	= 020000	TYPOC =	104402
BIT2	= 000004	ERR24	014632	PR3	= 000140	SW14	= 040000	TYPON =	104404
BIT3	= 000010	ERR25	014671	PR4	= 000200	SW15	= 100000	TYPOS =	104403
BIT4	= 000020	ERR26	014713	PR5	= 000240	SW2	= 000004	TOMCJ	015567
BIT5	= 000040	ERR3	013706	PR6	= 000300	SW3	= 000010	TOMSG1	015626
BIT6	= 000100	ERR4	013744	PR7	= 000340	SW4	= 000020	TOMSG2	015651
BIT7	= 000200	ERR5	014000	PS	= 177776	SW5	= 000040	TOMSG3	015705
BIT8	= 000400	ERR6	014033	PSW	= 177776	SW6	= 000100	TOMSG4	015737
BIT9	= 001000	ERR7	014070	PWRMSG	015215	SW7	= 000200	T1MSG1	015777
BPTVEC=	000014	ETSTNO	015044	PWRVEC=	000024	SW8	= 000400	T1MSG2	016006
CHACTR	006510	EXIT	006644	QU01	001764	SW9	= 001000	T1MSG3	016035
CHECK =	104420	FF	= 000014	QU02	002032	TABL64	016174	T1MSG4	016067
CHLC	005440	FSTPAD	001126	RDCHR =	104406	TAT	013356	T2EM	016134
CKFLAG	001155	FSTPAD	001124	RDDEC =	104410	TBITVE=	000014	T2SP	003400
CNLQAD=	104417	HOLD	= 104401	ROLIN =	104407	TCHAR	015205	T50M1	005424
CNTR	006606	HT	= 000011	REPORT	010044	TERR	006164	T50M2	005430
COLCTR	006506	IOTVEC=	000020	RESREG=	104412	TEST0	002254	T50PCT	005422
COLUMN	015031	KYBDF	007140	RESTR	001210	TEST1	003072	T64MSG	015415
COLUMN	014751	KYBST	007442	RESVEC=	000010	TEST2	003262	WIDTH	001150
CONTR	001220	LDPTR	011040	RSTADR	011316	TEST20	003614	WTMSG	015144
CP	= 000015	LF	= 000012	R6	=%000006	TEST21	003662	\$BELL	001156
CRLF	= 000200	LKS	001140	R7	=%000007	TEST22	003772	\$CHECK	007052
CSBR	001136	LKSRV	006566	SAVREG=	104411	TEST23	004060	\$CNLD	011410
CTLA	006346	LOAD	= 104415	SELECT	006752	TEST24	004114	\$CNTLG	012247
CTLB	006362	LPB	001116	SELTST	014767	TEST25	004406	\$CNTLU	012242
CT	006556	LPCTR	001132	SEPSW	001120	TEST26	004770	\$CR	001164
DISP	= 177570	LPKB	001112	SLOAD	011206	TEST27	005062	\$CRLF	001161
DISPLA	001144	LPKS	001110	SP0	003500	TEST30	005200	\$DBLK	010576
DISPRE	000174	LPS	001114	SP3	005434	TEST31	005226	\$DB20	012454
DSMSG1	015122	MANMSG	015253	SRDCI	006614	TEST50	005340	\$DB20	012704
DSMSG2	015132	MINCNT	006612	STACK =	001100	TEST60	005540	\$DECVL	012634
DSWA	= 177570	MLOAD =	104415	START	001174	TEST61	005654	\$DCAGN	005332
DUNCOL	006454	NCMSG	015225	STARTX	001226	TEST62	005766	\$DTBL	010566
DUNPA	006446	NUMLP	001122	STKLMT=	177774	TEST63	006050	\$ENCAD	005322

MACY11 27(1006) 01-MAR-77 14:45 PAGE 99  
 DZLAEB.P11 28-FEB-77 15:08 SYMBOL TABLE

\$ENDCT	005306	\$LOAD	011034	\$QUES	001160	\$SWR	= 162000	\$TMIN	012236
\$EJP	005262	\$MLOAD	011400	\$RDCHR	011662	\$TERM	= 000044	\$TPOS	010362
\$EJPT	005300	\$MNEW	012265	\$RDDEC	012276	\$TKB	001102	\$TYPE	010242
\$ERROR	007744	\$MSWR	012254	\$RDLIN	012002	\$TKS	001100	\$TYPEC	010344
\$ERRPC	010040	\$NULL	001170	\$ROSZ	= 000004	\$TN	= 000000	\$TYPC	010632
\$FF	001166	\$OCNT	011030	\$RESRE	010204	\$TNPWR	012564	\$TYPON	010646
\$FILLC	001172	\$OCTL	013006	\$RTNAD	005334	\$TPB	001106	\$TPOS	010606
\$FILLS	001171	\$OMODE	011032	\$SAVRE	010146	\$TPFLG	001173	\$GET4	= 000000
\$GET42	005312	\$PASS	005336	\$SAVR6	013354	\$TPS	001104	\$OFILL	011031
\$HC	= 000000	\$PRMR	011546	\$SB20	012650	\$TRAP	013060	.	= 016241
\$HOLD	007112	\$PRINT	011502	\$SB20	013024	\$TRAP2	013132		
\$JUMP	013350	\$PWRDN	013210	\$SETUP	= 000034	\$TRP	= 000022		
\$TEMB	010042	\$PWRMG	013344	\$STUP	= 177777	\$TRPAD	013144		
\$F	001162	\$PWRJP	013262	\$SVPC	= 000200	\$TSTNM	001146		

. ABS. 01624: 000

ERRORS DETECTED: 0  
 DEFAULT GLOBALS GENERATED: 0

DZLAEB.DZLAEB.SEG/SOL/NL:SEQ=DZLAEB.P11  
 RUN-TIME: 16 9 .3 SECONDS  
 RUN-TIME RATIO: 642 26=24.3  
 CORE USED: 18K (36 PAGES)