

I D E N T I F I C A T I O N

PRODUCT CODE: AC-8680D-MC

PRODUCT NAME: CZDUBD0 DU11 OFFLINE RECEIVER TESTS

RELEASE DATE: JUN 1978

MAINTAINER : DIAGNOSTICS

THE INFORMATION IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT CORPORATION. DIGITAL EQUIPMENT CORPORATION ASSUMES NO RESPONSIBILITY FOR ANY ERRORS THAT MAY APPEAR IN THIS DOCUMENT.

THE SOFTWARE DESCRIBED IN THIS DOCUMENT IS FURNISHED UNDER A LICENSE AND MAY ONLY BE USED OR COPIED IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE.

DIGITAL EQUIPMENT CORPORATION ASSUMES NO RESPONSIBILITY FOR THE USE OF RELIABILITY OF ITS SOFTWARE ON EQUIPMENT THAT IS NOT SUPPLIED BY DIGITAL.

COPYRIGHT (C) 1973, 1978 BY DIGITAL EQUIPMENT CORPORATION

GENERAL DESCRIPTION

THIS DIAGNOSTIC CAN CHAIN 16 DU11'S. THIS MEANS THAT 16 DEVICES CAN BE SEQUENTIALLY EXERCISED. THE DIAGNOSTIC MAKES ONE PASS BEFORE PROCEEDING TO THE NEXT DEVICE, AND CONTINUES EXERCISING ALL DEVICES IN THIS FASHION UNTIL HALTED.

1. THE DU11 OFFLINE RECEIVER TESTS VERIFY THAT THE RECEIVER CHIP/LOGIC WORKS PROPERLY

2. REQUIREMENTS

PDP-11 FAMILY STANDARD COMPUTER WITH OR WITHOUT HARDWARE SWITCH REGISTER (LOC. 177570)

DU11 SYNCHRONOUS/ISOCRONOUS OPTION

ONE CONSOLE TELETYPE OR EQUIVALENT

2.2 STORAGE

THE PROGRAM LOADS AND RUNS IN 8K OF MEMORY.

3. LOADING PROCEDURE

THE STANDARD PROCEDURE FOR LOADING ABSOLUTE BINARY TAPES IS TO BE USED.

STARTING ADDRESS
FOR ABSOLUTE LOADER

4K	017500
8K	037500
12K	057500
16K	077500
20K	117500
24K	137500
28K	157500

4. STARTING PROCEDURE

NOTE:

BEFORE PROCEEDING IT IS IMPORTANT TO REALIZE IF ONE DOESNOT HAVE THE DU11 SET UP TO THE DEFAULT PARAMETERS (SEE SECTION 8 OF THIS DOCUMENT) , THEN ONE MUST

SET SW00 = 1, AND ANSWER THE PARAMETER
QUESTION ROUTINE.

4.1 CONTROL SWITCH SETTINGS

NOTE: SOFTWARE SWITCH REGISTER IS DEFINED AS LOC. 176, WHILE
THE SOFTWARE DISPLAY REGISTER IS DEFINED AS LOC. 174.

4.1.1 AFTER PROGRAM LOAD (INITIAL PROGRAM START)
ALL CONSOLE SWITCHES DOWN

4.1.2 TO MODIFY DEVICE VECTOR AND CONTROL REGISTER ADDRESSES
AFTER PROGRAM RESTART OR TO RUN MULTIPLE DEVICES

SW00=1

4.1.3 TO START PROGRAM AT SELECTED TEST AFTER A PROGRAM RESTART
(ONLY IN SINGLE DEVICE TESTS)

SW01=1

4.1.4 TO LOCK ON SELECTED TEST AFTER A PROGRAM RESTART
(ONLY IN SINGLE DEVICE TESTS)

SW02=1

NOTE1: IN GENERAL SW01 WILL BE USED WHEN SW02=1 IS USED
NOTE2: WITHOUT SW01=1 "LOCK ON TEST" WILL DEFAULT TO TEST 1

4.2 STARTING ADDRESS

THE STARTING ADDRESS FOR ALL TESTS IS 000200

THE RETARTING ADDRESS FOR ALL TESTS IS 000200
THE STARTING ADDRESS TO ENTER A SELECTED TEST IS 000200
THE STARTING ADDRESS TO LOCK ON TEST IS 000200

4.3 PROGRAM AND/OR OPERATOR ACTION

4.3.1 INITIAL PROGRAM START

4.3.1.1 LOAD PROGRAM INTO MEMORY WITH ABSOLUTE LOADER

4.3.1.2 LOAD ADDRESS 000200

4.3.1.3 CLEAR CONSOLE SWITCHES

4.3.1.4 PRESS START

4.3.1.5 THE PROGRAM WILL TYPE 'DU11 CZDUB-D TAPE B' (ONCE ONLY)

NOTE: IF THE SOFTWARE SWITCH REGISTER IS SELECTED THEN THE FOLLOWING
WILL BE TYPED AFTER THE PROGRAM IDENTIFIES ITSELF:

SWR=XXXXXX NEW= (REFER TO SECTION 5. FOR OPERATOR'S OPTION)

4.3.1.7 THE PROGRAM WILL TYPE 'R' TO INDICATE THAT IT IS ABOUT TO START TESTING ,AND THEN TESTING WILL BEGIN

4.3.2 PROGRAM RESTART WITH ALL SWITCHES DOWN

4.3.2.1 THE PROGRAM WILL TYPE 'R' AND WILL COMMENCE TESTING

4.3.3 PROGRAM RESTART WITH SW00=1

4.3.3.1 LOAD ADDRESS 000200

4.3.3.2 SET SW00=1

4.3.3.3 PRESS START

NOTE:IF THE SOFTWARE SWITCH REGISTER IS SELECTED THEN THE FOLLOWING WILL BE TYPED AFTER THE PROGRAM IDENTIFIES ITSELF:

SWR=XXXXXX NEW= (REFER TO SECTION 5. FOR OPERATOR'S OPTION)

4.3.3.4 THE PROGRAM WILL TYPE " 1ST DEVICE: RECEIVER CONTROL REGISTER ADDRESS" AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.5 TYPE IN THE ADDRESS OF THE FIRST RECEIVER CONTROL REGISTER ADDRESS OF THE DU11 TO BE TESTED FOLLOWED BY A <CARRIAGE RETURN>

IF AN INCORRECT ADDRESS IS TYPED ,THE PROGRAM WILL TYPE "?" AND WILL THEN REPEAT THE MESSAGE OF 4.3.3.4

4.3.3.6 THE PROGRAM WILL TYPE 'VECTOR ADDRESS-' AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.7 TYPE IN THE BASE RECEIVER INTERRUPT VECTOR ADDRESS FOR THE DU11 TO BE TESTED FOLLOWED BY A <CARRIAGE RETURN>

IF AN INCORRECT ADDRESS IS TYPED ,THE PROGRAM WILL TYPE "?" AND WILL THEN REPEAT THE MESSAGE OF 4.3.3.6

4.3.3.8 THE PROGRAM WILL TYPE 'ARE YOU RUNNING MULTIPLE DEVICES ?' (Y OR N)-' AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.9 TYPE IN THE APPROPRIATE ANSWER YES OR NO FOLLOWED BY A <CARRIAGE RETURN>

IF AN INCORRECT ANSWER IS GIVEN, THE PROGRAM WILL TYPE "?" AND WILL THEN REPEAT THE MESSAGE OF 4.3.3.8

IF A 'NO' ANSWER IS GIVEN: JUMP TO SECTION 4.3.3.12
IF A 'YES' ANSWER IS GIVEN:THE NEXT QUESTION IS ASKED

4.3.3.10 THE PROGRAM WILL TYPE 'LAST DEVICE:RECEIVER CONTROL REGISTER ADDRESS-' AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.11 TYPE IN THE ADDRESS OF THE LAST RECEIVER CONTROL REGISTER ADDRESS OF THE DU11 TO BE TESTED FOLLOWED BY A <CARRIAGE RETURN>

IF AN INCORRECT ANSWER IS TYPED ,THE PROGRAM WILL TYPE '?' AND WILL THEN REPEAT THE MESSAGE OF 4.3.3.10
NOTE:ALL ADDRESSES SHALL BE CONTIGUOUS

4.3.3.11.1 IF AN 'OUT OF RANGE' ADDRESS IS TYPED IE. MORE THAN 16 (10) DEVICES AWAY (UPWARDS).....THE PROGRAM WILL TYPE 'OUT OF RANGE:RETYPE LAST DEVICE RXCSR ADDRESS-' AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.11.2 TYPE IN THE ADDRESS OF THE LAST RECEIVER CONTROL REGISTER ADDRESS OF THE DU11 TO BE TESTED FOLLOWED BY A <CARRIAGE RETURN>

IF AN INCORRECT ANSWER IS TYPED ,THE PROGRAM WILL TYPE '?' AND WILL REPEAT THE MESSAGE OF 4.3.3.11.1

IF A DEVICE ADDRESS LOWER THAN 1ST DEVICE ADDRESS IS TYPED.....
.....SCHOOLS OUT.....THERE IS NO PROTECTION FOR THIS.
THE PROGRAM WILL DEFAULT TO TWO DEVICES ACTIVE (UPWARDS FROM 1ST DEVICE ADDRESS).THE SAME APPLIES TO IDENTICAL ADDRESSES TYPED FOR FIRST AND LAST DEVICE.
OBSERVE LOCATION @ ACTREG: SEE SECTION 7.2

4.3.3.12 THE PROGRAM WILL TYPE 'DU PRIORITY LEVEL-' AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.13 TYPE IN THE APPROPRIATE DEVICE PRIORITY LEVEL OF THE DU11 OR DU11'S TO BE TESTED FOLLOWED BY A <CARRIAGE RETURN> (NOTE THAT ALL MULTIPLE DEVICES MUST BE AT THE SAME PRIORITY LEVEL). IE '5'

IF AN INCORRECT LEVEL IS TYPED ,THE PROGRAM WILL TYPE '?' AND REPEAT THE MESSAGE OF 4.3.3.12

4.3.3.14 THE PROGRAM WILL TYPE '# OF SYNC CHARS SELECTED (1 OR 2)-' AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.15 TYPE IN THE APPROPRIATE ANSWER '1' OR '2' FOLLOWED BY A <CARRIAGE RETURN>.(NOTE:ALL MULTIPLE DEVICES MUST BE THE SAME)

IF AN INCORRECT ANSWER IS TYPED ,THE PROGRAM WILL TYPE '?' AND WILL REPEAT THE MESSAGE OF 4.3.3.14

4.3.3.16 THE PROGRAM WILL TYPE " IS SEC XMIT JUMPER #6 IN ? (Y OR N)-"
AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.17 TYPE IN THE APPROPRIATE ANSWER YES OR NO FOLLOWED
BY A <CARRIAGE RETURN>. (NOTE THAT ALL MULTIPLE DEVICES
MUST BE THE SAME)

IF AN INCORRECT ANSWER IS TYPED ,THE PROGRAM WILL TYPE "?"
AND WILL REPEAT THE MESSAGE OF 4.3.3.16

4.3.3.18 THE PROGRAM WILL TYPE "IS SEC REC JUMPER # 5 IN ?
(Y OR N)-" AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.19 TYPE IN THE APPROPRIATE ANSWER YES OR NO FOLLOWED
BY A <CARRIAGE RETURN>. (NOTE: ALL MULTIPLE DEVICES MUST BE THE SAME)

IF AN INCORRECT ANSWER IS TYPED ,THE PROGRAM WILL TYPE "?"
AND WILL REPEAT THE MESSAGE OF 4.3.3.18

4.3.3.20 THE PROGRAM WILL TYPE "IS OPT CLR ENABLE JUMPER
4 IN ? (Y OR N)-" AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.21 TYPE IN THE APPROPRIATE ANSWER YES OR NO FOLLOWED
BY A <CARRIAGE RETURN>. (NOTE: ALL MULTIPLE DEVICES MUST BE THE SAME)

IF AN INCORRECT ANSWER IS TYPED ,THE PROGRAM WILL TYPE "?"
AND WILL REPEAT THE MESSAGE OF 4.3.3.20

4.3.3.22 THE PROGRAM WILL TYPE "ARE YOU RUNNING IN MAINT.
MODE EXTERNAL ? ANDDO YOU HAVE THE EXTERNAL MODEM
BYPASS JUMPER CONNECTOR ON ? (Y OR N)-" AND WAIT FOR AN
INPUT FROM THE TELETYPE KEYBOARD

4.3.3.23 TYPE IN THE APPROPRIATE ANSWER YES OR NO FOLLOWED BY
A <CARRIAGE RETURN>. (NOTE: ALL MULTIPLE DEVICES MUST BE THE SAME)

IF AN INCORRECT ANSWER IS TYPED ,THE PROGRAM WILL TYPE "?"
AND WILL REPEAT THE MESSAGE OF 4.3.3.22

4.3.3.24 THE PROGRAM WILL TYPE "R" TO INDICATE THAT IT
HAS STARTED AND WILL COMMENCE TESTING AT TEST 1

4.3.4 PROGRAM RESTART WITH SW01=1
NOTE: THIS WILL ONLY WORK WHEN A SINGLE DEVICE IS SELECTED
...IT WILL NOT WORK IF MULTIPLE DEVICES ARE SELECTED

IF MULTIPLE DEVICES WERE PREVIOUSLY SELECTED,LOAD 000200,
AND SELECT SW00=1 AND ANSWER "NO" TO THE MULTIPLE DEVICE QUESTION
SEE 4.3.3

4.3.4.1 LOAD 000200

4.3.4.2 SET SW01=1

4.3.4.3 PRESS START

NOTE: IF THE SOFTWARE SWITCH REGISTER IS SELECTED THEN THE FOLLOWING
WILL BE TYPED AFTER THE PROGRAM IDENTIFIES ITSELF:
SWR=XXXXXX NEW= (REFER TO SECTION 5. FOR OPERATOR'S OPTION)

4.3.4.4 THE PROGRAM WILL TYPE 'TEST PC-' AND WAIT FOR AN INPUT FROM
THE TELETYPE KEYBOARD

4.3.4.5 TYPE IN THE ADDRESS OF THE TEST AT WHICH THE PROGRAM IS TO
BE STARTED FOLLOWED BY A <CARRIAGE RETURN>

4.3.4.6 THE PROGRAM WILL TYPE 'R' TO INDICATE THAT IT HAS STARTED
TESTING AT THE SELECTED TEST

NOTE: CARE MUST BE TAKEN WHEN THIS FEATURE IS USED
SINCE THERE IS NO PROTECTION AGAINST SELECTING AN ADDRESS
THAT IS IN THE MIDDLE OF A TEST

4.3.5 PROGRAM RESTART WITH SW02 =1

NOTE: THIS WILL ONLY WORK WHEN A SINGLE DEVICE IS SELECTED
SEE NOTE IN 4.3.4 FOR MORE DETAILS

4.3.5.1 LOAD ADDRESS 000200

4.3.5.2 SET SW02 =1

NOTE: IT MAY BE ADVANTAGEOUS TO SET SW01=1 (OPTIONAL)

4.3.5.3 PRESS START

NOTE: IF THE SOFTWARE SWITCH REGISTER IS SELECTED THEN THE FOLLOWING
WILL BE TYPED AFTER THE PROGRAM IDENTIFIES ITSELF:
SWR=XXXXXX NEW= (REFER TO SECTION 5. FOR OPERATOR'S OPTION)

4.3.5.4 THE PROGRAM WILL TYPE 'LOCK ON SELECTED TEST ? (Y OR N)-'
AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.5.5 TYPE IN THE APPROPRIATE ANSWER YES OR NO FOLLOWED BY A
<CARRIAGE RETURN>

IF A NO ANSWER IS GIVEN: THIS LOCK ON TEST WILL BE IGNORED
AND THE PROGRAM WILL TYPE 'R' TO INDICATE THAT IT HAS STARTED
TESTING AT TEST 1

4.3.5.6 IF A YES ANSWER WAS GIVEN: THE PROGRAM WILL ACT AS FOLLOWS...
THE PROGRAM WILL TYPE 'R' TO INDICATE THAT IT HAS STARTED
TESTING AT TEST 1 AND WILL REMAIN IN TEST 1 UNTIL HALTED
OR IF ANY KEY IS STRUCK ON THE TELETYPE, THE PROGRAM
WILL FREEZE ON THE NEXT TEST UNTIL A KEY IS STRUCK ON
THE TELETYPE AND SO FORTH THRU THE PROGRAM. IF SW01 =1 IT
WILL PERFORM AS IN SECTION 4.3.4 ALLOWING ONE TO FREEZE
ON A SELECTED TEST RATHER THAN DEFAULTING TO TEST 1

4.4 STATUS MAP

THE STATUS MAP IS AN AREA OF THE DU11 DIAGNOSTICS, WHICH WILL ALLOW THE TRANSFER OF PARAMETERS BETWEEN DIAGNOSTICS. IF YOU WISH TO TEST A DU11, WHICH IS NOT AT THE DEFAULT VALUES, YOU NEED ONLY GO THROUGH THE TEDIOUS QUESTIONING AND ANSWERING ROUTINE ONCE.

THE FOLLOWING COMBINATIONS OF SWITCH REGISTER SETTINGS WILL ALLOW YOU ACCESS TO THE STATUS MAP.

- 1) SW07=1
- 2) START AT 200
- 3) THE DIAGNOSTIC WILL GO TO THE STATUS MAP AND BYPASS ALL OF THE QUESTIONING ROUTINE.

NOTE: IT IS EXTREMELY IMPORTANT THAT EITHER YOU HAVE JUST ANSWERED THESE QUESTIONS DURING A PRIOR DIAGNOSTIC OR THAT YOU HAVE MANUALLY ENTERED THE CORRECT VALUES FOR VECTOR ADDRESSES ETC., IN THE AREA DESIGNATED FOR THE STATUS MAP. IT IS IMPORTANT THAT THIS BE PERFORMED BEFORE STARTING AT 200.

THE DIAGNOSTIC HAS NO METHOD TO DETERMINE THAT THE STATUS MAP HAS INDEED BEEN LOADED CORRECTLY. THE DIAGNOSTIC ASSUMES THAT WHEN SW07=1 THE VALUES IN THE STATUS MAP ARE THE VALUES TO BE USED. THESE VALUES CAN BE THE WRONG VALUES, BUT THE DIAGNOSTIC WILL NOT REALIZE THAT A MISTAKE HAS BEEN MADE.

IF BOTH SW07 AND SW00 (SWITCH REGISTER SWITCHES) ARE SET (EQUAL TO 1), THE PROGRAM WILL IGNORE SW00 AND SEEING SW07 SET, THE VALUES FROM THE STATUS MAP WILL BE USED. TO USE THE DEFAULT VALUES FOR THE DU11'S THE OPERATOR MUST SET SW00=0 AND SW07=0. THE USE OF SW00 IS EXPLAINED IN GREATER DETAIL IN SECTION 4.3 OF THIS DOCUMENT.

THE FIRST TIME A PROGRAM IS LOADED OR THE FIRST TIME A PROGRAM IS ALTERED VIA THE PARAMETER RESELECTION QUESTION AND ANSWER ROUTINE, A PARTIAL STATUS MAP WILL BE PRINTED. THIS MAP WILL BE PRINTED ONCE FOR ANY COMBINATION OF SWITCHES EXCEPT SW01. RESTARTING THE PROGRAM WILL NOT PRINT OUT A MAP UNLESS THE PROGRAM PARAMETERS ARE BEING RESELECTED BY PUTTING SW00=1. (ON)

THE MAP WILL LOOK LIKE:

STATUS MAP

1300/ 17777

1302/ 000000

1304/ 177777

THE BYTES ARE DEFINED AS FOLLOWS:

1300 THE NUMBER OF SYNCHRONOUS CHARACTERS REQUIRED FOR
SYNCHRONIZATION.
1301 SEC TRANSMIT JUMPER
1302 SEC RECEIVER JUMPER
1303 OPTIONAL JUMPER
1304 MULTIPLE DEVICES (NO=0 , YES= 1)
1305 EXTERNAL MODEM BYPASS? (NO=0 , YES= 1)

IF THE BYTE IS 0 , THE JUMPER IS NOT CONNECTED
AND IF THE BYTE IS 377 ETC. THE JUMPER SHOULD BE CONNECTED.

5. OPERATING PROCEDURE

IF THE DIAGNOSTIC IS RUN ON A CPU WITHOUT A SWITCH
REGISTER THEN A SOFTWARE SWITCH REGISTER IS USED WHICH ALLOWS
THE USER THE SAME SWITCH OPTIONS AS THE HARDWARE SWITCH REGISTER.
IF THE HARDWARE SWITCH REGISTER DOES NOT EXIST OR IF ONE DOES
AND IT CONTAINS ALL ONES (177777) THEN THE SOFTWARE SWITCH
REGISTER (LOC. 176) IS USED.

CONTROL:

THIS PROGRAM ALSO SUPPORTS THE DYNAMIC LOADING OF THE SOFTWARE SWITCH
REGISTER (LOC. 176) FROM THE TTY. THIS CAN BE ACCOMPLISHED BY
DOING THE FOLLOWING:

- 1) TYPE CONTROL G <^G>; THIS WILL ALLOW THE TTY TO ENTER DATA INTO
LOC. 176 AT SELECTED POINTS WITHIN THE PROGRAM.
- 2) THE MACHINE WILL THEN TYPE: SWR=XXXXXXNEW= (XXXXXX IS THE OCTAL CONTENTS
OF THE SOFTWARE SWITCH REGISTER.)
- 3) AFTER THE ''NEW='' HAS BEEN TYPED THEN THE OPERATOR CAN DO ONE
OF THE FOLLOWING AT THE TTY:
 - A) TYPE A NUMBER TO BE LOADED INTO LOC. 176 FOLLOWED BY A <CR>.
(ONLY NUMBERS BETWEEN 0-7 WILL BE ACCEPTED AND ONLY 6 NUMBERS
WILL BE ALLOWED)
IF A <CR> IS THE FIRST KEY DEPRESSED THE SOFTWARE SWITCH
REGISTER CONTENTS WILL NOT BE CHANGED.
 - B) IF A CONTROL U <^U> IS DEPRESSED THEN THE PROGRAM WILL SEND YOU
BACK TO STEP 2.

5.1

OPERATIONAL SWITCH SETTINGS
SW15 =1 HALT ON ERROR
SW14 =1 LOOP ON CURRENT TEST
SW13 =1 INHIBIT ERROR TYPEOUT
SW11 =1 INHIBIT ITERATIONS
SW10 =1 ESCAPE TO NEXT TEST ON ERROR

SW08 =1 LOOP ON ERROR
SW07 =1 USE STATUS MAP PARAMETERS
SW02 =1 LOCK ON TEST
SW01 =1 RESTART PROGRAM AT SELECTED TEST
SW00 =1 RESELECT VECTOR AND CONTROL REGISTER ADDRESSES
&PARAMETERS AFTER A PROGRAM RESTART
TO INHIBIT 'END OF PASS' TYPEOUT - TURN TELETYPE OFF

6. ERRORS

6.1 ERROR HALTS
THERE ARE FOUR DISTINCT ERROR TYPEOUTS

NOTE: IF THE SOFTWARE SWITCH REGISTER IS TO BE CHANGED AFTER A HALT
THE THE OPERATOR IS REQUIRED TO TYPE A <^G> BEFORE DEPRESSING CONTINUE.
THE FOLLOWING WILL BE TYPED:
SWR=XXXXXX NEW= (REFER TO SECTION 5. FOR OPERATOR OPTION)

6.1.1 PC+2 = ERROR PC
WHERE PC +2 IS THE ADDRESS OF THE CALL TO THE ERROR HANDLER +2
REFER TO THE ABOVE 'HLT' IN DIAGNOSTIC FOR ERROR DESCRIPTION

CHECK ADDRESS @ RXCSR: TO LOCATE THE DEVICE PRESENTLY UNDER
TEST WHEN RUNNING MULTIPLE DEVICES

6.1.2 PC +2 = REGISTER ERROR PC
REGISTER EXPECTED ACTUAL
16XXXX YYYYYY ZZZZZZ

WHERE 16XXXX IS THE ADDRESS OF THE FAILING DEVICE REGISTER

WHERE YYYYYY IS THE EXPECTED CONTENTS OF THAT REGISTER

WHERE ZZZZZZ IS THE ACTUAL CONTENTS OF THAT REGISTER

6.1.3 PC +2 = RECEIVER ERROR PC
REGISTER EXPECTED ACTUAL
16XXXX YYYYYY ZZZZZZ

WHERE 16XXXX IS THE ADDRESS OF THE FAILING RECEIVER (RXDBUF) REGISTER

WHERE YYYYYY IS THE EXPECTED DATA CONTENTS OF THAT REGISTER

WHERE ZZZZZZ IS THE ACTUAL DATA CONTENTS OF THAT REGISTER

6.1.4 PC +2 = TRANSMITTER ERROR PC
REGISTER EXPECTED ACTUAL
16XXXX YYYYYY ZZZZZZ

WHERE 16XXXX IS THE ADDRESS OF THE FAILING TRANSMITTER (TXCSR) REGISTER

WHERE YYYYYY IS THE EXPECTED CONTENTS OF THAT REGISTER

WHERE ZZZZZZ IS THE ACTUAL CONTENTS OF THAT REGISTER

6.1.5 ERROR DESCRIPTIONS
SEE LISTINGS FOR DETAILS OF ERRORS

6.2 ERROR RECOVERY

6.2.1 SW15 =0
IF THE PROGRAM IS RUN WITH SW15 =0 ,NO OPERATOR ACTION IS
REQUIRED TO CONTINUE TESTING

6.2.2 SW15 =1
IF THE PROGRAM IS RUN WITH SW15 =1 ,TO CONTINUE TESTING
AFTER THE PROGRAM HAS HALTED ,PRESS THE PROCESSOR
CONSOLE 'CONTINUE SWITCH'

NOTE: THE PC + 2 OF THE 'HLT'' WILL BE DISPLAYED IN THE DATA LIGHTS

6.2.3 ILLEGAL INTERRUPTS
IF AN INTERRUPT OCCURS TO A VECTOR ADDRESS NOT SELECTED
DURING PROGRAM INITIALIZATION, THE PROGRAM WILL HALT IN
THE TRAPCATCHER. THE ADDRESS AT WHICH THE PROGRAM
HALTS IS 2 GREATER THAN THE ADDRESS TO WHICH THE INTERRUPT
OCCURED. THE PROGRAM MUST BE RESTARTED AT 000200 TO
RECOVER FROM THIS ERROR.

6.2.4 ADDITIONAL TROUBLESHOOTING AIDS ERRCNT: & PASCNT:
CHECK THESE TWO TAG LOCATIONS FOR TOTAL # OF ERRORS AND PASSES RESPECTIVELY.
LOADING 000200 AND RESTARTING WILL CLEAR THESE LOCATIONS.

6.3 END OF PASS ROUTINE
THIS TYPEOUT IS MENTIONED HERE FOR CONVENIENCE
IT IS IN THE FORM:

END OF PASS TAPE Y
16XXXX = DEVICE

WHERE Y IS THE TAPE LOADED

WHERE 16XXXX IS THE DEVICE'S BASE REGISTER ADDRESS

TO INHIBIT THIS TYPEOUT - TURN TELETYPE OFF

7. RESTRICTIONS

7.1 MULTIPLE DEVICES
UP TO 16(10) DEVICES MAY BE TESTED. HOWEVER, THEY
MUST HAVE CONTIGUOUS ADDRESSES AND VECTORS

NOTE: IF ALL DEVICES UNDER TEST HAVE THE SAME INTERRUPT VECTOR
YOU CAN CHANGE 'ZERO: ADD #10,BASEIV ;NEXT BLOCK
(VECTORS)'' TO 'ZERO: ADD #0,BASEIV';
THEREBY THE VECTOR ADDRESSES WILL NOT BE
UPDATED AFTER EACH PASS.

7.2 DISQUALIFYING DEVICES WHEN RUNNING MULTIPLE DEVICES

WHEN RUNNING MULTIPLE DEVICES AN ACTIVE BIT IS SET
FOR EACH DEVICE RUNNING UNDER TEST IE. BIT 0 FOR
DEVICE 0 BIT 15 FOR DEVICE 15
TO DISQUALIFY DEVICES:

- 7.2.1 IF DEVICE 0 IS TO BE DISQUALIFIED, SIMPLY RESTART
PROGRAM WITH SW00 =1 AND OMIT THE FIRST DEVICE.
- 7.2.2 IF HOWEVER, DEVICES 1 THRU 15 OR ANY COMBINATION THEREOF
ARE TO BE DISQUALIFIED....LOAD THE LOCATION OF ACTREG:
OBSERVE THE ACTIVE BITS (ACTIVE =1, NONACTIVE = 0)
AND DEPOSIT 0 WHERE THOSE DEVICES ARE TO BE DISQUALIFIED
 - 7.2.2.1 TO RESTART...LOAD 000200 IN SWR AND DEPRESS START....
THE PROGRAM WILL CONTINUE WITH THE DEVICE IT WAS IN BEFORE HALTING.
 - 7.2.2.2ORLOAD 000200 WITH SW00 =1 AND DEPRESS START....
ANSWER THE QUESTION :1ST DEVICE : ETC.....
.....THE PROGRAM WILL CONTINUE WITH DEVICE 0
 - 7.2.2.3 IF ALL DEVICES ARE DISQUALIFIED BY MISTAKE THE PROGRAM
WILL TYPEOUT AN ERROR MESSAGE.....LOAD & START AT 000200
- 7.3 CABLE DELAYS
NOTE: EXTERNAL LOOP BACK TESTS ONLY (MODEM CABLE WITH H315 CONNECTOR ON)
 - 7.3.1 TO PROVIDE SUFFICIENT DELAY FOR CLOCK SIGNAL OVER THE CABLE,
LOCATION 'HOLD:' MUST BE MODIFIED TO ACCOMODATE FOR FASTER MACHINES.
PRESENTLY 'HOLD:' =20 IS SUFFICIENT TIME ON AN 11/20 MACHINE.
IF RUNNING ON AN 11/40 OR AN 11/45 'HOLD:' MUST BE PATCHED TO 40

BASICALLY DON'T TRY TO EXCEED 10K TO 12K RATE USING THE EIA DRIVERS
- 7.4 TO USE THE 'XOR' TESTER, THE BRANCH AROUND THE 'XOR'
CODE MUST BE PATCHED TO A 'NOP'. (SEE LISTINGS FOR DETAILS)
- 8. DEFAULT PARAMETERS:
1ST DEVICE: RECEIVER CONTROL REGISTER ADDRESS- RXCSR: 160040
VECTOR ADDRESS- DURIV: 770
ARE YOU RUNNING MULTIPLE DEVICES ?- NO MULTD: 0
LAST DEVICE: RECEIVER CONTROL REGISTER ADDRESS- LASTADD: 0
DU PRIORITY LEVEL- LEVEL 5 DUPRT: LEVEL 5
OF SYNC CHARS SELECTED - 2 SYNCND: 377
IS SEC XMIT JUMPER # 6 IN ?- YES SEXMIT: 377
IS SEC REC JUMPER # 5 IN ?- YES SEREC: 377
IS OPT CLR ENABLE JUMPER # 4 IN ?- YES OPTCLR: 377

DO YOU HAVE THE EXTERNAL MODEM BYPASS JUMPER
CONNECTOR ON (H315)- YES

JMRBY: 377

9. PROGRAM DESCRIPTION

9.1 THIS PROGRAM PERFORMS THE OFFLINE RECEIVER SECTION TESTING
OF THE DEVICE
SEE LISTING FOR DETAILS

10. FLOW CHARTS: RECEIVER FLOW, TRANSMITTER FLOW, TRANSMITTER & RECEIVER FLOW

11. LISTINGS

674
675 000000* 000000G

D

676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709

.ENABLE ABS

:DU11 DZDUB-C TAPE B
:COPYRIGHT 1973, DIGITAL EQUIPMENT CORP., MAYNARD, MASS. 01754

:STARTING PROCEDURE
:LOAD PROGRAM
:PRESS START
:PROGRAM WILL TYPE 'DU11 DZDUB-C TAPE B ''
:PROGRAM WILL TYPE 'R' TO INDICATE THAT TESTING HAS STARTED
:AT THE END OF A PASS, PROGRAM WILL TYPE 'END OF PASS TAPE B''
:AND THEN RESUME TESTING

:SWITCH REGISTER OPTIONS

100000
040000
020000
010000
004000
002000
001000
000400
000200
000100
000040
000020
000010
000004
000002
000001

SW15=100000
SW14=40000
SW13=20000
SW12=10000
SW11=4000
SW10=2000
SW09=1000
SW08=400
SW07=200
SW06=100
SW05=40
SW04=20
SW03=10
SW02=4
SW01=2
SW00=1

=1,HALT ON ERROR
=1,LOOP ON CURRENT TEST
=1,INHIBIT ERROR TYPEOUT

=1,INHIBIT ITERATIONS
=1,ESCAPE TO NEXT TEST ON ERROR
=1,LOOP WITH CURRENT DATA
=1,LOOP ON ERROR
+ =1, USE STATUS MAP

:LOCK ON TEST SELECT
:RESTART PROGRAM AT SELECTED TEST
:RESELECT VECTOR AND CONTROL REGISTER
:ADDRESS AFTER PROGRAM RESTART

```
710
711 ;REGISTER DEFINITIONS
712
713 000000 R0=%0 ;GENERAL REGISTER
714 000001 R1=%1 ;GENERAL REGISTER
715 000002 R2=%2 ;GENERAL REGISTER
716 000003 R3=%3 ;GENERAL REGISTER
717 000004 R4=%4 ;GENERAL REGISTER
718 000005 R5=%5 ;GENERAL REGISTER
719 000006 SP=%6 ;PROCESSOR STACK POINTER
720 000007 PC=%7 ;PROGRAM COUNTER
721
722 ;LOCATION EQUIVALENCIES
723
724 177570 DSWR=177570 ;HARDWARE SWITCH REGISTER LOC.
725 177570 DLIGHTS=177570 ;HARDWARE DISPLAY REGISTER LOC.
726 177776 PS=177776 ;PROCESSOR STATUS WORD
727 001100 STACK=1100 ;START OF PROCESSOR STACK
728
729 ;INSTRUCTION DEFINITIONS
730
731 005746 PUSH1SP=5746 ;DECREMENT PROCESSOR STACK 1 WORD =TST -(SP)
732 005726 POP1SP=5726 ;INCREMENT PROCESSOR STACK 1 WORD =TST (SP)+
733 010046 PUSHRO=10046 ;SAVE R0 ON STACK =MOV R0,-(SP)
734 012600 POPRO=12600 ;RESTORE R0 FROM STACK =MOV (SP)+,R0
735 024646 PUSH2SP=24646 ;DECREMENT STACK TWICE =CMP -(SP),-(SP)
736 022626 POP2SP=22626 ;INCREMENT STACK TWICE =CMP (SP)+,(SP)+
737 .EQUIV EMT,HLT ;BASIC DEFINITION OF ERROR CALL
738
739
740 100000 BIT15=100000
741 040000 BIT14=40000
742 020000 BIT13=20000
743 010000 BIT12=10000
744 004000 BIT11=4000
745 002000 BIT10=2000
746 001000 BIT9=1000
747 000400 BIT8=400
748 000200 BIT7=200
749 000100 BIT6=100
750 000040 BIT5=40
751 000020 BIT4=20
752 000010 BIT3=10
753 000004 BIT2=4
754 000002 BIT1=2
755 000001 BIT0=1
756
757 ;PROCESSER LEVELS
758 000340 LEVEL7=340
759 000300 LEVEL6=300
760 000240 LEVEL5=240
761 000200 LEVEL4=200
762 000140 LEVEL3=140
763 000100 LEVEL2=100
764 000040 LEVEL1=040
765 000000 LEVEL0=000
```

```

766      :REGISTER DEFINITIONS
767      :RXCSR BIT DEFINITIONS
768      100000 DSC=BIT15      :DATA SET CHANGE
769      040000 RING=BIT14     :RING
770      020000 CTS=BIT13     :CLR TO SEND
771      010000 CARDET=BIT12  :CARRIER DETECT
772      004000 RECACT=BIT11  :REC ACTIVE
773      002000 SRD=BIT10     :SEC REC DATA
774      001000 DSR=BIT9      :DATA SET RDY
775      000400 STPSYN=BIT8   :STRIP SYNC
776      000200 RXDONE=BIT7   :REC DONE
777      000100 RINTEN=BIT6   :REC INTR ENABLE
778      000040 DSINTE=BIT5   :DSC INTR ENABLE
779      000020 SYNSCH=BIT4   :SYNC SEARCH
780      000010 STD=BIT3      :SEC XMIT DATA
781      000004 RTS=BIT2      :REQ TO SEND
782      000002 DTR=BIT1     :DATA TERM RDY
783      000001 VOID=BIT0
784      :RXDBUF BIT DEFINITIONS
785      100000 RXERR=BIT15    :REC ERROR
786      040000 OVRRUN=BIT14  :OVERRUN
787      020000 FRMERR=BIT13  :FRAME ERROR
788      010000 PARER=BIT12   :PARITY ERROR
789      :PARCSR BIT DEFINITIONS
790      001000 PAREN=BIT9     :PARITY ENABLE
791      000400 EVPAR=BIT8     :EVEN PARITY SENSE
792      :PARCSR WRD DEFINITIONS
793      030000 SYNINT=30000   :SYNC EXTERNAL MODE
794      020000 SYNEXT=20000  :SYNC INTERNAL MODE
795      000000 ISYMOD=0      :ISOC MODE
796      000000 FIVE=0        :WORD LENGTH 5 BITS
797      002000 SIX=2000      :WORD LENGTH 6 BITS
798      004000 SEVEN=4000    :WORD LENGTH 7 BITS
799      006000 EIGHT=6000   :WORD LENGTH 8 BITS
800      000000 NOPAR=0      :NO PARITY
801      001000 ODDPAR=1000   :ODD PARITY
802      001400 EVEPAR=1400  :EVEN PARITY
803      :TXCSR BIT DEFINITIONS
804      100000 DNA=BIT15     :DATA NOT AVAILABLE
805      040000 MTDATA=BIT14  :MAINT DATA
806      020000 CLK=BIT13     :CLK
807      002000 BITW=BIT10    :BIT WINDOW
808      000400 MRESET=BIT8   :MASTER RESET
809      000200 TXDONE=BIT7   :XMIT DONE
810      000100 TXINTE=BIT6   :XMIT INTR ENABLE
811      000040 DNAINTE=BIT5  :DNA INTR ENAB
812      000020 SEND=BIT4     :SEND
813      000010 HDXEN=BIT3    :HDX/FDX
814      000001 BREAK=BIT0   :BREAK
815      :TXCSR WRD DEFINITIONS
816      000000 USER=0        :USER MODE
817      004000 MINT=4000     :MAINT INT MODE
818      010000 MEXT=10000    :MAINT EXT MODE
819      014000 SYSTST=14000  :SYSTEM TEST MODE
820      :TRAPCATC:ER FOR ILLEGAL INTERRUPTS
  
```

```

821                                     ;STANDARD INTERRUPT VECTORS
822
823
824                                     . =24
825 000024 016104                       .PFAIL                       ;POWER FAIL HANDLER
826 000026 000340                       340                          ;SERVICE AT LEVEL 7
827 000030 015634                       .HLT                          ;ERROR HANDLER
828 000032 000340                       340                          ;SERVICE AT LEVEL 7
829 000034 015602                       .TRPSRV                       ;GENERAL HANDLER DISPATCH SERVICE
830 000036 000340                       340                          ;SERVICE AT LEVEL 7
831
832                                     ;SOFTWARE SWITCH REGISTER
833
834                                     . =174
835 000174 000000                       DISPREG: .WORD 0              ;SOFTWARE DISPLAY REG.
836 000176 000000                       SWREG:  .WORD 0              ;SOFTWARE SWITCH REGISTER
837 000200 000167 001214                 JMP      .START              ;GO TO START OF PROGRAM
838
839
840                                     . =1100
841                                     . =1100
842
843                                     ;INDIRECT POINTERS
844
845 001100 177570                       SWR: 177570                   ;SWITCH REGISTER POINTER
846 001102 177570                       LIGHTS:177570                ;DISPLAY REGISTER POINTER
847 001104 177560                       TKCSR: 177560                ;TELETYPE KEYBOARD CONTROL REGISTER
848 001106 177562                       TKDBR: 177562                ;TELETYPE KEYBOARD DATA BUFFER
849 001110 177564                       TPCSR: 177564                ;TELEPRINTER CONTROL REGISTER
850 001112 177566                       TPDBR: 177566                ;TELEPRINTER DATA BUFFER
851
852                                     ;PROGRAM CONTROL PARAMETERS
853
854 001114 000000                       RTRN: 0                      ;SCOPE ADDRESS FOR LOOP ON TEST
855 001116 000000                       NEXT: 0                      ;ADDRESS OF NEXT TEST TO BE EXECUTED
856 001120 000000                       LOCK: 0                      ;ADDRESS FOR LOCK ON CURRENT DATA
857 001122 000000                       ICOUNT: 0                    ;NUMBER OF ITERATIONS THAT CURRENT TEST WILL BE EXECUTED
858 001124 000000                       LPCNT: 0                    ;NUMBER OF ITERATIONS COMPLETED
859 001126 000000                       TSTNO: 0                    ;NUMBER OF TEST IN PROGRESS
860 001130 000000                       PASCNT: 0                   ;NUMBER OF PASSES COMPLETED
861 001132 000000                       ERRCNT: 0                   ;TOTAL NUMBER OF ERRORS
862 001134 000000                       LSTERR: 0                   ;PC OF LAST ERROR CALL
863
864                                     ;PROGRAM VARIABLES
865
866 001136 000020                       HOLD: 20                     ;TEMPORARY STORAGE=DELAY TIME FOR CABLES
867 001140 000000                       SHIFT: 0                    ;TEMPORARY STORAGE= # OF SHIFTS PER CHAR
868 001142 000000                       COUNT: 0                    ;TEMPORARY STORAGE= # OF TIMES A CHAR WILL BE SENT
869 001144 000000                       TEMP1: 0                    ;TEMPORARY STORAGE
870 001146 000000                       TEMP2: 0                    ;TEMPORARY STORAGE
871 001150 000000                       TEMP3: 0                    ;TEMPORARY STORAGE
872 001152 000000                       TEMP4: 0                    ;TEMPORARY STORAGE
873 001154 000000                       TEMP5: 0                    ;TEMPORARY STORAGE
874 001156 000000                       SAVR0: 0                    ;R0 STORAGE
875 001160 000000                       SAVR1: 0                    ;R1 STORAGE
876 001162 000000                       SAVR2: 0                    ;R2 STORAGE

```

877 001164 000000
878 001166 000000
879 001170 000000
880 001172 000000
881 001174 000000

SAVR3: 0
SAVR4: 0
SAVR5: 0
SAVSP: 0
SAVPC: 0

:R3 STORAGE
:R4 STORAGE
:R5 STORAGE
:STACK POINTER STORAGE
:PROGRAM COUNTER STORAGE

```
882                                     ;PROGRAM CONVERSATIONAL PARAMETERS
883 001176 377 SYNCNO: .BYTE 377 ;# OF SYNC CHARS REQ'D FOR SYNC'ZATION
884 001177 377 SEXMIT: .BYTE 377 ;SEC XMIT JUMPER 'IN'
885 001200 377 SEREC: .BYTE 377 ;SEC REC JUMPER 'IN'
886 001201 377 OPTCLR: .BYTE 377 ;OPTIONAL JUMPER CLR 'IN'
887 001202 000 MULTD: .BYTE 0 ;NO MULTIPLE DEVICE FLAG
888 001203 377 JMRBY: .BYTE 377 ;EXTERNAL MODEM BYPASS JUMPER 'IN'
889 .EVEN
890
891                                     ;PROGRAM MULTIPLE DEVICE PARAMETERS
892 001204 000000 BASEADD: 0 ;PROG CONTROLLED 1ST DEVICE ADDR
893 001206 000000 KEEPADD: 0 ;SAVED 1ST DEVICE ADDR
894 001210 000000 LASTADD: 0 ;LAST DEVICE RXCSR ADDR
895 001212 000000 BASEIV: 0 ;PROG CONTROLLED IV
896 001214 000000 KEEPIV: 0 ;SAVED INTR VECTOR
897 001216 000000 ACTREG: 0 ;ACTIVE REGISTER ...MODIFY THIS
898 ;LOCATION TO DISQUALIFY OR QUALIFY
899 ;DEVICES (1= RUN,,0= DON'T RUN)
900 001220 000000 ROTADD: 0 ;ROTATING POINTER FOR ACTREG..POINTS
901 ;TO DEVICE PRESENTLY UNDER TEST WHEN RUNNING MULTIPLE DE
902 ;*****
903
904 ; THESE ARE STORAGE FOR THE STATUS MAP PRINT OUT
905 001222 000000 FLAG:0 ; FLAGS FOR STATUS MAP PRINT OUT (SSP)
906 001224 000000 HOLD0: 0 ; HOLDS R0 IN STATUS MAP PRINT
907 001226 000000 HOLD1:0 ; R1 ETC.
908 001230 000000 COUNT1:0 ; FOR COUNTING 3 WORDS
909 001232 000002 TABLE : 2 ; FOR CONVRT ROUTINE
910 001234 003006 3006
911 001236 000000 0
912 001240 003006 3006
913 001242 000000 0
914 ;*****
915 ;PROGRAM CONTROL FLAGS
916
917
918 001244 000 INIFLG: .BYTE 0 ;PROGRAM INITIALIZATION FLAG
919 001245 000 STFLG: .BYTE 0 ;TEST START FLAG
920 001246 000 ERRFLG: .BYTE 0 ;ERROR OCCURED FLAG
921 001247 000 LOKFLG: .BYTE 0 ;LOCK ON CURRENT TEST FLAG
922
923 .EVEN
924
925 ;***** STATUS MAP *****
926
927 .=1300
928 001300 000001 STATUS: NOSYNC: .BLKB 1 ;SYNC CHARS
929 001301 000001 MITSEX: .BLKB 1 ;XMIT JUMPER
930 001302 000001 RESEC: .BLKB 1 ;REC SEC JUMPER
931 001303 000001 CLROPT: .BLKB 1 ;OPTIONAL JUMPER
932 001304 000001 DMULT: .BLKB 1 ;MULTIPLE DEVICE FLAG
933 001305 000001 BYJMR: .BLKB 1 ;EXTERNAL MODEM
934
935 ; MULTIPLE DEVICE PARAMETERS
936
937 001306 000001 ADDBASE: .BLKW 1 ;PROG CONTROLLED 1ST DEVICE ADDR
```

938 001310 000001
 939 001312 000001
 940 001314 000001
 941 001316 000001
 942 001320 000001
 943 001322 000001
 944 001324 000001
 945 001326 000001
 946 001330 000001
 947 001332 000001
 948 001334 000001
 949 001336 000001
 950 001340 000001
 951 001342 000001
 952 001344 000001
 953 001346 000001
 954 001350 000001
 955 001352 000001
 956 001354 000001
 957 001356 000001
 958 001360 000001
 959 001362 000001
 960 001364 000001
 961
 962
 963
 964
 965
 966
 967 001366
 968
 969
 970 104400
 971 001366 014366
 972 104401
 973 001370 014552
 974 104402
 975 001372 014572
 976 104403
 977 001374 014632
 978 104404
 979 001376 014750
 980 104405
 981 001400 015002
 982 104406
 983 001402 015216
 984 104407
 985 001404 015256
 986 104410
 987 001406 015310
 988 104411
 989 001410 015314
 990 104412
 991 001412 015534
 992 104413
 993 001414 016250

ADDKEEP: .BLKW 1 ;SAVED 1ST DEVICE ADDR
 ADDLAST: .BLKW 1 ;LAST DEVICE RXCSR ADDR
 IVBASE: .BLKW 1 ;PROG CONTROLLED IV
 IVKEEP: .BLKW 1 ;SAVED INTR VECTOR
 REGACT: .BLKW 1 ;ACTIVE REGISTER
 ADDROT: .BLKW 1 ;ROTATING POINTER
 PRTDU: .BLKW 1 ;DU11 PRIORITY
 RIVDU: .BLKW 1 ;DU11 REC INTR VECTOR
 TIVDU: .BLKW 1 ;DU11 XMIT INTR VECTOR
 TISDU: .BLKW 1 ;DU11 XMIT INTR STATUS
 RISDU: .BLKW 1 ;DU11 REC INTR STATUS
 LIESS: .BLKW 1 ;PRIORITY TO ALLOW INTR
 CSRRX: .BLKW 1 ; DEFAULT OR ALTERED PARAMETERS
 CSRRHX: .BLKW 1 ;
 BUFRXD: .BLKW 1 ;
 BUFHRXD: .BLKW 1 ;
 CSRPAR: .BLKW 1 ;
 CSRHPAR: .BLKW 1 ;
 CSRTX: .BLKW 1 ;
 CSRHTX: .BLKW 1 ;
 BUFTXD: .BLKW 1 ;
 BUFHTXD: .BLKW 1 ;
 BASEDU: .BLKW 1 ;DU11 RXCSR BASE ADDR
 .EVEN

;DEFINITIONS FOR TRAP SUBROUTINE CALLS
 ;POINTERS TO SUBROUTINES CAN BE FOUND
 ;IN THE TABLE IMMEDIATELY FOLLOWING THE DEFINITIONS

.TRPTAB:
 ;*****
 ;*****
 .SCOPE SCOPE=TRAP+0 ;CALL TO SCOPE LOOP AND ITERATION HANDLER
 .SCOP1 SCOP1=TRAP+1 ;CALL TO LOOP ON CURRENT DATA HANDLER
 .TYPE TYPE=TRAP+2 ;CALL TO TELETYPE OUTPUT ROUTINE
 .INSTR INSTR=TRAP+3 ;CALL TO ASCII STRING INPUT ROUTINE
 .INSTER INSTER=TRAP+4 ;CALL TO INPUT ERROR HANDLER
 .PARAM PARAM=TRAP+5 ;CALL TO NUMERICAL DATA INPUT ROUTINE
 .SAV05 SAV05=TRAP+6 ;CALL TO REGISTER SAVE ROUTINE
 .RES05 RES05=TRAP+7 ;CALL TO REGISTER RESTORE ROUTINE
 .CONVRT CONVRT=TRAP+10 ;CALL TO DATA OUTPUT ROUTINE
 .CNVRT CNVRT=TRAP+11 ;CALL TO DATA OUTPUT ROUTINE WITHOUT CR/LF
 .SETFLG SETFLG=TRAP+12 ;CALL TO FLAG SET ROUTINE
 .CKSWR CKSWR=TRAP+13 ;CALL TO ALLOW SWREG TO BE LOADED FROM TTY

```
994      104414
995 001416 016324
996
997
998
999
1000
1001
1002
1003
1004
1005
1006 001420 012767 000340 176350 .START: MOV #340,PS ;LOCK OUT INTERRUPTS
1007 001426 012706 001100 MOV #STACK,SP ;SET UP STACK
1008 001432 012737 016104 000024 MOV #.PFAIL,@#24 ;SET UP POWER FAIL VECTOR
1009 001440 005067 177460 CLR LPCNT ;CLEAR # OF ITERATION COMPLETED LOCATION
1010 001444 105067 177575 CLR STFLG ;CLEAR START FLAG
1011 001450 005067 177454 CLR PASCNT ;CLEAR PASS COUNT
1012 001454 105067 177566 CLR RB ERRFLG ;CLEAR ERROR FLAG
1013 001460 005067 177446 CLR ERRCNT ;CLEAR ERROR COUNT
1014 001464 005067 177444 CLR LSTERR ;CLEAR LAST ERROR POINTER
1015 001470 012767 000001 177430 MOV #1,TSTNO ;SET UP FOR TEST 1
1016 001476 012767 001420 177410 MOV #.START,RTRN ;SET UP FOR POWER FAIL BEFORE
1017 ;TESTING STARTS
1018 001504 105767 177534 TSTB INIFLG ;HAS INITIALIZATION BEEN PERFORMED
1019 001510 001004 BNE ONCE
1020 001512 104402 016424 TYPE ,MTITLE ;TYPE TITLE MESSAGE
1021 001516 105167 177522 COMB INIFLG ;IF NOT SET FLAG AND DO
1022 001522 012767 177570 177350 ONCE: MOV #DSWR,SWR ;RELOAD HARDWARE SWITCH REGISTER INTO POINTER
1023 001530 012767 177570 177344 MOV #DLIGHTS,LIGHTS ;RELOAD HARDWARE DISPLAY REGISTER INTO POINTER
1024 001536 013746 000006 MOV @#6,-(SP) ;SAVE VECTORS
1025 001542 013746 000004 MOV @#4,-(SP)
1026 001546 012737 001566 000004 MOV #64$,@#4 ;SET UP FOR TIMEOUT
1027 001554 022777 177777 177316 CMP #-1,@SWR ;REFERENCE HARDWARE SWITCH REGISTER
1028 001562 001402 BEQ 65$
1029 001564 000407 BR 66$
1030 001566 022626 64$: CMP (SP)+,(SP)+ ;ADJUST STACK
1031 001570 012767 000176 177302 65$: MOV #SWREG,SWR ;POINT TO SOFTWARE SWITCH REG
1032 001576 012767 000174 177276 MOV #DISPREG,LIGHTS ;POINT TO SOFT DISPLAY REG
1033 001604 012637 000004 66$: MOV (SP)+,@#4 ;RESTORE VECTORS
1034 001610 012637 000006 MOV (SP)+,@#6
1035 001614 005737 000042 TST @#42 ;UNDER MONITOR
1036 001620 001005 BNE MAP
1037 001622 022767 000176 177250 CMP #SWREG,SWR ;IS SWREG USED
1038 001630 001001 BNE MAP ; BRANCH TO CHECK FOR STATUS MAP
1039 001632 104414 CNTLU
1040 ;*****
1041 ; CODE FOR STATUS MAP
1042 ; CODE ADDED FOR REV. E OF DIAGNOSTICS
1043 ; IF SW07= 1 ,THEN YOU USE THE STATUS MAP PREVIOUSLY
1044 ; SETUP, OR REENTER QUESTIONING ROUTINE
1045
1046 001634 032777 000200 177236 MAP: BIT #SW07,@SWR ; IS SW07=1?
1047 001642 001537 BEQ $67 ; IF NOT, GO TO TEST FOR SW00=1
1048 ; NOW SET UP MAP VALUES FOR PROGRAM
1049 ; THESE VALUES FROM THE STATUS MAP WILL BE USED IN THE
```

```

1050      ; OPERATION OF THIS PROGRAM.
1051 001644 116767 177430 177324  MOVB NOSYNC      ,SYNCHNO      ; SYNC CHAR
1052 001652 116767 177423 177317  MOVB MITSEX      ,SEXMIT      ; XMIT JUMPER
1053 001660 116767 177416 177312  MOVB RESEC       ,SEREC       ; SEC REC JUMPER
1054 001666 116767 177411 177305  MOVB CLROPT     ,OPTCLR     ; OPTIONAL JUMPER
1055 001674 116767 177404 177300  MOVB DMULT      ,MULTD     ; MULTIPLE DEVICE
1056 001702 116767 177377 177273  MOVB BYJMR      ,JMRYBY    ; EXTERNAL MODEM
1057 001710 016767 177372 177266  MOV  ADDBASE    ,BASEADD    ; PROG 1ST DEVICE ADDR
1058 001716 016767 177366 177262  MOV  ADDKEEP    ,KEEPADD    ; SAVED 1ST DEVICE ADDR
1059 001724 016767 177362 177256  MOV  ADDLAST    ,LASTADD    ; LAST DEVICE RXCSR ADDR
1060 001732 016767 177360 177254  MOV  IVKEEP     ,KEEPIV    ; SAVED INTR VECTOR
1061 001740 016767 177354 177250  MOV  REGACT     ,ACTREG    ; ACTIVE REGISTER
1062 001746 016767 177350 177244  MOV  ADDRROT    ,ROTADD    ; ROTATING POINTER
1063 001754 016767 177334 177230  MOV  IVBASE     ,BASEIV    ; BASE INTR VECTOR
1064 001762 016767 177220 177214  MOV  KEEPADD    ,BASEADD    ; RELOAD BASEADD
1065 001770 016767 177332 016572  MOV  RIVDU     ,DURIV    ; REC INTR VECTOR
1066 001776 016767 177332 016566  MOV  RISDU     ,DURIS    ; REC INTR STATUS
1067 002004 016767 177320 016562  MOV  TIVDU     ,DUTIV    ; XMIT INTR VECTOR
1068 002012 016767 177314 016556  MOV  TISDU     ,DUTIS    ; XMIT INTR STATUS
1069 002020 016767 177312 016064  MOV  L1ESS     ,LESS1    ; PRIORITY TO ALLOW INTR
1070 002026 013737 001324 020110  MOV  @#PRTDU   ,@#DUPRT   ; PRIORITY RELOADED
1071 002034 016767 177324 016204  MOV  BASEDU    ,DUBASE    ;
1072 002042 016767 177272 016474  MOV  CSRRX     ,RXCSR    ;
1073 002050 016767 177266 016470  MOV  CSRHRX    ,HRXCSR   ;
1074 002056 016767 177262 016464  MOV  BUFRXD    ,RXDBUF   ;
1075 002064 016767 177256 016460  MOV  BUFRXD    ,RXDBUF   ;
1076 002072 016767 177252 016454  MOV  CSRPAR    ,PARCSR   ; HRXDBUF
1077 002100 016767 177246 016450  MOV  CSRHPAR   ,HPCRSR   ; PARCSR
1078 002106 016767 177242 016444  MOV  CSRTX     ,TXCSR    ; CSRHPAR
1079 002114 016767 177236 016440  MOV  CSRHTX    ,HTXCSR   ; CSRTX
1080 002122 016767 177232 016434  MOV  BUFTXD    ,TXDBUF   ; CSRHTX
1081 002130 016767 177226 016430  MOV  BUFTXD    ,TXDBUF   ;
1082 002136 000167 000466  ;      JMP  .BEGIN      ; HTXDBUF
1083      ; *****
1084 002142 032777 000001 176730 $67:  BIT  #SW00    ,@SWR    ; RESELECT VECTOR $ CONTROL REG?
1085 002150 001002      ;      BNE  1$      ; BRANCH TO QUESTIONING
1086 002152 000167 000452      ;      JMP  .BEGIN  ; GO TO LOAD STATUS MAP ETC.
1087 002156 005037 001222 1$:  CLR  @#FLAG    ; CLEAR FLAG SO STATUS MAP PRINTS OUT
1088 002162 012700 000300      ;      MOV  #300,R0  ; RESTORE VECTOR AREA TO TRAPCATCHER
1089 002166 012701 000302      ;      MOV  #302,R1  ; START AT LOCATION 300
1090 002172 012702 000004      ;      MOV  #4,R2
1091 002176 010110 2$:  MOV  R1,(R0)
1092 002200 005011      ;      CLR  (R1)
1093 002202 060200      ;      ADD  R2,R0
1094 002204 060201      ;      ADD  R2,R1
1095 002206 022701 001000      ;      CMP  #1000,R1  ; END AT LOCATION 776
1096 002212 002771      ;      BLT  2$
1097 002214 104403      ;      INSTR      ; OUTPUT MESSAGE & GET INPUT STRING
1098 002216 016500      ;      MREGAD     ; MESSAGE
1099 002220 104405      ;      PARAM     ; CONVERT STRING
1100 002222 160000      ;      160000    ; LOW LIMIT
1101 002224 167776      ;      167776    ; HIGH LIMIT
1102 002226 020246      ;      DUBASE    ; STORE AT THIS LOCATION
1103 002230 001      ;      .BYTE 1    ; MASK
1104 002231 001      ;      .BYTE 1    ; HOW MANY TIMES + 2
1105 002232 016767 016010 176746  MOV  DUBASE,KEEPADD ;SAVE

```

```

1106 002240 004767 015650 JSR PC,DUADDR
1107 002244 016767 176736 176732 MOV KEEPADD,BASEADD ;RESTORE FOR ROTATION
1108 002252 104403 INSTR ;OUTPUT MESSAGE & GET INPUT STRING
1109 002254 016456 MVECTO ;MESSAGE
1110 002256 104405 PARAM ;CONVERT STRING
1111 002260 000300 300 ;LOW LIMIT
1112 002262 000776 776 ;HIGH LIMIT
1113 002264 020570 DURIV ;STORE AT THIS LOCATION
1114 002266 001 .BYTE 1 ;MASK
1115 002267 004 .BYTE 4 ;HOW MANY TIMES + 2
1116 002270 016767 016274 176716 MOV DURIV,KEEPIV ;SAVE
1117 002276 016767 016266 176706 MOV DURIV,BASEIV ;SET UP FOR ROTATION
1118 002304 104403 INSTR ;OUTPUT MESSAGE & GET INPUT STRING
1119 002306 016561 MMULT ;MESSAGE
1120 002310 104412 SETFLG ;SET FLAG BASED UPON INPUT STRING
1121 002312 001202 MULTD ;THIS FLAG
1122 002314 105767 176662 TSTB MULTD ;ARE THERE MULTIPLE DEVICES
1123 ;ON THE SYSTEM ?
1124 002320 100406 BMI BBB ;YES,ASK NEXT QUESTION
1125 002322 005067 176670 CLR ACTREG
1126 002326 005067 176666 CLR ROTADD
1127 002332 000167 000140 JMP OUTMUL ;JUMP AROUND NEXT QUESTION
1128 002336 BBB:
1129 002336 104403 INSTR ;OUTPUT MESSAGE & GET INPUT STRING
1130 002340 016640 MLASTD ;MESSAGE
1131 002342 104405 PARAM ;CONVERT STRING
1132 002344 160000 160000 ;LOW LIMIT
1133 002346 167776 167776 ;HIGH LIMIT
1134 002350 001210 LASTADD ;STORE AT THIS LOCATION
1135 002352 001 .BYTE 1 ;MASK
1136 002353 001 .BYTE 1 ;HOW MANY TIMES + 2
1137 ;THE FOLLOWING ROUTINE SETS UP ACTREG FOR THE FIRST TIME
1138 002354 012767 000001 176636 1$: MOV #1,ROTADD ;SET UP POINTER
1139 002362 005067 176630 CLR ACTREG ;CLR ACTIVE REGISTER
1140 002366 056767 176626 176622 2$: BIS ROTADD,ACTREG ;MAKE THIS DEVICE ACTIVE
1141 002374 000241 CLC
1142 002376 006167 176616 ROL ROTADD ;SET UP POINTER
1143 002402 103421 BCS 3$ ;ARE YOU OUT OF RANGE ?
1144 002404 062767 000010 176572 ADD #10,BASEADD ;SET UP BASE ADDRESS
1145 002412 026767 176572 176564 CMP LASTADD,BASEADD ;IS THIS THE LAST DEVICE ?
1146 002420 101362 BHI 2$ ;NO DO IT AGAIN
1147 002422 056767 176572 176566 BIS ROTADD,ACTREG ;THIS ASSUMES THAT THERE ARE AT
1148 ;LEAST TWO DEVICES WHEN YOU ANSWER YES TO
1149 ;MULTIPLE DEVICE QUESTION
1150 002430 012767 000001 176562 4$: MOV #1,ROTADD ;SET UP FOR LATER USE IN END OF PASS ROUTINE
1151 002436 016767 176544 176540 MOV KEEPADD,BASEADD ;DITTO
1152 002444 000414 BR OUTMUL ;CONTINUE QUESTIONS
1153 002446 016767 176534 176530 3$: MOV KEEPADD,BASEADD ;RESTORE
1154 002454 104403 INSTR ;OUTPUT MESSAGE & GET INPUT STRING
1155 002456 017023 MRANGE ;MESSAGE
1156 002460 104405 PARAM ;CONVERT STRING
1157 002462 160000 160000 ;LOW LIMIT
1158 002464 167776 167776 ;HIGH LIMIT
1159 002466 001210 LASTADD ;STORE AT THIS LOCATION
1160 002470 001 .BYTE 1 ;MASK
1161 002471 001 .BYTE 1 ;HOW MANY TIMES + 2

```

```

1162 002472 000167 177656          JMP      1$      ;DO IT AGAIN
1163 002476                                OUTMUL:
1164 002476 104403                    INSTR
1165 002500 017307                    MLEVEL        ;OUTPUT MESSAGE & GET INPUT STRING
1166 002502 104405                    PARAM          ;MESSAGE
1167 002504 000004                    4             ;CONVERT STRING
1168 002506 000007                    7             ;LOW LIMIT
1169 002510 020110                    DUPRT         ;HIGH LIMIT
1170 002512      000                    0             ;STORE AT THIS LOCATION
1171 002513      001                    .BYTE        ;MASK
1172 002514 004767 015320            .BYTE        ;HOW MANY TIMES + 2
1173                                JSR      PC,DULEV
1174                                ;COMPARE THE FIRST CHARACTER IN THE TELETYPE INPUT
1175                                ;BUFFER TO THE CHARACTERS '1' AND '2'
1176                                ;IF THE CHARACTER IS '1' CLEAR THE FLAG
1177                                ;IF THE CHARACTER IS '2' SET THE FLAG
1177 002520                                AAA:
1178 002520 104403                    INSTR
1179 002522 017334                    MSYNC
1180 002524 122767 000061 015146    3$:      CMPB     #'1,INBUF ;OUTPUT MESSAGE & GET INPUT STRING
1181 002532 001003                    BNE      1$      ;MESSAGE
1182 002534 105067 176436                    CLRB     SYNCNO ;IS IT '1' ?
1183 002540 000412                    BR       4$      ;000
1184 002542 122767 000062 015130    1$:      CMPB     #'2,INBUF ;IS IT '2' ?
1185 002550 001004                    BNE      2$
1186 002552 112767 177777 176416    MOVB     #-1,SYNCNO ;377
1187 002560 000402                    BR       4$
1188 002562 104404                    2$:      INSTER
1189 002564 000757                    BR       3$      ;RETRY
1190 002566 000240                    4$:      NOP
1191 002570 104403                    INSTR
1192 002572 017402                    MWIRE6
1193 002574 104412                    SETFLG
1194 002576 001177                    SEXMIT
1195 002600 104403                    INSTR
1196 002602 017450                    MWIRE5
1197 002604 104412                    SETFLG
1198 002606 001200                    SEREC
1199 002610 104403                    INSTR
1200 002612 017515                    MWIRE4
1201 002614 104412                    SETFLG
1202 002616 001201                    OPTCLR
1203 002620 104403                    INSTR
1204 002622 017571                    MEXTJ
1205 002624 104412                    SETFLG
1206 002626 001203                    JMRBY
1207
1208
1209                                ;TEST START AND RESTART
1210
1211 002630 012767 000340 175140    .BEGIN: MOV     #340,PS ;LOCK OUT INTERRUPTS
1212                                ; ***** LOAD STATUS MAP *****
1213                                ;THE VALUES NOW BEING LOADED INTO THE STATUS MAP WILL BE
1214                                ; USED IN THIS PROGRAM AND WILL BE PASSED TO ANY
1215                                ;OTHER DU11 PROGRAMS LOADED IMMEDIATELY FOLLOWING THIS PROG.
1216 002636 032777 000200 176234    BIT     #SW07 ;@SWR ; SW07 SET , IF YES BRANCH
1217 002644 001132                    BNE     HEREU
  
```

1218	002646	116767	176324	176424
1219	002654	116767	176317	176417
1220	002662	116767	176312	176412
1221	002670	116767	176305	176405
1222	002676	116767	176300	176400
1223	002704	116767	176273	176373
1224	002712	016767	176266	176366
1225	002720	016767	176262	176362
1226	002726	016767	176256	176356
1227	002734	016767	176254	176354
1228	002742	016767	176244	176344
1229	002750	016767	176242	176342
1230	002756	016767	176236	176336
1231	002764	013737	020110	001324
1232	002772	016767	015572	176326
1233	003000	016767	015566	176326
1234	003006	016767	015562	176314
1235	003014	016767	015556	176310
1236	003022	016767	015064	176306
1237	003030	016767	015212	176326
1238	003036	016767	015502	176274
1239	003044	016767	015476	176270
1240	003052	016767	015472	176264
1241	003060	016767	015466	176260
1242	003066	016767	015462	176254
1243	003074	016767	015456	176250
1244	003102	016767	015452	176244
1245	003110	016767	015446	176240
1246	003116	016767	015442	176234
1247	003124	016767	015436	176230
1248				
1249				
1250				
1251				
1252				
1253				
1254				
1255				
1256				
1257				
1258	003132	005737	001222	
1259	003136	001402		
1260	003140	000167	000116	
1261	003144	104402	017646	
1262	003150	062737	000001	001222
1263	003156	010067	176042	
1264	003162	010167	176040	
1265	003166	012767	000003	176034
1266	003174	012700	000002	
1267	003200	012701	001300	
1268	003204	010120		
1269	003206	062701	000002	
1270	003212	020127	001306	
1271	003216	001372		
1272	003220	012700	000002	
1273	003224	010067	176006	

```

MOV B SYNCNO      ,NOSYNC      ; SYNC CHARS
MOV B SEXMIT      ,MITSEX      ; XMIT JUMPER
MOV B SEREC       ,RESEC       ; SEC REC JUMPER
MOV B OPTCLR      ,CLROPT      ; OPTIONAL JUMPER
MOV B MULTD       ,DMULT       ; MULTIPLE DEVICES
MOV B JMRBY       ,BYJMR       ; EXTERNAL MODEM
MOV BASEADD       ,ADDBASE     ; PROG CONTROLLED 1ST ADDR
MOV KEEPADD       ,ADDKEEP     ; SAVED 1ST DEVICE ADDR
MOV LASTADD       ,ADDLAST     ; LAST DEVICE RXCSR ADDR
MOV KEEPIV        ,IVKEEP     ; SAVED INTR VECTOR
MOV BASEIV        ,IVBASE     ; RELOAD BASE INTR VECTOR
MOV ACTREG        ,REGACT     ; ACTIVE REGISTER
MOV ROTADD        ,ADDRROT     ; ROTATING POINTER
MOV @#DUPRT       ,@#PRTDU    ; DU11 PRIORITY
MOV DURIV         ,RIVDU      ; REC INTR VECTOR
MOV DURIS         ,RISDU      ; REC INTR STATUS
MOV DUTIV         ,TIVDU      ; XMIT INTR VECTOR
MOV DUTIS         ,TISDU      ; XMIT INTR STATUS
MOV LESS1         ,L1ESS      ; PRIORITY TO ALLOW INTR
MOV DUBASE        ,BASEDU     ; RXCSR BASE ADDRESS
MOV RXCSR         ,CSRRX
MOV HRXCSR        ,CSRHRX
MOV RXDBUF        ,BUFRXD
MOV HRXDBUF       ,BUFHRXD
MOV PARCSR        ,CSRPAR
MOV HPARCSR       ,CSRHPAR
MOV TXCSR         ,CSRTX
MOV HTXCSR        ,CSRHTX
MOV TXDBUF        ,BUFTXD
MOV HTXDBUF       ,BUFHTXD
;*****
; THE FOLLOWING CODE WILL PRINT
; THE CONVERSATIONALLY SET JUMPER
; SETTINGS FROM THE STATUS MAP
; ON THE FIRST PASS OF
; THIS DIAGNOSTIC OR
; JUST AFTER THE QUESTIONING
; AND ANSWERING .
;*****
HEREU:          TST @#FLAG      ; TEST IF 1ST PASS
                BEQ SETFG      ; IF FIRST PASS SET FLAG/PRINT
                JMP THRU
SETFG:          TYPE MSTATUS    ; AROUND IF PASS > 1
                ADD #1, @#FLAG  ; PRINT 'STATUS MAP'
                MOV R0, HOLD0   ; SET FLAG ON 1ST PASS
                MOV R1, HOLD1   ; SAVE R0
                MOV #3, COUNT1  ; SAVE R1
                MOV #BUFF1, R0  ; COUNTER FOR WORDS PRINTED
                MOV #STATUS, R1 ; (BUFF1)=STATUS ETC.
FILBUF:        MOV R1, (R0)+    ; LOAD BUFF AS ABOVE
                ADD #2, R1      ; PREPARE STATUS ADDRESS
                CMP R1, #STATUS+6 ; CHECK IF 3 WORDS LOADED
                BNE FILBUF      ; BACK TO LOAD NEXT ADDRESS
                MOV #BUFF1, R0  ; LOAD FOR PRINT OUT
UP:            MOV R0, TABLE+4 ; LOAD ADDRESS TO PRINT
  
```

```

1274 003230 012067 176006      MOV (R0)+, TABLE+10      ; LOAD CONTENTS
1275 003234 104410 001232      CONVRT , TABLE          ; PRINT ADDRESS/CONTENTS PAIR
1276 003240 104402 017110      TYPE, MCRLF              ; CR AND LF
1277 003244 005367 175760      DEC COUNT1              ; COUNT WORDS PRINTED
1278 003250 001365              BNE UP                   ; GO PRINT NEXT ADDRESS/CONTENTS
1279 003252 016700 175746      MOV HOLD0,R0
1280 003256 016701 175744      MOV HOLD1, R1
1281
1282      ;*****
1283 003262 012706 001100      THRU: MOV #STACK,SP      ;SET UP STACK
1284 003266 005737 000042      TST @#42                ;IS PROGRAM UNDER MONITOR CONTROL
1285 003272 001056              BNE 3$
1286 003274 105767 175702      TSTB MULTD ;DON'T ALLOW LOCK ON TEST IF RUNNING
1287      ;MULTIPLE DEVICES
1288 003300 001407              BEQ 5$                  ;IF NO,TEST FOR LOCK ON TEST
1289 003302 016767 011240 011140  MOV BRW,TTST            ;RESTORE NORMAL SCOPE LOOP
1290 003310 016767 011234 011134  MOV BRX,TTST+2         ;DITTO
1291 003316 000444              BR 3$                   ;JUMP AROUND IF YES
1292 003320 032777 000004 175552 5$: BIT #BIT2,@SWR         ;CHECK FOR LOCK ON TEST
1293 003326 001416              BEQ 1$
1294 003330 104403              INSTR                  ;OUTPUT MESSAGE & GET INPUT STRING
1295 003332 017244              MLOCK                  ;MESSAGE
1296 003334 104412              SETFLG                 ;SET FLAG BASED UPON INPUT STRING
1297 003336 001247              LOKFLG                 ;THIS FLAG
1298 003340 105767 175703      TSTB LOKFLG            ;IS LOCK ON TEST OPTION SELECTED
1299 003344 001407              BEQ 1$
1300 003346 012767 000240 011074  MOV #NOP,TTST
1301 003354 012767 000240 011070  MOV #NOP,TTST+2        ;SET UP TO LOCK
1302 003362 000406              BR 2$
1303 003364 016767 011156 011056 1$: MOV BRW,TTST
1304 003372 016767 011152 011052  MOV BRX,TTST+2        ;LOCK NOT SELECTED, SET UP FOR NORMAL SCOPE LOOP
1305 003400 032777 000002 175472 2$: BIT #SW01,@SWR        ;IF SW01=1, GET STARTING PC
1306 003406 001410              BEQ 3$
1307 003410 104403              INSTR                  ;OUTPUT MESSAGE & GET INPUT STRING
1308 003412 017231              MTSTPC                 ;MESSAGE
1309 003414 104405              PARAM                  ;CONVERT STRING
1310 003416 003446              TST1                   ;LOW LIMIT
1311 003420 013610              TLAST                  ;HIGH LIMIT
1312 003422 001114              RTRN                   ;STORE AT THIS LOCATION
1313 003424 001          .BYTE 1                  ;MASK
1314 003425 001          .BYTE 1                  ;HOW MANY TIMES + 2
1315 003426 000403              BR 4$
1316 003430 012767 003446 175456 3$: MOV #TST1,RTRN          ;START AT TEST 1
1317 003436 104402 017225 4$: TYPE ,MR                ;TYPE R
1318 003442 000177 175446      JMP @RTRN              ;START TESTING
1319
1320      ;;THIS TEST VERIFYS WORD LENGTH SELECT OF THE
1321      ;;RECEIVER SECTION,IT USES THE ERROR FLAGS
1322      ;;TO DETERMINE THAT IT WAS SELECTED CORRECTLY
1323      ;;(OVRUN,RXERR)
1324      ;;MODE:ISYMOD
1325      ;;LENGTH:SIX
1326      ;;CHAR:25
1327
1328 003446 012767 000001 175452 TST1: MOV #?,TSTNO          ;SAVE THIS
1329 003454 012767 003710 175434  MOV #TST2,NEXT        ;GO TO THIS TEST WHEN THRU

```

```

1330 003462 052777 000400 015070      BIS      #MRESET,@TXCSR ;MASTER RESET
1331 003470 012777 000000 015056      MOV      #ISYMOD,@PARCSR ;SET THE MODE
1332 003476 052777 000400 015054      BIS      #MRESET,@TXCSR ;MASTER RESET
1333
1334                                     ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
1335 003504 012777 064001 015046      MOV      #MTDATA!CLK!MINT!BREAK,@TXCSR
1336
1337                                     ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
1338 003512 012777 002000 015034      MOV      #ISYMOD!SIX!NOPAR!0,@PARCSR
1339 003520 052777 000020 015016      BIS      #SYNSCH,@RXCSR ;SET SYNC SEARCH
1340                                     ;POKE CLK TO GET RECEIVER INTO SYNCROIZATION....
1341 003526 042777 020000 015024      BIC      #CLK,@TXCSR ;POKE CLK DOWN
1342 003534 052777 020000 015016      BIS      #CLK,@TXCSR ;POKE CLK UP
1343                                     ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
1344 003542 042777 020000 015010      BIC      #CLK,@TXCSR ;POKE CLK DOWN
1345 003550 052777 020000 015002      BIS      #CLK,@TXCSR ;PCKE CLK UP
1346 003556 016703 014766      MOV      RXDBUF,R3 ;SET UP FOR ERROR MESSAGE
1347 003562 012700 000025      MOV      #25,R0 ;EXPECTED
1348 003566 012767 000010 175344      MOV      #8,SHIFT ;# OF SHIFTS
1349 003574 012767 000252 175342      MOV      #252,TEMP1 ;DATA CHAR
1350 003602 004767 014442      JSR      PC,RPOKE ;SHIFT IN THIS CHAR
1351 003606 105777 014732      TSTB    @RXCSR ;RXDONE ?
1352 003612 100401      BMI     64$
1353 003614 104000      HLT
1354 003616                                     64$:
1355 003616 017701 014726      MOV      @RXDBUF,R1 ;ACTUAL
1356 003622 020001      CMP      R0,R1 ;COMPARE EXPECTED VS. ACTUAL
1357 003624 001401      BEQ     65$
1358 003626 104002      HLT      2 ;RECEIVED DATA DID NOT MATCH
1359                                     ;EXPECTED DATA - CHECK MAINT DATA
1360                                     ;OR RECEIVER LOGIC
1361 003630                                     65$:
1362 003630 012767 000010 175302      MOV      #8,SHIFT ;# OF SHIFTS
1363 003636 012767 000252 175300      MOV      #252,TEMP1 ;DATA CHAR
1364 003644 004767 014400      JSR      PC,RPOKE ;SHIFT IN THIS CHAR
1365                                     ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
1366 003650 012767 000010 175262      MOV      #8,SHIFT ;# OF SHIFTS
1367 003656 012767 000252 175260      MOV      #252,TEMP1 ;DATA CHAR
1368 003664 004767 014360      JSR      PC,RPOKE ;SHIFT IN THIS CHAR
1369 003670 012700 140025      MOV      #140000!25,R0 ;EXPECTED DATA PLUS
1370                                     ;RXERR & OVRRUN
1371 003674 017701 014650      MOV      @RXDBUF,R1 ;ACTUAL
1372 003700 020001      CMP      R0,R1 ;COMPARE EXP VS. ACT
1373 003702 001401      BEQ     66$
1374 003704 104002      HLT      2 ;SPECIFICALLY LOOK AT RXERR &
1375                                     ;OVRRUN BITS...THEY BOTH SHOULD BE SET
1376 003706                                     66$:
1377 003706 104400      SCOPE
1378      ;;THIS TEST VERIFYS WORD LENGTH SELECT OF THE
1379      ;;RECEIVER SECTION,IT USES THE ERROR FLAGS
1380      ;;TO DETERMINE THAT IT WAS SELECTED CORRECTLY
1381      ;;(OVRRUN,RXERR)
1382      ;;MODE:ISYMOD
1383      ;;LENGTH:SIX
1384      ;;CHAR:52
1385      ;;
  
```

```

1386 003710 012767 000002 175210 TST2: MOV #2,TSTNO ;SAVE THIS
1387 003716 012767 004152 175172 MOV #TST3,NEXT ;GO TO THIS TEST WHEN THRU
1388 003724 052777 000400 014626 BIS #MRESET,@TXCSR ;MASTER RESET
1389 003732 012777 000000 014614 MOV #ISYMOD,@PARCSR ;SET THE MODE
1390 003740 052777 000400 014612 BIS #MRESET,@TXCSR ;MASTER RESET
1391
1392 ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
1393 003746 012777 064001 014604 MOV #MTDATA!CLK!MINT!BREAK,@TXCSR
1394
1395 ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
1396 003754 012777 002000 014572 MOV #ISYMOD!SIX!NOPAR!0,@PARCSR
1397 003762 052777 000020 014554 BIS #SYNSCH,@RXCSR ;SET SYNC SEARCH
1398 ;POKE CLK TO GET RECEIVER INTO SYNCROIZATION....
1399 003770 042777 020000 014562 BIC #CLK,@TXCSR ;POKE CLK DOWN
1400 003776 052777 020000 014554 BIS #CLK,@TXCSR ;POKE CLK UP
1401 ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
1402 004004 042777 020000 014546 BIC #CLK,@TXCSR ;POKE CLK DOWN
1403 004012 052777 020000 014540 BIS #CLK,@TXCSR ;POKE CLK UP
1404 004020 016703 014524 MOV RXDBUF,R3 ;SET UP FOR ERROR MESSAGE
1405 004024 012700 000052 MOV #52,R0 ;EXPECTED
1406 004030 012767 000010 175102 MOV #8,,SHIFT ;# OF SHIFTS
1407 004036 012767 000324 175100 MOV #324,TEMP1 ;DATA CHAR
1408 004044 004767 014200 JSR PC,RPOKE ;SHIFT IN THIS CHAR
1409 004050 105777 014470 TSTB @RXCSR ;RXDONE ?
1410 004054 100401 BMI 64$
1411 004056 104000 HLT ;RXDONE SHOULD BE SET
1412 004060
1413 004060 017701 014464 64$: MOV @RXDBUF,R1 ;ACTUAL
1414 004064 020001 CMP R0,R1 ;COMPARE EXPECTED VS. ACTUAL
1415 004066 001401 BEQ 65$
1416 004070 104002 HLT 2 ;RECEIVED DATA DID NOT MATCH
1417 ;EXPECTED DATA - CHECK MAINT DATA
1418 ;OR RECEIVER LOGIC
1419 004072
1420 004072 012767 000010 175040 65$: MOV #8,,SHIFT ;# OF SHIFTS
1421 004100 012767 000324 175036 MOV #324,TEMP1 ;DATA CHAR
1422 004106 004767 014136 JSR PC,RPOKE ;SHIFT IN THIS CHAR
1423 ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
1424 004112 012767 000010 175020 MOV #8,,SHIFT ;# OF SHIFTS
1425 004120 012767 000324 175016 MOV #324,TEMP1 ;DATA CHAR
1426 004126 004767 014116 JSR PC,RPOKE ;SHIFT IN THIS CHAR
1427 004132 012700 140052 MOV #140000!52,R0 ;EXPECTED DATA PLUS
1428 ;RXERR & OVRRUN
1429 004136 017701 014406 MOV @RXDBUF,R1 ;ACTUAL
1430 004142 020001 CMP R0,R1 ;COMPARE EXP VS. ACT
1431 004144 001401 BEQ 66$
1432 004146 104002 HLT 2 ;SPECIFICALLY LOOK AT RXERR &
1433 ;OVRRUN BITS...THEY BOTH SHOULD BE SET
1434 004150
1435 004150 104400 66$: SCOPE
1436 ;:THIS TEST VERIFYS WORD LENGTH SELECT OF THE
1437 ;:RECEIVER SECTION,IT USES THE ERROR FLAGS
1438 ;:TO DETERMINE THAT IT WAS SELECTED CORRECTLY
1439 ;:(OVRRUN,RXERR)
1440 ;:MODE:IS:MOD
1441 ;:LENGTH:SIX

```

```

1442      ::CHAR:77
1443      ::
1444 004152 012767 000003 174746 TST3:  MOV    #3,TSTNO      ;SAVE THIS
1445 004160 012767 004414 174730      MOV    #TST4,NEXT    ;GO TO THIS TEST WHEN THRU
1446 004166 052777 000400 014364      BIS    #MRESET,@TXCSR ;MASTER RESET
1447 004174 012777 000000 014352      MOV    #ISYMOD,@PARCSR ;SET THE MODE
1448 004202 052777 000400 014350      BIS    #MRESET,@TXCSR ;MASTER RESET
1449
1450      ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
1451 004210 012777 064001 014342      MOV    #MTDATA!CLK!MINT!BREAK,@TXCSR
1452
1453      ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
1454 004216 012777 002000 014330      MOV    #ISYMOD!SIX!NOPAR!0,@PARCSR
1455 004224 052777 000020 014312      BIS    #SYNSCH,@RXCSR  ;SET SYNC SEARCH
1456      ;POKE CLK TO GET RECEIVER INTO SYNCROIZATION....
1457 004232 042777 020000 014320      BIC    #CLK,@TXCSR    ;POKE CLK DOWN
1458 004240 052777 020000 014312      BIS    #CLK,@TXCSR    ;POKE CLK UP
1459      ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
1460 004246 042777 020000 014304      BIC    #CLK,@TXCSR    ;POKE CLK DOWN
1461 004254 052777 020000 014276      BIS    #CLK,@TXCSR    ;POKE CLK UP
1462 004262 016703 014262      MOV    RXDBUF,R3      ;SET UP FOR ERROR MESSAGE
1463 004266 012700 000077      MOV    #77,R0         ;EXPECTED
1464 004272 012767 000010 174640      MOV    #8,,SHIFT      ;# OF SHIFTS
1465 004300 012767 000376 174636      MOV    #376,TEMP1     ;DATA CHAR
1466 004306 004767 013736      JSR    PC,RPOKE       ;SHIFT IN THIS CHAR
1467 004312 105777 014226      TSTB   @RXCSR ;RXDONE ?
1468 004316 100401      BMI    64$
1469 004320 104000      HLT    ;RXDONE SHOULD BE SET
1470
1471 004322 017701 014222      64$:  MOV    @RXDBUF,R1      ;ACTUAL
1472 004326 020001      CMP    R0,R1          ;COMPARE EXPECTED VS. ACTUAL
1473 004330 001401      BEQ   65$
1474 004332 104002      HLT    2              ;RECEIVED DATA DID NOT MATCH
1475      ;EXPECTED DATA - CHECK MAINT DATA
1476      ;OR RECEIVER LOGIC
1477
1478 004334 012767 000010 174576      65$:  MOV    #8,,SHIFT      ;# OF SHIFTS
1479 004342 012767 000376 174574      MOV    #376,TEMP1     ;DATA CHAR
1480 004350 004767 013674      JSR    PC,RPOKE       ;SHIFT IN THIS CHAR
1481      ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
1482 004354 012767 000010 174556      MOV    #8,,SHIFT      ;# OF SHIFTS
1483 004362 012767 000376 174554      MOV    #376,TEMP1     ;DATA CHAR
1484 004370 004767 013654      JSR    PC,RPOKE       ;SHIFT IN THIS CHAR
1485 004374 012700 140077      MOV    #140000!77,R0  ;EXPECTED DATA PLUS
1486      ;RXERR & OVRUN
1487 004400 017701 014144      MOV    @RXDBUF,R1      ;ACTUAL
1488 004404 020001      CMP    R0,R1          ;COMPARE EXP VS. ACT
1489 004406 001401      BEQ   66$
1490 004410 104002      HLT    2              ;SPECIFICALLY LOOK AT RXERR &
1491      ;OVRUN BITS...THEY BOTH SHOULD BE SET
1492
1493 004412 104400      66$:  SCOPE
1494      ;:THIS TEST VERIFYS WORD LENGTH SELECT OF THE
1495      ;:RECEIVER SECTION,IT USES THE ERROR FLAGS
1496      ;:TO DETERMINE THAT IT WAS SELECTED CORRECTLY
1497      ;:(OVRUN,RXERR)

```

```

1498      ::MODE:ISYMOD
1499      ::LENGTH:SIX
1500      ::CHAR:0
1501      ::
1502 004414 012767 000004 174504 TST4:  MOV    #4,TSTNO      ;SAVE THIS
1503 004422 012767 004656 174466      MOV    #TST5,NEXT      ;GO TO THIS TEST WHEN THRU
1504 004430 052777 000400 014122      BIS    #MRESET,@TXCSR ;MASTER RESET
1505 004436 012777 000000 014110      MOV    #ISYMOD,@PARCSR ;SET THE MODE
1506 004444 052777 000400 014106      BIS    #MRESET,@TXCSR ;MASTER RESET
1507
1508      ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
1509 004452 012777 064001 014100      MOV    #MTDATA!CLK!MINT!BREAK,@TXCSR
1510
1511      ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
1512 004460 012777 002000 014066      MOV    #ISYMOD!SIX!NOPAR!0,@PARCSR
1513 004466 052777 000020 014050      BIS    #SYNSCH,@RXCSR ;SET SYNC SEARCH
1514      ;POKE CLK TO GET RECEIVER INTO SYNCROIZATION....
1515 004474 042777 020000 014056      BIC    #CLK,@TXCSR    ;POKE CLK DOWN
1516 004502 052777 020000 014050      BIS    #CLK,@TXCSR    ;POKE CLK UP
1517      ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
1518 004510 042777 020000 014042      BIC    #CLK,@TXCSR    ;POKE CLK DOWN
1519 004516 052777 020000 014034      BIS    #CLK,@TXCSR    ;POKE CLK UP
1520 004524 016703 014020      MOV    RXDBUF,R3      ;SET UP FOR ERROR MESSAGE
1521 004530 012700 000000      MOV    #0,R0          ;EXPECTED
1522 004534 012767 000010 174376      MOV    #8,,SHIFT      ;# OF SHIFTS
1523 004542 012767 000200 174374      MOV    #200,TEMP1     ;DATA CHAR
1524 004550 004767 013474      JSR    PC,RPOKE       ;SHIFT IN THIS CHAR
1525 004554 105777 013764      TSTB   @RXCSR ;RXDONE ?
1526 004560 100401      BMI    64$
1527 004562 104000      HLT    ;RXDONE SHOULD BE SET
1528 004564
1529 004564 017701 013760 64$:   MOV    @RXDBUF,R1     ;ACTUAL
1530 004570 020001      CMP    R0,R1          ;COMPARE EXPECTED VS. ACTUAL
1531 004572 001401      BEQ   65$
1532 004574 104002      HLT    2              ;RECEIVED DATA DID NOT MATCH
1533      ;EXPECTED DATA - CHECK MAINT DATA
1534      ;OR RECEIVER LOGIC
1535 004576
1536 004576 012767 000010 174334 65$:   MOV    #8,,SHIFT      ;# OF SHIFTS
1537 004604 012767 000200 174332      MOV    #200,TEMP1     ;DATA CHAR
1538 004612 004767 013432      JSR    PC,RPOKE       ;SHIFT IN THIS CHAR
1539      ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
1540 004616 012767 000010 174314      MOV    #8,,SHIFT      ;# OF SHIFTS
1541 004624 012767 000200 174312      MOV    #200,TEMP1     ;DATA CHAR
1542 004632 004767 013412      JSR    PC,RPOKE       ;SHIFT IN THIS CHAR
1543 004636 012700 140000      MOV    #140000!0,R0   ;EXPECTED DATA PLUS
1544      ;RXERR & OVRRUN
1545 004642 017701 013702      MOV    @RXDBUF,R1     ;ACTUAL
1546 004646 020001      CMP    R0,R1          ;COMPARE EXP VS. ACT
1547 004650 001401      BEQ   66$
1548 004652 104002      HLT    2              ;SPECIFICALLY LOOK AT RXERR &
1549      ;OVRRUN BITS...THEY BOTH SHOULD BE SET
1550 004654
1551 004654 104400 66$:   SCOPE
1552      ;:THIS TEST VERIFYS WORD LENGTH SELECT OF THE
1553      ;:RECEIVER SECTION,IT USES THE ERROR FLAGS

```

```

1554      ::TO DETERMINE THAT IT WAS SELECTED CORRECTLY
1555      ::(OVRUN,RXERR)
1556      ::MODE:ISYMOD
1557      ::LENGTH:SEVEN
1558      ::CHAR:125
1559      ::
1560 004656 012767 000005 174242 TST5:  MOV    #5,TSTNO      ;SAVE THIS
1561 004664 012767 005120 174224      MOV    #TST6,NEXT    ;GO TO THIS TEST WHEN THRU
1562 004672 052777 000400 013660      BIS    #MRESET,@TXCSR ;MASTER RESET
1563 004700 012777 000000 013646      MOV    #ISYMOD,@PARCSR ;SET THE MODE
1564 004706 052777 000400 013644      BIS    #MRESET,@TXCSR ;MASTER RESET
1565
1566      ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
1567 004714 012777 064001 013636      MOV    #MTDATA!CLK!MINT!BREAK,@TXCSR
1568
1569      ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
1570 004722 012777 004000 013624      MOV    #ISYMOD!SEVEN!NOPAR!0,@PARCSR
1571 004730 052777 000020 013606      BIS    #SYNSCH,@RXCSR ;SET SYNC SEARCH
1572      ;POKE CLK TO GET RECEIVER INTO SYNCROIZATION....
1573 004736 042777 020000 013614      BIC    #CLK,@TXCSR    ;POKE CLK DOWN
1574 004744 052777 020000 013606      BIS    #CLK,@TXCSR    ;POKE CLK UP
1575      ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
1576 004752 042777 020000 013600      BIC    #CLK,@TXCSR    ;POKE CLK DOWN
1577 004760 052777 020000 013572      BIS    #CLK,@TXCSR    ;POKE CLK UP
1578 004766 016703 013556      MOV    RXDBUF,R3      ;SET UP FOR ERROR MESSAGE
1579 004772 012700 000125      MOV    #125,R0 ;EXPECTED
1580 004776 012767 000011 174134      MOV    #9,SHIFT      ;# OF SHIFTS
1581 005004 012767 000652 174132      MOV    #652,TEMP1    ;DATA CHAR
1582 005012 004767 013232      JSR    PC,RPOKE      ;SHIFT IN THIS CHAR
1583 005016 105777 013522      TSTB   @RXCSR ;RXDONE ?
1584 005022 100401      BMI    64$
1585 005024 104000      HLT    ;RXDONE SHOULD BE SET
1586 005026
1587 005026 017701 013516      64$:  MOV    @RXDBUF,R1    ;ACTUAL
1588 005032 020001      CMP    R0,R1 ;COMPARE EXPECTED VS. ACTUAL
1589 005034 001401      BEQ   65$
1590 005036 104002      HLT    2 ;RECEIVED DATA DID NOT MATCH
1591      ;EXPECTED DATA - CHECK MAINT DATA
1592      ;OR RECEIVER LOGIC
1593 005040
1594 005040 012767 000011 174072      65$:  MOV    #9,SHIFT      ;# OF SHIFTS
1595 005046 012767 000652 174070      MOV    #652,TEMP1    ;DATA CHAR
1596 005054 004767 013170      JSR    PC,RPOKE      ;SHIFT IN THIS CHAR
1597      ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
1598 005060 012767 000011 174052      MOV    #9,SHIFT      ;# OF SHIFTS
1599 005066 012767 000652 174050      MOV    #652,TEMP1    ;DATA CHAR
1600 005074 004767 013150      JSR    PC,RPOKE      ;SHIFT IN THIS CHAR
1601 005100 012700 140125      MOV    #140000!125,R0 ;EXPECTED DATA PLUS
1602      ;RXERR & OVRUN
1603 005104 017701 013440      MOV    @RXDBUF,R1    ;ACTUAL
1604 005110 020001      CMP    R0,R1 ;COMPARE EXP VS. ACT
1605 005112 001401      BEQ   66$
1606 005114 104002      HLT    2 ;SPECIFICALLY LOOK AT RXERR &
1607      ;OVRUN BITS...THEY BOTH SHOULD BE SET
1608 005116
1609 005116 104400      66$:  SCOPE
  
```

```

1610                                     ::THIS TEST VERIFYS WORD LENGTH SELECT OF THE
1611                                     ::RECEIVER SECTION,IT USES THE ERROR FLAGS
1612                                     ::TO DETERMINE THAT IT WAS SELECTED CORRECTLY
1613                                     ::(OVRRUN,RXERR)
1614                                     ::MODE:ISYMOD
1615                                     ::LENGTH:SEVEN
1616                                     ::CHAR:52
1617                                     ::
1618 005120 012767 000006 174000 TST6:  MOV    #6,TSTNO      ;SAVE THIS
1619 005126 012767 005362 173762      MOV    #TST7,NEXT    ;GO TO THIS TEST WHEN THRU
1620 005134 052777 000400 013416      BIS    #MRESET,@TXCSR ;MASTER RESET
1621 005142 012777 000000 013404      MOV    #ISYMOD,@PARCSR ;SET THE MODE
1622 005150 052777 000400 013402      BIS    #MRESET,@TXCSR ;MASTER RESET
1623
1624                                     ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
1625 005156 012777 064001 013374      MOV    #MTDATA!CLK!MINT!BREAK,@TXCSR
1626
1627                                     ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
1628 005164 012777 004000 013362      MOV    #ISYMOD!SEVEN!NOPAR!0,@PARCSR
1629 005172 052777 000020 013344      BIS    #SYNSCH,@RXCSR  ;SET SYNC SEARCH
1630                                     ;POKE CLK TO GET RECEIVER INTO SYNCROIZATION....
1631 005200 042777 020000 013352      BIC    #CLK,@TXCSR    ;POKE CLK DOWN
1632 005206 052777 020000 013344      BIS    #CLK,@TXCSR    ;POKE CLK UP
1633                                     ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
1634 005214 042777 020000 013336      BIC    #CLK,@TXCSR    ;POKE CLK DOWN
1635 005222 052777 020000 013330      BIS    #CLK,@TXCSR    ;POKE CLK UP
1636 005230 016703 013314                MOV    RXDBUF,R3      ;SET UP FOR ERROR MESSAGE
1637 005234 012700 000052                MOV    #52,R0        ;EXPECTED
1638 005240 012767 000011 173672      MOV    #9,SHIFT      ;# OF SHIFTS
1639 005246 012767 000524 173670      MOV    #524,TEMP1    ;DATA CHAR
1640 005254 004767 012770                JSR    PC,RPOKE      ;SHIFT IN THIS CHAR
1641 005260 105777 013260                TSTB   @RXCSR ;RXDONE ?
1642 005264 100401                BMI    64$
1643 005266 104000                HLT    ;RXDONE SHOULD BE SET
1644 005270
1645 005270 017701 013254      64$:  MOV    @RXDBUF,R1    ;ACTUAL
1646 005274 020001                CMP    R0,R1        ;COMPARE EXPECTED VS. ACTUAL
1647 005276 001401                BEQ   65$
1648 005300 104002                HLT    2            ;RECEIVED DATA DID NOT MATCH
1649                                     ;EXPECTED DATA - CHECK MAINT DATA
1650                                     ;OR RECE!VER LOGIC
1651 005302
1652 005302 012767 000011 173630      65$:  MOV    #9,SHIFT      ;# OF SHIFTS
1653 005310 012767 000524 173626      MOV    #524,TEMP1    ;DATA CHAR
1654 005316 004767 012726                JSR    PC,RPOKE      ;SHIFT IN THIS CHAR
1655                                     ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
1656 005322 012767 000011 173610      MOV    #9,SHIFT      ;# OF SHIFTS
1657 005330 012767 000524 173606      MOV    #524,TEMP1    ;DATA CHAR
1658 005336 004767 012706                JSR    PC,RPOKE      ;SHIFT IN THIS CHAR
1659 005342 012700 140052                MOV    #140000!52,R0 ;EXPECTED DATA PLUS
1660                                     ;RXERR & OVRRUN
1661 005346 017701 013176      MOV    @RXDBUF,R1    ;ACTUAL
1662 005352 020001                CMP    R0,R1        ;COMPARE EXP VS. ACT
1663 005354 001401                BEQ   66$
1664 005356 104002                HLT    2            ;SPECIFICALLY LOOK AT RXERR &
1665                                     ;OVRRUN BITS...THEY BOTH SHOULD BE SET

```

```

1666 005360
1667 005360 104400
1668
1669
1670
1671
1672
1673
1674
1675
1676 005362 012767 000007 173536 TST7: MOV #7,TSTNO ;SAVE THIS
1677 005370 012767 005624 173520 MOV #TST8,NEXT ;GO TO THIS TEST WHEN THRU
1678 005376 052777 000400 013154 BIS #MRESET,@TXCSR ;MASTER RESET
1679 005404 012777 000000 013142 MOV #ISYMOD,@PARCSR ;SET THE MODE
1680 005412 052777 000400 013140 BIS #MRESET,@TXCSR ;MASTER RESET
1681
1682 ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
1683 005420 012777 064001 013132 MOV #MTDATA!CLK!MINT!BREAK,@TXCSR
1684
1685 ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
1686 005426 012777 004000 013120 MOV #ISYMOD!SEVEN!NOPAR!0,@PARCSR
1687 005434 052777 000020 013102 BIS #SYNSCH,@RXCSR ;SET SYNC SEARCH
1688 ;POKE CLK TO GET RECEIVER INTO SYNCROIZATION....
1689 005442 042777 020000 013110 BIC #CLK,@TXCSR ;POKE CLK DOWN
1690 005450 052777 020000 013102 BIS #CLK,@TXCSR ;POKE CLK UP
1691
1692 ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
1693 005456 042777 020000 013074 BIC #CLK,@TXCSR ;POKE CLK DOWN
1694 005464 052777 020000 013066 BIS #CLK,@TXCSR ;POKE CLK UP
1695 005472 016703 013052 MOV RXDBUF,R3 ;SET UP FOR ERROR MESSAGE
1696 005476 012700 000177 MOV #177,R0 ;EXPECTED
1697 005502 012767 000011 173430 MOV #9,SHIFT ;# OF SHIFTS
1698 005510 012767 000776 173426 MOV #776,TEMP1 ;DATA CHAR
1699 005516 004767 012526 JSR PC,RPOKE ;SHIFT IN THIS CHAR
1700 005522 105777 013016 TSTB @RXCSR ;RXDONE ?
1701 005526 100401 BMI 64$
1702 005530 104000 HLT ;RXDONE SHOULD BE SET
1703 005532 017701 013012 64$: MOV @RXDBUF,R1 ;ACTUAL
1704 005536 020001 CMP R0,R1 ;COMPARE EXPECTED VS. ACTUAL
1705 005540 001401 BEQ 65$
1706 005542 104002 HLT 2 ;RECEIVED DATA DID NOT MATCH
1707 ;EXPECTED DATA - CHECK MAINT DATA
1708 ;OR RECEIVER LOGIC
1709
1710 005544 012767 000011 173366 65$: MOV #9,SHIFT ;# OF SHIFTS
1711 005552 012767 000776 173364 MOV #776,TEMP1 ;DATA CHAR
1712 005560 004767 012464 JSR PC,RPOKE ;SHIFT IN THIS CHAR
1713 ;NOW SH!FT IN A SECOND CHARACTER WITHOUT READING RXDBUF
1714 005564 012767 000011 173346 MOV #9,SHIFT ;# OF SHIFTS
1715 005572 012767 000776 173344 MOV #776,TEMP1 ;DATA CHAR
1716 005600 004767 012444 JSR PC,RPOKE ;SHIFT IN THIS CHAR
1717 005604 012700 140177 MOV #140000!177,R0 ;EXPECTED DATA PLUS
1718 ;RXERR & OVRRUN
1719 005610 017701 012734 MOV @RXDBUF,R1 ;ACTUAL
1720 005614 020001 CMP RC,R1 ;COMPARE EXP VS. ACT
1721 005616 001401 BEQ 66$
  
```

```

1722 005620 104002          HLT      2          ;SPECIFICALLY LOOK AT RXERR &
1723                                     ;OVRUN BITS...THEY BOTH SHOULD BE SET
1724 005622                66$:
1725 005622 104400          SCOPE
1726                                     ;;THIS TEST VERIFYS WORD LENGTH SELECT OF THE
1727                                     ;;RECEIVER SECTION,IT USES THE ERROR FLAGS
1728                                     ;;TO DETERMINE THAT IT WAS SELECTED CORRECTLY
1729                                     ;;(OVRUN,RXERR)
1730                                     ;;MODE:ISYMOD
1731                                     ;;LENGTH:SEVEN
1732                                     ;;CHAR:0
1733
1734 005624 012767 000010 173274 TST8:  MOV      #8,TSTNO          ;SAVE THIS
1735 005632 012767 006066 173256      MOV      #TST9,NEXT          ;GO TO THIS TEST WHEN THRU
1736 005640 052777 000400 012712      BIS      #MRESET,@TXCSR    ;MASTER RESET
1737 005646 012777 000000 012700      MOV      #ISYMOD,@PARCSR   ;SET THE MODE
1738 005654 052777 000400 012676      BIS      #MRESET,@TXCSR    ;MASTER RESET
1739
1740                                     ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
1741 005662 012777 064001 012670      MOV      #MTDATA!CLK!MINT!BREAK,@TXCSR
1742
1743                                     ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
1744 005670 012777 004000 012656      MOV      #ISYMOD!SEVEN!NOPAR!0,@PARCSR
1745 005676 052777 000020 012640      BIS      #SYNSCH,@RXCSR    ;SET SYNC SEARCH
1746                                     ;POKE CLK TO GET RECEIVER INTO SYNCROIZATION....
1747 005704 042777 020000 012646      BIC      #CLK,@TXCSR       ;POKE CLK DOWN
1748 005712 052777 020000 012640      BIS      #CLK,@TXCSR       ;POKE CLK UP
1749
1750                                     ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
1751 005720 042777 020000 012632      BIC      #CLK,@TXCSR       ;POKE CLK DOWN
1752 005726 052777 020000 012624      BIS      #CLK,@TXCSR       ;POKE CLK UP
1753 005734 016703 012610          MOV      RXDBUF,R3          ;SET UP FOR ERROR MESSAGE
1754 005740 012700 000000          MOV      #0,R0              ;EXPECTED
1755 005744 012767 000011 173166      MOV      #9,SHIFT           ;# OF SHIFTS
1756 005752 012767 000400 173164      MOV      #400,TEMP1         ;DATA CHAR
1757 005760 004767 012264          JSR      PC,RPOKE           ;SHIFT IN THIS CHAR
1758 005764 105777 012554          TSTB    @RXCSR ;RXDONE ?
1759 005770 100401          BMI     64$
1760 005772 104000          HLT     ;RXDONE SHOULD BE SET
1761 005774 017701 012550          64$:  MOV      @RXDBUF,R1         ;ACTUAL
1762 006000 020001          CMP     R0,R1              ;COMPARE EXPECTED VS. ACTUAL
1763 006002 001401          BEQ    65$
1764 006004 104002          HLT     2                  ;RECEIVED DATA DID NOT MATCH
1765                                     ;EXPECTED DATA - CHECK MAINT DATA
1766                                     ;OR RECEIVER LOGIC
1767 006006          65$:
1768 006006 012767 000011 173124      MOV      #9,SHIFT           ;# OF SHIFTS
1769 006014 012767 000400 173122      MOV      #400,TEMP1         ;DATA CHAR
1770 006022 004767 012222          JSR      PC,RPOKE           ;SHIFT IN THIS CHAR
1771                                     ;NOW SHIFT IN A SECOND CHARACTER WITHOJT READING RXDBUF
1772 006026 012767 000011 173104      MOV      #9,SHIFT           ;# OF SHIFTS
1773 006034 012767 000400 173102      MOV      #400,TEMP1         ;DATA CHAR
1774 006042 004767 012202          JSR      PC,RPOKE           ;SHIFT IN THIS CHAR
1775 006046 012700 140000          MOV      #140000!0,R0       ;EXPECTED DATA PLUS
1776                                     ;RXERR & OVRUN
1777 006052 017701 012472          MOV      @RXDBUF,R1         ;ACTUAL
  
```

```

1778 006056 020001          CMP    R0,R1    ;COMPARE EXP VS. ACT
1779 006060 001401          BEQ    66$
1780 006062 104002          HLT    2        ;SPECIFICALLY LOOK AT RXERR &
1781                                     ;OVRUN BITS...THEY BOTH SHOULD BE SET
1782 006064          66$:
1783 006064 104400          SCOPE
1784                                     ::THIS TEST VERIFYS WORD LENGTH SELECT OF THE
1785                                     ::RECEIVER SECTION,IT USES THE ERROR FLAGS
1786                                     ::TO DETERMINE THAT IT WAS SELECTED CORRECTLY
1787                                     ::(OVRUN,RXERR)
1788                                     ::MODE:ISYMOD
1789                                     ::LENGTH:EIGHT
1790                                     ::CHAR:125
1791                                     ::
1792 006066 012767 000011 173032 TST9:  MOV    #9,TSTNO    ;SAVE THIS
1793 006074 012767 006330 173014      MOV    #TST10,NEXT ;GO TO THIS TEST WHEN THRU
1794 006102 052777 000400 012450      BIS    #MRESET,@TXCSR ;MASTER RESET
1795 006110 012777 000000 012436      MOV    #ISYMOD,@PARCSR ;SET THE MODE
1796 006116 052777 000400 012434      BIS    #MRESET,@TXCSR ;MASTER RESET
1797
1798                                     ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
1799 006124 012777 064001 012426      MOV    #MTDATA!CLK!MINT!BREAK,@TXCSR
1800
1801                                     ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
1802 006132 012777 006000 012414      MOV    #ISYMOD!EIGHT!NOPAR!0,@PARCSR
1803 006140 052777 000020 012376      BIS    #SYNSCH,@RXCSR ;SET SYNC SEARCH
1804                                     ;POKE CLK TO GET RECEIVER INTO SYNCROIZATION....
1805 006146 042777 020000 012404      BIC    #CLK,@TXCSR    ;POKE CLK DOWN
1806 006154 052777 020000 012376      BIS    #CLK,@TXCSR    ;POKE CLK UP
1807                                     ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
1808 006162 042777 020000 012370      BIC    #CLK,@TXCSR    ;POKE CLK DOWN
1809 006170 052777 020000 012362      BIS    #CLK,@TXCSR    ;POKE CLK UP
1810 006176 016703 012346          MOV    RXDBUF,R3     ;SET UP FOR ERROR MESSAGE
1811 006202 012700 000125          MOV    #125,R0      ;EXPECTED
1812 006206 012767 000012 172724      MOV    #10,SHIFT    ;# OF SHIFTS
1813 006214 012767 001252 172722      MOV    #1252,TEMP1  ;DATA CHAR
1814 006222 004767 012022          JSR    PC,RPOKE     ;SHIFT IN THIS CHAR
1815 006226 105777 012312          TSTB   @RXCSR ;RXDONE ?
1816 006232 100401          BMI    64$
1817 006234 104000          HLT    ;RXDONE SHOULD BE SET
1818 006236          64$:
1819 006236 017701 012306          MOV    @RXDBUF,R1   ;ACTUAL
1820 006242 020001          CMP    R0,R1      ;COMPARE EXPECTED VS. ACTUAL
1821 006244 001401          BEQ    65$
1822 006246 104002          HLT    2          ;RECEIVED DATA DID NOT MATCH
1823                                     ;EXPECTED DATA - CHECK MAINT DATA
1824                                     ;OR RECEIVER LOGIC
1825 006250          65$:
1826 006250 012767 000012 172662      MOV    #10,SHIFT    ;# OF SHIFTS
1827 006256 012767 001252 172660      MOV    #1252,TEMP1  ;DATA CHAR
1828 006264 004767 011760          JSR    PC,RPOKE     ;SHIFT IN THIS CHAR
1829                                     ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
1830 006270 012767 000012 172642      MOV    #10,SHIFT    ;# OF SHIFTS
1831 006276 012767 001252 172640      MOV    #1252,TEMP1  ;DATA CHAR
1832 006304 004767 011740          JSR    PC,RPOKE     ;SHIFT IN THIS CHAR
1833 006310 012700 140125          MOV    #140000!125,R0 ;EXPECTED DATA PLUS

```

```

1834
1835 006314 017701 012230      MOV    @RXDBUF,R1      ;RXERR & OVRRUN
1836 006320 020001              CMP    R0,R1          ;ACTUAL
1837 006322 001401              BEQ   66$             ;COMPARE EXP VS. ACT
1838 006324 104002              HLT   2                ;SPECIFICALLY LOOK AT RXERR &
1839                                ;OVRRUN BITS...THEY BOTH SHOULD BE SET
1840 006326 104400      66$:
1841 006326 104400      SCOPE
1842                                ;;THIS TEST VERIFYS WORD LENGTH SELECT OF THE
1843                                ;;RECEIVER SECTION,IT USES THE ERROR FLAGS
1844                                ;;TO DETERMINE THAT IT WAS SELECTED CORRECTLY
1845                                ;;(OVRRUN,RXERR)
1846                                ;;MODE:ISYMOD
1847                                ;;LENGTH:EIGHT
1848                                ;;CHAR:252
1849
1850 006330 012767 000012 172570  TST10: MOV    #10,TSTNO      ;SAVE THIS
1851 006336 012767 006572 172552      MOV    #TST11,NEXT      ;GO TO THIS TEST WHEN THRU
1852 006344 052777 000400 012206      BIS    #MRESET,@TXCSR   ;MASTER RESET
1853 006352 012777 000000 012174      MOV    #ISYMOD,@PARCSR  ;SET THE MODE
1854 006360 052777 000400 012172      BIS    #MRESET,@TXCSR   ;MASTER RESET
1855
1856                                ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
1857 006366 012777 064001 012164      MOV    #MTDATA!CLK!MINT!BREAK,@TXCSR
1858
1859                                ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
1860 006374 012777 006000 012152      MOV    #ISYMOD!EIGHT!NOPAR!0,@PARCSR
1861 006402 052777 000020 012134      BIS    #SYNSCH,@RXCSR   ;SET SYNC SEARCH
1862                                ;POKE CLK TO GET RECEIVER INTO SYNCROIZATION....
1863 006410 042777 020000 012142      BIC    #CLK,@TXCSR      ;POKE CLK DOWN
1864 006416 052777 020000 012134      BIS    #CLK,@TXCSR      ;POKE CLK UP
1865                                ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
1866 006424 042777 020000 012126      BIC    #CLK,@TXCSR      ;POKE CLK DOWN
1867 006432 052777 020000 012120      BIS    #CLK,@TXCSR      ;POKE CLK UP
1868 006440 016703 012104              MOV    RXDBUF,R3        ;SET UP FOR ERROR MESSAGE
1869 006444 012700 000252              MOV    #252,R0          ;EXPECTED
1870 006450 012767 000012 172462      MOV    #10,SHIFT        ;# OF SHIFTS
1871 006456 012767 001524 172460      MOV    #1524,TEMP1      ;DATA CHAR
1872 006464 004767 011560              JSR    PC,RPOKE         ;SHIFT IN THIS CHAR
1873 006470 105777 012050              TSTB   @RXCSR           ;RXDONE ?
1874 006474 100401              BMI   64$              ;RXDONE SHOULD BE SET
1875 006476 104000
1876 006500
1877 006500 017701 012044      64$:
1878 006504 020001              MOV    @RXDBUF,R1      ;ACTUAL
1879 006506 001401              CMP    R0,R1          ;COMPARE EXPECTED VS. ACTUAL
1880 006510 104002              BEQ   65$             ;RECEIVED DATA DID NOT MATCH
1881                                ;EXPECTED DATA - CHECK MAINT DATA
1882                                ;OR RECEIVER LOGIC
1883
1884 006512 012767 000012 172420      65$:
1885 006520 012767 001524 172416      MOV    #10,SHIFT        ;# OF SHIFTS
1886 006526 004767 011516      MOV    #1524,TEMP1      ;DATA CHAR
1887                                JSR    PC,RPOKE         ;SHIFT IN THIS CHAR
1888                                ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
1888 006532 012767 000012 172400      MOV    #10,SHIFT        ;# OF SHIFTS
1889 006540 012767 001524 172376      MOV    #1524,TEMP1      ;DATA CHAR

```

```

1890 006546 004767 011476      JSR    PC,RPOKE      ;SHIFT IN THIS CHAR
1891 006552 012700 140252      MOV    #140000!252,R0 ;EXPECTED DATA PLUS
1892                                     ;RXERR & OVRUN
1893 006556 017701 011766      MOV    @RXDBUF,R1    ;ACTUAL
1894 006562 020001                                     ;COMPARE EXP VS. ACT
1895 006564 001401      BEQ    66$
1896 006566 104002      HLT    2             ;SPECIFICALLY LOOK AT RXERR &
1897                                     ;OVRUN BITS...THEY BOTH SHOULD BE SET
1898 006570                                     66$:
1899 006570 104400      SCOPE
1900                                     ::THIS TEST VERIFYS WORD LENGTH SELECT OF THE
1901                                     ::RECEIVER SECTION,IT USES THE ERROR FLAGS
1902                                     ::TO DETERMINE THAT IT WAS SELECTED CORRECTLY
1903                                     ::(OVRUN,RXERR)
1904                                     ::MODE:ISYMOD
1905                                     ::LENGTH:EIGHT
1906                                     ::CHAR:377
1907                                     ::
1908 006572 012767 000013 172326  TST11: MOV    #11,TSTNO      ;SAVE THIS
1909 006600 012767 007034 172310      MOV    #TST12,NEXT    ;GO TO THIS TEST WHEN THRU
1910 006606 052777 000400 011744      BIS    #MRESET,@TXCSR ;MASTER RESET
1911 006614 012777 000000 011732      MOV    #ISYMOD,@PARCSR ;SET THE MODE
1912 006622 052777 000400 011730      BIS    #MRESET,@TXCSR ;MASTER RESET
1913
1914                                     ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
1915 006630 012777 064001 011722      MOV    #MTDATA!CLK!MINT!BREAK,@TXCSR
1916
1917                                     ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
1918 006636 012777 006000 011710      MOV    #ISYMOD!EIGHT!NOPAR!0,@PARCSR
1919 006644 052777 000020 011672      BIS    #SYNSCH,@RXCSR ;SET SYNC SEARCH
1920                                     ;POKE CLK TO GET RECEIVER INTO SYNCROIZATION....
1921 006652 042777 020000 011700      BIC    #CLK,@TXCSR    ;POKE CLK DOWN
1922 006660 052777 020000 011672      BIS    #CLK,@TXCSR    ;POKE CLK UP
1923                                     ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
1924 006666 042777 020000 011664      BIC    #CLK,@TXCSR    ;POKE CLK DOWN
1925 006674 052777 020000 011656      BIS    #CLK,@TXCSR    ;POKE CLK UP
1926 006702 016703 011642      MOV    RXDBUF,R3     ;SET UP FOR ERROR MESSAGE
1927 006706 012700 000377      MOV    #377,R0       ;EXPECTED
1928 006712 012767 000012 172220      MOV    #10,SHIFT     ;# OF SHIFTS
1929 006720 012767 001776 172216      MOV    #1776,TEMP1   ;DATA CHAR
1930 006726 004767 011316      JSR    PC,RPOKE      ;SHIFT IN THIS CHAR
1931 006732 105777 011606      TSTB   @RXCSR        ;RXDONE ?
1932 006736 100401      BMI    64$
1933 006740 104000      HLT
1934 006742                                     64$:
1935 006742 017701 011602      MOV    @RXDBUF,R1    ;ACTUAL
1936 006746 020001      CMP    R0,R1         ;COMPARE EXPECTED VS. ACTUAL
1937 006750 001401      BEQ    65$
1938 006752 104002      HLT    2             ;RECEIVED DATA DID NOT MATCH
1939                                     ;EXPECTED DATA - CHECK MAINT DATA
1940                                     ;OR RECEIVER LOGIC
1941 006754                                     65$:
1942 006754 012767 000012 172156      MOV    #10,SHIFT     ;# OF SHIFTS
1943 006762 012767 001776 172154      MOV    #1776,TEMP1   ;DATA CHAR
1944 006770 004767 011254      JSR    PC,RPOKE      ;SHIFT IN THIS CHAR
1945                                     ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF

```

1946	006774	012767	000012	172136	MOV	#10,SHIFT	:# OF SHIFTS
1947	007002	012767	001776	172134	MOV	#1776,TEMP1	:DATA CHAR
1948	007010	004767	011234		JSR	PC,RPOKE	:SHIFT IN THIS CHAR
1949	007014	012700	140377		MOV	#140000!377,R0	:EXPECTED DATA PLUS
1950							:RXERR & OVRRUN
1951	007020	017701	011524		MOV	@RXDBUF,R1	:ACTUAL
1952	007024	020001			CMP	R0,R1	:COMPARE EXP VS. ACT
1953	007026	001401			BEQ	66\$	
1954	007030	104002			HLT	2	:SPECIFICALLY LOOK AT RXERR &
1955							:OVRRUN BITS...THEY BOTH SHOULD BE SET
1956	007032				66\$:		
1957	007032	104400					
1958						SCOPE	
1959						::THIS TEST VERIFYS WORD LENGTH SELECT OF THE	
1960						::RECEIVER SECTION,IT USES THE ERROR FLAGS	
1961						::TO DETERMINE THAT IT WAS SELECTED CORRECTLY	
1962						::(OVRRUN,RXERR)	
1963						::MODE:ISYMOD	
1964						::LENGTH:EIGHT	
1965						::CHAR:0	
1966	007034	012767	000014	172064	TST12:	MOV	#12,TSTNO ;SAVE THIS
1967	007042	012767	007276	172046		MOV	#TST13,NEXT ;GC TO THIS TEST WHEN THRU
1968	007050	052777	000400	011502		BIS	#MRESET,@TXCSR ;MASTER RESET
1969	007056	012777	000000	011470		MOV	#ISYMOD,@PARCSR ;SET THE MODE
1970	007064	052777	000400	011466		BIS	#MRESET,@TXCSR ;MASTER RESET
1971							
1972							:SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
1973	007072	012777	064001	011460		MOV	#MTDATA!CLK!MINT!BREAK,@TXCSR
1974							
1975							:SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
1976	007100	012777	006000	011446		MOV	#ISYMOD!EIGHT!NOPAR!0,@PARCSR
1977	007106	052777	000020	011430		BIS	#SYNSCH,@RXCSR ;SET SYNC SEARCH
1978							:POKE CLK TO GET RECEIVER INTO SYNCROIZATION....
1979	007114	042777	020000	011436		BIC	#CLK,@TXCSR ;POKE CLK DOWN
1980	007122	052777	020000	011430		BIS	#CLK,@TXCSR ;POKE CLK UP
1981							:POKE CLK TO GET LOGIC INTO SYNCRONIZATION
1982	007130	042777	020000	011422		BIC	#CLK,@TXCSR ;POKE CLK DOWN
1983	007136	052777	020000	011414		BIS	#CLK,@TXCSR ;POKE CLK UP
1984	007144	016703	011400			MOV	RXDBUF,R3 ;SET UP FOR ERROR MESSAGE
1985	007150	012700	000000			MOV	#0,R0 ;EXPECTED
1986	007154	012767	000012	171756		MOV	#10,SHIFT ;# OF SHIFTS
1987	007162	012767	001000	171754		MOV	#1000,TEMP1 ;DATA CHAR
1988	007170	004767	011054			JSR	PC,RPOKE ;SHIFT IN THIS CHAR
1989	007174	105777	011344			TSTB	@RXCSR ;RXDONE ?
1990	007200	100401				BMI	64\$
1991	007202	104000				HLT	:RXDONE SHOULD BE SET
1992	007204				64\$:		
1993	007204	017701	011340			MOV	@RXDBUF,R1 ;ACTUAL
1994	007210	020001				CMP	R0,R1 ;COMPARE EXPECTED VS. ACTUAL
1995	007212	001401				BEQ	65\$
1996	007214	104002				HLT	2 ;RECEIVED DATA DID NOT MATCH
1997							:EXPECTED DATA - CHECK MAINT DATA
1998							:OR RECEIVER LOGIC
1999	007216				65\$:		
2000	007216	012767	000012	171714		MOV	#10,SHIFT ;# OF SHIFTS
2001	007224	012767	001000	171712		MOV	#1000,TEMP1 ;DATA CHAR

```

2002 007232 004767 011012          JSR    PC,RPOKE      ;SHIFT IN THIS CHAR
2003                                ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
2004 007236 012767 000012 171674    MOV    #10,SHIFT     ;# OF SHIFTS
2005 007244 012767 001000 171672    MOV    #1000,TEMP1   ;DATA CHAR
2006 007252 004767 010772          JSR    PC,RPOKE      ;SHIFT IN THIS CHAR
2007 007256 012700 140000          MOV    #140000!0,RO  ;EXPECTED DATA PLUS
2008                                ;RXERR & OVRUN
2009 007262 017701 011262          MOV    @RXDBUF,R1    ;ACTUAL
2010 007266 020001          CMP    RO,R1        ;COMPARE EXP VS. ACT
2011 007270 001401          BEQ    66$
2012 007272 104002          HLT    2            ;SPECIFICALLY LOOK AT RXERR &
2013                                ;OVRUN BITS...THEY BOTH SHOULD BE SET
2014 007274          66$:
2015 007274 104400          SCOPE
2016                                ;;THIS TEST VERIFYS WORD LENGTH SELECT OF THE
2017                                ;;RECEIVER SECTION,IT USES THE ERROR FLAGS
2018                                ;;TO DETERMINE THAT IT WAS SELECTED CORRECTLY
2019                                ;;(OVRUN,RXERR)
2020                                ;;MODE:SYNEXT
2021                                ;;LENGTH:FIVE
2022                                ;;CHAR:25
2023                                ;;
2024 007276 012767 000015 171622    TST13: MOV    #13,TSTNO      ;SAVE THIS
2025 007304 012767 007524 171604    MOV    #TST14,NEXT   ;GO TO THIS TEST WHEN THRU
2026 007312 052777 000400 011240    BIS    #MRESET,@TXCSR ;MASTER RESET
2027 007320 012777 020000 011226    MOV    #SYNEXT,@PARCSR ;SET THE MODE
2028 007326 052777 000400 011224    BIS    #MRESET,@TXCSR ;MASTER RESET
2029
2030                                ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
2031 007334 012777 064001 011216    MOV    #MTDATA!CLK!MINT!BREAK,@TXCSR
2032
2033                                ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
2034 007342 012777 020000 011204    MOV    #SYNEXT!FIVE!NOPAR!0,@PARCSR
2035 007350 052777 000020 011166    BIS    #SYNSCH,@RXCSR ;SET SEARCH SYNC
2036                                ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
2037 007356 042777 020000 011174    BIC    #CLK,@TXCSR   ;POKE CLK DOWN
2038 007364 052777 020000 011166    BIS    #CLK,@TXCSR   ;POKE CLK UP
2039 007372 016703 011152          MOV    RXDBUF,R3     ;SET UP FOR ERROR MESSAGE
2040 007376 012700 000025          MOV    #25,RO        ;EXPECTED
2041 007402 012767 000005 171530    MOV    #5,SHIFT     ;# OF SHIFTS
2042 007410 012767 000025 171526    MOV    #25,TEMP1    ;DATA CHAR
2043 007416 004767 010626          JSR    PC,RPOKE      ;SHIFT IN THIS CHAR
2044 007422 105777 011116          TSTB   @RXCSR        ;RXDONE ?
2045 007426 100401          BMI    64$
2046 007430 104000          HLT
2047                                64$:
2048 007432 017701 011112          MOV    @RXDBUF,R1    ;ACTUAL
2049 007436 020001          CMP    RO,R1        ;COMPARE EXPECTED VS. ACTUAL
2050 007440 001401          BEQ    65$
2051 007442 104002          HLT    2            ;RECEIVED DATA DID NOT MATCH
2052                                ;EXPECTED DATA - CHECK MAINT DATA
2053                                ;OR RECEIVER LOGIC
2054                                65$:
2055 007444 012767 000005 171466    MOV    #5,SHIFT     ;# OF SHIFTS
2056 007452 012767 000025 171464    MOV    #25,TEMP1    ;DATA CHAR
2057 007460 004767 010564          JSR    PC,RPOKE      ;SHIFT IN THIS CHAR

```

```

2058 ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
2059 007464 012767 000005 171446 MOV #5,SHIFT ;# OF SHIFTS
2060 007472 012767 000025 171444 MOV #25,TEMP1 ;DATA CHAR
2061 007500 004767 010544 JSR PC,RPOKE ;SHIFT IN THIS CHAR
2062 007504 012700 140025 MOV #140000!25,R0 ;EXPECTED DATA PLUS
2063 ;RXERR & OVRRUN
2064 007510 017701 011034 MOV @RXDBUF,R1 ;ACTUAL
2065 007514 020001 CMP R0,R1 ;COMPARE EXP VS. ACT
2066 007516 001401 BEQ 66$
2067 007520 104002 HLT 2 ;SPECIFICALLY LOOK AT RXERR &
2068 ;OVRRUN BITS...THEY BOTH SHOULD BE SET
2069 007522 66$:
2070 007522 104400 SCOPE
2071 ;;THIS TEST VERIFYS WORD LENGTH SELECT OF THE
2072 ;;RECEIVER SECTION,IT USES THE ERROR FLAGS
2073 ;;TO DETERMINE THAT IT WAS SELECTED CORRECTLY
2074 ;;(OVRRUN,RXERR)
2075 ;;MODE:SYNEXT
2076 ;;LENGTH:FIVE
2077 ;;CHAR:12
2078 ;;
2079 007524 012767 000016 171374 TST14: MOV #14,TSTNO ;SAVE THIS
2080 007532 012767 007752 171356 MOV #TST15,NEXT ;GO TO THIS TEST WHEN THRU
2081 007540 052777 000400 011012 BIS #MRESET,@TXCSR ;MASTER RESET
2082 007546 012777 020000 011000 MOV #SYNEXT,@PARCSR ;SET THE MODE
2083 007554 052777 000400 010776 BIS #MRESET,@TXCSR ;MASTER RESET
2084
2085 ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
2086 007562 012777 064001 010770 MOV #MMDATA!CLK!MINT!BREAK,@TXCSR
2087
2088 ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
2089 007570 012777 020000 010756 MOV #SYNEXT!FIVE!NOPAR!0,@PARCSR
2090 007576 052777 000020 010740 BIS #SYNSCH,@RXCSR ;SET SEARCH SYNC
2091 ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
2092 007604 042777 020000 010746 BIC #CLK,@TXCSR ;POKE CLK DOWN
2093 007612 052777 020000 010740 BIS #CLK,@TXCSR ;POKE CLK UP
2094 007620 016703 010724 MOV RXDBUF,R3 ;SET UP FOR ERROR MESSAGE
2095 007624 012700 000012 MOV #12,R0 ;EXPECTED
2096 007630 012767 000005 171302 MOV #5,SHIFT ;# OF SHIFTS
2097 007636 012767 000012 171300 MOV #12,TEMP1 ;DATA CHAR
2098 007644 004767 010400 JSR PC,RPOKE ;SHIFT IN THIS CHAR
2099 007650 105777 010670 TSTB @RXCSR ;RXDONE ?
2100 007654 100401 BMI 64$
2101 007656 104000 HLT ;RXDONE SHOULD BE SET
2102 007660 64$:
2103 007660 017701 010664 MOV @RXDBUF,R1 ;ACTUAL
2104 007664 020001 CMP R0,R1 ;COMPARE EXPECTED VS. ACTUAL
2105 007666 001401 BEQ 65$
2106 007670 104002 HLT 2 ;RECEIVED DATA DID NOT MATCH
2107 ;EXPECTED DATA - CHECK MAINT DATA
2108 ;OR RECEIVER LOGIC
2109 007672 65$:
2110 007672 012767 000005 171240 MOV #5,SHIFT ;# OF SHIFTS
2111 007700 012767 000012 171236 MOV #12,TEMP1 ;DATA CHAR
2112 007706 004767 010336 JSR PC,RPOKE ;SHIFT IN THIS CHAR
2113 ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
  
```

```

2114 007712 012767 000005 171220      MOV      #5,SHIFT      ;# OF SHIFTS
2115 007720 012767 000012 171216      MOV      #12,TEMP1     ;DATA CHAR
2116 007726 004767 010316              JSR      PC,RPOKE      ;SHIFT IN THIS CHAR
2117 007732 012700 140012              MOV      #14000!12,R0  ;EXPECTED DATA PLUS
2118                                ;RXERR & OVRRUN
2119 007736 017701 010606              MOV      @RXDBUF,R1    ;ACTUAL
2120 007742 020001              CMP      R0,R1        ;COMPARE EXP VS. ACT
2121 007744 001401              BEQ      66$
2122 007746 104002              HLT      2            ;SPECIFICALLY LOOK AT RXERR &
2123                                ;OVRRUN BITS...THEY BOTH SHOULD BE SET
2124 007750              66$:
2125 007750 104400              SCOPE
2126                                ;;THIS TEST VERIFYS WORD LENGTH SELECT OF THE
2127                                ;;RECEIVER SECTION,IT USES THE ERROR FLAGS
2128                                ;;TO DETERMINE THAT IT WAS SELECTED CORRECTLY
2129                                ;;(OVRRUN,RXERR)
2130                                ;;MODE:SYNEXT
2131                                ;;LENGTH:FIVE
2132                                ;;CHAR:37
2133                                ;;
2134 007752 012767 000017 171146      TST15: MOV      #15,TSTNO      ;SAVE THIS
2135 007760 012767 010200 171130      MOV      #TST16,NEXT   ;GO TO THIS TEST WHEN THRU
2136 007766 052777 000400 010564      BIS      #MRESET,@TXCSR ;MASTER RESET
2137 007774 012777 020000 010552      MOV      #SYNEXT,@PARCSR ;SET THE MODE
2138 010002 052777 000400 010550      BIS      #MRESET,@TXCSR ;MASTER RESET
2139
2140                                ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
2141 010010 012777 064001 010542      MOV      #MTDATA!CLK!MINT!BREAK,@TXCSR
2142
2143                                ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
2144 010016 012777 020000 010530      MOV      #SYNEXT!FIVE!NOPAR!0,@PARCSR
2145 010024 052777 000020 010512      BIS      #SYNSCH,@RXCSR ;SET SEARCH SYNC
2146                                ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
2147 010032 042777 020000 010520      BIC      #CLK,@TXCSR   ;POKE CLK DOWN
2148 010040 052777 020000 010512      BIS      #CLK,@TXCSR   ;POKE CLK UP
2149 010046 016703 010476              MOV      RXDBUF,R3     ;SET UP FOR ERROR MESSAGE
2150 010052 012700 000037              MOV      #37,R0        ;EXPECTED
2151 010056 012767 000005 171054      MOV      #5,SHIFT      ;# OF SHIFTS
2152 010064 012767 000037 171052      MOV      #37,TEMP1     ;DATA CHAR
2153 010072 004767 010152              JSR      PC,RPOKE      ;SHIFT IN THIS CHAR
2154 010076 105777 010442              TSTB     @RXCSR        ;RXDONE ?
2155 010102 100401              BMI      64$
2156 010104 104000              HLT
2157                                64$:
2158 010106 017701 010436              MOV      @RXDBUF,R1    ;ACTUAL
2159 010112 020001              CMP      R0,R1        ;COMPARE EXPECTED VS. ACTUAL
2160 010114 001401              BEQ      65$
2161 010116 104002              HLT      2            ;RECEIVED DATA DID NOT MATCH
2162                                ;EXPECTED DATA - CHECK MAINT DATA
2163                                ;OR RECEIVER LOGIC
2164 010120              65$:
2165 010120 012767 000005 171012      MOV      #5,SHIFT      ;# OF SHIFTS
2166 010126 012767 000037 171010      MOV      #37,TEMP1     ;DATA CHAR
2167 010134 004767 010110              JSR      PC,RPOKE      ;SHIFT IN THIS CHAR
2168                                ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
2169 010140 012767 000005 170772      MOV      #5,SHIFT      ;# OF SHIFTS

```

```

2170 010146 012767 000037 170770      MOV      #37,TEMP1      ;DATA CHAR
2171 010154 004767 010070      JSR      PC,RPOKE      ;SHIFT IN THIS CHAR
2172 010160 012700 140037      MOV      #140000!37,R0 ;EXPECTED DATA PLUS
2173                                     ;RXERR & OVRRUN
2174 010164 017701 010360      MOV      @RXDBUF,R1    ;ACTUAL
2175 010170 020001      CMP      R0,R1        ;COMPARE EXP VS. ACT
2176 010172 001401      BEQ     66$
2177 010174 104002      HLT     2              ;SPECIFICALLY LOOK AT RXERR &
2178                                     ;OVRRUN BITS...THEY BOTH SHOULD BE SET
2179 010176                                     66$:
2180 010176 104400      SCOPE
2181                                     ;;THIS TEST VERIFYS WORD LENGTH SELECT OF THE
2182                                     ;;RECEIVER SECTION,IT USES THE ERROR FLAGS
2183                                     ;;TO DETERMINE THAT IT WAS SELECTED CORRECTLY
2184                                     ;;(OVRRUN,RXERR)
2185                                     ;;MODE:SYNEXT
2186                                     ;;LENGTH:FIVE
2187                                     ;;CHAR:0
2188                                     ;;
2189 010200 012767 000020 170720  TST16: MOV      #16,TSTNO      ;SAVE THIS
2190 010206 012767 010426 170702      MOV      #TST17,NEXT   ;GO TO THIS TEST WHEN THRU
2191 010214 052777 000400 010336      BIS      #MRESET,@TXCSR ;MASTER RESET
2192 010222 012777 020000 010324      MOV      #SYNEXT,@PARCSR ;SET THE MODE
2193 010230 052777 000400 010322      BIS      #MRESET,@TXCSR ;MASTER RESET
2194
2195                                     ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
2196 010236 012777 064001 010314      MOV      #MTDATA!CLK!MINT!BREAK,@TXCSR
2197
2198                                     ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
2199 010244 012777 020000 010302      MOV      #SYNEXT!FIVE!NOPAR!0,@PARCSR
2200 010252 052777 000020 010264      BIS      #SYNSCH,@RXCSR ;SET SEARCH SYNC
2201                                     ;POKE CLK TO GET LOGIC INTO SYNCHRONIZATION
2202 010260 042777 020000 010272      BIC      #CLK,@TXCSR   ;POKE CLK DOWN
2203 010266 052777 020000 010264      BIS      #CLK,@TXCSR   ;POKE CLK UP
2204 010274 016703 010250      MOV      RXDBUF,R3     ;SET UP FOR ERROR MESSAGE
2205 010300 012700 000000      MOV      #0,R0        ;EXPECTED
2206 010304 012767 000005 170626      MOV      #5,SHIFT      ;# OF SHIFTS
2207 010312 012767 000000 170624      MOV      #0,TEMP1      ;DATA CHAR
2208 010320 004767 007724      JSR      PC,RPOKE      ;SHIFT IN THIS CHAR
2209 010324 105777 010214      TSTB    @RXCSR        ;RXDONE ?
2210 010330 100401      BMI     64$
2211 010332 104000      HLT     ;RXDONE SHOULD BE SET
2212
2213 010334 017701 010210 64$:
2214 010340 020001      MOV      @RXDBUF,R1    ;ACTUAL
2215 010342 001401      CMP      R0,R1        ;COMPARE EXPECTED VS. ACTUAL
2216 010344 104002      BEQ     65$
2217                                     ;RECEIVED DATA DID NOT MATCH
2218                                     ;EXPECTED DATA - CHECK MAINT DATA
2219                                     ;OR RECEIVER LOGIC
2220 010346 012767 000005 170564 65$:
2221 010354 012767 000000 170562      MOV      #5,SHIFT      ;# OF SHIFTS
2222 010362 004767 007662      MOV      #0,TEMP1      ;DATA CHAR
2223                                     ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
2224 010366 012767 000005 170544      JSR      PC,RPOKE      ;SHIFT IN THIS CHAR
2225 010374 012767 000000 170542      MOV      #5,SHIFT      ;# OF SHIFTS
2226                                     ;DATA CHAR

```

```

2226 010402 004767 007642      JSR    PC,RPOKE      ;SHIFT IN THIS CHAR
2227 010406 012700 140000      MOV    #140000!0,R0  ;EXPECTED DATA PLUS
2228                                ;RXERR & OVRRUN
2229 010412 017701 010132      MOV    @RXDBUF,R1    ;ACTUAL
2230 010416 020001                CMP    R0,R1        ;COMPARE EXP VS. ACT
2231 010420 001401                BEQ    66$
2232 010422 104002                HLT    2            ;SPECIFICALLY LOOK AT RXERR &
2233                                ;OVRRUN BITS...THEY BOTH SHOULD BE SET
2234 010424                66$:
2235 010424 104400                SCOPE
2236                                ;;THIS TEST VERIFYS WORD LENGTH SELECT OF THE
2237                                ;;RECEIVER SECTION,IT USES THE ERROR FLAGS
2238                                ;;TO DETERMINE THAT IT WAS SELECTED CORRECTLY
2239                                ;;(OVRRUN,RXERR)
2240                                ;;MODE:SYNEXT
2241                                ;;LENGTH:SIX
2242                                ;;CHAR:25
2243                                ;;
2244 010426 012767 000021 170472  TST17: MOV    #17,TSTNO      ;SAVE THIS
2245 010434 012767 010654 170454  MOV    #TST18,NEXT    ;GO TO THIS TEST WHEN THRU
2246 010442 052777 000400 010110  BIS    #MRESET,@TXCSR ;MASTER RESET
2247 010450 012777 020000 010076  MOV    #SYNEXT,@PARCSR ;SET THE MODE
2248 010456 052777 000400 010074  BIS    #MRESET,@TXCSR ;MASTER RESET
2249
2250                                ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
2251 010464 012777 064001 010066  MOV    #MNTDATA!CLK!MINT!BREAK,@TXCSR
2252
2253                                ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
2254 010472 012777 022000 010054  MOV    #SYNEXT!SIX!NOPAR!0,@PARCSR
2255 010500 052777 000020 010036  BIS    #SYNSCH,@RXCSR  ;SET SEARCH SYNC
2256                                ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
2257 010506 042777 020000 010044  BIC    #CLK,@TXCSR    ;POKE CLK DOWN
2258 010514 052777 020000 010036  BIS    #CLK,@TXCSR    ;POKE CLK UP
2259 010522 016703 010022                MOV    RXDBUF,R3      ;SET UP FOR ERROR MESSAGE
2260 010526 012700 000025                MOV    #25,R0        ;EXPECTED
2261 010532 012767 000006 170400  MOV    #6,SHIFT      ;# OF SHIFTS
2262 010540 012767 000025 170376  MOV    #25,TEMP1     ;DATA CHAR
2263 010546 004767 007476                JSR    PC,RPOKE      ;SHIFT IN THIS CHAR
2264 010552 105777 007766                TSTB   @RXCSR        ;RXDONE ?
2265 010556 100401                BMI    64$
2266 010560 104000                HLT
2267 010562                64$:
2268 010562 017701 007762                MOV    @RXDBUF,R1    ;ACTUAL
2269 010566 020001                CMP    R0,R1        ;COMPARE EXPECTED VS. ACTUAL
2270 010570 001401                BEQ    65$
2271 010572 104002                HLT    2            ;RECEIVED DATA DID NOT MATCH
2272                                ;EXPECTED DATA - CHECK MAINT DATA
2273                                ;OR RECEIVER LOGIC
2274 010574                65$:
2275 010574 012767 000006 170336  MOV    #6,SHIFT      ;# OF SHIFTS
2276 010602 012767 000025 170334  MOV    #25,TEMP1     ;DATA CHAR
2277 010610 004767 007434                JSR    PC,RPOKE      ;SHIFT IN THIS CHAR
2278                                ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
2279 010614 012767 000006 170316  MOV    #6,SHIFT      ;# OF SHIFTS
2280 010622 012767 000025 170314  MOV    #25,TEMP1     ;DATA CHAR
2281 010630 004767 007414                JSR    PC,RPOKE      ;SHIFT IN THIS CHAR

```

```

2282 010634 012700 140025      MOV      #140000!25,R0      ;EXPECTED DATA PLUS
2283                                     ;RXERR & OVRRUN
2284 010640 017701 007704      MOV      @RXDBUF,R1        ;ACTUAL
2285 010644 020001                CMP      R0,R1             ;COMPARE EXP VS. ACT
2286 010646 001401                BEQ      66$
2287 010650 104002                HLT      2                 ;SPECIFICALLY LOOK AT RXERR &
2288                                     ;OVRRUN BITS...THEY BOTH SHOULD BE SET
2289 010652                66$:
2290 010652 104400                SCOPE
2291                                     ;;THIS TEST VERIFYS WORD LENGTH SELECT OF THE
2292                                     ;;RECEIVER SECTION,IT USES THE ERROR FLAGS
2293                                     ;;TO DETERMINE THAT IT WAS SELECTED CORRECTLY
2294                                     ;;(OVRRUN,RXERR)
2295                                     ;;MODE:SYNEXT
2296                                     ;;LENGTH:SIX
2297                                     ;;CHAR:52
2298                                     ;;
2299 010654 012767 000022 170244  TST18:  MOV      #18,TSTNO        ;SAVE THIS
2300 010662 012767 011102 170226      MOV      #TST19,NEXT       ;GO TO THIS TEST WHEN THRU
2301 010670 052777 000400 007662      BIS      #MRESET,@TXCSR    ;MASTER RESET
2302 010676 012777 020000 007650      MOV      #SYNEXT,@PARCSR   ;SET THE MODE
2303 010704 052777 000400 007646      BIS      #MRESET,@TXCSR    ;MASTER RESET
2304
2305                                     ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
2306 010712 012777 064001 007640      MOV      #MCDATA!CLK!MINT!BREAK,@TXCSR
2307
2308                                     ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
2309 010720 012777 022000 007626      MOV      #SYNEXT!SIX!NOPAR!0,@PARCSR
2310 010726 052777 000020 007610      BIS      #SYNSCH,@RXCSR    ;SET SEARCH SYNC
2311                                     ;POKE CLK TO GET LOGIC INTO SYNCHRONIZATION
2312 010734 042777 020000 007616      BIC      #CLK,@TXCSR       ;POKE CLK DOWN
2313 010742 052777 020000 007610      BIS      #CLK,@TXCSR       ;POKE CLK UP
2314 010750 016703 007574                MOV      RXDBUF,R3         ;SET UP FOR ERROR MESSAGE
2315 010754 012700 000052                MOV      #52,R0           ;EXPECTED
2316 010760 012767 000006 170152      MOV      #6,SHIFT          ;# OF SHIFTS
2317 010766 012767 000052 170150      MOV      #52,TEMP1         ;DATA CHAR
2318 010774 004767 007250                JSR      PC,RPOKE          ;SHIFT IN THIS CHAR
2319 011000 105777 007540                TSTB    @RXCSR ;RXDONE ?
2320 011004 100401                BMI      64$
2321 011006 104000                HLT      ;RXDONE SHOULD BE SET
2322 011010                64$:
2323 011010 017701 007534                MOV      @RXDBUF,R1        ;ACTUAL
2324 011014 020001                CMP      R0,R1             ;COMPARE EXPECTED VS. ACTUAL
2325 011016 001401                BEQ      65$
2326 011020 104002                HLT      2                 ;RECEIVED DATA DID NOT MATCH
2327                                     ;EXPECTED DATA - CHECK MAINT DATA
2328                                     ;OR RECEIVER LOGIC
2329 011022                65$:
2330 011022 012767 000006 170110      MOV      #6,SHIFT          ;# OF SHIFTS
2331 011030 012767 000052 170106      MOV      #52,TEMP1         ;DATA CHAR
2332 011036 004767 007206                JSR      PC,RPOKE          ;SHIFT IN THIS CHAR
2333                                     ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
2334 011042 012767 000006 170070      MOV      #6,SHIFT          ;# OF SHIFTS
2335 011050 012767 000052 170066      MOV      #52,TEMP1         ;DATA CHAR
2336 011056 004767 007166                JSR      PC,RPOKE          ;SHIFT IN THIS CHAR
2337 011062 012700 140052                MOV      #140000!52,R0    ;EXPECTED DATA PLUS

```



```

2394 011314 017701 007230      MOV    @RXDBUF,R1      ;ACTUAL
2395 011320 020001              CMP    R0,R1          ;COMPARE EXP VS. ACT
2396 011322 001401              BEQ   66$
2397 011324 104002              HLT   2               ;SPECIFICALLY LOOK AT RXERR &
2398                                ;OVRRUN BITS...THEY BOTH SHOULD BE SET
2399 011326              66$:
2400 011326 104400              SCOPE
2401                                ;;THIS TEST VERIFYS WORD LENGTH SELECT OF THE
2402                                ;;RECEIVER SECTION,IT USES THE ERROR FLAGS
2403                                ;;TO DETERMINE THAT IT WAS SELECTED CORRECTLY
2404                                ;;(OVRRUN,RXERR)
2405                                ;;MODE:SYNEXT
2406                                ;;LENGTH:SIX
2407                                ;;CHAR:0
2408                                ;;
2409 011330 012767 000024 167570  TST20: MOV    #20,TSTNO      ;SAVE THIS
2410 011336 012767 011556 167552      MOV    #TST21,NEXT     ;GO TO THIS TEST WHEN THRU
2411 011344 052777 000400 007206      BIS    #MRESET,@TXCSR  ;MASTER RESET
2412 011352 012777 020000 007174      MOV    #SYNEXT,@PARCSR ;SET THE MODE
2413 011360 052777 000400 007172      BIS    #MRESET,@TXCSR  ;MASTER RESET
2414
2415                                ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
2416 011366 012777 064001 007164      MOV    #MTDATA!CLK!MINT!BREAK,@TXCSR
2417
2418                                ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
2419 011374 012777 022000 007152      MOV    #SYNEXT!SIX!NOPAR!0,@PARCSR
2420 011402 052777 000020 007134      BIS    #SYNSCH,@RXCSR  ;SET SEARCH SYNC
2421                                ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
2422 011410 042777 020000 007142      BIC    #CLK,@TXCSR     ;POKE CLK DOWN
2423 011416 052777 020000 007134      BIS    #CLK,@TXCSR     ;POKE CLK UP
2424 011424 016703 007120              MOV    RXDBUF,R3       ;SET UP FOR ERROR MESSAGE
2425 011430 012700 000000              MOV    #0,R0           ;EXPECTED
2426 011434 012767 000006 167476      MOV    #6,SHIFT        ;# OF SHIFTS
2427 011442 012767 000000 167474      MOV    #0,TEMP1        ;DATA CHAR
2428 011450 004767 006574              JSR    PC,RPOKE        ;SHIFT IN THIS CHAR
2429 011454 105777 007064              TSTB   @RXCSR ;RXDONE ?
2430 011460 100401
2431 011462 104000              BMI   64$
2432                                HLT   ;RXDONE SHOULD BE SET
2433                                64$:
2433 011464 017701 007060      MOV    @RXDBUF,R1      ;ACTUAL
2434 011470 020001              CMP    R0,R1          ;COMPARE EXPECTED VS. ACTUAL
2435 011472 001401              BEQ   65$
2436 011474 104002              HLT   2               ;RECEIVED DATA DID NOT MATCH
2437                                ;EXPECTED DATA - CHECK MAINT DATA
2438                                ;OR RECEIVER LOGIC
2439                                65$:
2440 011476 012767 000006 167434      MOV    #6,SHIFT        ;# OF SHIFTS
2441 011504 012767 000000 167432      MOV    #0,TEMP1        ;DATA CHAR
2442 011512 004767 006532              JSR    PC,RPOKE        ;SHIFT IN THIS CHAR
2443                                ;NOW SHIFT IN A SECOND CHARACTER WITHOJT READING RXDBUF
2444 011516 012767 000006 167414      MOV    #6,SHIFT        ;# OF SHIFTS
2445 011524 012767 000000 167412      MOV    #0,TEMP1        ;DATA CHAR
2446 011532 004767 006512              JSR    PC,RPOKE        ;SHIFT IN THIS CHAR
2447 011536 012700 140000              MOV    #140000!0,R0    ;EXPECTED DATA PLUS
2448                                ;RXERR & OVRRUN
2449 011542 017701 007002      MOV    @RXDBUF,R1      ;ACTUAL
  
```

```

2450 011546 020001      CMP      R0,R1      ;COMPARE EXP VS. ACT
2451 011550 001401      BEQ      66$
2452 011552 104002      HLT      2          ;SPECIFICALLY LOOK AT RXERR &
2453                                     ;OVRUN BITS...THEY BOTH SHOULD BE SET
2454 011554                                     66$:
2455 011554 104400      SCOPE
2456                                     ;;THIS TEST VERIFYS WORD LENGTH SELECT OF THE
2457                                     ;;RECEIVER SECTION,IT USES THE ERROR FLAGS
2458                                     ;;TO DETERMINE THAT IT WAS SELECTED CORRECTLY
2459                                     ;;(OVRUN,RXERR)
2460                                     ;;MODE:SYNEXT
2461                                     ;;LENGTH:SEVEN
2462                                     ;;CHAR:125
2463                                     ;;
2464 011556 012767 000025 167342 TST21: MOV      #21,TSTNO      ;SAVE THIS
2465 011564 012767 012004 167324      MOV      #TST22,NEXT      ;GO TO THIS TEST WHEN THRU
2466 011572 052777 000400 006760      BIS      #PRESET,@TXCSR  ;MASTER RESET
2467 011600 012777 020000 006746      MOV      #SYNEXT,@PARCSR ;SET THE MODE
2468 011606 052777 000400 006744      BIS      #PRESET,@TXCSR  ;MASTER RESET
2469
2470                                     ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
2471 011614 012777 064001 006736      MOV      #MTDATA!CLK!MINT!BREAK,@TXCSR
2472
2473                                     ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
2474 011622 012777 024000 006724      MOV      #SYNEXT!SEVEN!NOPAR!0,@PARCSR
2475 011630 052777 000020 006706      BIS      #SYNSCH,@RXCSR  ;SET SEARCH SYNC
2476                                     ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
2477 011636 042777 020000 006714      BIC      #CLK,@TXCSR     ;POKE CLK DOWN
2478 011644 052777 020000 006706      BIS      #CLK,@TXCSR     ;POKE CLK UP
2479 011652 016703 006672                                     MOV      RXDBUF,R3      ;SET UP FOR ERROR MESSAGE
2480 011656 012700 000125                                     MOV      #125,R0 ;EXPECTED
2481 011662 012767 000007 167250      MOV      #7,SHIFT        ;# OF SHIFTS
2482 011670 012767 000125 167246      MOV      #125,TEMP1      ;DATA CHAR
2483 011676 004767 006346      JSR      PC,RPOKE        ;SHIFT IN THIS CHAR
2484 011702 105777 006636      TSTB    @RXCSR ;RXDONE ?
2485 011706 100401                                     BMI      64$
2486 011710 104000      HLT      ;RXDONE SHOULD BE SET
2487 011712
2488 011712 017701 006632      64$:      MOV      @RXDBUF,R1      ;ACTUAL
2489 011716 020001      CMP      R0,R1      ;COMPARE EXPECTED VS. ACTUAL
2490 011720 001401      BEQ      65$
2491 011722 104002      HLT      2          ;RECEIVED DATA DID NOT MATCH
2492                                     ;EXPECTED DATA - CHECK MAINT DATA
2493                                     ;OR RECEIVER LOGIC
2494 011724
2495 011724 012767 000007 167206      65$:      MOV      #7,SHIFT        ;# OF SHIFTS
2496 011732 012767 000125 167204      MOV      #125,TEMP1      ;DATA CHAR
2497 011740 004767 006304      JSR      PC,RPOKE        ;SHIFT IN THIS CHAR
2498                                     ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
2499 011744 012767 000007 167166      MOV      #7,SHIFT        ;# OF SHIFTS
2500 011752 012767 000125 167164      MOV      #125,TEMP1      ;DATA CHAR
2501 011760 004767 006264      JSR      PC,RPOKE        ;SHIFT IN THIS CHAR
2502 011764 012700 140125      MOV      #140000!125,R0 ;EXPECTED DATA PLUS
2503                                     ;RXERR & OVRUN
2504 011770 017701 006554      MOV      @RXDBUF,R1      ;ACTUAL
2505 011774 020001      CMP      R0,R1      ;COMPARE EXP VS. ACT
  
```

```

2506 011776 001401          BEQ      66$
2507 012000 104002          HLT      2      ;SPECIFICALLY LOOK AT RXERR &
2508                                     ;OVRUN BITS...THEY BOTH SHOULD BE SET
2509 012002          66$:
2510 012002 104400          SCOPE
2511                                     ::THIS TEST VERIFYS WORD LENGTH SELECT OF THE
2512                                     ::RECEIVER SECTION,IT USES THE ERROR FLAGS
2513                                     ::TO DETERMINE THAT IT WAS SELECTED CORRECTLY
2514                                     ::(OVRUN,RXERR)
2515                                     ::MODE:SYNEXT
2516                                     ::LENGTH:SEVEN
2517                                     ::CHAR:52
2518                                     ::
2519 012004 012767 000026 167114 TST22: MOV      #22,TSTNO      ;SAVE THIS
2520 012012 012767 012232 167076      MOV      #TST23,NEXT      ;GO TO THIS TEST WHEN THRU
2521 012020 052777 000400 006532      BIS      #MRESET,@TXCSR  ;MASTER RESET
2522 012026 012777 020000 006520      MOV      #SYNEXT,@PARCSR ;SET THE MODE
2523 012034 052777 000400 006516      BIS      #MRESET,@TXCSR  ;MASTER RESET
2524
2525                                     ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
2526 012042 012777 064001 006510      MOV      #MTDATA!CLK!MINT!BREAK,@TXCSR
2527
2528                                     ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
2529 012050 012777 024000 006476      MOV      #SYNEXT!SEVEN!NOPAR!0,@PARCSR
2530 012056 052777 000020 006460      BIS      #SYNSCH,@RXCSR  ;SET SEARCH SYNC
2531                                     ;POKE CLK TO GET LOGIC INTO SYNCHRONIZATION
2532 012064 042777 020000 006466      BIC      #CLK,@TXCSR     ;POKE CLK DOWN
2533 012072 052777 020000 006460      BIS      #CLK,@TXCSR     ;POKE CLK UP
2534 012100 016703 006444          MOV      RXDBUF,R3      ;SET UP FOR ERROR MESSAGE
2535 012104 012700 000052          MOV      #52,R0        ;EXPECTED
2536 012110 012767 000007 167022      MOV      #7,SHIFT      ;# OF SHIFTS
2537 012116 012767 000052 167020      MOV      #52,TEMP1     ;DATA CHAR
2538 012124 004767 006120          JSR      PC,RPOKE      ;SHIFT IN THIS CHAR
2539 012130 105777 006410          TSTB    @RXCSR ;RXDONE ?
2540 012134 100401          BMI     64$
2541 012136 104000          HLT     ;RXDONE SHOULD BE SET
2542 012140          64$:
2543 012140 017701 006404          MOV      @RXDBUF,R1    ;ACTUAL
2544 012144 020001          CMP     R0,R1        ;COMPARE EXPECTED VS. ACTUAL
2545 012146 001401          BEQ     65$
2546 012150 104002          HLT     2            ;RECEIVED DATA DID NOT MATCH
2547                                     ;EXPECTED DATA - CHECK MAINT DATA
2548                                     ;OR RECEIVER LOGIC
2549          65$:
2550 012152 012767 000007 166760      MOV      #7,SHIFT      ;# OF SHIFTS
2551 012160 012767 000052 166756      MOV      #52,TEMP1     ;DATA CHAR
2552 012166 004767 006056          JSR      PC,RPOKE      ;SHIFT IN THIS CHAR
2553                                     ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
2554 012172 012767 000007 166740      MOV      #7,SHIFT      ;# OF SHIFTS
2555 012200 012767 000052 166736      MOV      #52,TEMP1     ;DATA CHAR
2556 012206 004767 006036          JSR      PC,RPOKE      ;SHIFT IN THIS CHAR
2557 012212 012700 140052          MOV      #140000!52,R0 ;EXPECTED DATA PLUS
2558                                     ;RXERR & OVRUN
2559 012216 017701 006326          MOV      @RXDBUF,R1    ;ACTUAL
2560 012222 020001          CMP     R0,R1        ;COMPARE EXP VS. ACT
2561 012224 001401          BEQ     66$
  
```



```

2618                                     ;OVRUN BITS...THEY BOTH SHOULD BE SET
2619 012456                                66$:
2620 012456 104400                          SCOPE
2621                                     ::THIS TEST VERIFYS WORD LENGTH SELECT OF THE
2622                                     ::RECEIVER SECTION,IT USES THE ERROR FLAGS
2623                                     ::TO DETERMINE THAT IT WAS SELECTED CORRECTLY
2624                                     ::(OVRUN,RXERR)
2625                                     ::MODE:SYNEXT
2626                                     ::LENGTH:SEVEN
2627                                     ::CHAR:0
2628
2629 012460 012767 000030 166440 TST24: MOV #24,TSTNO ;SAVE THIS
2630 012466 012767 012706 166422      MOV #TST25,NEXT ;GO TO THIS TEST WHEN THRU
2631 012474 052777 000400 006056      BIS #MRESET,@TXCSR ;MASTER RESET
2632 012502 012777 020000 006044      MOV #SYNEXT,@PARCSR ;SET THE MODE
2633 012510 052777 000400 006042      BIS #MRESET,@TXCSR ;MASTER RESET
2634
2635                                     ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
2636 012516 012777 064001 006034      MOV #MTDATA!CLK!MINT!BREAK,@TXCSR
2637
2638                                     ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
2639 012524 012777 024000 006022      MOV #SYNEXT!SEVEN!NOPAR!0,@PARCSR
2640 012532 052777 000020 006004      BIS #SYNSCH,@RXCSR ;SET SEARCH SYNC
2641                                     ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
2642 012540 042777 020000 006012      BIC #CLK,@TXCSR ;POKE CLK DOWN
2643 012546 052777 020000 006004      BIS #CLK,@TXCSR ;POKE CLK UP
2644 012554 016703 005770              MOV RXDBUF,R3 ;SET UP FOR ERROR MESSAGE
2645 012560 012700 000000              MOV #0,R0 ;EXPECTED
2646 012564 012767 000007 166346      MOV #7,SHIFT ;# OF SHIFTS
2647 012572 012767 000000 166344      MOV #0,TEMP1 ;DATA CHAR
2648 012600 004767 005444              JSR PC,RPOKE ;SHIFT IN THIS CHAR
2649 012604 105777 005734              TSTB @RXCSR ;RXDONE ?
2650 012610 100401                      BMI 64$
2651 012612 104000                      HLT ;RXDONE SHOULD BE SET
2652
2653 012614 017701 005730 64$:          MOV @RXDBUF,R1 ;ACTUAL
2654 012620 020001                      CMP R0,R1 ;COMPARE EXPECTED VS. ACTUAL
2655 012622 001401                      BEQ 65$
2656 012624 104002                      HLT 2 ;RECEIVED DATA DID NOT MATCH
2657                                     ;EXPECTED DATA - CHECK MAINT DATA
2658                                     ;OR RECE!VER LOGIC
2659
2660 012626 012767 000007 166304 65$:  MOV #7,SHIFT ;# OF SHIFTS
2661 012634 012767 000000 166302      MOV #0,TEMP1 ;DATA CHAR
2662 012642 004767 005402              JSR PC,RPOKE ;SHIFT IN THIS CHAR
2663                                     ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
2664 012646 012767 000007 166264      MOV #7,SHIFT ;# OF SHIFTS
2665 012654 012767 000000 166262      MOV #0,TEMP1 ;DATA CHAR
2666 012662 004767 005362              JSR PC,RPOKE ;SHIFT IN THIS CHAR
2667 012666 012700 140000              MOV #140000!0,R0 ;EXPECTED DATA PLUS
2668                                     ;RXERR & OVRUN
2669 012672 017701 005652              MOV @RXDBUF,R1 ;ACTUAL
2670 012676 020001                      CMP R0,R1 ;COMPARE EXP VS. ACT
2671 012700 001401                      BEQ 66$
2672 012702 104002                      HLT 2 ;SPECIFICALLY LOOK AT RXERR &
2673                                     ;OVRUN BITS...THEY BOTH SHOULD BE SET

```

```

2674 012704
2675 012704 104400
2676
2677
2678
2679
2680
2681
2682
2683
2684 012706 012767 000031 166212 TST25: MOV #25,TSTNO ;SAVE THIS
2685 012714 012767 013134 166174 MOV #TST26,NEXT ;GO TO THIS TEST WHEN THRU
2686 012722 052777 000400 005630 BIS #MRESET,@TXCSR ;MASTER RESET
2687 012730 012777 020000 005616 MOV #SYNEXT,@PARCSR ;SET THE MODE
2688 012736 052777 000400 005614 BIS #MRESET,@TXCSR ;MASTER RESET
2689
2690 ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
2691 012744 012777 064001 005606 MOV #MTDATA!CLK!MINT!BREAK,@TXCSR
2692
2693 ;SET MODE,# OF BITS,PARITY SENSE,&LOAD SYNC REG
2694 012752 012777 026000 005574 MOV #SYNEXT!EIGHT!NOPAR!0,@PARCSR
2695 012760 052777 000020 005556 BIS #SYNSCH,@RXCSR ;SET SEARCH SYNC
2696 ;POKE CLK TO GET LOGIC INTO SYNCHRONIZATION
2697 012766 042777 020000 005564 BIC #CLK,@TXCSR ;POKE CLK DOWN
2698 012774 052777 020000 005556 BIS #CLK,@TXCSR ;POKE CLK UP
2699 013002 016703 005542 MOV RXDBUF,R3 ;SET UP FOR ERROR MESSAGE
2700 013006 012700 000125 MOV #125,R0 ;EXPECTED
2701 013012 012767 000010 166120 MOV #8,SHIFT ;# OF SHIFTS
2702 013020 012767 000125 166116 MOV #125,TEMP1 ;DATA CHAR
2703 013026 004767 005216 JSR PC,RPOKE ;SHIFT IN THIS CHAR
2704 013032 105777 005506 TSTB @RXCSR ;RXDONE ?
2705 013036 100401 BMI 64$
2706 013040 104000 HLT ;RXDONE SHOULD BE SET
2707 013042
2708 013042 017701 005502 64$: MOV @RXDBUF,R1 ;ACTUAL
2709 013046 020001 CMP R0,R1 ;COMPARE EXPECTED VS. ACTUAL
2710 013050 001401 BEQ 65$
2711 013052 104002 HLT 2 ;RECEIVED DATA DID NOT MATCH
2712 ;EXPECTED DATA - CHECK MAINT DATA
2713 ;OR RECEIVER LOGIC
2714 013054
2715 013054 012767 000010 166056 65$: MOV #8,SHIFT ;# OF SHIFTS
2716 013062 012767 000125 166054 MOV #125,TEMP1 ;DATA CHAR
2717 013070 004767 005154 JSR PC,RPOKE ;SHIFT IN THIS CHAR
2718 ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
2719 013074 012767 000010 166036 MOV #8,SHIFT ;# OF SHIFTS
2720 013102 012767 000125 166034 MOV #125,TEMP1 ;DATA CHAR
2721 013110 004767 005134 JSR PC,RPOKE ;SHIFT IN THIS CHAR
2722 013114 012700 140125 MOV #140000!125,R0 ;EXPECTED DATA PLUS
2723 ;RXERR & OVERRUN
2724 013120 017701 005424 MOV @RXDBUF,R1 ;ACTUAL
2725 013124 020001 CMP R0,R1 ;COMPARE EXP VS. ACT
2726 013126 001401 BEQ 66$
2727 013130 104002 HLT 2 ;SPECIFICALLY LOOK AT RXERR &
2728 ;OVERRUN BITS...THEY BOTH SHOULD BE SET
2729 013132 66$:

```

```

2730 013132 104400          SCOPE
2731                      ::THIS TEST VERIFYS WORD LENGTH SELECT OF THE
2732                      ::RECEIVER SECTION,IT USES THE ERROR FLAGS
2733                      ::TO DETERMINE THAT IT WAS SELECTED CORRECTLY
2734                      ::(OVRUN,RXERR)
2735                      ::MODE:SYNEXT
2736                      ::LENGTH:EIGHT
2737                      ::CHAR:252
2738                      ::
2739 013134 012767 000032 165764 TST26: MOV #26,TSTNO ;SAVE THIS
2740 013142 012767 013362 165746 MOV #TST27,NEXT ;GO TO THIS TEST WHEN THRU
2741 013150 052777 000400 005402 BIS #MRESET,@TXCSR ;MASTER RESET
2742 013156 012777 020000 005370 MOV #SYNEXT,@PARCSR ;SET THE MODE
2743 013164 052777 000400 005366 BIS #MRESET,@TXCSR ;MASTER RESET
2744
2745                      ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
2746 013172 012777 064001 005360 MOV #MTDATA!CLK!MINT!BREAK,@TXCSR
2747
2748                      ;SET MODE,# OF BITS,PARITY SENSE,&LOAD SYNC REG
2749 013200 012777 026000 005346 MOV #SYNEXT!EIGHT!NOPAR!0,@PARCSR
2750 013206 052777 000020 005330 BIS #SYNSCH,@RXCSR ;SET SEARCH SYNC
2751                      ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
2752 013214 042777 020000 005336 BIC #CLK,@TXCSR ;POKE CLK DOWN
2753 013222 052777 020000 005330 BIS #CLK,@TXCSR ;POKE CLK UP
2754 013230 016703 005314 MOV RXDBUF,R3 ;SET UP FOR ERROR MESSAGE
2755 013234 012700 000252 MOV #252,R0 ;EXPECTED
2756 013240 012767 000010 165672 MOV #8,SHIFT ;# OF SHIFTS
2757 013246 012767 000252 165670 MOV #252,TEMP1 ;DATA CHAR
2758 013254 004767 004770 JSR PC,RPOKE ;SHIFT IN THIS CHAR
2759 013260 105777 005260 TSTB @RXCSR ;RXDONE ?
2760 013264 100401 BMI 64$
2761 013266 104000 HLT ;RXDONE SHOULD BE SET
2762 013270
2763 013270 017701 005254 64$: MOV @RXDBUF,R1 ;ACTUAL
2764 013274 020001 CMP R0,R1 ;COMPARE EXPECTED VS. ACTUAL
2765 013276 001401 BEQ 65$
2766 013300 104002 HLT 2 ;RECEIVED DATA DID NOT MATCH
2767                      ;EXPECTED DATA - CHECK MAINT DATA
2768                      ;OR RECEIVER LOGIC
2769 013302
2770 013302 012767 000010 165630 65$: MOV #8,SHIFT ;# OF SHIFTS
2771 013310 012767 000252 165626 MOV #252,TEMP1 ;DATA CHAR
2772 013316 004767 004726 JSR PC,RPOKE ;SHIFT IN THIS CHAR
2773                      ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
2774 013322 012767 000010 165610 MOV #8,SHIFT ;# OF SHIFTS
2775 013330 012767 000252 165606 MOV #252,TEMP1 ;DATA CHAR
2776 013336 004767 004706 JSR PC,RPOKE ;SHIFT IN THIS CHAR
2777 013342 012700 140252 MOV #140000!252,R0 ;EXPECTED DATA PLUS
2778                      ;RXERR & OVRUN
2779 013346 017701 005176 MOV @RXDBUF,R1 ;ACTUAL
2780 013352 020001 CMP R0,R1 ;COMPARE EXP VS. ACT
2781 013354 001401 BEQ 66$
2782 013356 104002 HLT 2 ;SPECIFICALLY LOOK AT RXERR &
2783                      ;OVRUN BITS...THEY BOTH SHOULD BE SET
2784 013360
2785 013360 104400 66$: SCOPE
  
```

```

2786                                     ;; THIS TEST VERIFYS WORD LENGTH SELECT OF THE
2787                                     ;; RECEIVER SECTION, IT USES THE ERROR FLAGS
2788                                     ;; TO DETERMINE THAT IT WAS SELECTED CORRECTLY
2789                                     ;; (OVRRUN, RXERR)
2790                                     ;; MODE: SYNEXT
2791                                     ;; LENGTH: EIGHT
2792                                     ;; CHAR: 377
2793
2794 013362 012767 000033 165536 TST27: MOV #27, TSTNO ;SAVE THIS
2795 013370 012767 013610 165520 MOV #TST28, NEXT ;GO TO THIS TEST WHEN THRU
2796 013376 052777 000400 005154 BIS #MRESET, @TXCSR ;MASTER RESET
2797 013404 012777 020000 005142 MOV #SYNEXT, @PARCSR ;SET THE MODE
2798 013412 052777 000400 005140 BIS #MRESET, @TXCSR ;MASTER RESET
2799
2800 ;SET MAINT DATA, CLK, BREAK, & MAINTENANCE MODE
2801 013420 012777 064001 005132 MOV #MTDATA!CLK!MINT!BREAK, @TXCSR
2802
2803 ;SET MODE, # OF BITS, PARITY SENSE, & LOAD SYNC REG
2804 013426 012777 026000 005120 MOV #SYNEXT!EIGHT!NOPAR!0, @PARCSR
2805 013434 052777 000020 005102 BIS #SYNSCH, @RXCSR ;SET SEARCH SYNC
2806 ;POKE CLK TO GET LOGIC INTO SYNCHRONIZATION
2807 013442 042777 020000 005110 BIC #CLK, @TXCSR ;POKE CLK DOWN
2808 013450 052777 020000 005102 BIS #CLK, @TXCSR ;POKE CLK UP
2809 013456 016703 005066 MOV RXDBUF, R3 ;SET UP FOR ERROR MESSAGE
2810 013462 012700 000377 MOV #377, R0 ;EXPECTED
2811 013466 012767 000010 165444 MOV #8, SHIFT ;# OF SHIFTS
2812 013474 012767 000377 165442 MOV #377, TEMP1 ;DATA CHAR
2813 013502 004767 004542 JSR PC, RPOKE ;SHIFT IN THIS CHAR
2814 013506 105777 005032 TSTB @RXCSR ;RXDONE ?
2815 013512 100401 BMI 64$
2816 013514 104000 HLT ;RXDONE SHOULD BE SET
2817 013516
2818 013516 017701 005026 64$: MOV @RXDBUF, R1 ;ACTUAL
2819 013522 020001 CMP R0, R1 ;COMPARE EXPECTED VS. ACTUAL
2820 013524 001401 BEQ 65$
2821 013526 104002 HLT 2 ;RECEIVED DATA DID NOT MATCH
2822 ;EXPECTED DATA - CHECK MAINT DATA
2823 ;OR RECEIVER LOGIC
2824 013530
2825 013530 012767 000010 165402 65$: MOV #8, SHIFT ;# OF SHIFTS
2826 013536 012767 000377 165400 MOV #377, TEMP1 ;DATA CHAR
2827 013544 004767 004500 JSR PC, RPOKE ;SHIFT IN THIS CHAR
2828 ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
2829 013550 012767 000010 165362 MOV #8, SHIFT ;# OF SHIFTS
2830 013556 012767 000377 165360 MOV #377, TEMP1 ;DATA CHAR
2831 013564 004767 004460 JSR PC, RPOKE ;SHIFT IN THIS CHAR
2832 013570 012700 140377 MOV #140000!377, R0 ;EXPECTED DATA PLUS
2833 ;RXERR & OVRRUN
2834 013574 017701 004750 MOV @RXDBUF, R1 ;ACTUAL
2835 013600 020001 CMP R0, R1 ;COMPARE EXP VS. ACT
2836 013602 001401 BEQ 66$
2837 013604 104002 HLT 2 ;SPECIFICALLY LOOK AT RXERR &
2838 ;OVRRUN BITS...THEY BOTH SHOULD BE SET
2839 013606
2840 013606 104400 66$: SCOPE
2841 ;: THIS TEST VERIFYS WORD LENGTH SELECT OF THE

```

```

2842                                     ;;RECEIVER SECTION,IT USES THE ERROR FLAGS
2843                                     ;;TO DETERMINE THAT IT WAS SELECTED CORRECTLY
2844                                     ;;(OVRUN,RXERR)
2845                                     ;;MODE:SYNEXT
2846                                     ;;LENGTH:EIGHT
2847                                     ;;CHAR:0
2848                                     ;;
2849 013610 012767 000034 165310 TST28: MOV #28,TSTNO ;SAVE THIS
2850 013616 012767 014036 165272 MOV #.EOP,NEXT ;GO TO THIS TEST WHEN THRU
2851 013624 052777 000400 004726 BIS #MRESET,@TXCSR ;MASTER RESET
2852 013632 012777 020000 004714 MOV #SYNEXT,@PARCSR ;SET THE MODE
2853 013640 052777 000400 004712 BIS #MRESET,@TXCSR ;MASTER RESET
2854
2855 ;SET MAINT DATA,CLK,BREAK,&MAINTENANCE MODE
2856 013646 012777 064001 004704 MOV #MNTDATA!CLK!MINT!BREAK,@TXCSR
2857
2858 ;SET MODE ,# OF BITS,PARITY SENSE,&LOAD SYNC REG
2859 013654 012777 026000 004672 MOV #SYNEXT!EIGHT!NOPAR!0,@PARCSR
2860 013662 052777 000020 004654 BIS #SYNSCH,@RXCSR ;SET SEARCH SYNC
2861 ;POKE CLK TO GET LOGIC INTO SYNCRONIZATION
2862 013670 042777 020000 004662 BIC #CLK,@TXCSR ;POKE CLK DOWN
2863 013676 052777 020000 004654 BIS #CLK,@TXCSR ;POKE CLK UP
2864 013704 016703 004640 MOV RXDBUF,R3 ;SET UP FOR ERROR MESSAGE
2865 013710 012700 000000 MOV #0,R0 ;EXPECTED
2866 013714 012767 000010 165216 MOV #8.,SHIFT ;# OF SHIFTS
2867 013722 012767 000000 165214 MOV #0,TEMP1 ;DATA CHAR
2868 013730 004767 004314 JSR PC,RPOKE ;SHIFT IN THIS CHAR
2869 013734 105777 004604 TSTB @RXCSR ;RXDONE ?
2870 013740 100401 BMI 64$
2871 013742 104000 HLT ;RXDONE SHOULD BE SET
2872 013744 64$:
2873 013744 017701 004600 MOV @RXDBUF,R1 ;ACTUAL
2874 013750 020001 CMP R0,R1 ;COMPARE EXPECTED VS. ACTUAL
2875 013752 001401 BEQ 65$
2876 013754 104002 HLT 2 ;RECEIVED DATA DID NOT MATCH
2877 ;EXPECTED DATA - CHECK MAINT DATA
2878 ;OR RECEIVER LOGIC
2879 013756 65$:
2880 013756 012767 000010 165154 MOV #8.,SHIFT ;# OF SHIFTS
2881 013764 012767 000000 165152 MOV #0,TEMP1 ;DATA CHAR
2882 013772 004767 004252 JSR PC,RPOKE ;SHIFT IN THIS CHAR
2883 ;NOW SHIFT IN A SECOND CHARACTER WITHOUT READING RXDBUF
2884 013776 012767 000010 165134 MOV #8.,SHIFT ;# OF SHIFTS
2885 014004 012767 000000 165132 MOV #0,TEMP1 ;DATA CHAR
2886 014012 004767 004232 JSR PC,RPOKE ;SHIFT IN THIS CHAR
2887 014016 012700 140000 MOV #140000!0,R0 ;EXPECTED DATA PLUS
2888 ;RXERR & OVRUN
2889 014022 017701 004522 MOV @RXDBUF,R1 ;ACTUAL
2890 014026 020001 CMP R0,R1 ;COMPARE EXP VS. ACT
2891 014030 001401 BEQ 66$
2892 014032 104002 HLT 2 ;SPECIFICALLY LOOK AT RXERR &
2893 ;OVRUN BITS...THEY BOTH SHOULD BE SET
2894 014034 66$:
2895 014034 104400 SCOPE

```

```

2896
2897
2898
2899
2900
2901
2902
2903 014036 104402
2904 014040 017200
2905 014042 104410 014274
2906 014046 104402 016721
2907 014052 105767 165124
2908 014056 001511
2909 014060 005767 165132
2910 014064 001007
2911 014066 104402 016733
2912 014072 016700 165120
2913 014076 000000
2914
2915 014100 000167 165314
2916 014104 062767 000010 165072
2917 014112 062767 000010 165072
2918 014120 000241
2919 014122 006167 165072
2920 014126 103410
2921
2922 014130 036767 165064 165060
2923 014136 001762
2924 014140 004767 000034
2925 014144 000167 000174
2926 014150 012767 000001 165042
2927
2928 014156 016767 165024 165020
2929 014164 016767 165024 165020
2930 014172 004767 000002
2931 014176 000441
2932 014200 016767 165000 004040
2933 014206 004767 003702
2934 014212 016767 164774 004350
2935 014220 062767 000002 164764
2936 014226 016767 164760 004336
2937 014234 062767 000002 164750
2938 014242 016767 164744 004324
2939 014250 062767 000002 164734
2940 014256 016767 164730 004312
2941 014264 016767 004300 164720
2942 014272 000207
2943
2944 014274 000001
2945 014276 006 002
2946 014300 020544
2947
2948 014302
2949 014302 005067 164626
2950 014306 005067 164734
2951 014312 005267 164612

```

```

:END OF PASS
:TYPE NAME OF TEST
:UPDATE PASS COUNT
:CHECK FOR EXIT TO ACT-11
:RESTART TEST

.EOP: TYPE ;TYPE NAME OF TEST
MEPASS
CONVRT ,OUTCRY
TYPE ,DEVICE
TSTB MULTD - ;ARE YOU RUNNING MULTIPLE DEVICES ?
BEQ CCC ;NO, JUMP AROUND
TST ACTREG ;ARE ANY DEVICES ACTIVE ?
BNE RUNIT ;YES
TYPE ,MCOW ;NO
MOV ACTREG,RO ;DISPLAY ACTREG
HALT ;SELECT SOMETHING TO RUN @ ACTREG:
;SELECT SWITCHES & HIT CONTINUE (PUT SW00 =1)
JMP .START ;START OVER AGAIN.....YOU DESELECTED EVERYTHING
ADD #10,BASEADD ;NEXT BLOCK (ADDRESSES)
ADD #10,BASEIV ;NEXT BLOCK (VECTORS)
CLC
ROL ROTADD ;UP DATE ROTATING POINTER
BCS 2$ ;IS IT THE LAST DEVICE
;TO BE TESTED IN THIS PASS ?
BIT ROTADD,ACTREG ;TEST THIS DEVICE FOR ACTIVE STATUS
BEQ RUNIT ;IF NOT ACTIVE, TRY NEXT ADDRESS
JSR PC,REPLAY ;CALCULATE NEW PARAMETERS
JMP RESTRT ;YES IT WAS ACTIVE,TEST THIS DEVICE
MOV #1,ROTADD ;OK!,NOW SET UP ROTATING
;POINTER FOR NEXT MULTIPLE PASS
MOV KEEPADD,BASEADD ;RESTORE BASE ADDRESS
MOV KEEPIV,BASEIV ;RESTORE BASE INTERRUPT VECTORS
JSR PC,REPLAY ;CALC NEW PARAMETERS
BR CCC ;JUMP AROUND REPLAY
REPLAY: MOV BASEADD,DUBASE ;SET UP FOR NEW ADDRESSES
JSR PC,DUADDR ;CREATE NEW ADDRESSES
MOV BASEIV,DURIV ;CREATE DURIV
ADD #2,BASEIV
MOV BASEIV,DURIS ;CREATE DURIS
ADD #2,BASEIV
MOV BASEIV,DUTIV ;CREATE DUTIV
ADD #2,BASEIV
MOV BASEIV,DUTIS ;CREATE DUTIS
MOV DURIV,BASEIV ;RESTORE
RTS PC

OUTCRY: 1
.BYTE 6,2
RXCSR

CCC: CLR LSTERR ;CLEAR LAST ERROR PC
CLR ER:FLG ;CLEAR ERROR FLAG
INC PASCNT ;UPDATE PASS COUNT

```

```

2952 014316 016777 164606 164556      MOV    PASCNT,@LIGHTS      ;DISPLAY PASS COUNT
2953 014324 013701 000042              MOV    @#42,R1             ;CHECK FOR ACT-11 OR DDP
2954 014330 001405                      BEQ    RESTRT              ;IF NOT, CONTINUE TESTING
2955 014332 000005                      RESET
2956 014334 004711                      LOGICAL: JSR    PC,(R1)
2957 014336 000240                      NOP
2958 014340 000240                      NOP
2959 014342 000240                      NOP
2960 014344 012767 000340 163424  RESTRT: MOV    #340,PS      ;PREVENT INTERRUPTS (PRIO: 7)
2961 014352 104413                      CKSWR                      ;CHECK FOR ^G
2962 014354 012767 003446 164532      MOV    #TST1,RTRN
2963 014362 000167 167060              JMP    TST1
2964
2965
2966
2967 014366                      ;SCOPE LOOP AND INTERATION HANDLER
2968
2969 014366 000424                      .SCOPE:
2970
2971 014370 013746 000004              ;**** START OF CODE FOR THE X OR TESTER *****
2972 014374 012737 014414 000004      BR     4$                  ;IF RUNNING ON THE X OR TESTER CHANGE
2973 014402 005737 177060              MOV    @#4,-(SP)          ;THIS INSTRUCTION TO A 'NOP'(NOP=240)
2974 014406 012637 000004              MOV    #1$,@#4           ;SAVE CONTENTS OF ERROR VECTOR
2975 014412 000404                      TST    @#177060          ;SET FOR TIME OUT
2976 014414 022626                      MOV    (SP)+,@#4         ;TIME OUT ON X OR ?
2977 014416 012637 000004              BR     2$                 ;RESTORE ERROR VECTOR
2978 014422 000403                      BR     2$                 ;GO TO NEXT TEST
2979 014424 016767 164466 164462      CMP    (SP)+,(SP)+       ;CLEAR THE STACK AFTER A TIMEOUT
2980 014432 016716 164456              MOV    (SP)+,@#4         ;RESTORE ERROR VECTOR
2981 014436 000002                      BR     3$                 ;LOOP ON PRESENT TEST
2982 014440                      2$: MOV    NEXT,RTRN      ;SET UP NEXT TEST IN RTRN
2983 014440                      3$: MOV    RTRN,(SP)     ;SET UP STACK FOR RTI
2984 014442 032777 040000 164430      RTI
2985 014450 001407                      ;**** END OF CODE FOR THE X OR TESTER *****
2986 014452 000432                      CKSWR                      ;CHECK FOR ^G
2987 014454 105777 164424              BIT    #SW14,@SWR        ;LOOP ON CURRENT TEST ?
2988 014460 100027                      TTST: BEQ    1$
2989 014462 017700 164420              BR     3$
2990 014466 000412                      TSTB  @TKCSR             ;TEST TTY FLAG
2991 014470 032777 004000 164402      BPL    3$
2992 014476 001006                      MOV    @TKDBR,R0        ;CLR DONE BIT
2993 014500 005267 164420              BR     2$                 ;IF A TTY KEY IS STRUCK GO TO NEXT TST
2994 014504 026767 164414 164410      BIT    #SW11,@SWR       ;INHIBIT ITERATIONS ?
2995 014512 101412                      BNE    2$
2996 014514 105067 164526              INC    LPCNT
2997 014520 005067 164400              CMP    LPCNT,ICOUNT     ;CHECK FOR ITERATION CNT FINISH
2998 014524 012767 000005 164370      BLOS  3$
2999 014532 016767 164360 164354      CLRB  ERRFLG
3000 014540 016716 164350              CLR    LPCNT
3001 014544 000002                      MOV    #5,ICOUNT        ;SET UP ITERATION COUNT
3002 014546 001407                      MOV    NEXT,RTRN       ;SET UP NEXT TEST IN RTRN
3003 014550 000432                      MOV    RTRN,(SP)       ;SET UP STACK FOR RTI
3004
3005
3006
3007 014552 104413                      BRW: 140'                ;RESTORE 'BEQ 1$' INSTRUCTION
                                BRX: 432                ;RESTORE 'BR 3$' INSTRUCTION
                                ;CHECK FOR FREEZE ON CURRENT DATA
                                .SCOPE1: CKSWR          ;CHECK FOR ^G

```

```

3008 014554 032777 001000 164316      BIT      #SW09,@SWR
3009 014562 001402                BEQ      1$
3010 014564 016716 164330                MOV      LOCK,(SP)
3011 014570 000002                1$:     RTI
3012
3013                                ;TELETYPE OUTPUT ROUTINE
3014
3015 014572 010546                .TYPE:  MOV      R5,-(SP)
3016 014574 017605 000002                MOV      @2(SP),R5
3017 014600 062766 000002 000002                ADD      #2,2(SP)
3018 014606 105715                1$:     TSTB      (R5)                ;LOOK FOR '0'
3019 014610 001406                BEQ      3$
3020 014612 105777 164272                2$:     TSTB      @TPCSR                ;TEST DONE BIT
3021 014616 100375                BPL      2$
3022 014620 112577 164266                MOV      (R5)+,@TPDBR                ;TYPE CHAR
3023 014624 000770                BR       1$                ;DO IT AGAIN UNTIL '0' IS SEEN
3024 014626 012605                3$:     MOV      (SP)+,R5
3025 014630 000002                RTI
3026
3027                                ;ASCII STRING INPUT ROUTINE
3028
3029 014632 010346                .INSTR: MOV      R3,-(SP)
3030 014634 010446                MOV      R4,-(SP)
3031 014636 017667 000004 000010                MCV      @4(SP),.MSG
3032 014644 062766 000002 000004                ADD      #2,4(SP)
3033 014652 104402                .INST1: TYPE
3034 014654 000000                .MSG:   0
3035 014656 012704 017700                MOV      #INBUF,R4
3036 014662 012703 000007                MOV      #7,R3
3037 014666 105777 164212                1$:     TSTB      @TKCSR
3038 014672 100375                BPL      1$
3039 014674 117714 164206                MOV      @TKDBR,(R4)
3040 014700 142714 000200                BICB      #200,(R4)
3041 014704 121427 000025                CMPB      (R4),#25                ;IS IT <^U>
3042 014710 001003                BNE      200$
3043 014712 104402 017110                TYPE ,MCRLF
3044 014716 000755                BR       .INST1
3045 014720 122427 000015                200$:   CMPB      (R4)+,#15
3046 014724 001423                BEQ      INSTR2
3047 014726 117777 164154 164156                MOV      @TKDBR,@TPDBR
3048 014734 105777 164150                2$:     TSTB      @TPCSR
3049 014740 100375                BPL      2$
3050 014742 005303                DEC      R3
3051 014744 001350                BNE      1$
3052 014746 000402                BR       .INSTG
3053 014750 010346                .INSTE: MOV      R3,-(SP)
3054 014752 010446                MOV      R4,-(SP)
3055 014754 104402                .INSTG: TYPE
3056 014756 017104                MQM
3057 014760 005737 016246                TST      @#RDSW
3058 014764 001402                BEQ      400$
3059 014766 104402 017110                TYPE ,MCRLF
3060 014772 000727                400$:   BR       .INST1
3061 014774 012604                INSTR2: MOV      (SP)+,R4
3062 014776 012603                MOV      (SP)+,R3
3063 015000 000002                RTI

```

```

3064
3065
3066
3067 015002 010546
3068 015004 010446
3069 015006 016605 000004
3070 015012 012567 000170
3071 015016 012567 000166
3072 015022 012567 000164
3073 015026 112567 000162
3074 015032 112567 000157
3075 015036 010566 000004
3076 015042 005005
3077 015044 012704 017700
3078 015050 122714 000015
3079 015054 001420
3080 015056 121427 000060
3081 015062 002415
3082 015064 121427 000067
3083 015070 003012
3084 015072 142714 000060
3085 015076 152405
3086 015100 122714 000015
3087 015104 001414
3088 015106 006305
3089 015110 006305
3090 015112 006305
3091 015114 000760
3092 015116 122714 000015
3093 015122 001003
3094 015124 005737 016246
3095 015130 001023
3096 015132 104404
3097 015134 000742
3098
3099
3100
3101 015136 020567 000046
3102 015142 101365
3103 015144 020567 000036
3104 015150 103762
3105 015152 136705 000036
3106 015156 001357
3107
3108
3109
3110 015160 016704 000026
3111 015164 010524
3112 015166 062705 000002
3113 015172 105367 000017
3114 015176 001372
3115 015200 012604
3116 015202 012605
3117 015204 000002
3118 015206 000000
3119 015210 000000

;CONVERT ASCII STRING TO OCTAL
.PARAM: MOV R5,-(SP)
MOV R4,-(SP)
MOV 4(SP),R5
MOV (R5)+,LOLIM
MOV (R5)+,HILIM
MOV (R5)+,DEVADR
MOVB (R5)+,LOBITS
MOVB (R5)+,ADRCNT
MOV R5,4(SP)
PARAM1: CLR R5
MOV #INBUF,R4
CMPB #15,(R4)
BEQ PARERR
1$: CMPB (R4),#60
BLT PARERR
CMPB (R4),#67
BGT PARERR
BICB #60,(R4)
BISB (R4)+,R5
CMPB #15,(R4)
BEQ LIMITS
ASL R5
ASL R5
ASL R5
BR 1$
PARERR: CMPB #15,(R4) ;IS FIRST CHARACTER A <CR>
BNE 120$
TST @#RDSW ;IS CKSWR ROUTINE BEING USED
BNE PARTI
120$: INSTER
BR PARAM1

;TEST TO SEE IF NUMBER IS WITHIN LIMITS
LIMITS: CMP R5,HILIM
BHI PARERR
CMP R5,LOLIM
BLO PARERR
BITB LOBITS,R5
BNE PARERR

;STORE NUMBER AT SPECIFIED ADDRESS
1$: MOV DEVADR,R4
MOV R5,(R4)+
ADD #2,R5
DECB ADRCNT
BNE 1$
PARTI: MOV (SP)+,R4
MOV (SP)+,R5
RTI
LCLIM: 0
HILIM: 0

```

```

3120 015212 000000          DEVADR: 0
3121 015214 000000          LOBITS: 0
3122                015215          ADRCNT=LOBITS+1
3123
3124                ;SAVE PC OF TEST THAT FAILED AND R0-R5
3125
3126 015216 016667 000004 163750 .SAV05: MOV    4(SP),SAVPC
3127
3128                ;SAVE R0-R5
3129
3130 015224 010567 163740      SV05:  MOV    R5,SAVR5
3131 015230 010467 163732      MOV    R4,SAVR4
3132 015234 010367 163724      MOV    R3,SAVR3
3133 015240 010267 163716      MOV    R2,SAVR2
3134 015244 010167 163710      MOV    R1,SAVR1
3135 015250 010067 163702      MOV    R0,SAVR0
3136 015254 000002          RTI
3137
3138                ;RESTORE R0-R5
3139
3140 015256 016700 163674      .RES05: MOV    SAVR0,R0
3141 015262 016701 163672      MOV    SAVR1,R1
3142 015266 016702 163670      MOV    SAVR2,R2
3143 015272 016703 163666      MOV    SAVR3,R3
3144 015276 016704 163664      MOV    SAVR4,R4
3145 015302 016705 163662      MOV    SAVR5,R5
3146 015306 000002          RTI
3147
3148                ;CONVERT OCTAL NUMBER TO ASCII AND OUTPUT TO TELEPRINTER
3149
3150 015310 104402          .CONVR: TYPE
3151 015312 017110          MCRLF
3152 015314 010046          .CNVRT: MOV    R0,-(SP)
3153 015316 010146          MOV    R1,-(SP)
3154 015320 010346          MOV    R3,-(SP)
3155 015322 010446          MOV    R4,-(SP)
3156 015324 010546          MOV    R5,-(SP)
3157 015326 017601 000012      MOV    @12(SP),R1
3158 015332 016767 002402 163610  MOV    TEMP,TEMP3
3159 015340 062766 000002 000012  ADD    #2,12(SP)
3160 015346 012167 000154          MOV    (R1)+,WRDCNT
3161 015352 112167 000152          1$:  MOV    (R1)+,CHRCNT
3162 015356 112167 000147          MOV    (R1)+,SPACNT
3163 015362 013167 000144          MOV    @ (R1)+,BINWRD
3164 015366 016704 000140          2$:  MOV    BINWRD,R4
3165 015372 116705 000132          MOV    CHRCNT,R5
3166 015376 012700 017740          MOV    #TEMP,R0
3167 015402 010403          3$:  MOV    R4,R3
3168 015404 042703 177770          BIC    #177770,R3
3169 015410 062703 000060          ADD    #060,R3
3170 015414 110320          MOV    R3,(R0)+
3171 015416 006204          ASR    R4
3172 015420 042704 100000          BIC    #100000,R4
3173 015424 006204          ASR    R4
3174 015426 006204          ASR    R4
3175 015430 005305          DEC    R5

```

```

:SHIFT FOR NEXT #
:CLUGE TO STOP BIT 15 PROPAGATING.
:DITTO
:DITTO

```

3176	015432	001363				BNE	3\$	
3177	015434	012703	020000			MOV	#MDATA,R3	
3178	015440	114023			4\$:	MOVB	-(R0),(R3)+	
3179	015442	105367	000062			DECB	CHRCNT	
3180	015446	001374				BNE	4\$	
3181	015450	105767	000055			TSTB	SPACNT	
3182	015454	001405				BEQ	6\$	
3183	015456	112723	000040		5\$:	MOVB	#040,(R3)+	
3184	015462	105367	000043			DECB	SPACNT	
3185	015466	001373				BNE	5\$	
3186	015470	105013			6\$:	CLRB	(R3)	
3187	015472	104402				TYPE		
3188	015474	020000				MDATA		
3189	015476	005367	000024			DEC	WRDCNT	
3190	015502	001323				BNE	1\$	
3191	015504	016767	163440	002226		MOV	TEMP3,TEMP	
3192	015512	012605				MOV	(SP)+,R5	
3193	015514	012604				MOV	(SP)+,R4	
3194	015516	012603				MOV	(SP)+,R3	
3195	015520	012601				MOV	(SP)+,R1	
3196	015522	012600				MOV	(SP)+,R0	
3197	015524	000002				RTI		
3198	015526	000000				WRDCNT:	0	
3199	015530	000000				CHRCNT:	0	
3200		015531				SPACNT=	CHRCNT+1	
3201	015532	000000				BINWRD:	0	
3202								
3203								
3204								
3205								
3206								
3207								
3208	015534	017605	000000			.SETFLG:MOV	@(SP),R5	
3209	015540	122767	000116	002132		CMPB	#'N',INBUF	:IS IT 'N' ?
3210	015546	001002				BNE	1\$	
3211	015550	105015				CLRB	(R5) ;000	
3212	015552	000406				BR	2\$	
3213	015554	122767	000131	002116	1\$:	CMPB	#'Y',INBUF	:IS IT 'Y' ?
3214	015562	001005				BNE	3\$	
3215	015564	112715	177777			MOVB	#-1,(R5)	:377
3216	015570	062716	000002		2\$:	ADD	#2,(SP)	
3217	015574	000002				RTI		
3218	015576	104404			3\$:	INSTR		:RETRY
3219	015600	000755				BR	.SETFLG	
3220								
3221								
3222								
3223								
3224								
3225	015602	011646				.TRPSR:MOV	(SP),-(SP)	:GET PC OF RETURN
3226	015604	162716	000002			SUB	#2,(SP)	:PC OF TRAP
3227	015610	017616	000000			MOV	@(SP),(SP)	:GET TRP
3228	015614	006316			TRPOK:	ASL	(SP)	:MULTIPLY TRAP ARG BY 2
3229	015616	042716	177001			BIC	#177001,(SP)	:CLEAR UNWANTED BITS
3230	015622	062716	001366			ADD	#.TRPTAB,(SP)	:POINTER TO SUBROUTINE ADDRESS
3231	015626	017616	000000			MOV	@(SP),(SP)	:SUBROUTINE ADDRESS

:COMPARE THE FIRST CHARACTER IN THE TELETYPE INPUT
 :BUFFER TO THE CHARACTERS 'N' AND 'Y'.
 :IF THE CHARACTER IS 'N' CLEAR THE FLAG
 :IF THE CHARACTER IS 'Y' SET THE FLAG

:TRAP DISPATCH SERVICE
 :ARGUMENT OF TRAP IS EXTRACTED
 :AND USED AS OFFSET TO OBTAIN POINTER
 :TO SELECTED SUBROUTINE

```

3232 015632 000136      JMP      @(SP)+          ;GO TO SUBROUTINE
3233
3234                      ;ERROR HANDLER
3235
3236 015634 104413      .HLT:   CKSWR          ;CHECK FOR ^G
3237 015636 032777 020000 163234      BIT      #SW13,@SWR    ;INHIBIT ERROR TYPE OUT ?
3238 015644 001061      BNE     HALTS
3239 015646 021667 163262      CMP     (SP),LSTERR
3240 015652 001404      BEQ     1$
3241 015654 011667 163254      MOV     (SP),LSTERR
3242 015660 105067 163362      CLRB   ERRFLG
3243 015664 104406      1$:    SAVO5
3244 015666 011605      MOV     (SP),R5
3245 015670 162705 000002      SUB     #2,R5
3246 015674 011504      MOV     (R5),R4
3247 015676 006304      ASL    R4
3248 015700 061504      ADD     (R5),R4
3249 015702 006304      ASL    R4
3250 015704 042704 177001      BIC     #177001,R4
3251 015710 062704 020514      ADD     #.ERRTAB,R4
3252 015714 012467 000040      MOV     (R4)+,ERRMSG
3253 015720 012467 000046      MOV     (R4)+,DATAHD
3254 015724 011467 000054      MOV     (R4),DATABP
3255 015730 105767 163312      TSTB   ERRFLG
3256 015734 001403      BEQ     TYPMSG
3257 015736 005767 000042      TST    DATABP
3258 015742 001014      BNE     TYPDAT
3259 015744 104410      TYPMSG: CONVRT
3260 015746 016076      ERTABO
3261 015750 112767 177777 163270      MOVB   #-1,ERRFLG
3262 015756 104402      TYPE
3263 015760 000000      ERRMSG: 0
3264 015762 005767 000004      TST    DATAHD
3265 015766 001402      BEQ     TYPDAT
3266 015770 104402      TYPE
3267 015772 000000      DATAHD: 0
3268 015774 005767 000004      TYPDAT: TST    DATABP
3269 016000 001402      BEQ     RESREG
3270 016002 104410      CONVRT
3271 016004 000000      DATABP: 0
3272 016006 104407      RESREG: RESO5
3273 016010 005777 163064      HALTS: TST    @SWR
3274 016014 100005      BPL    EXITER
3275 016016 010046      PUSHRO
3276 016020 016600 000002      MOV     2(SP),R0
3277 016024 000000      HALT
3278 016026 012600      POPRO
3279 016030 104413      EXITER: CKSWR          ;CHECK FOR ^G
3280 016032 005267 163074      INC     ERRCNT
3281 016036 032777 000400 163034      BIT     #SW08,@SWR    ;LOOP ON ERROR ?
3282 016044 001007      BNE     1$
3283 016046 032777 002000 163024      BIT     #SW10,@SWR    ;ESCAPE TO NEXT ON ERROR ?
3284 016054 001407      BEQ     2$
3285 016056 016767 163034 163030      MOV     NEXT,RTRN    ;SET UP FOR NEXT TEST
3286 016064 012706 001100      1$:    MOV     #CTACK,SP    ;REINITIALIZE SP
3287 016070 000177 163020      JMP     @RTRN
  
```

```

3288 016074 000002      2$: RTI
3289 016076 000001      ERTAB: 1
3290 016100 006        002      .BYTE 6,2
3291 016102 001174      SAVPC
3292                                     ;ENTER HERE ON POWER FAILURE
3293
3294
3295 016104 010046      .PFAIL: MOV R0,-(SP) ;SAVE R0-R5 ON PROCESSOR STACK
3296 016106 010146      MOV R1,-(SP)
3297 016110 010246      MOV R2,-(SP)
3298 016112 010346      MOV R3,-(SP)
3299 016114 010446      MOV R4,-(SP)
3300 016116 010546      MOV R5,-(SP)
3301 016120 016746      161700      MOV 24,-(SP)
3302 016124 010667      163042      MOV SP,SAVSP ;SAVE STACK POINTER
3303 016130 012767      016142 161666      MOV #RESTART,24 ;SET UP FOR POWER UP TRAP
3304 016136 000000      HALT ;HALT ON POWER DOWN NORMAL
3305 016140 000777      1$: BR 1$
3306
3307                                     ;PROCESSOR WILL TRAP HERE WHEN POWER IS RESTORED
3308
3309 016142 016706      163024      RESTAR: MOV SAVSP,SP ;RESTORE STACK POINTER
3310 016146 012605      MOV (SP)+,R5 ;RESTORE R0-R5
3311 016150 012604      MOV (SP)+,R4
3312 016152 012603      MOV (SP)+,R3
3313 016154 012602      MOV (SP)+,R2
3314 016156 012601      MOV (SP)+,R1
3315 016160 012600      MOV (SP)+,R0
3316 016162 012767      016104 161634      MOV #.PFAIL,24 ;SET UP FOR POWER FAILURE
3317 016170 012767      000340 161600      MOV #340,PS
3318 016176 012706      001100      MOV #STACK,SP
3319 016202 005067      001532      CLR TEMP
3320 016206 005267      001526      1$: INC TEMP
3321 016212 001375      BNE 1$
3322 016214 104410      CONVRT
3323 016216 016240      PFTAB
3324 016220 104402      TYPE
3325 016222 017113      MPFAIL
3326 016224 005067      163016      CLR ERRFLG
3327 016230 005067      162700      CLR LSTERR
3328 016234 000177      162654      JMP @RTRN
3329 016240 000001      PFTAB: 1
3330 016242 006        002      .BYTE 6,2
3331 016244 001114      RTRN
3332
3333
3334                                     ;CHECK SWITCH REGISTER ROUTINE. CHECKS FOR ^G TO ALLOW CHANGING
3335                                     ;OF LOC.176.
3336                                     ;LOCATIONS USED:
3337 016246 000000      RDSW: .WORD 0
3338
3339
3340 016250 005737      000042      .CKSWR: TST @#42
3341 016254 001042      BNE OUT
3342 016256 022767      000176 162614      CMP #CJREG,SWR ;SOFTWARE SWITCH REGISTER PRESENT
3343 016264 001036      BNE OUT ;NO, GET OUT

```

3344	016266	105777	162612		TSTB	@TKCSR		:YES, WAIT FOR
3345	016272	100033			BPL	OUT		:READY, GET CHARACTER
3346	016274	017767	162606	176352	MOV	@TKDBR, .MSG		:AND STRIP OFF
3347	016302	042767	177600	176344	BIC	#177600, .MSG		:THE GARBAGE
3348	016310	122767	000007	176336	CMPB	#7, .MSG		:IS IT A <^G>
3349	016316	001021			BNE	OUT		
3350	016320	104402	016376		TYPE, \$CNTG			
3351	016324	005137	016246		.CNTLU: COM	@#RDSW		
3352	016330	104402	016403		TYPE, \$MSWR			
3353	016334	104411	016370		CNVRT, SWREGC			
3354	016340	104403	016413		INSTR, \$MNEW			
3355	016344	104405			PARAM			
3356	016346	000000			0			
3357	016350	177777			177777			
3358	016352	000176			SWREG			
3359	016354	000	001		.BYTE	0,1		
3360	016356	104402	017110		TYPE, MCRLF			
3361	016362	005037	016246		OUT: CLR	@#RDSW		
3362	016366	000002			RTI			
3363	016370	000001			SWREGC: 1			
3364	016372	006	002		.BYTE	6,2		
3365	016374	000176			SWREG			
3366	016376	005015	043536	000	\$CNTG: .ASCIZ	<15><12>/^G/		
3367	016403	015	051412	051127	\$MSWR: .ASCIZ	<15><12>/SWR= /		
3368	016410	020075	000					
3369	016413	040	047040	053505	\$MNEW: .ASCIZ	/ NEW= /		
3370	016420	020075	000					
3371		016424			.EVEN			
3372	016424	005015	042012	030525	MTITLE: .ASCIZ	<15><12><12>/DU11 CZDUB-C TAPE B /<15><12>		
3373	016432	020061	055103	052504				
3374	016440	026502	020103	040524				
3375	016446	042520	041040	006440				
3376	016454	000012						
3377	016456	005015	042526	052103	MVECTO: .ASCIZ	<15><12>/VECTOR ADDRESS-/		
3378	016464	051117	040440	042104				
3379	016472	042522	051523	000055				
3380	016500	005015	051461	020124	MREGAD: .ASCIZ	<15><12>/1ST DEVICE: RECEIVER CONTROL REGISTER ADDRESS-/		
3381	016506	042504	044526	042503				
3382	016514	020072	042522	042503				
3383	016522	053111	051105	041440				
3384	016530	047117	051124	046117				
3385	016536	051040	043505	051511				
3386	016544	042524	020122	042101				
3387	016552	051104	051505	026523				
3388	016560	000						
3389	016561	015	040412	042522	MMULT: .ASCIZ	<15><12>/ARE YOU RUNNING MULTIPLE DEVICES ? (Y OR N)-/		
3390	016566	054440	052517	051040				
3391	016574	047125	044516	043516				
3392	016602	046440	046125	044524				
3393	016610	046120	020105	042504				
3394	016616	044526	042503	020123				
3395	016624	020077	054450	047440				
3396	016632	020122	024516	000055				
3397	016640	005015	040514	052123	MLASTD: .ASCIZ	<15><12>/LAST DEVICE:RECEIVER CONTROL REGISTER ADDRESS-/		
3398	016646	042040	053105	041511				
3399	016654	035105	042522	042503				

3400	016662	053111	051105	041440	
3401	016670	047117	051124	046117	
3402	016676	051040	043505	051511	
3403	016704	042524	020122	042101	
3404	016712	051104	051505	026523	
3405	016720	000			
3406	016721	075	042504	044526	DEVICE: .ASCIZ /=DEVICE /
3407	016726	042503	020040	000	
3408	016733	015	044012	053517	MCOW: .ASCIZ <15><12>/HOW NOW BROWN COW? ...SELECT SOMETHING TO RUN @ACTREG/
3409	016740	047040	053517	041040	
3410	016746	047522	047127	041440	
3411	016754	053517	020077	027056	
3412	016762	051456	046105	041505	
3413	016770	020124	047523	042515	
3414	016776	044124	047111	020107	
3415	017004	047524	051040	047125	
3416	017012	040040	041501	051124	
3417	017020	043505	000		
3418	017023	015	047412	052125	MRANGE: .ASCIZ <15><12>/OUT OF RANGE:RETYPE LAST DEVICE RXCSR ADDRESS-/
3419	017030	047440	020106	040522	
3420	017036	043516	035105	042522	
3421	017044	054524	042520	046040	
3422	017052	051501	020124	042504	
3423	017060	044526	042503	051040	
3424	017066	041530	051123	040440	
3425	017074	042104	042522	051523	
3426	017102	000055			
3427	017104	020040	000077		MQM: .ASCIZ / ?/
3428	017110	005015	000		MCRLF: .ASCIZ <15><12>
3429	017113	040	050040	053517	MPFAIL: .ASCIZ / POWER FAILURE, PROGRAM RESTART AT TEST IN PROGRESS/
3430	017120	051105	043040	044501	
3431	017126	052514	042522	020054	
3432	017134	051120	043517	040522	
3433	017142	020115	042522	052123	
3434	017150	051101	020124	052101	
3435	017156	052040	051505	020124	
3436	017164	047111	050040	047522	
3437	017172	051107	051505	000123	
3438	017200	005015	047105	020104	MEPASS: .ASCIZ <15><12>/END OF PASS TAPE B/
3439	017206	043117	050040	051501	
3440	017214	020123	040524	042520	
3441	017222	041040	000		
3442	017225	015	051012	000	MR: .ASCIZ <15><12>/R/
3443	017231	015	052012	051505	MTSTPC: .ASCIZ <15><12>/TEST PC-/
3444	017236	020124	041520	000055	
3445	017244	005015	047514	045503	MLOCK: .ASCIZ <15><12>/LOCK ON SELECTED TEST? (Y OR N)-/
3446	017252	047440	020116	042523	
3447	017260	042514	052103	042105	
3448	017266	052040	051505	037524	
3449	017274	024040	020131	051117	
3450	017302	047040	026451	000	
3451	017307	015	042012	020125	MLEVEL: .ASCIZ <15><12>/DU PRIORITY LEVEL-/
3452	017314	051120	047511	044522	
3453	017322	054524	046040	053105	
3454	017330	046105	000055		
3455	017334	005015	020043	043117	MSYNC: .ASCIZ <15><12>/# OF SYNC CHARS SELECTED (1 OR 2)-/

3456 017342 051440 047131 020103
3457 017350 044103 051101 020123
3458 017356 042523 042514 052103
3459 017364 042105 024040 030440
3460 017372 047440 020122 024462
3461 017400 000055
3462 017402 005015 051511 051440
3463 017410 041505 054040 044515
3464 017416 020124 052512 050115
3465 017424 051105 021440 020066
3466 017432 047111 020077 054450
3467 017440 047440 020122 024516
3468 017446 000055
3469 017450 005015 051511 051440
3470 017456 041505 051040 041505
3471 017464 045040 046525 042520
3472 017472 020122 032443 044440
3473 017500 037516 024040 020131
3474 017506 051117 047040 026451
3475 017514 000
3476 017515 015 044412 020123
3477 017522 050117 020124 046103
3478 017530 020122 047105 041101
3479 017536 042514 045040 046525
3480 017544 042520 020122 032043
3481 017552 044440 037516 024040
3482 017560 020131 051117 047040
3483 017566 026451 000
3484 017571 015 044412 020123
3485 017576 044124 020105 042524
3486 017604 052123 041440 047117
3487 017612 042516 052103 051117
3488 017620 044440 051516 040524
3489 017626 046114 042105 037440
3490 017634 054450 047440 020122
3491 017642 024516 000055
3492 017646 006412 020040 020040
3493 017654 052123 052101 051525
3494 017662 020040 046440 050101
3495 017670 020040 020040 005040
3496 017676 000015
3497
3498
3499
3500
3501 017700 000040
3502 017740 000040
3503 020000 000040
3504
3505
3506
3507
3508
3509 020040 006367 000044
3510 020044 006367 000040
3511 020050 006367 000034

MWIRE6: .ASCIZ <15><12>/IS SEC XMIT JUMPER #6 IN? (Y OR N)-/

MWIRE5: .ASCIZ <15><12>/IS SEC REC JUMPER #5 IN? (Y OR N)-/

MWIRE4: .ASCIZ <15><12>/IS OPT CLR ENABLE JUMPER #4 IN? (Y OR N)-/

MEXTJ: .ASCIZ <15><12>/IS THE TEST CONNECTOR INSTALLED?(Y OR N)-/

MSTATUS: .ASCIZ <12> <15>/ STATUS MAP / <12> <15>

.EVEN

;BUFFERS FOR INPUT-OUTPUT

INBUF: .BLKB 40
TEMP: .BLKB 40
MDATA: .BLKB 40

;UTILITIES

;THIS UTILITY CALCULATES PRIORITY LEVEL

DULEV: ASL DUPRT ;SHIFT LEFT
ASL DUPRT ;
ASL DUPRT ;

```

3512 020054 006367 000030      ASL      DUPRT      ;
3513 020060 006367 000024      ASL      DUPRT      ;
3514 020064 016767 000020 000020  MOV      DUPRT,LESS1 ;MOVE THIS TO LESS1
3515 020072 162767 000001 000012  SUB      #1,LESS1    ;CREATE LESS1
3516 020100 042767 000037 000004  BIC      #37,LESS1   ;CLEAR TNZVC
3517 020106 000207      RTS      PC
3518 020110 000240      DUPRT:  LEVEL5
3519 020112 000200      LESS1:  LEVEL4 ;LEVEL TO ALLOW INTERRUPTS
3520
3521      ;NEW DU ADDRESSES
3522 020114 016767 000126 000422  DUADDR:  MOV      DUBASE,RXCSR ;XXX0
3523 020122 005267 000120      INC      DUBASE
3524 020126 016767 000114 000412  MOV      DUBASE,HRXCSR ;XXX1
3525 020134 005267 000106      INC      DUBASE
3526 020140 016767 000102 000402  MOV      DUBASE,RXDBUF ;XXX2
3527 020146 016767 000074 000400  MOV      DUBASE,PARCSR ;XXX2
3528 020154 005267 000066      INC      DUBASE
3529 020160 016767 000062 000364  MOV      DUBASE,HRXDBUF ;XXX3
3530 020166 016767 000054 000362  MOV      DUBASE,HPARCSR ;XXX3
3531 020174 005267 000046      INC      DUBASE
3532 020200 016767 000042 000352  MOV      DUBASE,TXCSR  ;XXX4
3533 020206 005267 000034      INC      DUBASE
3534 020212 016767 000030 000342  MOV      DUBASE,HTXCSR ;XXX5
3535 020220 005267 000022      INC      DUBASE
3536 020224 016767 000016 000332  MOV      DUBASE,TXDBUF ;XXX6
3537 020232 005267 000010      INC      DUBASE
3538 020236 016767 000004 000322  MOV      DUBASE,HTXDBUF ;XXX7
3539 020244 000207      RTS      PC
3540 020246 000000      DUBASE:  0
3541
3542      ;THIS UTILITY POKES THE MAINT DATA BASED UPON THE
3543      ;INFORMATION CONTAINED IN TEMP1 AND IT IS
3544      ;SHIFTED IN BY THE CONTENTS OF SHIFT
3545 020250 042777 040000 000302  RPOKE:  BIC      #MTDATA,@TXCSR
3546 020256 005067 160664      CLR      TEMP2
3547 020262 006067 160656      ROR      TEMP1 ;FORCE CARRY
3548 020266 006067 160654      ROR      TEMP2 ;PICK UP CARRY IN BIT 15
3549 020272 006267 160650      ASR      TEMP2 ;SHIFT INTO BIT 14
3550 020276 042767 100000 160642  BIC      #BIT15,TEMP2 ;CLR BIT 15
3551 020304 056777 160636 000246  BIS      TEMP2,@TXCSR ;POKE MAINT DATA
3552 020312 042777 020000 000240  BIC      #CLK,@TXCSR ;POKE CLK
3553 020320 052777 020000 000232  BIS      #CLK,@TXCSR ;
3554 020326 005367 160606      DEC      SHIFT
3555 020332 001346      BNE      RPOKE
3556 020334 000207      RTS      PC
3557      ;THIS ROUTINE CALCULATES ODD PARITY FOR AN 8 BIT CHAR
3558 020336 016767 160602 160602  ODD8:  MOV      TEMP1,TEMP2 ;SAVE TEMP1
3559 020344 005067 160600      CLR      TEMP3
3560 020350 012727 000010      MOV      #8.,(PC)+
3561 020354 000000      4$:  0
3562 020356 006067 160564      1$:  ROR      TEMP2
3563 020362 005567 160562      ADC      TEMP3
3564 020366 005367 177762      DEC      4$
3565 020372 001371      BNE      1$
3566 020374 006067 160550      ROR      TEMP3
3567 020400 103404      BCS      2$

```

```

3568 020402 052767 000400 160534      BIS    #BIT8,TEMP1      ;SET ODD PARITY
3569 020410 000403                    BR     3$
3570 020412 042767 000400 160524 2$:  BIC    #BIT8,TEMP1      ;CLR EVEN PARITY
3571                    :TEMP1 NOW HAS ODD PARITY CHARACTER
3572 020420 000207                    3$:  RTS     PC
3573
3574                    ;THIS ROUTINE CALCULATES EVEN PARITY FOR AN 8 BIT CHARACTER
3575 020422 016767 160516 160516  EVEN8: MOV    TEMP1,TEMP2      ;SAVE TEMP1
3576 020430 005067 160514                    CLR    TEMP3
3577 020434 012727 000010                    MOV    #8.,(PC)+
3578 020440 000000                    4$:  0
3579 020442 006067 160500                    1$:  ROR    TEMP2
3580 020446 005567 160476                    ADC    TEMP3
3581 020452 005367 177762                    DEC    4$
3582 020456 001371                    BNE    1$
3583 020460 006067 160464                    ROR    TEMP3
3584 020464 103004                    BCC    2$
3585 020466 052767 000400 160450      BIS    #BIT8,TEMP1      ;SET EVEN PARITY
3586 020474 000403                    BR     3$
3587 020476 042767 000400 160440 2$:  BIC    #BIT8,TEMP1      ;CLR ODD PARITY
3588                    :TEMP1 NOW HAS EVEN PARITY CHARACTER
3589 020504 000207                    3$:  RTS     PC
3590
3591 020506 062716 000002      TRPREG: ADD    #2,(SP) ;ALLOW IT TO 'CRUNCH' INTO HLT BACK
3592                    ;IN MAIN PART OF THE PROGRAM
3593 020512 000002                    RTI
3594                    ;ERROR HLT TABLE
3595 020514 020600      .ERRTAB: EMO    ;HLT 0 BIT ERROR (GENERAL)
3596 020516 000000                    0
3597 020520 000000                    0
3598 020522 020614                    EM1    ;HLT 1 REGISTER ERROR
3599 020524 020765                    DH1
3600 020526 021006                    DT1
3601 020530 020656                    EM2    ;HLT 2 RECEIVER ERROR
3602 020532 020765                    DH1
3603 020534 021006                    DT1
3604 020536 020720                    EM3    ;HLT 3 TRANSMITTER ERROR
3605 020540 020765                    DH1
3606 020542 021006                    DT1
3607
3608 020544 160040      RXCSR: 160040 ;DEFAULT DU ADDRESSES
3609 020546 160041      HRXCSR: 160041
3610 020550 160042      RXDBUF: 160042
3611 020552 160043      HRXDBUF: 160043
3612 020554 160042      PARCSR: 160042
3613 020556 160043      HPARCSR: 160043
3614 020560 160044      TXCSR: 160044
3615 020562 160045      HTXCSR: 160045
3616 020564 160046      TXDBUF: 160046
3617 020566 160047      HTXDBUF: 160047
3618
3619 020570 000770      DURIV: 770    ;DEFAULT DU VECTORS
3620 020572 000772      DURIS: 772    ;REC INTR VECTOR
3621 020574 000774      DUTIV: 774    ;REC INTR STATUS
3622 020576 000776      DUTIS: 776    ;XMIT INTR VECTOR
3623                    ;XMIT INTR STATUS
                    ;ERROR MESSAGES

```

```
3624 020600 036440 042440 051122 EM0: .ASCIZ / = ERROR PC/
3625 020606 051117 050040 000103
3626 020614 036440 051040 043505 EM1: .ASCIZ / = REGISTER ERROR PC/<15><12><1>/REGISTER /
3627 020622 051511 042524 020122
3628 020630 051105 047522 020122
3629 020636 041520 005015 051001
3630 020644 043505 051511 042524
3631 020652 020122 000040
3632 020656 036440 051040 041505 EM2: .ASCIZ / = RECEIVER ERROR PC/<15><12><1>/REGISTER /
3633 020664 044505 042526 020122
3634 020672 051105 047522 020122
3635 020700 041520 005015 051001
3636 020706 043505 051511 042524
3637 020714 020122 000040
3638 020720 036440 052040 040522 EM3: .ASCIZ / = TRANSMITTER ERROR PC/<15><12><1>/REGISTER /
3639 020726 051516 044515 052124
3640 020734 051105 042440 051122
3641 020742 051117 050040 006503
3642 020750 000412 042522 044507
3643 020756 052123 051105 020040
3644 020764 000
3645 :DATA HEADERS FOR ERROR MESSAGES
3646 020765 105 050130 041505 DH1: .ASCIZ /EXPECTED ACTUAL/
3647 020772 042524 020104 040440
3648 021000 052103 040525 000114
3649 .EVEN
3650 :DATA TABLES FOR ERROR MESSAGES
3651 021006 000003 DT1: 3
3652 021010 006 004 .BYTE 6,4
3653 021012 001164 SAVR3 :REGISTER
3654 021014 006 004 .BYTE 6,4
3655 021016 001156 SAVR0 :EXPECTED DATA
3656 021020 006 002 .BYTE 6,2
3657 021022 001160 SAVR1 :ACTUAL DATA
3658 000001 .END
```


.HLT	015634	827	3236#			
.INSTE	014750	979	3053#			
.INSTG	014754	3052	3055#			
.INSTR	014632	977	3029#			
.INST1	014652	3033#	3044	3060		
.MSG	014654	3031*	3034#	3346*	3347*	3348
.PARAM	015002	981	3067#			
.PFAIL	016104	825	1008	3295#	3316	
.RES05	015256	985	3140#			
.SAV05	015216	983	3126#			
.SCOPE	014366	971	2967#			
.SCOP1	014552	973	3007#			
.SETFL	015534	991	3208#	3219		
.START	001420	837	1006#	1016	2915	
.TRPSR	015602	829	3225#			
.TRPTA	001366	967#	3230			
.TYPE	014572	975	3015#			

	676#	970	972	974	976	978	980	982	984	986	988	990	992	994	
STRPDE	676#	970	972	974	976	978	980	982	984	986	988	990	992	994	
STRPSR	676#	3220													
STSTNO	676#	1328	1386	1444	1502	1560	1618	1676	1734	1792	1850	1908	1966	2024	2079
	2134	2189	2244	2299	2354	2409	2464	2519	2574	2629	2684	2739	2794	2849	
STYPE	676#	3012													
SUNIBU	676#														
SVARIA	676#	840													
SWORDF	676#														
SWORDO	676#	1320	1378	1436	1494	1552	1610	1668	1726	1784	1842	1900	1958	2016	2071
	2126	2181	2236	2291	2346	2401	2456	2511	2566	2621	2676	2731	2786	2841	
SWORDP	676#														

. ABS. 021024 000

ERRORS DETECTED: 0

CZDUBD.BIN,CZDUBD.SEQ/CRF/SOL/NL:TOC=CZDU11.HLO/EQ:RUNB,CZDU11.PAR,CZDU11.KET,CZDUBD.P11
 RUN-TIME: 8 12 1 SECONDS
 RUN-TIME RATIO: 92/22=4.0
 CORE USED: 19K (37 PAGES)