



Unit 14, The Bridge, Beresford Way
 Chesterfield, Derbyshire, S41 9FG, UK
 T e l : + 44 (0) 1246 452909
 F a x : + 44 (0) 1246 452942
 W e b : w w w . e t p s . c o . u k
 E m a i l : s a l e s @ e t p s . c o . u k
 S a l e s : 0 8 0 0 6 1 2 9 5 7 5

ELP-3310F Dynamic DC Electronic Load Modules

Description

These true dynamic loads offer an incredible degree of functionality at a very reasonable cost. Constant current, resistance, voltage and power operation are provided as standard. Dual ranges for CC and CR modes enables tight resolution at the lower end. Voltage, current and power values are simultaneously shown on the 4½ digit displays. The front panel voltage and ammeters have a 16 bit resolution and offer a high degree of accuracy. An adjustable short mode along with OCP and OPP tests are also built in. The load can be set to turn on and off at a preset voltage level making these units ideal for discharging batteries. An input for connecting an arbitrary waveform generator is provided to enable the unit to follow complex load patterns. Load currents can be viewed graphically by connecting a scope to the BNC connector on the front panel of the load. The 3310F are housed within the single slot, desktop 3302F mainframe. Dual slot (3305F) and four slot (3300F) mainframes are also available. All F-series mainframes can be fitted with RS232, LAN, USB or GPIB interface cards. Common test values can be stored via the front panel in the non-volatile memory of the mainframe. These values can also be sequenced with time allowing frequent test procedures to be quickly implemented.



- CC, CR, CV, CP, dynamic & short mode
- Large LCD display with scope output
- 150 store/recall memory
- OCP & OPP test function
- External oscillator input
- Labview drivers

Selection Table

Part Number	Maximum Power	Operation Voltage	Current Range	Module Weight	Dimensions (Width x Height x Depth)
ELP-3310F	150W	60V	0 - 30A	3.5kg	108 x 143 x 405mm
ELP-3311F	300W	60V	0 - 60A	3.5kg	108 x 143 x 405mm
ELP-3312F	300W	250V	0 - 12A	3.5kg	108 x 143 x 405mm
ELP-3314F	300W	500V	0 - 12A	3.5kg	108 x 143 x 405mm
ELP-3315F	75W	60V	0 - 15A	3.5kg	108 x 143 x 405mm

Options Table

Code	Description
/3302F.....	Single slot mainframe (separate summary available)
/3305F.....	Dual slot mainframe (separate summary available)
/3300F.....	Four slot mainframe (separate summary available)
/GPIB.....	Mainframe selection includes GPIB interface card
/RS232.....	Mainframe selection includes RS232 interface card
/LAN.....	Mainframe selection includes LAN interface card
/USB.....	Mainframe selection includes USB interface card
/DSK.....	Disable short test function key
/0001.....	1m IEEE488.2 cable
/0002.....	2m IEEE488.2 cable
/0003.....	2m RS232 cable
/9931.....	Remote controller



sales@etps.co.uk
0800 612 95 75

Technical Data

	ELP-3310F	ELP-3311F	ELP-3312F	ELP-3314F	ELP-3315F
Over Power Protection	≈ 157.5W	≈ 315W	≈ 315W	≈ 315W	≈ 78.75W
Over Current Protection	≈ 30A	≈ 63A	≈ 12A	≈ 12.6A	≈ 15.75A
Over Voltage Protection	≈ 60V	≈ 60V	≈ 262.5V	≈ 525V	≈ 63V
Over Temp. Protection	≈ 85 °C				
CC Mode					
Range 1	0 - 3A	0 - 6A	0 - 1A	0 - 1.2A	0 - 1.5A
Range 1 Resolution	0.05mA	0.1mA	0.268mA	0.02mA	0.0254mA
Range 2	0 - 30A	0 - 60A	0 - 10A	0 - 12A	0 - 15A
Range 2 Resolution	0.5mA	1mA	2.68mA	0.2mA	4.0mA
Accuracy	± 0.1% of (setting + range)				
CR Mode					
Range 1	2 - 120KΩ	1 - 60KΩ	25 - 1500KΩ	50-3000KΩ	4 - 24KΩ
Range 1 Resolution	0.0083mΩ	0.0166mS	0.00066mΩ	0.00033mS	0.04166mS
Range 2	0.2-2 KΩ	0.015 - 1Ω	0.08 - 25Ω	0.5 - 50Ω	0.02 - 4Ω
Range 2 Resolution	0.033mS	0.0166mΩ	0.4166mΩ	0.8333mΩ	0.0666mΩ
Accuracy	± 0.2% of (setting + range)				
CV Mode					
Range 1	0 - 6V	0 - 6V	0 - 30V	0 - 60V	0 - 6V
Range 1 Resolution	0.1mV	0.1mV	0.5mV	0.001V	0.0001V
Range 2	0 - 60V	0 - 60V	0 - 250V	0 - 500V	0 - 60V
Range 2 Resolution	1mV	1mV	10mV	0.01V	0.001V
Accuracy	± 0.05% of (setting + range)				
CP Mode					
Range	0 - 15W	0 - 30W	0 - 30W	0 - 30W	0 - 7.5W
Resolution	0.25mW	1mW	1mW	0.001W	0.000125W
Range	0 - 150W	0 - 300W	0 - 300W	0 - 300W	0 - 75W
Resolution	2.5mW	10mW	10mW	0.01W	0.00125W
Accuracy	± 0.5% of (setting + range)				
Dynamic Operation					
Thigh & Tlow	50µSec to 9.999Sec				
Slew Rate 1	2.0 - 125mA/µsec	4 - 250mA/µsec	0.8 - 50mA/µsec	0.8 - 50mA/µsec	1 - 62.5mA/µsec
Slew Rate 2	20 - 1250mA/µsec	40 - 2500mA/µsec	8 - 0.5A/µsec	8 - 500mA/µsec	10 - 625mA/µsec
Accuracy	± (5% of setting) ± 10µS			± (10% of setting) ± 10µS	
Voltage Readback					
Range 1	6V	6V	30V	60V	6V
Range 1 Resolution	0.0001V	0.0001V	0.001V	0.001V	0.0001V
Range 2	60V	60V	250V	500V	60V
Range 2 Resolution	0.001V	0.001V	0.01V	0.01V	0.001V
Accuracy	± 0.025% of (reading + range)				
Current Readback					
Range 1	3A	6A	1.2A	1.2A	1.5A
Range 1 Resolution	0.0001A	0.0001A	0.00002A	0.00002A	0.000025A
Range 2	30A	60A	12A	12A	15A
Range 2 Resolution	0.001A	0.001A	0.0002A	0.0002A	0.00025A
Accuracy	± 0.1% of (reading + range)				
Other					
Current Monitor Output	Full scale 10V (Isolated with load module)				
Accuracy	± 0.5% of (setting + range)				
Current Program Input	Full scale 10V (Isolated with other load module)				
Programmable Short	Built in				
Load On Voltage	0.1 - 25V	0.1 - 25V	0.2 - 50V	0.4 - 100V	0.1 - 25V
Accuracy	± 1% of (setting + range)				
Load Off Voltage	0 - 25V	0 - 25V	0 - 50V	0 - 100V	0 - 25V
Accuracy	± 0.025% of (setting + range)				
Typical Short Resistance	0.02Ω	0.00833Ω	0.08Ω	0.5Ω	0.02Ω
Max. Short Current	30A	60A	10A	10A	15A

Every effort is made to ensure that the information provided within this technical summary is accurate. However, ET must reserve the right to make changes to the published specifications without prior notice. Where certain operating parameters are critical for your application we advise that they be confirmed at the time of order. Please note that your actual unit may differ from that shown.