



# "Non-incendive" Pocket-PC 39a-Ex

COMPAQ

## Leader of the Handheld Pack

The Pocket-PC 39a-Ex is still leaps and bounds ahead of the handheld pack. Offering all of the features that made it famous -like an Intel® processor, extreme battery life and dazzling, full-color display - the Pocket-PC 39a-Ex takes it one step further with a wealth of comprehensive wireless solutions with Expansion Packs. So you can stay connected to what's important, wherever you may roam. With Expansion Pack technology, the Pocket-PC 39a-Ex just keeps getting better.

#### Benefits

- · Dazzling display has higher contrast, better color saturation and more than 65.000 colors
- Accelerating multimedia and multitasking with the 400 MHz Intel® X-Scale Processor
- Pocket-PC 39a-Ex Backup backs up your applications and data to a CF card, SD card
- Consumer IR -control office electronics systems with all the functions of a highend learning Universal Remote Control
- •Standby settings user-adjustable standby settings to customize usage time or battery standby period
- •64 MB SDRAM for applications, files and more
- Technical data:

# Operating System:

Pocket PC 2002

Processor:

Intel PXA250 (XScale)

Processor speed:

400 MHz

Memory:

48 MB Flash ROM / 64 MB SDRAM

Display:

transflective color TFT, 240 x 320 pixels, 64K-color depth, backlight illumination

Touchscreen:

soft keyboard, handwriting recognition

Audio:

speaker, 3.5 mm stereo headphone jack, microphone

- •Microsoft ®Pocket PC Software 2002
- Optional Expansion Packs
- Bluetooth link wirelessly between notebooks, mobile phones and the Internet

## Scope of supply:

EFOID

Power supply, Docking Cradle Display-cover, Software-CD

## System Requirements

- •For ActiveSync ®3.5:
- -Microsoft ®Windows ®2000, 98, Windows NT ® Workstation 4.0 or XP with a 486/33DX or higher processor (Pentium ®90 MHz recommended)
- For USB Synchronization: -Microsoft ®Windows ®2000, 98 or XP
- 12 MB of memory for Windows NT ® or XP
- Hard disk drive with 10 to 50 MB of available hard disk space (actual requirements will vary based on selection of features and user's system configuration)
- Available 9 or 25 pin communication port (adapter required for 25 pin communication port)
- CD-ROM drive
- VGA or higher resolution graphics card
- Mouse or compatible pointing device
- USB port

#### Ex-data:

Ex designation: NI Class | Div. 2 A-DT6 AEx nA Group II CT6

#### Accessories:

•On demand

#### Infrared:

IrDA, I.I compatible

#### Bluetooth:

internal

#### Communications:

com. port, expansion pack connector

#### Slot:

SD/MMC card

## Indicators:

3 mode LED alarm notification

#### Operating Time:

277 min

#### Power Supply:

1400 mAh Lithium Polymer rechargeable battery

## Docking Cradle:

Universal USB or Serial with AC power and charging

# Dimensions & Weight

#### Unit:

 $5.3" \times 3.3" \times 0.6"$  (6.5 oz.) 134mm x 84mm x 16mm (184gr)

# Unit Package:

 $12.5" \times 9.00" \times 4.13"$  (3 lbs.)

317mm  $\times 228$ mm  $\times 105$ mm (1320gr)

# Operating Temperature:

32° to 104°F (0° to 40°C)

#### Storage Temperature:

-22° to 140°F (-30° to 60°C)