



DIMENSIONS IN INCHES

DIMENSIONAL DATA

DIM.	MIN.	MAX.	REF.
A	2.336	2.450	
B	2.028	2.088	
C	1.005	1.000	
D	6.75	7.00	
E	.305	.370	
F	.305	.370	
G	.950	.985	
H	.360	.387	
J	5.40	5.75	
K	.220	.275	
L	.311	.375	
M	.031	.062	.188
P	.080	.096	

NOTES

1. SOCKET SPECIFICATIONS
2. MAT'L & FINISHES
3. SOCKET BODY - 96% ALUMINUM SER.
4. CONTACTS - NON-FERROUS SPRING ALLOY, HEAT TREATED & .001 A.
5. WT. -.093 LB. MAX.
6. OPER. TEMP. - 175°C MAX.
7. DIMENSIONS ARE FOR INFO ONLY & ARE NOT REQS. FOR PRODUCTION PURPOSES.

NO.	DESCRIPTION OF CHANGE	REQD.	DATE	BY	DATE	BY
1	CHANGED DIMS & DROPPED		2-1-67			
2	MIN. MAX. DIM. N		23411	2-20-67	CBK	
3	2. F330R		23281	6-5-70C	AK	

SCALE: NONE DIVISION PAT. 5% SUPERSEDES

NO. SK-660A-60

DATE: 2-1-67

SCALE: NONE

NO. SK-660A-60

MITTEL-MCCULLOUGH INC.
SAN CARLOS, CALIF.
PART NO. SK-660A
SOCKET - ELECTRON TUBE
NO. SK-660A-60