

Safety and Maintenance instructions

- Make sure that all electric connections and connection cables meet the pertaining regulations and are in conformity with the operating instructions.
- Do not overload electrical outlets or extension cords, fire or electric shocks can be the result.
- Please contact an expert in case you have any doubts about the mode of operation, the safety or connecting the appliances.
- Keep all parts away from young children's reach.
- Do not store this item on top, very cold or warm places, this can damage the electronic circuit boards.
- Always place the device on a flat surface, this can damage the electronic boards.
- Never replace damaged power cables yourself! In such a case, remove them from the net and take the devices to a workshop.
- Do not attempt to repair this item, it may only be performed by an authorised workshop.
- Wireless systems are subject to interference from cordless phones, microwaves, and other wireless devices operating in the 2.4GHz range. Keep the system AT LEAST 10 ft away from the devices during installation and operation.

Maintenance

The devices are maintenance-free, so never open them. The guarantee becomes void when you open the appliances. Only clean the outside of the devices with a soft, dry cloth or a brush. Prior to cleaning, remove the devices from all voltage sources.

- Do not use any carboxylic cleaning agents such as petrol, alcohol or similar. These attack the surfaces of the devices. Besides, the vapors are hazardous to your health and explosive. Do not use any sharp edged tools, screw drivers, metal brushes or similar for cleaning.

Instructions de sécurité et d'entretien

- Vérifier que toutes les connexions électriques et câbles sont conformes aux règlements afférents et aux instructions d'utilisation.
- Né pas créer de surtension sur les prises électriques ou les rallonges, cela peut être cause de feu ou d'électrocution.
- Ne pas laisser un expert en cas de doute sur le mode d'utilisation, de sécurité ou la connexion des appareils.
- Placer hors de portée des enfants.
- Né pas disposer dans un endroit humide, très froid ou très chaud, cela pourrait endommager le tableau de circuits électroniques.
- Éviter de faire tomber ou de cogner les appareils ; cela pourrait endommager le tableau de circuits électroniques.
- Né jamais remplacer soi-même des fils électriques endommagés! Si les fils électriques sont endommagés, les réparer et réajuster et les appeler d'un réparateur agréé.
- La réparation et l'ouverture des différents éléments ne peuvent être effectuées que par un magasin spécialisé.
- Né jamais sans fil sujet aux interférences des téléphones sans fil, des micro-ondes, et autres appareils sans fil utilisant la fréquence 2.4MHz. Placer le système AU MOINS 3 mètres de ces appareils au cours de l'installation et au moment de l'utilisation.

Maintenance

Les appareils sont en libre utilisation, ne jamais les ouvrir. La garantie n'est plus valide si les appareils sont ouverts. Ne nettoyer que l'extérieur des appareils avec un chiffon doux et sec ou une brosse. Avant de nettoyer, débrancher les appareils.

- Né pas utiliser d'agents nettoyants à facile carboxyliques, tels que l'alcool, l'essence, d'alcool ou autre produit inflammable. Ces produits attaquent la surface des appareils. Par ailleurs, les vapeurs sont dangereuses pour la santé et explosives. Né pas utiliser d'ustensils à bout tranchant, de tournevis, de brosse métallique ou autre élément semblable pour le nettoyage.

Veiligheids- en onderhoudsinstructies

- Alle elektrische verbindingen en verbindingskabels moeten voldoen aan de juiste regels en overeenkomen met de bedieningsinstructies.
- Overbelast de elektrische stopcontacten of verlengsnoeren nooit; dit kan anders leiden tot brand of elektrische schok.
- Laat het apparaat niet met een expert in geval je twijfels hebt over de bedieningswijze, de veiligheid of de aansluiting van de apparaten.
- Hou alle delen uit het bereik van kinderen.
- Verwijder het apparaat niet op natte, erg koude of warme plaatsen; dit kan de elektronische circuitborden beschadigen.
- Vermijd vallen of schokken; dit kan de elektronische boarden beschadigen.
- Verwijng beschadigde stroomkabels nooit zelf! In dit geval verwijder ze uit het net en breng de toestellen naar een winkel.
- Herstellen of openen van dit voorwerp mag enkel gebeuren door een erkende hersteller.
- Dradloze systemen kunnen gestoord worden door draadloze telefoons, microgolven en andere draadloze toestellen die werken op het bereik van 2,4GHz. Hou het systeem MINSTENS op 3m afstand van de toestellen tijdens installatie en bediening.

Onderhoud

De toestellen zijn onderhoudsvrij, dus maak ze niet open. De garantie vervalt als je het apparaat opent. Reinig enkel de buitenkant van de toestellen met een zachte, droge doek of borstel. Voor je ze reinigt, haal de toestellen uit alle spanningsbronnen.

- Gebruik geen carboxylisch schoonmaakmiddelen of benzine, alcohol of gelijkaardige producten. Deze werken agressief op het oppervlak van de toestellen. Bovendien zijn ze dampen gevaarlijk voor je gezondheid en ontbrandbaar. Gebruik geen scherp instrumenten, schroevendraaiers, metalen borstels of gelijkaardige dingen om te reinigen.

Sicherheits- und Wartungshinweise

- Stellen Sie sicher, dass alle elektrischen Anschlüsse sowie Kabelverbindungen an weitere Geräte den betreffenden Richtlinien entsprechen und sich gleichzeitig in Übereinstimmung mit der Bedienungsanleitung befinden.
- Achten Sie darauf, Steckdosen und Verlängerungskabel nicht zu überlasten, das kann zu Feuer oder Stromschlag führen.
- Schließen Ihnen irgendwelche Zweifel an Betrieb, Sicherheit oder Anschluss der Geräte aufkommen, dann wenden Sie sich bitte an einen Fachmann.
- Alle Teile vor Kindern geschützt aufbewahren.
- Bitte nicht in feuchter, sehr kalter oder heißer Umgebung aufbewahren, das kann zu Beschädigung der elektronischen Schaltkreise führen.
- Vermieden Sie harte Stöße, das kann zu Beschädigung der elektronischen Schaltkreise führen.
- Vermeiden Sie beschädigte Stromkabel niemals selbst! Nehmen Sie die Geräte vom Netz und wenden sich an einen Fachbetrieb.
- Öffnen und Reparieren der Geräte ausschließlich durch autorisierten Fachbetrieb.
- Kabellose Systeme sind Störempfänger von Mobiltelefonen, Mikrowellenherden sowie anderen elektronischen Geräten, die im 2,4GHz-Bereich arbeiten, ausgestattet. Halten Sie einen MINDESTABSTAND VON WENIGSTENS 3 METERN während Installation und Betrieb ein.

Wartung

Die Geräte sind wartungsfrei, also öffnen Sie sie bitte nicht. Ihre Garantie verfällt, wenn Sie die Geräte öffnen. Reinigen Sie die Geräte außen mit einem weichen und trockenen Tuch oder einer Bürste. Vor dem Reinigen ziehen Sie bitte alle Stromzuführungen ab.

- Verwenden Sie keine Reinigungsmittel, die Carbonsäure, Benzin, Alkohol oder ähnliches enthalten. Diese Mittel greifen die Oberfläche der Geräte an und die Ausdrücker sind gesundheitsschädlich und explosiv. Verwenden Sie keine scharfkantigen Werkzeuge. Schraubenzieher, Drahtbürsten oder ähnliches, um die Geräte zu reinigen.



AB600T REMOTE CONTROLLER WITH LCD

- GB USER'S MANUAL
- NL HANDLEIDING
- S BRUKSANVISNING
- DK BRUGSVEJLEDNING
- PL PODRECZNIK UZYTKOWNIKA
- RUS РУКОВОДСТВО ПОЛЬЗОВАТЕЛЯ
- H HASZNÁLTÁJÁRUTATY
- RO MANUALUL UTILIZATORULUI
- SK UŤVÁŤATEĽSKÉ PRŮRUKY
- HR UPUTSTVA ZA UPORABU
- SLO PRIROCNIK ZA UPORABNIKE
- D BEDIENUNGSANLEITUNG
- F MANUEL DE L'UTILISATEUR
- BG БРЪКОВОДСТВО НА ПОТРЕБИТЕЛЯ
- I MANUALE UTENTE
- CZ UŤVÁŤATEĽSKÝ MANUÁL
- GR ΕΓΧΕΙΡΙΔΙΟ ΧΡΗΣΤΗ
- TR KULLANMA KILAVUZU
- E MANUAL DEL USUARIO
- P MANUAL DO USUÁRIO
- UA ПОСІБНИК КОРИСТУВАЧА

TECHNICAL SPECIFICATIONS

Battery type 4 x 1.5V AAAA type
Operating frequency 433.92 MHz
Channels 16
Range up to 50m (depends on situation)

WWW.ELRO.EU

Ros Electronics bv
Postbus 117, 5126 ZJ Gilze, Holland
WWW.ELRO.NL/UK - WWW.ELRO.BE.COM
Ros Electronics GmbH Amsberg-Germany
WWW.ROSELECTRONICS.DE
EDEN, Yvalloirs, France WWW.EDEN.FR
C H Byron Corporation, Brommrose, U.K.
WWW.CBYRON.COM



GB

What you get
remote control
- 4 x AAAA type battery
this manual

INTRODUCTION
With this multipurpose remote controller, you easily and affordably enhance the comfort and security of your home or office. You'll see how easy it is to create a totally custom system quickly and conveniently. The remote controls almost any professional standard appliance. The unit can control each single device from AB600 series, in addition several devices can be operated together under separate channels. Every group of devices can be controlled by numerous devices, for example when getting up, simply press a button, the lamps in the porch and corridor will be turned on and the coffee machine will start. The remote control of the unit can also be set in auto mode and the devices included to the program mode and/or to the preferred mode can periodically execute automatically when the time for operation is up.

Symbol	on LCD screen	Description
1	Power	Power button
2	On/Off	On/Off button
3	Mode	Mode button
4	Group	Group button
5	Channel	Channel button
6	Repeat	Repeat button
7	Light	Light button
8	Volume	Volume buttons
9	Power	Power button
10	On/Off	On/Off button
11	Mode	Mode button
12	Group	Group button
13	Channel	Channel button
14	Repeat	Repeat button
15	Light	Light button
16	Volume	Volume buttons

Keyval button
1. Press and hold the button next to 1 for 3 seconds.
2. After pressing 1, HH of HH starts flashing. Use Δ / ∇ to choose AM or PM.
3. After pressing 1, HH of HH starts flashing. Use Δ / ∇ to choose AM or PM. Further pressing 1 will return the time to 12:00. Press 1 to stop flashing.
(Note: Use Δ / ∇ to choose the item that needs to be adjusted.)
4. Press Δ / ∇ to choose the preferred number and their corresponding type of products will be shown. Press 1 continuously will return to step 2 for addition.
5. To complete, press OK to save and exit.

Symbol	Name of Symbol	Significance
1	Power	Power button
2	On/Off	On/Off button
3	Mode	Mode button
4	Group	Group button
5	Channel	Channel button
6	Repeat	Repeat button
7	Light	Light button
8	Volume	Volume buttons
9	Power	Power button
10	On/Off	On/Off button
11	Mode	Mode button
12	Group	Group button
13	Channel	Channel button
14	Repeat	Repeat button
15	Light	Light button
16	Volume	Volume buttons

Channel Setting (Valid for selecting the selected house code products)
1. Press the button next to 4 for 3 seconds till LCD screen reveals CH.
2. Select the house code of the products to be pressing Δ / ∇ to choose the house code as below tables.
3. Press OK to save and exit or press C to exit without saving.

AB600T Device House Code	AB600T Device House Code
CH01	CH01
CH02	CH02
CH03	CH03
CH04	CH04
CH05	CH05
CH06	CH06
CH07	CH07
CH08	CH08
CH09	CH09
CH10	CH10
CH11	CH11
CH12	CH12
CH13	CH13
CH14	CH14
CH15	CH15
CH16	CH16
CH17	CH17
CH18	CH18
CH19	CH19
CH20	CH20

Learning Mode
1. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
2. Use Δ / ∇ to choose type of product - S , I , R , M , H .
3. The type of product selected will be flashing.
4. Press OK to confirm the product type and their corresponding type of products will be shown. Press OK to save and exit or press C to exit without saving.
5. Press OK to save and exit or press C to exit without saving.

LED Indicator
1. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
2. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
3. If only some of the group codes need to be cleared.
4. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
5. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
6. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
7. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
8. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
9. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
10. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
11. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
12. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
13. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
14. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
15. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
16. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
17. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
18. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
19. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
20. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
21. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
22. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
23. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
24. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
25. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
26. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
27. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
28. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
29. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
30. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
31. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
32. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
33. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
34. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
35. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
36. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
37. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
38. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
39. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
40. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
41. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
42. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
43. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
44. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
45. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
46. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
47. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
48. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
49. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
50. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
51. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
52. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
53. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
54. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
55. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
56. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
57. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
58. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
59. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
60. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
61. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
62. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
63. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
64. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
65. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
66. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
67. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
68. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
69. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
70. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
71. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
72. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
73. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
74. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
75. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
76. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
77. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
78. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
79. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
80. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
81. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
82. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
83. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
84. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
85. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
86. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
87. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
88. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
89. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
90. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
91. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
92. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
93. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
94. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
95. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
96. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
97. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
98. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
99. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
100. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
101. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
102. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
103. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
104. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
105. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
106. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
107. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
108. Press OK 3 seconds until CH is flashing then release. CH is on steadily, which implies that the unit enters allocation mode. Allocation time period is 30 seconds.
109. Press OK 3 seconds until CH is

