General Index

GENERAL INFORMATION 1.1-1
Introduction 1.1-1
System Architecture 1.1-2
Local Control 1.1-2
Remote Login 1.1-3
Operational Features 1.1-4
Login 1.1-4
General Parameters Configuration 1.1-4
Unit Management 1.1-5
Port Equipment and Configuration 1.1-5
Remote Control Parameters Configuration 1.1-5
Alarm Parameters Setting 1.1-5
Protection Configuration 1.1-6
Traffic Management 1.1-6
Synchronism Management 1.1-6
ACTIVATING THE CONTROL APPLICATION 1.2-1
Connection of Personal Computer to ADM-1 ..... 1.2-1
Software Installation 1.2-3
Installing the Local Operator 1.2-3
Installing the Online Help files 1.2-7
Installing the Configuration File "download.ini" 1.2-10
Access the Control Application Software 1.2-11
Configuration of Communication Parameters 1.2-12
Login Access 1.2-13
Main Window 1.2-15
Password Management 1.2-16
Log out 1.2-17
Exit 1.2-17
MAIN FUNCTIONS 1.3-1
Working Area 1.3-1
The Menu Bar and Menus 1.3-1
The Graphical Area 1.3-3
The Connection Status Indication 1.3-7
The Serial Port Button Status Indication 1.3-7
The Tool Bar 1.3-8
Alarm and Event Monitor Window 1.3-12
VIEW OPTIONS 1.4-1
Toolbar 1.4-1
Status Bar 1.4-1
Zoom Fault Window 1.4-1
Refresh 1.4-1
CONFIGURATION 1.5-1
NE Configuration 1.5-1
Configuration of Unit 1.5-3

© ERICSSON TELECOM AB 1999 - All Rights Reserved

Protection Role....1.5-3
MSP Protection....1.5-5
MSP Switch Operations....1.5-8
MSP Protection Switch (Event Details)....1.5-9
Equipment Protection....1.5-10
Equipment Protection Switch Operations....1.5-12
Eqt Protection Switch (Event Details)....1.5-14
Protection Parameters....1.5-15
NE Log....1.5-16
Event Report....1.5-18
LC Log....1.5-19
Alarm Parameters....1.5-19
Alarm Attributes....1.5-22
Summary LEDs Status....1.5-23
Abnormal Condition....1.5-24
Rack Lamp Configuration....1.5-25
Ground Contacts....1.5-26
Parking Status....1.5-28
Synchronisation....1.5-29
Equipping Synchronisation Sources....1.5-29
System Synchronisation Sources....1.5-35
System Synchronisation Sources Switch Operations....1.5-38
Sync switch -> System Sync (Event Details)....1.5-40
External Synchronisation Outputs....1.5-41
External Synchronisation Output Switch Operations....1.5-45
Sync switch -> External Sync (Event Details)....1.5-46
QL Table Entry....1.5-47
Cross Connections....1.5-48
Multiply SDH Frame....1.5-50
Unidirectional Cross Connection....1.5-52
Bidirectional Cross Connection....1.5-53
Broadcast Cross Connection....1.5-54
Loopback Cross Connection....1.5-56
Split Access Cross Connection....1.5-57
Monitor Cross Connection....1.5-58
Dropped Cross Connections....1.5-59
Dropped Cross Connection Switch Operations....1.5-61
Path Prot. Switch (Event Details)....1.5-63
VC-2n-C Cross Connection....1.5-64
Administrative State....1.5-65
Busy Channel Indication....1.5-65
Deletion of a Cross Connection....1.5-66
SNC Protection....1.5-67
SNCP Switch Operations....1.5-70
Path Prot. Switch SNC (Event Details)....1.5-71
SOH Bytes Configuration....1.5-72

OSI Parameters Setup 1.5-73
OSI Parameters Get 1.5-75
MAINTENANCE 1.6-1
NE General Parameters 1.6-1
DCC Configuration 1.6-2
Network Configuration 1.6-4
Software Info 1.6-8
Inventory Data 1.6-9
Performance Parameters 1.6-10
Exception Report Enable 1.6-11
Performance Data Collection 1.6-12
Performance Exception Thresholds 1.6-15
Software Download 1.6-26
Database Upload 1.6-27
Database Download 1.6-28
MOST Switch 1.6-29
Serial Port Configuration 1.6-29
Language Configuration 1.6-30
Local Controller Protocol Version 1.6-30
Database Clear 1.6-31
Local Controller Software Version 1.6-31
UNIT FUNCTIONS 1.7-1
Unit Active Alarms 1.7-2
Unit Info 1.7-4
Unit Software Info 1.7-5
Unit Inventory Data 1.7-6
Unit Creation 1.7-7
Unit Deletion 1.7-8
Ports Equipment 1.7-8
Unit Configuration 1.7-9
STM-1 Configuration 1.7-9
STM-1 Port Configuration 1.7-10
STM-1 Path Information Configuration 1.7-14
STM-1 Unit Configuration 1.7-16
STM-1 Channel Parameters Configuration 1.7-18
STM-1 Optical Parameters Configuration 1.7-20
STM-1 SOH Reading 1.7-21
2Mbit/s Configuration 1.7-22
2Mbit/s Port Configuration 1.7-23
2Mbit/s Path Information Configuration 1.7-25
2Mbit/s Unit Configuration 1.7-27
34-45Mbit/s Configuration 1.7-28
34-45Mbit/s Port Configuration 1.7-29
34-45Mbit/s Path Information Configuration 1.7-31
34-45Mbit/s Unit Configuration 1.7-33
140Mbit/s Configuration 1.7-34

140Mbit/s Port Configuration....1.7-35
140Mbit/s Path Information Configuration....1.7-37
140Mbit/s Unit Configuration....1.7-39
Auxiliary Unit Configuration....1.7-40
Auxiliary General Configuration....1.7-40
EOW1 and EOW2 Configuration....1.7-41
G703 Channel Configuration....1.7-43
V11 Channel Configuration....1.7-45
Loopback List....1.7-46
Diagnostic....1.7-46
Software Reset....1.7-47
Software Restart....1.7-47
Bank Switch....1.7-47
Bank Validation....1.7-48
Alarm Monitoring....1.7-48
Optical Info....1.7-50
CONFIGURATION OF ADM-1 OSI PROTOCOL....1.8-1
Changing the OSI Protocol Parameters....1.8-2
Message: Configuration of a DCC Profile (template file: s_dccp0)....1.8-3
Message: Configuration of Connection-less Network Service (template file: s_clns)....1.8-7
Message: Configuration of Reachable Address Prefix (template file: s_addrap)....1.8-11
Message: Delete of Reachable Address Prefix (template file: s_delrap)....1.8-12
Message: Configuration of Ethernet Channels (template file: s_eth)....1.8-13
Message: Configuration of Transport Module (template file: s_tp4)....1.8-15
Message: Restart OSI Protocol Stack (template file: s_osirst)....1.8-18
Message: Update OSI protocol stack (template file: s_osiupt)....1.8-18
Example of Static Routing Configuration using the OSI Setup Option....1.8-19
FAULT DETECTION PROCEDURE....1.9-1
SPI - Signal Physical Interface Alarms....1.9-1
LaserPwrOut (SPI)....1.9-1
LaserBiasOut (SPI)....1.9-1
ALSDisabled (SPI)....1.9-2
LOS (SPI)....1.9-2
ScramblerFail (SPI)....1.9-2
DescramblerFail (SPI)....1.9-3
TxClockFail (SPI)....1.9-3
RxClockFail (SPI)....1.9-3
RST - Regenerator Section Terminal....1.9-4
LOF (RST)....1.9-4
RS-TIM (RST)....1.9-4
DCCrLAPDDisc (RST)....1.9-5
MST - Multiplex Section Termination Alarms....1.9-5
MS-AIS (MST)....1.9-5
MS-RDI (MST)....1.9-5
MS-EXC (MST)....1.9-6
MS-DEG (MST)....1.9-6

DCCmLAPDDisconnected (MST) 1.9-6
MSP Alarms - Multiplex Section Protection 1.9-7
MSP-INV (MSP) 1.9-7
MSP-PAM (MSP) 1.9-7
MSA Alarms - Multiplex Section Adaptation 1.9-8
AU-LOP (MSA) 1.9-8
AU-AIS (MSA) 1.9-8
TxRejustFail (MSA) 1.9-9
RxRejustFail (MSA) 1.9-9
HPT Alarms - Higher order Path overhead termination 1.9-10
HP-TIM (HPT) 1.9-10
HP-PLM (HPT) 1.9-10
HP-RDI (HPT) 1.9-10
HP-DEG (HPT) 1.9-11
HP-EXC (HPT) 1.9-11
HP-UNEQ (HPT) 1.9-11
HPA_3 - Higher order Path Adaptation 1.9-12
TU-LOP (HPA_3) 1.9-12
TU-AIS (HPA_3) 1.9-12
LPOM_3 - Lower order Path Overhead 1.9-13
LP-TIM (LPOM_3) 1.9-13
LP-RDI (LPOM_3) 1.9-13
LPOM-DEG (LPOM_3) 1.9-14
LPOM-EXC (LPOM_3) 1.9-14
LP-UNEQ (LPOM_3) 1.9-14
HPA_2 - Higher order Path Adaptation 1.9-15
HP-LOM (HPA_2) 1.9-15
TU-LOP (HPA_2) 1.9-15
TU-AIS (HPA_2) 1.9-16
LPOM_2 - Lower order Path Overhead 1.9-16
LP-TIM (LPOM_2) 1.9-16
LP-RDI (LPOM_2) 1.9-17
LPOM-DEG (LPOM_2) 1.9-17
LPOM-EXC (LPOM_2) 1.9-18
LP-UNEQ (LPOM_2) 1.9-18
HPA_12 - Higher order Path Adaptation 1.9-19
TU-LOP (HPA_12) 1.9-19
TU-AIS (HPA_12) 1.9-19
LPOM_12 - Lower order Path Overhead Monitor 1.9-20
LP-TIM (LPOM_12) 1.9-20
LP-RDI (LPOM_12) 1.9-20
LPOM-DEG (LPOM_12) 1.9-21
LPOM-EXC (LPOM_12) 1.9-21
LP-UNEQ (LPOM_12) 1.9-21
PPI_140Mb - 140Mbit/s PDH Physical Interface Alarms 1.9-22
PDH-LOS (PPI_140Mb) 1.9-22

PDH-AIS (PPI_140Mb) 1.9-22
PDH-EXC (PPI_140Mb) 1.9-23
PDH-DEG (PPI_140Mb) 1.9-23
PDH-LOF (PPI_140Mb) 1.9-24
PDH-RDI (PPI_140Mb) 1.9-24
TxPulseLoss (PPI_140Mb) 1.9-24
TxBufferCont (PPI_140Mb) 1.9-25
RxBufferCont (PPI_140Mb) 1.9-25
PPI_34_45 - 34 and 45Mbit/s PDH Physical Interface Alarms 1.9-26
PDH-LOS (PPI_34_45) 1.9-26
PDH-AIS (PPI_34_45) 1.9-26
PDH-EXC (PPI_34_45) 1.9-27
PDH-DEG (PPI_34_45) 1.9-27
PDH-LOF (PPI_34_45) 1.9-28
PDH-RDI (PPI_34_45) 1.9-28
TxPulseLoss (PPI_34_45) 1.9-28
TxBufferCont (PPI_34_45) 1.9-29
RxBufferCont (PPI_34_45) 1.9-29
LPT_VC-3 - Lower order Path Termination 1.9-30
LP-PLM (LPT_VC-3) 1.9-30
LP-RDI (LPOM_VC-3) 1.9-30
LPOM-DEG (LPOM_VC-3) 1.9-31
LP-TIM (LPOM_VC-3) 1.9-31
LPOM-EXC (LPOM_VC-3) 1.9-31
LP-UNEQ (LPOM_VC-3) 1.9-32
PPI_2Mb-1.5 and 2Mbit/s PDH Physical Interface Alarms 1.9-32
PDH-LOS (PPI_2Mb) 1.9-32
PDH-AIS (PPI_2Mb) 1.9-33
PDH-EXC (PPI_2Mb) 1.9-33
PDH-DEG (PPI_2Mb) 1.9-33
PDH-LOF (PPI_2Mb) 1.9-34
PDH-RDI (PPI_2Mb) 1.9-34
TxPulseLoss (PPI_2Mb) 1.9-34
TxBufferCont (PPI_2Mb) 1.9-35
RxBufferCont (PPI_2Mb) 1.9-35
LPT_VC-12 - Lower order Path Termination 1.9-36
LP-PLM (LPT_VC-12) 1.9-36
LP-RDI (LPOM_VC-12) 1.9-36
LPOM-DEG (LPOM_VC-12) 1.9-37
LP-TIM (LPOM_VC-12) 1.9-37
LPOM-EXC (LPOM_VC-12) 1.9-37
LP-UNEQ (LPOM_VC-12) 1.9-38
LPT_VC-2 - Lower order Path Termination 1.9-38
LP-PLM (LPT_VC-2) 1.9-38
LP-RDI (LPOM_VC-2) 1.9-38
LPOM-DEG (LPOM_VC-2) 1.9-39

LP-TIM (LPOM_VC-2) 1.9-39
LPOM-EXC (LPOM_VC-2) 1.9-40
LP-UNEQ (LPOM_VC-2) 1.9-40
PORT - Unit Alarms 1.9-40
Missing (PORT) 1.9-40
Wrong (PORT) 1.9-41
Fail (PORT) 1.9-41
Comm (PORT) 1.9-41
MatrixAFail (PORT) 1.9-41
MatrixBFail (PORT) 1.9-42
TimexAFail (PORT) 1.9-42
TimexBFail (PORT) 1.9-42
TxOHBusFail (PORT) 1.9-43
Sync Alarm 1.9-43
OutOfFreq (Sync) 1.9-43
QL Invalid (Sync) 1.9-43
SystemSyncFail (Sync) 1.9-44
ExtOutSyncFail (Sync) 1.9-44
SyncSrcFail (Sync) 1.9-44
Power Alarm 1.9-45
Or Battery (Power) 1.9-45
Ground Contacts Alarms 1.9-45
GC_n 1.9-45
Unit Internal Fault Trouble-Shooting Procedure 1.9-46
Bit Error Rate Trouble-Shooting Procedure 1.9-47
Bit error rate on the STM-1 optical signal (MS-EXC/DEG) 1.9-47
Bit error rate on the STM-1 electrical signal (MS- EXC/DEG) 1.9-48
Bit error rate on the VC payload (PPI-EXC/DEG) 1.9-49
ERROR MESSAGES 1.10-1
Database Failure 1.10-1
Database Busy 1.10-1
Database Locked 1.10-1
Syntax Error 1.10-1
Unknown Message 1.10-1
Generic Error 1.10-1
Invalid Parameter 1.10-2
Invalid Value 1.10-2
Invalid String 1.10-2
Operation Not Allowed 1.10-2
Data Missing 1.10-2
No Resource 1.10-2
Wrong Unit Identifier 1.10-2
Unit Equipped 1.10-2
Unit Not Equipped 1.10-3
NE Not Equipped 1.10-3
NE Single Equipped 1.10-3

Ne Regenerator Equipped 1.10-3
Wrong Unit Type 1.10-3
In Use Unit 1.10-3
Wrong Protection Role 1.10-3
Wrong Path Protection Role 1.10-4
Wrong Protection Type 1.10-4
Wrong Worker Resource 1.10-4
Wrong Protection Resource 1.10-4
Wrong Protection Schema 1.10-4
No Protection Config 1.10-4
Invalid Configuration 1.10-4
Wrong Port Identifier 1.10-5
Port Equipped 1.10-5
Port Not Equipped 1.10-5
Wrong Channel Identifier 1.10-5
Connected Channel 1.10-5
Channel Not Connected 1.10-5
Channel Mismatch 1.10-5
Invalid Channels Order 1.10-6
Connection Locked 1.10-6
Wrong Alarm Category 1.10-6
Wrong Alarm Source 1.10-6
Not Providing Service 1.10-6
Quality Level Priority Duplicate 1.10-6
Quality Level Priority Undefined 1.10-6
Sync Source Not Equipped 1.10-6
Sync Source In Use 1.10-7
Port In Use for Sync 1.10-7
Port In Use for DCC 1.10-7
Quality Level In Use 1.10-7
Sync Not Configured 1.10-7
DCC Not Configured 1.10-7
Maximum number of DCC already configured 1.10-7
DCC Parameters already configured 1.10-7
DCCr_m already configured 1.10-8
RAP Already Equipped 1.10-8
RAP Not Equipped 1.10-8
Already Enabled 1.10-8
Already Disabled 1.10-8
No Records Enough 1.10-8
Performance Not Enabled 1.10-8
No Data 1.10-8
Wrong Monitored Entity 1.10-9
Parking On 1.10-9
Data Non Available 1.10-9
DBQ Empty 1.10-9

Invalid Access Rights 1.10-9
Not Implemented 1.10-9
Synchronization Source Already Equipped 1.10-9
Channel In Use For Test 1.10-9
Wrong Channel For Test 1.10-10
Erase Error 1.10-10
File Type Error 1.10-10
Write Failure 1.10-10
Wrong Checksum 1.10-10
Header Error 1.10-10
Download Running 1.10-10
Wrong Sequence 1.10-10
Download In Progress 1.10-11
Download Not In Progress 1.10-11
Wrong Units List 1.10-11
Unit Not Present 1.10-11
Bank Failure 1.10-11
No Boot Bank 1.10-11
Invalid Software Code 1.10-11
Download Abort 1.10-11
Most B Master 1.10-12
Alignment in Progress 1.10-12
Too many Ring Auxiliary Cross Connections 1.10-12
Too many Auxiliary ByPass Cross Connection 1.10-12
Invalid OH Bus 1.10-12
Invalid SOH Byte 1.10-12
SOH Byte Already in Use 1.10-12
Invalid Ring CAI 1.10-12
OH Byte Reserved 1.10-13
OH Byte in Use 1.10-13
Invalid Channel Structure 1.10-13
Cannot Be Driven 1.10-13
Invalid POH Byte 1.10-13
DATA DICTIONARY 1.11-1
Act Bank 1.11-1
Alarm Source (Source) 1.11-1
Alarm Type 1.11-1
Availability State (Av. State) 1.11-1
Bank 1 Sw 1.11-2
Bank 2 Sw 1.11-2
Boot Eprom 1.11-2
Category 1.11-2
Command Status / Command State 1.11-2
Configuration State 1.11-3
Cnf. State 1.11-3
DCC Type 1.11-3

Event Type 1.11-3
LAPD Side 1.11-4
Loopbacks Num 1.11-4
Mode 1.11-5
Monitoring 1.11-5
MS - Protection Role 1.11-5
Num 1.11-5
Operative State / Op. State 1.11-5
Part Number 1.11-6
PDH Traff. Rate 1.11-6
PL Expected (hex) 1.11-7
PL Received (hex) 1.11-8
Priority 1.11-9
Probable Cause 1.11-9
Profile 1.11-9
Protected By / Protecting 1.11-9
Prot.Role 1.11-10
Protection State / MSP Condition Type 1.11-10
Protection Type / Prot. Type 1.11-12
Protection Unit 1.11-13
QL Forced 1.11-13
QL Rx 1.11-13
QL Rx Enabled 1.11-13
Received Mode 1.11-14
Slot 1.11-14
Source / Active Source 1.11-15
Standby State 1.11-15
State 1.11-15
Status 1.11-16
Unit Id 1.11-17
Unit Type 1.11-17
Worker Unit 1.11-18
HOW TO 1.12-1
... Configure the System 1.12-2
Configure the Network Element 1.12-2
Create the Units 1.12-2
Assign Protection Roles 1.12-2
Equip Traffic Port 1.12-3
Set the System Management Parameters 1.12-4
Assign Alarm Settings 1.12-5
... Configure Protections 1.12-7
Configure Equipment Protection 1.12-7
Configure Network Protections 1.12-7
... Configure Synchronism 1.12-8
Equip Synchronisation Sources 1.12-8
Configure System Synchronism 1.12-8

Configure External Synchronisation Outputs 1.12-9
... Create Cross Connections 1.12-9
... Manage Performances 1.12-10
Configure the Performance Data Collection 1.12-10
Display the Performance Data Collection 1.12-10
... Perform Maintenance Operations 1.12-11
Perform a Database Upload 1.12-11
Perform a Database Download 1.12-11
Realise a Software Upgrade of the Equipment 1.12-11

"See Also" Index

In the following is given an alphabetical list of all the subject treated in the handbook for a quick reference with the "See Also:" indication at the end of every topic.

.

... Configure Protections 1.12-7

... Configure Synchronism ... 1.12-8

... Configure the System ... 1.12-2

... Create Cross Connections ... 1.12-9

... Manage Performances ... 1.12-10

... Perform Maintenance Operations ... 1.12-11

1

140Mbit/s Configuration ... 1.7-34

140Mbit/s Path Information Configuration ... 1.7-37

140Mbit/s Port Configuration ... 1.7-35

140Mbit/s Unit Configuration ... 1.7-39

2

2Mbit/s Configuration ... 1.7-22

2Mbit/s Path Information Configuration ... 1.7-25

2Mbit/s Port Configuration ... 1.7-23

2Mbit/s Unit Configuration ... 1.7-27

3

34-45Mbit/s Configuration ... 1.7-28

34-45Mbit/s Path Information Configuration ... 1.7-31

34-45Mbit/s Port Configuration ... 1.7-29

34-45Mbit/s Unit Configuration ... 1.7-33

A

Abnormal Condition ... 1.5-24

Access the Control Application Software ... 1.2-11

Act Bank ... 1.11-1

Activating the Control Application ... 1.2-1

Administrate State ... 1.5-65

Alarm and Event Monitor Window 1.3-12
Alarm Attributes 1.5-22
Alarm Monitoring 1.7-48
Alarm Parameters 1.5-19
Alarm Parameters Setting 1.1-5
Alarm Source (Source) 1.11-1
Alarm Type 1.11-1
Alignment in Progress 1.10-12
Already Disabled 1.10-8
Already Enabled 1.10-8
ALSDisabled (SPI) 1.9-2
Assign Alarm Settings 1.12-5
Assign Protection Roles 1.12-2
AU-AIS (MSA) 1.9-8
AU-LOP (MSA) 1.9-8
Auxiliary General Configuration 1.7-40
Auxiliary Unit Configuration 1.7-40
Availability State (Av. State) 1.11-1

B

Bank 1 Sw 1.11-2
Bank 2 Sw 1.11-2
Bank Failure 1.10-11
Bank Switch 1.7-47
Bank Validation 1.7-48
Bidirectional Cross Connection 1.5-53
Bit error rate on the STM-1 electrical signal (MS- EXC/DEG) 1.9-48
Bit error rate on the STM-1 optical signal (MS-EXC/DEG) 1.9-47
Bit error rate on the VC payload (PPI-EXC/DEG) 1.9-49
Bit Error Rate Trouble-Shooting Procedure 1.9-47
Boot Eprom 1.11-2
Broadcast Cross Connection 1.5-54
Busy Channel Indication 1.5-65

C

Cannot Be Driven 1.10-13
Category 1.11-2
Changing the OSI Protocol Parameters 1.8-2
Channel In Use For Test 1.10-9
Channel Mismatch 1.10-5
Channel Not Connected 1.10-5
Cnf. State 1.11-3
Comm (PORT) 1.9-41
Command Status / Command State 1.11-2
Configuration 1.5-1
Configuration of ADM-1 OSI Protocol 1.8-1
Configuration of Communication Parameters 1.2-12
Configuration of Unit 1.5-3
Configuration State 1.11-3
Configure Equipment Protection 1.12-7
Configure External Synchronisation Outputs 1.12-9
Configure Network Protections 1.12-7
Configure System Synchronism 1.12-8
Configure the Network Element 1.12-2
Configure the Performance Data Collection 1.12-10
Connected Channel 1.10-5
Connection Locked 1.10-6
Connection of Personal Computer to ADM-1 ..... 1.2-1
Create the Units 1.12-2
Cross Connections 1.5-48

D

Data Dictionary 1.11-1
Data Missing 1.10-2
Data Non Available 1.10-9
Database Busy 1.10-1
Database Clear 1.6-31
Database Download 1.6-28
Database Failure 1.10-1

Database Locked 1.10-1
Database Upload 1.6-27
DBQ Empty 1.10-9
DCC Configuration 1.6-2
DCC Not Configured 1.10-7
DCC Parameters already configured 1.10-7
DCC Type 1.11-3
DCCmLAPDDisconnected (MST) 1.9-6
DCCr_m already configured 1.10-8
DCCrLAPDDisc (RST) 1.9-5
Deletion of a Cross Connection 1.5-66
DescramblerFail (SPI) 1.9-3
Diagnostic 1.7-46
Display the Performance Data Collection 1.12-10
Download Abort 1.10-11
Download In Progress 1.10-11
Download Not In Progress 1.10-11
Download Running 1.10-10
Dropped Cross Connection Switch Operations 1.5-61
Dropped Cross Connections 1.5-59

E

EOW1 and EOW2 Configuration 1.7-41
Eqt Protection Switch (Event Details) 1.5-14
Equip Synchronisation Sources 1.12-8
Equip Traffic Port 1.12-3
Equipment Protection 1.5-10
Equipment Protection Switch Operations 1.5-12
Equipping Synchronisation Sources 1.5-29
Erase Error 1.10-10
Error Messages 1.10-1
Event Report 1.5-18
Event Type 1.11-3
Example of Static Routing Configuration using the OSI Setup Option 1.8-19
Exception Report Enable 1.6-11
Exit 1.2-17

External Synchronisation Output Switch Operations 1.5-45
External Synchronisation Outputs 1.5-41
ExtOutSyncFail (Sync) 1.9-44

F

Fail (PORT) 1.9-41
Fault Detection Procedure 1.9-1
File Type Error 1.10-10

G

G703 Channel Configuration 1.7-43
GC_n 1.9-45
General Information 1.1-1
General Parameters Configuration 1.1-4
Generic Error 1.10-1
Ground Contacts 1.5-26
Ground Contacts Alarms 1.9-45

H

Header Error 1.10-10
How to 1.12-1
HPA_12 - Higher order Path Adaptation 1.9-19
HPA_2 - Higher order Path Adaptation 1.9-15
HPA_3 - Higher order Path Adaptation 1.9-12
HP-DEG (HPT) 1.9-11
HP-EXC (HPT) 1.9-11
HP-LOM (HPA_2) 1.9-15
HP-PLM (HPT) 1.9-10
HP-RDI (HPT) 1.9-10
HPT Alarms - Higher order Path overhead termination 1.9-10
HP-TIM (HPT) 1.9-10
HP-UNEQ (HPT) 1.9-11

I

In Use Unit 1.10-3
Installing the Configuration File "download.ini" 1.2-10
Installing the Local Operator 1.2-3
Installing the Online Help files 1.2-7
Introduction 1.1-1
Invalid Access Rights 1.10-9
Invalid Channel Structure 1.10-13
Invalid Channels Order 1.10-6
Invalid Configuration 1.10-4
Invalid OH Bus 1.10-12
Invalid Parameter 1.10-2
Invalid POH Byte 1.10-13
Invalid Ring CAI 1.10-12
Invalid Software Code 1.10-11
Invalid SOH Byte 1.10-12
Invalid String 1.10-2
Invalid Value 1.10-2
Inventory Data 1.6-9

L

Language Configuration 1.6-30
LAPD Side 1.11-4
LaserBiasOut (SPI) 1.9-1
LaserPwrOut (SPI) 1.9-1
LC Log 1.5-19
Local Control 1.1-2
Local Controller Protocol Version 1.6-30
Local Controller Software Version 1.6-31
LOF (RST) 1.9-4
Log out 1.2-17
Login 1.1-4
Login Access 1.2-13
Loopback Cross Connection 1.5-56
Loopback List 1.7-46

Loopbacks Num 1.11-4
LOS (SPI) 1.9-2
LPOM_12 - Lower order Path Overhead Monitor 1.9-20
LPOM_2 - Lower order Path Overhead 1.9-16
LPOM_3 - Lower order Path Overhead 1.9-13
LPOM-DEG (LPOM_12) 1.9-21
LPOM-DEG (LPOM_2) 1.9-17
LPOM-DEG (LPOM_3) 1.9-14
LPOM-DEG (LPOM_VC-12) 1.9-37
LPOM-DEG (LPOM_VC-2) 1.9-39
LPOM-DEG (LPOM_VC-3) 1.9-31
LPOM-EXC (LPOM_12) 1.9-21
LPOM-EXC (LPOM_2) 1.9-18
LPOM-EXC (LPOM_3) 1.9-14
LPOM-EXC (LPOM_VC-12) 1.9-37
LPOM-EXC (LPOM_VC-2) 1.9-40
LPOM-EXC (LPOM_VC-3) 1.9-31
LP-PLM (LPT_VC-12) 1.9-36
LP-PLM (LPT_VC-2) 1.9-38
LP-PLM (LPT_VC-3) 1.9-30
LP-RDI (LPOM_VC-12) 1.9-36
LP-RDI (LPOM_VC-2) 1.9-38
LP-RDI (LPOM_VC-3) 1.9-30
LP-RDI (LPOM_12) 1.9-20
LP-RDI (LPOM_2) 1.9-17
LP-RDI (LPOM_3) 1.9-13
LPT_VC-12 - Lower order Path Termination 1.9-36
LPT_VC-2 - Lower order Path Termination 1.9-38
LPT_VC-3 - Lower order Path Termination 1.9-30
LP-TIM (LPOM_12) 1.9-20
LP-TIM (LPOM_2) 1.9-16
LP-TIM (LPOM_3) 1.9-13
LP-TIM (LPOM_VC-12) 1.9-37
LP-TIM (LPOM_VC-2) 1.9-39
LP-TIM (LPOM_VC-3) 1.9-31

LP-UNEQ (LPOM_12) 1.9-21
LP-UNEQ (LPOM_2) 1.9-18
LP-UNEQ (LPOM_3) 1.9-14
LP-UNEQ (LPOM_VC-12) 1.9-38
LP-UNEQ (LPOM_VC-2) 1.9-40
LP-UNEQ (LPOM_VC-3) 1.9-32

M

Main Functions 1.3-1
Main Window 1.2-15
Maintenance 1.6-1
MatrixAFail (PORT) 1.9-41
MatrixBFail (PORT) 1.9-42
Maximum number of DCC already configured 1.10-7
Message: Configuration of a DCC Profile (template file: s_dccp0) 1.8-3
Message: Configuration of Connection-less Network Service (template file: s_clns) 1.8-7
Message: Configuration of Ethernet Channels (template file: s_eth) 1.8-13
Message: Configuration of Reachable Address Prefix (template file: s_addrap) 1.8-11
Message: Configuration of Transport Module (template file: s_tp4) 1.8-15
Message: Delete of Reachable Address Prefix (template file: s_delrap) 1.8-12
Message: Restart OSI Protocol Stack (template file: s_osirst) 1.8-18
Message: Update OSI protocol stack (template file: s_osiupt) 1.8-18
Missing (PORT) 1.9-40
Mode 1.11-5
Monitor Cross Connection 1.5-58
Monitoring 1.11-5
Most B Master 1.10-12
MOST Switch 1.6-29
MS - Protection Role 1.11-5
MSA Alarms - Multiplex Section Adaptation 1.9-8
MS-AIS (MST) 1.9-5
MS-DEG (MST) 1.9-6
MS-EXC (MST) 1.9-6
MSP Alarms - Multiplex Section Protection 1.9-7
MSP Protection 1.5-5
MSP Protection Switch (Event Details) 1.5-9

MSP Switch Operations 1.5-8
MSP-INV (MSP) 1.9-7
MSP-PAM (MSP) 1.9-7
MS-RDI (MST) 1.9-5
MST - Multiplex Section Termination Alarms 1.9-5
Multiply SDH Frame 1.5-50

N

NE Configuration 1.5-1
NE General Parameters 1.6-1
NE Log 1.5-16
NE Not Equipped 1.10-3
Ne Regenerator Equipped 1.10-3
NE Single Equipped 1.10-3
Network Configuration 1.6-4
No Boot Bank 1.10-11
No Data 1.10-8
No Protection Config 1.10-4
No Records Enough 1.10-8
No Resource 1.10-2
Not Implemented 1.10-9
Not Providing Service 1.10-6
Num 1.11-5

O

OH Byte in Use 1.10-13
OH Byte Reserved 1.10-13
Operation Not Allowed 1.10-2
Operational Features 1.1-4
Operative State / Op. State 1.11-5
Optical Info 1.7-50
Or Battery (Power) 1.9-45
OSI Parameters Get 1.5-75
OSI Parameters Setup 1.5-73
OutOfFreq (Sync) 1.9-43

P

Parking On 1.10-9
Parking Status 1.5-28
Part Number 1.11-6
Password Management 1.2-16
Path Prot. Switch (Event Details) 1.5-63
Path Prot. Switch SNC (Event Details) 1.5-71
PDH Traff. Rate 1.11-6
PDH-AIS (PPI_140Mb) 1.9-22
PDH-AIS (PPI_2Mb) 1.9-33
PDH-AIS (PPI_34_45) 1.9-26
PDH-DEG (PPI_140Mb) 1.9-23
PDH-DEG (PPI_2Mb) 1.9-33
PDH-DEG (PPI_34_45) 1.9-27
PDH-EXC (PPI_140Mb) 1.9-23
PDH-EXC (PPI_2Mb) 1.9-33
PDH-EXC (PPI_34_45) 1.9-27
PDH-LOF (PPI_140Mb) 1.9-24
PDH-LOF (PPI_2Mb) 1.9-34
PDH-LOF (PPI_34_45) 1.9-28
PDH-LOS (PPI_140Mb) 1.9-22
PDH-LOS (PPI_2Mb) 1.9-32
PDH-LOS (PPI_34_45) 1.9-26
PDH-RDI (PPI_140Mb) 1.9-24
PDH-RDI (PPI_2Mb) 1.9-34
PDH-RDI (PPI_34_45) 1.9-28
Perform a Database Download 1.12-11
Perform a Database Upload 1.12-11
Performance Data Collection 1.6-12
Performance Exception Thresholds 1.6-15
Performance Not Enabled 1.10-8
Performance Parameters 1.6-10
PL Expected (hex) 1.11-7
PL Received (hex) 1.11-8
PORT - Unit Alarms 1.9-40
Port Equipment and Configuration 1.1-5

Port Equipped 1.10-5
Port In Use for DCC 1.10-7
Port In Use for Sync 1.10-7
Port Not Equipped 1.10-5
Ports Equipment 1.7-8
Power Alarm 1.9-45
PPI_140Mb - 140Mbit/s PDH Physical Interface Alarms 1.9-22
PPI_2Mb-1.5 and 2Mbit/s PDH Physical Interface Alarms 1.9-32
PPI_34_45 - 34 and 45Mbit/s PDH Physical Interface Alarms 1.9-26
Priority 1.11-9
Probable Cause 1.11-9
Profile 1.11-9
Prot.Role 1.11-10
Protected By / Protecting 1.11-9
Protection Configuration 1.1-6
Protection Parameters 1.5-15
Protection Role 1.5-3
Protection State / MSP Condition Type 1.11-10
Protection Type / Prot. Type 1.11-12
Protection Unit 1.11-13

Q

QL Forced 1.11-13
QL Invalid (Sync) 1.9-43
QL Rx 1.11-13
QL Rx Enabled 1.11-13
QL Table Entry 1.5-47
Quality Level In Use 1.10-7
Quality Level Priority Duplicate 1.10-6
Quality Level Priority Undefined 1.10-6

R

Rack Lamp Configuration 1.5-25
RAP Already Equipped 1.10-8
RAP Not Equipped 1.10-8
Realise a Software Upgrade of the Equipment 1.12-11
Received Mode 1.11-14
Refresh 1.4-1
Remote Control Parameters Configuration 1.1-5
Remote Login 1.1-3
RST - Regenerator Section Terminal 1.9-4
RS-TIM (RST) 1.9-4
RxBufferCont (PPI_2Mb) 1.9-35
RxBufferCont (PPI_140Mb) 1.9-25
RxBufferCont (PPI_34_45) 1.9-29
RxClockFail (SPI) 1.9-3
RxRejustFail (MSA) 1.9-9

S

ScramblerFail (SPI) 1.9-2
Serial Port Configuration 1.6-29
Set the System Management Parameters 1.12-4
Slot 1.11-14
SNC Protection 1.5-67
SNCP Switch Operations 1.5-70
Software Download 1.6-26
Software Info 1.6-8
Software Installation 1.2-3
Software Reset 1.7-47
Software Restart 1.7-47
SOH Byte Already in Use 1.10-12
SOH Bytes Configuration 1.5-72
Source / Active Source 1.11-15
SPI - Signal Physical Interface Alarms 1.9-1
Split Access Cross Connection 1.5-57
Standby State 1.11-15

State 1.11-15
Status 1.11-16
Status Bar 1.4-1
STM-1 Channel Parameters Configuration 1.7-18
STM-1 Configuration 1.7-9
STM-1 Optical Parameters Configuration 1.7-20
STM-1 Path Information Configuration 1.7-14
STM-1 Port Configuration 1.7-10
STM-1 SOH Reading 1.7-21
STM-1 Unit Configuration 1.7-16
Summary LEDs Status 1.5-23
Sync Alarm 1.9-43
Sync Not Configured 1.10-7
Sync Source In Use 1.10-7
Sync Source Not Equipped 1.10-6
Sync switch -> External Sync (Event Details) 1.5-46
Sync switch -> System Sync (Event Details) 1.5-40
Synchronisation 1.5-29
Synchronism Management 1.1-6
Synchronization Source Already Equipped 1.10-9
SyncSrcFail (Sync) 1.9-44
Syntax Error 1.10-1
System Architecture 1.1-2
System Synchronisation Sources 1.5-35
System Synchronisation Sources Switch Operations 1.5-38
SystemSyncFail (Sync) 1.9-44

T

The Connection Status Indication 1.3-7
The Graphical Area 1.3-3
The Menu Bar and Menus 1.3-1
The Serial Port Button Status Indication 1.3-7
The Tool Bar 1.3-8
TimexAFail (PORT) 1.9-42
TimexBFail (PORT) 1.9-42
Too many Auxiliary ByPass Cross Connection 1.10-12

Too many Ring Auxiliary Cross Connections 1.10-12
Toolbar 1.4-1
Traffic Management 1.1-6
TU-AIS (HPA_12) 1.9-19
TU-AIS (HPA_3) 1.9-12
TU-AIS (HPA_2) 1.9-16
TU-LOP (HPA_12) 1.9-19
TU-LOP (HPA_3) 1.9-12
TU-LOP (HPA_2) 1.9-15
TxBufferCont (PPI_140Mb) 1.9-25
TxBufferCont (PPI_2Mb) 1.9-35
TxBufferCont (PPI_34_45) 1.9-29
TxClockFail (SPI) 1.9-3
TxOHBusFail (PORT) 1.9-43
TxPulseLoss (PPI_140Mb) 1.9-24
TxPulseLoss (PPI_2Mb) 1.9-34
TxPulseLoss (PPI_34_45) 1.9-28
TxRejustFail (MSA) 1.9-9

U

Unidirectional Cross Connection 1.5-52
Unit Active Alarms 1.7-2
Unit Configuration 1.7-9
Unit Creation 1.7-7
Unit Deletion 1.7-8
Unit Equipped 1.10-2
Unit Functions 1.7-1
Unit Id 1.11-17
Unit Info 1.7-4
Unit Internal Fault Trouble-Shooting Procedure 1.9-46
Unit Inventory Data 1.7-6
Unit Management 1.1-5
Unit Not Equipped 1.10-3
Unit Not Present 1.10-11
Unit Software Info 1.7-5
Unit Type 1.11-17

Unknown Message 1.10-1

V

V11 Channel Configuration 1.7-45
VC-2n-C Cross Connection 1.5-64
View Options 1.4-1

W

Worker Unit 1.11-18
Working Area 1.3-1
Write Failure 1.10-10
Wrong (PORT) 1.9-41
Wrong Alarm Category 1.10-6
Wrong Alarm Source 1.10-6
Wrong Channel For Test 1.10-10
Wrong Channel Identifier 1.10-5
Wrong Checksum 1.10-10
Wrong Monitored Entity 1.10-9
Wrong Path Protection Role 1.10-4
Wrong Port Identifier 1.10-5
Wrong Protection Resource 1.10-4
Wrong Protection Role 1.10-3
Wrong Protection Schema 1.10-4
Wrong Protection Type 1.10-4
Wrong Sequence 1.10-10
Wrong Unit Identifier 1.10-2
Wrong Unit Type 1.10-3
Wrong Units List 1.10-11
Wrong Worker Resource 1.10-4

Z

Zoom Fault Window 1.4-1