



SPOELN	CODE N°	CONDENSATOREN	CODE N°	WIERSTANDEN	CODE N°
S ₁ = 13 W	2564797	C ₁ = 500 μμF	25113070	R ₁ = 10000 Ω	77x13 GLAS- BUIS 2572189
S ₂ = 300 W 3x100		C ₂ = 41 μF		R ₂ = 400 Ω	
S ₃ = 32 W		C ₃ = 0,1 μF	MICR	R ₃ = 40000 Ω	
S ₄		C ₄ = 430 μμF		R ₄ = 100000 Ω	
S ₅ = 2 x 1614 W		C ₅ = 0,5 μF		R ₅ = 40000 Ω	
S ₆ = 20 W		C ₆ = 125 μμF	25112790	R ₆ = 2 MΩ	
S ₇ = 2 x 14 W		C ₇ = 0,25 μF		R ₇ = 0,32 MΩ	
S ₈		C ₈ = 500 μμF	MICR	R ₈ = 0,2 MΩ	
S ₉ = 4000 W		C ₉ = 250 μμF	25112020	R ₉ = 20000 Ω	
S ₁₀ = 57 W		C ₁₀ = 1 μF		R ₁₀ = 1 MΩ	
	2161	C ₁₁ = 8000 μμF	25113280	R ₁₁ = 10000 Ω	
		C ₁₂ = 8000 μμF	25113280	R ₁₂ = 1000 Ω	
		C ₁₃ = 0,25 μF		R ₁₃ = 640 Ω	
		C ₁₄ = 0,25 μF		R ₁₄ = 40 Ω	
		C ₁₅ = 16 μF	EL. COND	R ₁₅ = 4 MΩ	
		C ₁₆ = 16 μF	EL. COND	R ₁₆ = 1 MΩ	
		C ₁₇ = 800 μμF		R ₁₇ = 0,647 Ω	
			R ₁₈ = 50000 Ω		
			R ₁₉ = 10000 Ω		

LAMPEN	BYDEHOORENDE GEGEVENS
L ₁ = E 462	COND. DOOS: C ₂ , 3, 5-7, 10-13-2511330
L ₂ = E 462	LUIDSPREKER: 2161
L ₃ = E 443 H	
L ₄ = 1023	
L ₅ = 6V 0,3 A	

Auteursrecht volgens de wet voorbehouden

Titel:	Opmerkingen:	
PRINCIPE SCHEMA KY 120	KY 120	A 4

	20 = ± 0,5	Schaal:	Get. SCHOUTEN	2638
	25,0 = ± 0,2	Gecalq.	Gez.	
	25,0 = ± 0,05			