

Product DATASHEET

Dual Channel, Datalogging, True RMS MultiMeter

Measure and display two Voltages or Voltage and Current simultaneously

Features:

- 60,000 counts, dual input channels with dual display and 30 segment bargraph
- 0.03% basic DCV accuracy
- 200kHz AC bandwidth
- Auto/manual ranging
- Functions include Capacitance, Frequency, Resistance, Continuity, Duty Cycle (TTL & Sine Wave) and Diode test
- AC/DC Current to 10A with 0.01μA resolution
- Simultaneously displays Frequency and Duty Cycle
- Stand-alone datalogging of 10,708 data points on both channels
- Record data of both channels using a PC through the built-in RS-232 interface
- Relative, Min/Max, and Hold functions
- · Overload and low battery indication
- Complete with test leads, protective holster with built-in stand, Windows® 95/98/NT/2000/ME/XP compatible software, optically isolated RS-232 cable, and 9V battery

Applications:

- View input voltage and compare to output in an analog circuit
- · Observe and plot current vs. voltage
- Study the relationship of two voltages similar to a dual channel DSO
- Datalog input voltage and view response over time

(E CAT III-1000V

Specifications	Range	Max. Resolution	Basic Accuracy
DC Voltage:	60mV, 600mV, 6V, 60V, 600V, 1000V	0.001mV	±0.03%
AC Voltage:	60mV, 600mV, 6V, 60V, 600V, 1000V	0.001mV	±0.1%
DC Current:	600μA, 6000μA, 60mA, 600mA, 1A, 10A	0.01μΑ	±0.1%
AC Current:	600μA, 6000μA, 60mA, 600mA, 1A, 10A	0.01μΑ	±0.3%
Resistance:	1 k Ω , 10 k Ω , 100 k Ω , 1 M Ω , 10 M Ω , 40 M Ω	0.01Ω	±0.09%
Capacitance:	60nF, 600nF, 6μF, 60μF, 490μF	0.01nF	±0.8%
Frequency:	1Hz to 2MHz	0.0001Hz	±0.005%
Duty Cycle (TTL):	0.001% to 100.00%	0.001%	±3%
Dimensions/Wt:	8.15 x 4 x 1.85" (207 x 101 x 47mm) / 15.2oz (430g)		



Ordering Information:

380900Dual Channel, Datalogging, True RMS DMM **380900-NIST** ..Dual Channel, Datalogging, True RMS DMM w/NIST Cert.

