

# Manual Supplement

Manual Title:	74X Series Calibration	Supplement Issue:	1
Part Number:	602505	Issue Date:	4/06
Print Date:	February 1997	Page Count:	1
Revision/Date:	2, 4/99		

---

---

This supplement contains information necessary to ensure the accuracy of the above manual. Enter the corrections in the manual if either one of the following conditions exist:

1. The revision letter stamped on the indicated PCA is equal to or higher than that given with each change.
2. No revision letter is indicated at the beginning of the change.

## Change #1

On page 6, replace the bottom portion of the **Frequency Sourcing** table with the following:

<p><b>Waveform Choices:</b> Zero-symmetric sine or positive square wave, 50% duty cycle. <b>Amplitude:</b> 0.1 to 10 V pk (square wave, 0 V reference) 0.1 to 10 V p-p (sinewave) <b>Amplitude Accuracy:</b> <b>0 Hz to 1099 Hz:</b> 3% of output + 0.5% f.s. (squarewave) <b>1.0 Hz to 1099 Hz:</b> 3% of output + 0.5% f.s (sinewave) <b>1.1 kHz to 10.9 kHz:</b> 10% of output + 0.5% f.s. <b>11 kHz to 50 kHz:</b> 30% of output + 0.5% f.s. <b>Maximum Input Voltage:</b> 30 V dc</p>
--

Under **Temperature, Thermocouples Type E**, delete the entire third row.