Manual Supplement

Manual Title:787 CallibrationSupplement Issue:1Part Number:641891Issue Date:2/04Print Date:May 1998Page Count:1

Revision/Date: 1, 9/00

This supplement contains information necessary to ensure the accuracy of the above manual. Enter the corrections in the manual if either one of the following conditions exist:

- 1. The revision letter stamped on the indicated PCA is equal to or higher than that given with each change.
- 2. No revision letter is indicated at the beginning of the change.



787 Calibration Manual Supplement

Change #1

On page 5, under Table 2, replace the following sections of the table and delete the footnote:

Equipment	Minimum Specifications	Recommended Model
Digital Multimeter	No Substitute	Fluke 8508A
Calibration Module w/Battery Eliminator	⚠ No Substitute. A generic battery eliminator might pose a safety hazard. Includes Cal Module, Battery Eliminator, Calibration Manual.	Fluke-787CAL 120 (USA/Canada) Fluke-787CAL 230 (Europe) Fluke-787CAL 240 (UK) Fluke-787CAL 240AN (Australia) Fluke-787CAL 100 (Japan)
Personal Computer	Windows [®] 95 or later (Refer to MET/CAL [®] manual set), 64 MB RAM, 500 MB on disk, VGA monitor.	Pentium 133 MHz, IBM-compatible
Calibration Software	No Substitute	Fluke MET/CAL Calibration Software

On page 12, replace the **Computer-Automated Verification Test Procedures** with the following:

Computer-Automated Calibration Procedures

Computer-automated verification test procedures for the 787 ProcessMeter are available on Fluke's MET/CAL website.

These procedures require Fluke's MET/CAL Calibration Software, a 787 Calibration Module, a Fluke 5500A or 5520A Calibrator, and a Fluke 8508A Reference Multimeter.

Refer to the MET/CAL manual set for more information.

2/04