

Fluke 8060/8062A Technical Specifications	
VDC	Range and Resolution: 200.00 mV, 2.0000V, 20.000V, 200.00V, 1000.0V 8060A: 200.00 mV, 2.0000V, 20.000V, 200.00V, 1000.0V 8062A: $\pm(0.05\%+2)$
VAC (True-RMS, AC Coupled)	Range and Resolution: 200.00 mV, 2.0000V, 20.000V, 200.00V, 750.0V 8060A: $\pm(0.2\%+10)$ 8062A: $\pm(0.5\%+10)$
dBm, 600Ohms reference	Range and Resolution: -50.00 - +60.00 dBm 8060A: $\pm(0.15 \text{ dB})$ 8062A: NA
ADC	Range and Resolution: 200.00 μ A, 2.0000 mA, 20.000 mA, 200.00 mA, 2000.0 mA 8060A: $\pm(0.2\%+2)$ 8062A: $\pm(0.3\%+2)$
AAC (True-RMS)	Range and Resolution: 200.00 μ A, 2.0000 mA, 20.000 mA, 200.00 mA, 2000.0 mA 8060A: $\pm(0.75\%+10)$ 8062A: $\pm(0.75\%+10)$
Resistance	Range and Resolution: 200.00Ohms, 2.0000 kOhms, 20.000 kOhms, 200.00 kOhms, 300.0 MOhms 8060A: $\pm(0.07\%+2)$ 8062A: $\pm(0.1\%+2)$
Frequency	Range and Resolution: 200.00 Hz, 2.0000 kHz, 20.000 kHz, 200.00 kHz 8060A: $\pm(0.05\%+1)$ 8062A: NA
Conductance	Range and Resolution: 2000.0 nS (equivalent to 500 kOhms) 8060A: $\pm(0.5\%+20)$ 8062A: NA

General Specifications	
Battery Life	170 hours typical (9V alkaline)
Weight	0.41 kg (0.90 lb)
Size	180 mm L x 86 mm W x 45 mm D (7.1" L x 3.4" W x 1.8" D)
One Year Warranty	One year guaranteed calibration