



CE₁₃₀₉

PIV Prüfinstitut Schlösser und Beschläge Velbert
Wallstraße 41 – D 42551 Velbert
Director of the institute: Rainer Ehle, Dipl.-Ing.
Tel 0049-(0)2051-9506 5
Fax 0049-(0)2051-9506 69
Mail: piv.velbert@t-online.de

EC-Certificate of Conformity

Certificate

1309 - CPD - 0132

In compliance with the Directive 89/106/EEC of the Council of European Communities of 21 December 1988 on the approximation of laws, regulations and administrative provisions of the Member States relating to the construction products (Construction Products Directive - CPD), amended by the Directive 93/68/EEC of the Council of European Communities of 22 July 1993, it has been stated that the construction product

**Electronic automatic multi point locking system with anti-panic function
Autotronic 834P**

**Automatic multi point locking system with anti-panic function
Multisafe 833P**

for 2-leaf emergency exit doors

placed on the market by

Carl Fuhr GmbH & Co. KG
Carl-Fuhr-Str. 12
D-42579 Heiligenhaus

and produced in the factory

Carl Fuhr GmbH & Co. KG
D-42579 Heiligenhaus

is submitted by the manufacturer to a factory production control and to the further testing of samples taken at the factory in accordance with a prescribed test plan and that the notified body - < PIV > - has performed the initial type-testing for the relevant characteristics of the product, the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.

This certificate attests that all provisions concerning the attestation of conformity and the performances described in the Annex ZA. of the standard

EN 179:2008

Product classification key

1	2	3	4	5	6	7	8	9	10
3	7	6	0	1	3	5	2	A	A

were applied and that the product fulfils all the prescribed requirements.

This certificate was first issued on < 31.08.2011 > and remains valid as long as the conditions laid down in the harmonised technical specification in reference or the manufacturing conditions in the factory or the FPC itself are not modified significantly.

Stamp of the notified body

D-Velbert, 14.10.2011



H. Wichert
Deputy Manager of the Notified body

This certificate consists 4 pages.



Enclosure of accepted hardware:

Accepted panic exit devices / Locks / Accessories

Manufacturer	Product description	Remark	Function	Distance backset	Forend
FUHR	Autotronic 834P	Electronic automatic multi point locking system with anti-panic function	I and IV 1)	D = 92mm backset 35 to 80mm	Flat forend 16 - 30mm U-forend 22 - 30mm Length up to 2400 mm
FUHR	Multisafe 833P	Automatic multi point locking system with anti-panic function	I and IV 1)	D = 92mm backset 35 to 80mm	Flat forend 16 - 30mm U-forend 22 - 30mm Length up to 2400 mm
FUHR	MPG x	Anti-panic keep for inactive leave X stands for backset-/forend dimension-based item no.		D = 92 backset 35 - 65mm	Flat forend 16 - 30mm U-forend 22 - 30mm
FUHR	MPS	Switching lock			
FUHR	MPSU	Spacer to switching lock			
FUHR	MPM69N	Pushing flap			
FUHR	MPQRG0950 MPQRG1500 RS26720	Bottom round rod Top straight length Rod guiding system			

Function I: One-piece follower, all the time effective panic exit device function from the inside. From the inside the opening by the fitting is always possible. From the outside opening is possible with the key by latch lever.
Latch lever function E

Function IV: Split follower, all the time effective panic exit device function from the inside. From the inside the opening by the indoor fitting is always possible. In its basic position the door is locked automatically and the outdoor fitting is blocked. The outdoor fitting can always be released or be blocked (basic position) by key. After an inside actuation of hardware the door cannot be opened in its basic position by hardware from the outside.
Shift function B

- 1) Controlled latch locking device: By the actuation of the fitting all locking components are retracted and are locked in this position by the key of the profile cylinder. The locking components remain withdrawn up to the next actuation of the key. Not acceptable for fire doors and smoke control doors.



Accepted locking plates

Manufacturer	Product description	Remark
FUHR	Locking plate inactive top leaf MPRNR5174003	
FUHR	Locking plate inactive bottom leaf (Floor locking trough) MPRNR5174006	
FUHR	Latchbolt locking plate RNVVxxxxx	Xxxxx stands for profile-dependent item numbers

Accepted square pins

Manufacturer	Product description	Remark
FUHR	POM870xxx	Xxx stands for the length 50mm/ 60mm/ 70mm/ 80mm
FUHR	PVZS120Gxx PVZS120Sxx	2-part pins xx stands for the length 53mm/ 60mm/ 67mm/ 74mm 48mm/ 55mm/ 62mm/ 69mm
FUHR	PV9xxxV	Xxx stands for the length 60mm/ 70mm/ 100mm

Accepted handle sets

Manufacturer	Product description	Coding	Remark
DORMA	Plate series ZS 6500 to 7020	DO 20.4.01 DO 20.4.02	
HOPPE	All sets according to EN 179 with the adjoining coding	DO 20.20.01 DO 20.20.02 DO 20.2.02-RD DO 20.5.01 DO 20.5.02 DO 20.5.02-RD DO 20.7.01 DO 20.7.02	
KABA/GEGE (Grundmann)	11640072+11640075 11649768	DO 20.26.01 DO 20.26.02	Manufacturer Grundmann
KABA/GEGE (Glutz)	11643674+11643670 11643668	DO 20.21.01 DO 20.21.02	Manufacturer Glutz
VBH	Series 2017 to 2526 and 6011		
HAFI	Series 202, 205, 207, 209, 223, 224, 225	DO 20.32.01 DO 20.32.02	



Producttable for EC-Certificate of Conformity

1309 – CPD – 0132

FUHR

Accepted handle sets (Continue)

FSB	Series 7616 to 7651	DO 20.3.01 DO 20.3.02	
HEWI	111X, 112X, 113X, 114X, 165X, 166X, 161X, 163X, 171X and FSDG550.08	DO 20.13.01 DO 20.13.02	
ECO	D 110, D 115, D 116, D 120, D 190, D 330, D 335, D 410, D 415, D 490	DO 20.1.01 DO 20.1.02	

Accepted Doorkeepers

Manufacturer	Product description	Remark
GfS Hamburg	GfS Standard Doorkeeper GfS EH-Doorkeeper	

Using the locking cylinder the control element (key, knob or similar) must not obstruct the actuation of the handle.



H. Wichert
Deputy Manager of the Notified Body