



CE<sub>1309</sub>

PIV Prüfinstitut Schlösser und Beschläge Velbert  
Wallstraße 41 – D 42551 Velbert  
Director of the institute: Rainer Ehle, Dipl.-Ing.  
Tel 0049-(0)2051-9506 5  
Fax 0049-(0)2051-9506 69  
Mail: [piv.velbert@t-online.de](mailto:piv.velbert@t-online.de)

# EC-Certificate of Conformity

## Certificate

**1309 - CPD - 0140**

In compliance with the Directive 89/106/EEC of the Council of European Communities of 21 December 1988 on the approximation of laws, regulations and administrative provisions of the Member States relating to the construction products (Construction Products Directive - CPD), amended by the Directive 93/68/EEC of the Council of European Communities of 22 July 1993, it has been stated that the construction product

**Emergency exit device for single-leaf doors according to EN 179  
Multisafe 870 / Multitronic 881  
Type 11, Type 11 GL**

placed on the market by

**Carl Fuhr GmbH & Co. KG**  
Carl-Fuhr-Str. 12  
D-42579 Heiligenhaus

and produced in the factory

**Carl Fuhr GmbH & Co. KG**  
D-42579 Heiligenhaus

is submitted by the manufacturer to a factory production control and to the further testing of samples taken at the factory in accordance with a prescribed test plan and that the notified body - < PIV > - has performed the initial type-testing for the relevant characteristics of the product, the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.

This certificate attests that all provisions concerning the attestation of conformity and the performances described in the Annex ZA. of the standard

**EN 179:2008**

Product classification key

1	2	3	4	5	6	7	8	9	10
<b>3</b>	<b>7</b>	<b>6</b>	<b>B</b>	<b>1</b>	<b>3</b>	<b>5</b>	<b>1/2</b>	<b>A/B</b>	<b>B/D</b>

Pos. 4: Fire classification MPA Braunschweig, test report 3019/2006

were applied and that the product fulfils all the prescribed requirements.

This certificate was first issued on < 07.09.2011 > and remains valid as long as the conditions laid down in the harmonised technical specification in reference or the manufacturing conditions in the factory or the FPC itself are not modified significantly.

Stamp of the notified body

D-Velbert, 14.10.2011



H. Wichert  
Deputy Manager of the Notified body

This certificate consists 5 pages.



**Enclosure of accepted hardware:**

Accepted panic exit devices / Locks / Accessories

Manu- facturer	Product description	Remark	Function	Distance backset	Forend
FUHR	Multisafe 870 Type 11 Multisafe 870 Type 11 GL	Multi point locking system with anti-panic function	I and IIIa	D = 92mm D= 72mm  Square follower 8 and 9mm  backset 35 to 80mm	Flat forend 16 - 30mm  U-forend 22 - 30mm  Length up to 2400 mm
FUHR	Multitronic 881 Type 11 Multitronic 881 Type 11 GL	Electronic multi point locking system with anti-panic function	I and IVa	D = 92mm D = 72mm  Square follower 8 and 9mm  backset 35 to 80mm	Flat forend 16 - 30mm  U-forend 22 - 30mm  Length up to 2400 mm

Function I: One-piece follower, all the time effective panic exit device function from the inside. From the inside the opening by the fitting is always possible. From the outside opening is possible with the key by latch lever. (For 881 as well by access control, remote control, etc...)  
Latch lever function E

Function IIIa: For 870. Split follower, all the time effective panic exit device function from the inside. From the inside the opening by the indoor fitting is always possible. The outdoor fitting only actuates the latch. From the outside the bolt is operated by key only. After an inside actuation of hardware the door can be opened from the outside till manual re-locking.  
Access function D

Function IVa: For 881. Split follower, all the time effective panic exit device function from the inside. From the inside the opening by the indoor fitting is always possible. The outdoor fitting only actuates the latch. In its basic position the door is locked electronically. From the outside the bolt is operated by key, access control, remote control, etc. only. After an inside actuation of hardware the door cannot be opened in its basic position by hardware from the outside. Control system can be adjusted to daytime operation. Thus the multi-point locking is unlocked and can be actuated by handle from the inside and outside.  
Shift function B



Accepted locking plates

Manufacturer	Product description	Remark
FUHR	One-piece keep Rxxxxx Keeper Rxxxxx	Xxxxxx stands for profile-dependent item numbers from FUHR keepers and one-piece keeps

Accepted square pins

Manufacturer	Product description	Remark
FUHR	POM870xxx	Xxx stands for the length 50mm/ 60mm/ 70mm/ 80mm
FUHR	PVZS120Gxx PVZS120Sxx	2-part pins xx stands for the length 53mm/ 60mm/ 67mm/ 74mm 48mm/ 55mm/ 62mm/ 69mm
FUHR	PV9xxxV	Xxx stands for the length 60mm/ 70mm/ 100mm

Accepted handle sets

Manufacturer	Product description	Coding	Remark
DORMA	Plate series ZS 6500 to 7020 Handle series 8100 FS to 8998A FS	DO 20.4.01 DO 20.4.02	
HOPPE	All sets according to EN 179 with the adjoining coding	DO 20.20.01 DO 20.20.02 DO 20.2.02-RD DO 20.5.01 DO 20.5.02 DO 20.5.02-RD DO 20.7.01 DO 20.7.02	
KABA/GEGE (Grundmann)	11640072+11640075 11649768	DO 20.26.01 DO 20.26.02	Manufacturer Grundmann
KABA/GEGE (Glutz)	11643674+11643670 11643668	DO 20.21.01 DO 20.21.02	Manufacturer Glutz
VBH	Series 2017 to 2526 and 6011		
HAFI	Series 202, 205, 207, 209, 223, 224, 225	DO 20.32.01 DO 20.32.02	



Accepted handle sets (Continue)

<b>FSB</b>	Series 7616 to 7651	DO 20.3.01 DO 20.3.02	
<b>HEWI</b>	111X, 112X, 113X, 114X, 165X, 166X, 161X, 163X, 171X	DO 20.13.01	
<b>HEWI</b>	FSDG550.08	DO 20.13.02	Lever handle set
<b>ECO</b>	D 110, D 115, D 116, D 120, D 190, D 330, D 335, D 410, D 415, D 490	DO 20.1.01 DO 20.1.02	

Accepted electronic-opener

Manufacturer	Product description	Remark
<b>FUHR</b>	E-Motion	
<b>eff eff</b>	142 131	

Accepted doorkeepers

Manufacturer	Product description	Remark
<b>GfS Hamburg</b>	GfS Standard Doorkeeper GfS EH-Doorkeeper	

Accepted profile cylinders

Manufacturer	Product description	Remark
<b>CES</b>	8710F	
<b>WILKA</b>	1008/1408/2108/3608 double cylinder 1006/1406/2106/3606 knob cylinder	
<b>WINKHAUS</b>	Xpert/Xtra/AZ/VS/VS6/	with coupling „15“
<b>GERA</b>	3000	
<b>HARTMANN</b>	ZP600, ZP600WS	
<b>KABA/GEGE</b>	ANS2.5 FLRW 360°/ ANS2.6 FLRW 360°/ PX.5 FLRW 360°/ PX.6 FLRW 360°	
<b>SCHÜRING</b>	23.201.xx	
<b>MAUER Locking</b>	41DC1-MLS-NI	
<b>ASSA ABLOY</b>	LITTO select plus	
<b>ESCO/ VBH</b>	greenteQ SX	
<b>CEStronics</b>	Omega	Electronic locking cylinder
<b>DOM</b>	Protector	Electronic locking cylinder
<b>SIMONS VOSS</b>	3061FD	Electronic locking cylinder



Producttable for EC-Certificate of Conformity

1309 – CPD – 0140

**FUHR**

In addition to the above mentioned locking cylinders as a matter of principle only tested profile cylinders with freewheel function for transmission locks in panic exit device with “FZG” marking are allowed.

Using locking cylinders the operating element (key, knob, or similar) must not obstruct the actuation of the handle.



A handwritten signature in blue ink, appearing to read 'H. Wichert'.

H. Wichert  
Deputy Manager of the Notified Body