

www.fel.fujitsu.com



DL6400 Pro / DL6600 Pro
24 Wire Dot Matrix Printers

- **Print Technology:** Dot Matrix
- **Printing speed (letter, 10cpi):** 140 cps (DL6400 Pro) 180 cps (DL6600 Pro)
- **Printing speed (draft, 12 cpi):** 504 cps (DL6400 Pro) 648 cps (DL6600 Pro)
- **Resolution:** 360 x 360 dots per inch
- **Interface (standard):** Centronics or Centronics + RS232 (Auto switching)
- **Print line:** 136 columns

FUJITSU

THE POSSIBILITIES ARE INFINITE



Fujitsu's DL6400 Pro and DL6600 Pro are heavy duty printers and the rugged design coupled with the space saving footprint and a print speed of up to 648 characters per second at 12 characters per inch, means the DL6400 Pro and the DL6600 Pro are high speed printers.

Outstanding features

The most outstanding feature is a versatile paper handling ability, continuous form feed from the front and (optionally) from the rear and, as an accessory, there is a cut sheet feeder for the front.

Paper handling

The ability to print continuous forms with up to seven copies

makes for comfortable, high performance paper handling. A second paper tractor enables easy switching between stationary types.

Features

Additional features include Bar Code printing, a Host Controlled Paper Path and recyclable, refillable ribbon cartridges.

DL6400 Pro / DL6600 Specifications

| Model | DL6400 Pro | DL6600 Pro |
|--|--|-----------------------------------|
| Printing technology | 24-wire dot matrix, impact type logic-seeking, bi-directional | |
| Printing speed | Draft quality: 504 cps (12 cpi) 420 cps (10 cpi) | 648 cps (12 cpi) 540 cps (10 cpi) |
| | Correspondence/Report quality: 336 cps (12 cpi) 280 cps (10 cpi) | 432 cps (12 cpi) 360 cps (10 cpi) |
| | Letter quality: 168 cps (12 cpi) 140 cps (10 cpi) | 216 cps (12 cpi) 180 cps (10 cpi) |
| Resolution | Max. 360 x 360 dpi | |
| Character sets | IBM PC char. sets 1 and 2, IBM PS/2 char. sets (code pages 437, 850, 851, 852, 855, 860, 862, 863, 865, 866), ISO 8859-1/ECMA 94 National character sets (USA, UK, German, French, Italian, Spanish, Swedish, Finnish, Norwegian, Danish 1 and 2, Hungarian 1 and 2, Slovenian 1 and 2, Mazowia 1 and 2, Polish 1 and 2, Latin 2 1 and 2, Latin P, PG-DHN, Elot 927, Litvanian 1 and 2, Mik, Macedonian, PG-MAC, ABY-ABG, DEC GR, GREEK 11, HBR-OLD, HBR-DEC, ISO Turkish, ISO Latin, Kamenicky 1 and 2, Turkish 1 and 2, Elot 928, and Cyrillic) Bar code (Code 3 of 9, UPC Type A, Codabar, EAN13, EAN8, Industrial 2 of 5, Interleaved 2 of 5, Code 128, and Matrix 2 of 5) | |
| Resident fonts | Bitmap font: Courier 10, PICA 10, Prestige Elite 12, OCR-B, Boldface PS, Correspondence, Comprssion Draft, OCR-A. Outline Font: Courier, Nimbus Sans®, and Timeless. | |
| Input buffer | Max. 128 KB | |
| Print line | 354.4 mm (13.6 in.) 163 char. at 12 cpi, 136 char. at 10 cpi | |
| Line feed speed | 50 ms at 6 lpi | |
| Form feed speed | Front pass: 9 ips Rear pass: 9 ips | |
| Number of copies | Max. 8 (including original), depending on paper conditions. | |
| Paper sizes | 90 mm to 420 mm (width Max.) 0.65 mm (thick (depending on papers) | |
| Form feeders | Standard: Friction-feed platen, built-in bi-directional push tractor. Optional: Front single-bin cut sheet feeder. Rear-feed tractor. | |
| Interface Centronics | Optional: Centronics and RS-232C, Centronics: Bi-directional Centronics (IEEE1284 nibble mode) | |
| Emulations | Fujitsu DPL24C PLUS, IBM ProPrinter XL24E, Epson ESC/P2 | |
| Word processing functions | Outline, Image overlay, Overscore, Underscore, Superscript, Subscript, Bold overprint, Shadow, Justify, Italic, Multiple height (up to 11 fold), Multiple width (up to 11 fold) | |
| Power requirements | 100 V AC to 120 V AC ±10%, single-phase, 50 Hz to 60 Hz 220 V AC to 240 V AC +6%, -10%, single-phase, 50 Hz to 60 Hz | |
| Dimensions (W x D x H) | 600 mm x 300 mm x 325 mm | |
| Weight | 25 kg | |
| Acoustic noise level | 55 dBA | 56 dBA |
| MTBF (Mean Time Between Failures) | More than 8,000 power-on hours at 25% duty cycle | |
| Head life | 400 million strokes (each wire) | |
| Ribbon life | Black: 18 million characters (at DQ) | |

Specifications are subject to change without notice. For the latest information, contact your local Fujitsu representative.

Fujitsu Europe Limited

Hayes Park Central
Hayes End Road
Hayes Middlesex UB4 8FE
England
Tel: (+44-(0)20) 8573 4444
Fax: (+44-(0)20) 8573 2643
www.fel.fujitsu.com

Fujitsu Italia S.p.A.

Via Nazario Sauro, 38
20099 Sesto San Giovanni (MI)
Italy
Tel: (+39) 0226294.1
Fax: (+39) 0226294.201
www.fis.fujitsu.com

Fujitsu Deutschland GmbH

Frankfurter Ring 211
80807 Munich
Germany
Tel: (+49-(0)89) 32378-0
Fax: (+49-(0)89) 32378-100
www.fdg.fujitsu.com



FUJITSU