



Optical

MCE3064SS MCF3064SS Magneto-Optical Drives

- Ultra SCSI interface
- 23ms seek time and data transfer rates up to 4.9 MB/sec
- Up to 50% faster write performance with Over-Write (OW) media
- Ultra quiet design only 23dBA
- Unlimited rewrite capability on MO disks
- 640MB, 540MB, 230MB or 128MB rewritable disk options

The MCE3064SS and MCF3064SS magneto-optical drives deliver capacity, speed and reliability to meet the requirements of most of today's demanding applications.

Fujitsu Computer Products of America (FCPA) takes magneto-optical (MO) technology to new levels with the fourth-generation of SCSI MO drives. These state-of-the-art, high-performance drives store up to 640MB on industry standard MO disks, are faster and quieter than their predecessors, and offer the high level of ruggedness and reliability you've come to expect from FCPA's MO products.

High-Performance Storage

The MCF3064SS is a 3600 rpm drive that provides data transfer rates up to 3.9 megabytes per second. The MCE3064SS offers even higher performance at 4500 rpm and up to 4.9 MB/sec. Using Over-Write MO disks can further increase write performance up to 50%. Magneto-optical is ideal for backup, archiving, data acquisition, medium scale software distribution, anything that requires high capacity, reliable, removable storage.

Protecting Investments in Data

Fujitsu MO disks are extremely rugged and highly tolerant of the problems that plague magnetic media. Shock, vibration, moisture, dust and magnetic fields won't destroy data stored on a MO disk. Each disk comes with a lifetime warranty and because of their ruggedness, they make the perfect medium for office, home or industry.

Mobile

Desktop

Enterprise

Multiple Media Options

The MCE3064SS and MCF3064SS can read and write to all ISO compliant, 3.5-inch MO media capacities: 640MB, 540MB, 230MB and 128MB, as well as Over-Write disks. No other storage solution offers as many options to tailor the media selection to the application while providing such a high level of investment protection.

| About Fujitsu Computer Products |
|--|
| of America |
| Fujitsu Computer Products of America is a wholly |
| owned subsidiary of Fujitsu Limited, one of the |
| world's largest computer companies with \$43.3 |

owned subsidiary of Fujitsu Limited, one of the world's largest computer companies with \$43.3 billion in worldwide revenue in fiscal year 1998. Benefiting from Fujitsu Limited's \$3 billion annual investment in research and development, Fujitsu Computer Products provides innovative solutions

for the U.S. marketplace. Current product offerings include high-performance hard disk drives, tape drives, magneto-optical drives, high-volume scanners, and printers.

| MC | CE306 | 4SS | and MCF3 | 064SS Spec | ifications | <u> </u> | |
|--------------------------|---------------|---------|--|------------------|------------|---------------|--|
| Model | | | MCE3064SS / MCF3064SS | | | | |
| Functional Sp | ecificati | ons | • | | | | |
| Storage capacity by disk | | | 128MB | 230MB | 540MB | 640MB | |
| Standard | | | ISO/IEC 10090 | ISO/IEC 13963 | ISO/IE | ISO/IEC 15041 | |
| Sector capacity | | | | 512 bytes | | 2,048 bytes | |
| Format | | | 90 mm | | | | |
| Interface | | | Ultra SCSI | | | | |
| Data transfer | Drive | MCE | 1.3 MB/s | 1.6-2.6 MB/s | 2.9-4. | 9 MB/s | |
| rate (max.) | | MCF | 1.09 MB/s | 1.3-2.1 MB/s | 2.3-3.9 | 9 MB/s | |
| | Interfac | e | | 5 MB/s async; 20 | MB/s sync | | |
| Recording density (BPI) | | 24,400 | 29,300 | 52,900 | | | |
| Track density (TPI) | | 15,875 | 18,275 | 23,090 | | | |
| Random seek time | | | 23 ms | | | | |
| Average latency time | | | 6.6 ms (MCE) / 8.3 ms (MCF) | | | | |
| Rotational speed | | | 4,558 RPM (MCE) / 3,600 RPM (MCF) | | | | |
| Recording code | | | 2-7 RLLC 1-7 RLLC | | | | |
| Load/unload time | | | 7 sec. / 4 sec. | | | | |
| Buffer size | | | 2 MB | | | | |
| Physical Spec | ification | s | | | | | |
| Power requirements | | | 5VDC±5%: 1.1A | | | | |
| Power | Operating | | 4.9 W | | | | |
| consumption | Ready | | 3.9 W | | | | |
| • | Sleep mode | | 0.5 W | | | | |
| Dimension (H x W x D) | | | 25.4 mm x 101.6 mm x 150.0 mm (with bezel) | | | | |
| Weight | | | 470 g (with bezel) | | | | |
| Ambient | Operating | | 5°C - 45°C | | | | |
| temperature | Non-operating | | 0°C - 50°C | | | | |
| • | Gradient | | 15° C/h (operating) | | | | |
| Relative humidity | | | 10% - 85% (non-condensing) | | | | |
| Acoustic noise | | | 23 dBA | | | | |
| Vibration | Operating | | 0.4 G (5 to 500Hz) | | | | |
| | Non-operating | | 1.0 G (5 to 500Hz) | | | | |
| Shock | Operating | | 2.0 G (10 ms) | | | | |
| | Non-operating | | 5.0 G (10 ms) | | | | |
| | Transporting | | 50.0 G (10 ms, in packaging) | | | | |
| Altitude | Operating | | 3,000 m | | | | |
| | | erating | 12,000 m | | | | |
| Reliability Sp | ecificatio | ons | | | | | |
| MTBF | | | 120,000 hours | | | | |

© 1999 Fujitsu Computer Products of America. All rights reserved. The statements in this publication are not intended to create any warranty, expressed or implied. Fujitsu Computer Products reserves the right to change equipment and performance specifications stated herein without notice. Fujitsu and the Fujitsu logo are registered trademarks of Fujitsu Limited. All other trademarks mentioned herein are the property of their respective owners.



FUJITSU COMPUTER PRODUCTS OF AMERICA, INC. 2904 Orchard Parkway San Jose, CA 95134-2009 (800) 626-4686 (408) 432-6333 Web site: http://www.fcpa.com Email: info@fcpa.fujitsu.com