

METRACLIP[®] 70

Digital Clip-On Ammeter

3-349-064-03
1/7.00

Clip Functions

- Alternating current measurement 200 mA ... 1000 A_{eff}
- Direct current measurement 200 mA ... 1400 A

Multimeter Functions

- Alternating voltage measurement 200 mV ... 600 V_{eff}
- Direct voltage measurement 200 mV ... 600 V
- Resistance measurement 0.5 Ω ... 4 MΩ
- Acoustic continuity test
- Diode test
- Frequency measurement 1.00 Hz ... 4 kHz

Common Functions and Characteristics

- 4½ place digital display
- Automatic or manual measuring range selection
- DATA HOLD and MIN-MAX display



Features

Storage of Display Values to Memory (HOLD, MIN-MAX)

The current measurement value or MIN-MAX value can be frozen at the display.

Overrange Indication

Optical, and in some cases acoustic signals are generated if measuring ranges are exceeded.

Automatic Shut-Down

The instrument shuts itself off automatically if any of the keys or the rotary switch are not activated for a period of 10 minutes. The automatic shut-down function can be disabled.

Characteristic Values

Digital Display 7 segment characters, 4½ digits
Sampling Rate 500 ms

Direct and Alternating Current, A DC and A AC_{eff}

Measuring Range	Resolu- tion	Accuracy		Overload Capacity	
		V _{DC}	V _{eff}	Value	Duration
0.2 ... 399.9 A	100 mA	0.2 ... 50 A: 2% rdg. ± 10 D 50 A ... 399.9 2.5% rdg. ± 2 D		2000 A _{eff} to 1 kHz	contin- ous
400 ... 1000 A~ ... 1400 A _{DC}	1 A	400 ... 999 A: 2.5% rdg. ± 2 D 1000...1400 A: 8% rdg. ± 5 D	400 ... 799 A: 2.5% rdg. ± 2 D 800...1000 A: 5% rdg. ± 5 D		

Frequency range 45 Hz ... 450 Hz

Direct and Alternating Voltage, V DC and V AC_{eff}

Measuring Range	Resolution	Accuracy		Overload Capacity	
		V _{DC}	V _{eff}	Value	Duration
200 ... 399.9 mV	0.1 mV	1% rdg. ± 2 D	—	1 kV _{eff}	contin- ous
0.400 ... 3.999 V	1 mV		1.5% rdg. ± 2 D		
4.00 ... 39.99 V	10 mV				
40.0 ... 399.9 V	100 mV	1% rdg.	1.5% rdg.		
400 ... 600 V	1 V				

Frequency range 45 Hz ... 450 Hz

Input impedance 10 MΩ

Resistance Measurement

Measuring Range	Resolution	Accuracy	Overload Capacity	
			Value	Duration
0.5 ... 399.9 Ω	0.1 Ω	1.5% rdg. ± 7 D	600 V _{eff}	contin- ous
0.400 ... 3.999 kΩ	1 Ω	1.5% rdg. ± 4 D		
4.00 ... 39.99 kΩ	10 Ω			
40.0 ... 399.9 kΩ	100 Ω			
0.400 ... 3.999 MΩ	1 kΩ			

Maximum open-circuit voltage 0.5 V

Maximum short-circuit current 0.37 mA

Frequency

Measuring Range	Resolution	Accuracy
1.00 ... 99.99 Hz	0.01 Hz	0.1% rdg. ± 15 D
100.0 ... 999.9 Hz	0.1 Hz	
1000 ... 3999 Hz	1 Hz	

METRACLIP[®] 70

Digital Clip-On Ammeter

Diode Test

Forward Direction	Display: conducting-state voltage in V (4 V range)
Reverse Direction	Display: max. open-circuit voltage in V
Accuracy	3% rdg. \pm 10 mV
Resolution	1 mV
Max. Open-Circuit Voltage	3.5 V
Max. Short-Circuit Current	0.88 mA
Overload Protection	to 600 V _{eff} , continuous

Reference Conditions

Ambient Temperature	+ 23° C \pm 3 K
Relative Humidity	45 ... 75%
Battery Voltage	8.5 ... 9 V
Conductor Position	centered, in accordance with markings on the clip
Conductor Diameter	\leq 15 mm
Ext. AC Magnetic Field	none
Ext. Electrical Field	none
Frequency of AC Components for Sinusoidal Signals	45 ... 65 Hz

Power Supply

Battery	1 ea. 9 V alkaline-manganese block battery per IEC 6LR61
Service Life	Approx. 60 hours for alkaline-manganese block batteries
Battery Test	Battery symbol appears at display when battery voltage falls to below 7.8 V.
Automatic Shut-Down	At less than 7.2 V

Electromagnetic Compatibility (EMC)

Interference Emission	EN 50081-1: 1992
Interference Immunity	EN 50082-1: 1992

Electrical Safety

Protection Class	II (totally insulated) per IEC 61010-1/EN 61010-1/VDE 0411-1
Overvoltage Category	III
Contaminatin Level	2
Circuit Insulation Voltage	600 V

Ambient Conditions

Operating Temp.	0° C ... +50° C
Storage Temperature	-40° C ... +70° C (without battery)
Relative Humidity	0 ... 80% at max. 40° C, no condensation allowed
Elevation	to 2000 m
Applications	indoors only

Mechanical Design

Protection	IP 30
Clip Opening	2 busbars, 50 x 5 mm 2 cables, 25 mm diameter 1 cable, 42 mm diameter
Dimensions	W x H x D: 97 mm x 254 mm x 46 mm
Weight	approx. 600 gr. with battery

Applicable Regulations and Standards

IEC 61010-1/EN 61010-1/ VDE 0411-1	Safety requirements for electrical equipment for measurement, control and laboratory use
IEC 61010-2-032/ EN 61010-2-032/ VDE 0411-2-032	Special requirements for clip-on ammeters
EN 50081-1	Electromagnetic compatibility (EMC), generic standard for interference emission
EN 50082-1	Electromagnetic compatibility (EMC), generic standard for interference immunity

Standard Equipment

- 1 clip-on ammeter
- 1 bag
- 2 measuring cables with test probe
- 1 battery
- 1 operating instructions

Order Information

Description	Type	Article Number
Digital Clip-On Ammeter	METRACLIP [®] 70	M312A

Please refer to our *Measuring Instruments and Testers Catalog* for additional information concerning accessories.

Printed in Germany • Subject to change without notice

GOSSEN-METRAWATT GMBH
Thomas-Mann-Str. 16-20
90471 Nuremberg, Germany
Phone +49 911 8602-0
Fax +49 911 8602-669
e-mail: info@gmc-instruments.com
http://www.gmc-instruments.com

GOSSEN
METRAWATT
CAMILLE BAUER