Keysight InfiniiVision 3000 X-Series (EMEA)


Oscilloscopes redefined: Breakthrough technology delivers more scope for the same budget




Key specifications

| Bandwidth | 100 MHz, 200 MHz, 350 MHz, 500 MHz |
|----------------------|---|
| Channels | 2 or 4 analog channels (DSO) +16 digital channels (MSO) |
| Sample rate | Up to 5 GSa/s |
| Memory | Up to 4 Mpts (2 Mpts standard) |
| Display | 8.5-inch WVGA (800 x 480) |
| Update rate | 1,000,000 wfms/s |
| Upgradable | Bandwidth, MSO, measurement applications, |
| | integrated digital voltmeter and WaveGen |
| Warranty | Standard 3-year |
| Calibration interval | 2 year |
| Connectivity | USB host (one front, one back), USB device, LAN |
| | (optional), GPIB (optional) |
| Secure | Provides compliance with NISPOM chapter 8 |
| environment | requirements (standard) |







See more

of your signal more of the time

- High resolution 8.5-inch display
- Up to 1,000,000 wfms/s update rate
- Fast, responsive MegaZoom IV deep memory, up to 4 M

Do more

with the power of 5 instruments in 1

- Best-in-class oscilloscope
- Integrated 16 digital channel mixed signal oscilloscope (MSO) (optional)
- Serial protocol analyzer (optional)
- Industry-exclusive WaveGen built-in 20 MHz
 Function/Arbitrary WaveForm Generator (optional)
- Integrated digital voltmeter (optional)

Get more

investment protection with the industry's only fully upgradable scope

- Upgradable bandwidth
- Upgradable to MSO
- Upgradable to WaveGen 20 MHz
 Function/Arbitrary Waveform Generator
- Upgradeable integrated digital voltmeter
- Upgradable measurement applications
- 2-year recommended calibration interval



Oscilloscope models

| Model | Bandwidth | Maximum sample rate | Maxi- mum memory | Analog chan- nels | Digital chan- nels |
|-----------|-----------|---------------------------|------------------------|-------------------------|--------------------------|
| DSOX3012A | 100 MHz | 4 GSa/s | 4 M | 2 | - |
| MSOX3012A | 100 MHz | 4 GSa/s | 4 M | 2 | 16 |
| DSOX3014A | 100 MHz | 4 GSa/s | 4 M | 4 | - |
| MSOX3014A | 100 MHz | 4 GSa/s | 4 M | 4 | 16 |
| DSOX3024A | 200 MHz | 4 GSa/s | 4 M | 4 | - |
| MSOX3024A | 200 MHz | 4 GSa/s | 4 M | 4 | 16 |
| DSOX3032A | 350 MHz | 4 GSa/s | 4 M | 2 | - |
| MSOX3032A | 350 MHz | 4 GSa/s | 4 M | 2 | 16 |
| DSOX3034A | 350 MHz | 4 GSa/s | 4 M | 4 | - |
| MSOX3034A | 350 MHz | 4 GSa/s | 4 M | 4 | 16 |
| DSOX3052A | 500 MHz | 4 GSa/s | 4 M | 2 | _ |
| MSOX3052A | 500 MHz | 4 GSa/s | 4 M | 2 | 16 |
| DSOX3054A | 500 MHz | 4 GSa/s | 4 M | 4 | _ |
| MSOX3054A | 500 MHz | 4 GSa/s | 4 M | 4 | 16 |

Accessories included

Standard 3 year warranty

Standard SEC mode (Secure Environment), Certificate of Calibration, Documentation CD

| Documentation CD | | | | |
|-------------------|---|---|--|--|
| Standard probe | N2862A passive probe 150 MHz 10:1 attenuation | 1 per channel included 100 MHz models | | |
| | N2863A passive probe 300 MHz 10:1 attenuation | 1 per channel included 200 MHz models | | |
| | N2890A passive probe 500 MHz 10:1 attenuation | 1 per channel included 350/500 MHz models | | |
| | N6450-60001 16 digital channel MSO cable | 1 per scope included on al MSO models, DSOX3MSO and DSOXPERFMSO | | |

Built-in help language support for English, Japanese, simplified Chinese, traditional Chinese, Korean, German, French, Spanish, Russian, Portuguese and Italian

Interface language support

GUI menus: English, Japanese, simplified Chinese, traditional Chinese, Korean, German, French, Spanish, Russian, Portuguese and Italian

Localized power cord

www.keysight.com/find/3000X-Series

Measurement options

| Model | Description |
|------------------------|---|
| DSOX3MemUp | Memory upgrade - 4 M |
| DS0X3MS0 | MSO upgrade, 16 channel for 500 MHz models and below |
| DS0X3WAVEGEN | Function/Arbitrary Waveform Generator upgrade |
| DSOXDVM | Integrated Digital Voltmeter |
| DS0X3MASK | Mask limit testing |
| DS0X3ADVMATH | Advanced waveform math functions |
| DS0X3VID | HDTV video triggering and measurement analysis |
| DS0X3PWR | Power measurement and analysis (Embedded in the scope) |
| DSOX3AERO | Aerospace triggering and analysis (MIL-STD 1553, ARINC 429) |
| DS0X3SGM | Segmented memory |
| DS0X3EMBD | Embedded serial triggering and analysis (I ² C, SPI) |
| DS0X3C0MP | Computer serial triggering and analysis (RS232/422/485/UART) |
| DS0X3AUT0 | Automotive serial triggering and analysis (CAN, LIN) |
| DS0X3FLEX | FlexRay triggering and analysis |
| DS0X3AUDI0 | Audio serial triggering and analysis (I ² S) |
| 33503A | Benchlink Waveform Builder Pro and Basic |
| DSOXEDK | Educator's oscilloscope training kit |
| N8900A | InfiniView oscilloscope analysis software |
| 64997A | Keysight spectrum vsualizer (ASV) |
| DSOX3BW24 | Bandwidth upgrade from 100 MHz to 200 MHz on 4 channel models |
| DSOX3BW32 ¹ | Bandwidth upgrade from 100 MHz to 350 MHz on 2 channel models |
| DSOX3BW34 ¹ | Bandwidth upgrade from 200 MHz to 350 MHz on 4 channel models |
| DSOX3BW52 | Bandwidth upgrade from 350 MHz to 500 MHz on 2 channel models |
| DSOX3BW54 | Bandwidth upgrade from 350 MHz to 500 MHz on 4 channel models |
| DSOX3BW12 1 | Bandwidth upgrade 500 MHz on 2 channel models |
| DSOX3BW14 ¹ | Bandwidth upgrade 500 MHz on 4 channel models |
| Opt SEC | Secure Environment Mode (comes standard) |

1. Requires return to Keysight Service Center. All other products are licensed and customer installable.



Three-Year Warranty www.keysight.com/find/ThreeYearWarranty

Keysight's commitment to superior product quality and lower total cost of ownership. The only test and measurement company with three-year warranty standard on all instruments, worldwide.



Keysight Assurance Plans www.keysight.com/find/AssurancePlans

Up to five years of protection and no budgetary surprises to ensure your instruments are operating to specification so you can rely on accurate measurements.

Probing options

For complete list of compatible probes, see Keysight document 5968-8153EN.

| Model | Description |
|-----------------|---|
| N2862B | Passive probe 150 MHz 10:1 attenuation (1 per channel included 100 MHz models) |
| N2863B | Passive probe 300 MHz, 10:1 attenuation (1 per channel included 200 MHz models) |
| N2890A | Passive probe 500 MHz, 10:1 attenuation (1 per channel included 350/500 MHz models) |
| N6450- 60001 | 16 digital channel MSO cable (1 per scope included MSO models, DSOX3MSO and DSOXPERFMSO upgrades) |
| N2889A | Passive probe 350 MHz 10:1/1:1 switchable attenuation |
| 10076B | Passive probe 250 MHz 100:1 attenuation |
| N2771B | Passive probe 50 MHz 1000:1 attenuation |
| N2790A | Differential active probe 100 MHz ±1.4 kV with AutoProbe interface |
| N2791A | Differential active probe 25MHz ±700 V |
| N2792A | Differential active probe 200 MHz ±20 V |
| N2793A | Differential active probe 800 MHz ±15 V |
| 1146A | AC/DC current probe 100 kHz 100 A |
| 1147A | AC/DC current probe 50 MHz 15 A with AutoProbe interface |
| 1157A | Single-ended 2.5 GHz with AutoProbe interface |
| N2893A | AC/DC current probe 100 MHz 15 A with AutoProbe interface |
| N2744A | T2A (Tektronix TekProbe interface to Keysight AutoProbe) probe interface adapter |
| | |

Accessories

| Model | Description |
|----------|------------------------------------|
| DSOXLAN | Module - LAN and VGA |
| DSOXGPIB | Module - GPIB |
| N6456A | Rack mount kit |
| N6457A | Soft carrying case and front cover |
| N6458A | Hard copy manual |
| N2747A | Front panel cover only |
| | |

