

가
DC
Agilent 66312A
DC
Agilent 6611C,6612C,6613C,6614C



Agilent Technologies

Agilent .5962-8252

Microfiche 5962-xxxx

2000 6

Agilent 66312A
DC

DC

Agilent 6611C/6612C/6613C/6614C

Agilent 66312A

40W

DC

Agilent 6611C, 6612C, 6613C
50W DC

6614C

가 40W

DC

- 50W
-
- 가 가
-
- ,
- 가
- 30% (sinking)
-
-

- GPIB (IEEE-488) RS-232 ()
- SCIP ()
- (Agilent 66312A)
- I/O


가

가

© Copyright 1999, 2000 Agilent Technologies, Inc

14-

가



dc

- Local
- GPIB
- RS-232
- SCPI
-




- 가 / 가
-
-
-
- ▲ ▼

-
- □ □
- □ □

가

Meter


On



가

(Backspace)

Meter





CV CC Unr Dis OCP Prot Cal Shift Rmt Addr Err SRQ

CV													
CC													
Unr													
Dis		Off		. Output	On/Off		On						가
OCP				가	ON					OCP			
Prot							가					. Prot	Clear
Cal			ON. Cal	Off			Enter						
Shift		Shift											
Rmt							(GPIB	RS-232)			. Local	
Addr				talk	listen								
Err		SCPI			가					. Error			
SRQ			가										

Output On/Off		DC		ON, Off									
Local			가			(Lockout)					
Shift	Prot Clr					가							
Shift	OCP			가		가							

Address		ADDRESS7 INTF GPIB BAUDRATE 300 PARITY NONE FLOW NONE LANG SCPI	GPIB (GPIB RS232) (Baud Rate) (300,600,1200,2400,4800,9600) (NONE, EVEN, ODD, MARK, SPACE) (XON-XOFF, RTS-CTS, DTR-DSR, NONE) (SCPI COMP)
Recall		*RCL 0	
Shift	Save	*SAV 0	
Shift	Error	ERROR 0	SCPI
Meter		12.000V 0.204A 12.500V MAX 1.000V MIN 12.330V HIGH 0.080V LOW 12.000V RMS 0.350A MAX 0.050A MIN 0.400A High 0.012A LOW 0.210A RMS	 rms 1 1 rms 1
Voltage		VOLT20.000	
Current		CURR2.000	
Protect		OC- - -	()
Output		*RST PON: STATE RST PROT:DLY 0.08 RILATCHING DFI OFF DFI:SOUR OFF PORT RIDFI DIGIO7 RELAY ON RELAY NORM	DC - (power -on) (RST RCL0) (LATCHING, LIVE OFF) (ON OFF) DFI (QUES, OPER, ESB, RQS, OFF) (RIDFI DIGIO) I/O (0~7) (ON OFF) ² (NOM REV) ²
Shift	OV	VOLT: PROT 22	
Shift	Input	CURR:RANG HIGH CURR: DET ACDC	(HIGH, LOW AUTO) (ACDC DC) ¹
Shift	Cal	CAL ON	(가)

, Meter

¹Agilent 6611C-6614C

Compatibility

가.

²Agilent 66312A

가.

A B O R t
C A L i b r a t e
 :CURREnt [:POSitive]
 :NEGative
 :MEASure :LOWRange
 :AC¹
 :DATA<n>
 :LEVel P1/P2/P3/P4
 :PASSword<n>
 :SAVE
 :STATe<bool>[,<n>]
 :VOLTag e :PROTection
D I S P l a y
 <bool>
 :MODE NORMal/TEXT
 :TEXT<display_string>
I N I T i a t e
 :SEQuence[1/2]¹
 :NAME TRANsient/ACQuire¹
 :CONTInuous :SEQuence[1],<bool>
 :NAME TRANsient,<bool>
M E A S u r e / F E T C h²
 :ARRay :CURREnt?¹
 :VOLTag e?¹
 [:CURREnt][:DC]?¹
 :ACDC?¹
 :HIGH?¹
 :LOW?¹
 :MAX?¹
 :MIN?¹
 :VOLTag e [:DC]?¹
 :ACDC?¹
 :HIGH?¹
 :LOW?¹
 :MAX?¹
 :MIN?¹
O U T P u t
 <bool>[,NORelay]
 :DFI<bool>
 :SOURCE QUES/OPER/ESB/RQS/OFF
 PON:STATe RST/RCL0
 PROTection:CLEar
 DELay<n>
 RELay[:STATe]<bool>³
 :POLarity NORM/REV³
 RI :MODE LATCHing/LIVE/OFF

¹Agilent 6611C-6614C 가

²Fetch Agilent 6611C-6614C 가


³Agilent 66312A 가

S E N S e
 :CURREnt:RANGe<n>
 :DETeCTOR ACDC/DC¹
 :FUNCTion "VOLT"/"CURR"¹
 :SWEep :OFFSet :POINts<n>¹
 :POINts<n>
 :TINTeRval<n>
[S O U R c e :] CURREnt<n>
 :TRIGgered<n>
 :PROTection:STATe<bool>
D I G I t a l:DATA<n>
 :FUNCTion RIDF/DIG
V O L T a g e <n>
 :TRIGgerd<n>
 :PROTection<n>
 :ALC :BANDwidth?/ :BWIDth?
S T A T u s
 :PRESet
 :OPERation [:EVENT]?
 :CONDition?
 :ENABle<n>
 :NTRansition<n>
 :PTRansition<n>
 :QUESTionable [:EVENT]?
 :CONDition?
 :ENABle<n>
 :NTRansition<n>
 :PTRansition<n>
S Y S T e m
 :ERRor?
 :LANGUage SCPI/COMPatibility
 :VERsion?
 :LOCal
 :REMote
 :RWLock
T R I G g e r
 :SEQuence2/ :ACQuire [:IMMediate]¹
 :COUNT :CURREnt<n>¹
 :VOLTag e<n>¹
 :HYSTeresis:CURREnt<n>¹
 :VOLTag e<n>¹
 :LEVel :CURREnt<n>¹
 :VOLTag e<n>¹
 :SLOPe :CURREnt POS/NEG/EITH¹
 :VOLTag e POS/NEG/EIGH¹
 :SOURCE BUS/INTernal¹
 [:SEQuence1/:TRANsient][:IMMediate]
 :SOURCE BUS
 SEQuence1:DEFine TRANsient
 SEQuence2:DEFine ACQuire¹

GPIB (IEEE-488)

RS-232

INH/FLT (INHibit/
FauLT)



Remote Local

(IEC 320)

- GPIB RS-232 (가 4)
- GPIB (가 4)
- RS-232 (가 4)