



PXA *Drive your evolution*



PXA X-Series Signal Analyzer N9030A

- 3 Hz up to 50 GHz frequency range
- Up to 75 dB spurious-free dynamic range with 160 MHz analysis bandwidth
- ± 0.19 dB amplitude accuracy
- -172 dBm DANL with Noise Floor Extension technology



Agilent Technologies



What is X-Series Signal Analysis?

Future-ready

Optimize your investment and extend instrument longevity with upgradeable processor, memory, connectivity, and more to keep your test assets current today and tomorrow.

Consistent measurement framework

Achieve measurement integrity across your organization and drive more productivity in less time by leveraging a proven foundation for signal analysis and identical operation across the X-Series instruments.

Broadest set of applications

Address the changing demands of technology with more than 25 measurement applications, the ability to run software inside the open Windows® operating system, and a first-to-market track record in emerging standards.


Stay ready, stay in sync, and **arrive ahead**—with the Agilent X-Series.



Summary of Key Specifications

Frequency ranges	Minimum: 3 Hz
	Maximum: 3.6, 8.4, 13.6, 26.5, 43, 44, 50 GHz
	Up to 325 GHz and beyond with external mixing
Analysis bandwidth	10, 25, 40, and 160 MHz
Displayed average noise level (DANL)	-172 dBm at 1 GHz, preamplifier and noise floor extension on
Third-order intermodulation (TOI) distortion	+22 dBm at 1 GHz
W-CDMA ACLR dynamic range	-83 dBc (-88 dBc nominal) with noise correction on
Phase noise	-129 dBc/Hz at 10 kHz offset (1 GHz carrier)
Amplitude accuracy	± 0.19 dB

www.agilent.com/find/X-Series



Drive Your Evolution

In real-world signal analysis, the ability to evolve equals success. For future designs, excellent measurement performance enables detailed analysis of complex signals. For existing technologies, versatile capabilities help you reduce product cost. And for legacy test systems, drop-in replacement ensures ongoing stability.

Designed for the real world, Agilent's future-ready PXA signal analyzer is the evolutionary replacement for your current high-performance analyzer. It helps you sustain past achievements, enhance current designs, and accelerate future innovations. Take control with the PXA signal analyzer—and drive your evolution.

Evolve in R&D

With the performance and flexibility of the PXA, you'll be equipped to create state-of-the-art original designs. Unravel complex signals through the PXA's broad set of measurement applications and demodulation capabilities, such as the Agilent 89600 VSA software and MATLAB.

Evolve in operations (ATE)

The ATE system you create today will be able to keep pace with future changes. Through its outstanding speed and performance, the PXA will help you reduce measurement uncertainties and improve yields.

Whatever the pace of your product life cycle, you can drive your evolution with the Agilent PXA signal analyzer.



What it means to be "future ready"

A truly future-ready signal analyzer offers flexibility to upgrade and enhance every major subsystem: mechanical, electronic, firmware, and software. The PXA delivers in all four areas:

- A mechanical assembly that provides seven expansion slots for future enhancements
- A removable CPU motherboard that enables CPU, memory, and I/O upgrades
- GPIB and LXI/LAN ports for automated testing
- Firmware-based measurement applications that add specific or standards-compliant capabilities
- An open Windows operating system that lets you run software applications inside the analyzer

These capabilities let you and the PXA evolve as your needs change—and help protect your equipment investment.




You Can Upgrade!

Options can be added after initial purchase.

Go deeper with Noise Floor Extension

In 2000, we introduced near-noise correction for ACPR measurements in the PSA signal analyzer. Today, our Noise Floor Extension (NFE) technology provides a dramatic improvement in the PXA signal analyzer's ability to accurately measure low-level signals approaching the theoretical "kTB" noise floor.

NFE compensates for the noise contribution from active microcircuits in the RF and IF chain. The foundation of this technique is a comprehensive calibration procedure performed prior to shipment. With increased averaging, the analyzer's effective noise floor can be extended by up to 10 dB because 90% or more of the contributed noise power is predictable, which means it can be measured, calibrated, and then eliminated during normal measurements.



Maximize Signal Insights With Outstanding Performance

Measure with confidence


The PXA is ideally suited for high-performance R&D applications in aerospace defense and commercial wireless communications. The PXA analyzes signals over wider bandwidths, reduces measurement uncertainty, and reveals previously hidden signals with:

- Super-wide IF technology that provides almost twice the PSA's internal measurement bandwidth, an industry-leading 160 MHz, with up to 75 dB of spurious-free dynamic range
- ± 0.19 dB power measurement accuracy
- -172 dBm/Hz effective sensitivity (DANL, at 2 GHz using NFE and optional RF preamp on)

- Excellent TOI distortion of +22 dBm at 1 GHz with up to -88 dBc 3GPP ACPR and 115 dB of third order dynamic range at 2 GHz
- -129 dBc/Hz at 10 kHz offset close-in phase noise (1 GHz carrier)
- Signal measurement up to 50 GHz, or up to 325 GHz and beyond with external mixing

For greater insight, we offer Agilent-exclusive NFE technology (see sidebar). Within the PXA, this technique reduces the measurement noise by up to 3.5 dB for CW and pulsed signals and up to 8 dB for noise-like signals.

Every PXA also includes I/Q analyzer functionality and the Agilent PowerSuite. I/Q analyzer allows viewing of magnitude, phase, or I/Q behavior for complex modulated signals over the maximum available analysis bandwidth. PowerSuite provides a wealth of one-button, standards-based measurements such as TOI, harmonic distortion, and burst power.



Noise Floor Extension technology



Achieve Faster Throughput and Greater Efficiency

Hewlett Packard and Agilent have contributed decades of innovations and product excellence in spectrum and signal analysis. Naturally, many users of our past-generation analyzers are looking to migrate to the latest technology with more performance, faster measurement time, and the highest level of backwards compatibility.

Up to 70% faster to improve measurement time

Enhance your test systems with the power of the PXA. Compared to past-generation analyzers, the PXA offers improved speed and performance, leading to improved yields and reduced measurement uncertainties.

The PXA's speed advantage can translate into fewer test stations. It provides up to 70% faster test times than the Agilent PSA spectrum analyzer, and is often much faster than the HP/Agilent 856x spectrum analyzers.

Expect great reliability and uptime

To help you maximize system uptime, expect the PXA to provide excellent reliability based on the proven dependability and reliability of the X-Series. X-Series instruments share a common architecture and simplified design that includes one-third fewer major subassemblies compared to our past-generation analyzers.

Simplify migration and match past results

We've also made it easy for you to migrate PSA-based systems. By design, the PXA utilizes the same command language (SCPI) as the PSA for the most commonly used spectrum and signal analysis functions. The PXA also includes extensive command aliasing, which allows it to parse, accept, and process legacy PSA commands without interruption.

To further maximize compatibility, the PXA is designed to match previous results through core spectrum measurements that use the same proven algorithms as several other Agilent signal analyzers.

Learn more by downloading the "Why Migrate from the PSA to the PXA" technical overview, literature number 5990-3990EN.



www.agilent.com/find/psa2pxa

Reveal New Levels of Signal Detail with Advanced Capabilities

Today and tomorrow, you can configure and reconfigure the PXA to fit evolving requirements. This starts with optional advanced measurement applications such as noise figure, phase noise, cellular communications, wireless connectivity, and digital video. Identical across the X-Series, these applications use the same measurement algorithms and provide consistent results whether you run them on the PXA, MXA, EXA, or CXA. To save time, ensure ease of use, and simplify programming, all four models use the same user interface and SCPI commands.

The ability to run the same library of X-Series advanced measurement applications ensures consistent, repeatable results. Available transport of the applications across the X-Series lets you mix and match the hardware that provides your required levels of performance for the specific measurement at hand.

Our integrated approach to the X-Series control code, applications, functions, and user interface ensures a seamless transition from R&D to manufacturing. To enhance ease-of-use, the user interface retains the look and feel of our classic spectrum analyzers while giving you access to a wealth of advanced measurement techniques and analysis capabilities.

Delve deeply into complex and modulated signals

Agilent's industry-leading 89600 VSA software and VXA measurement application provide comprehensive signal visualization and analysis in the time, frequency, and modulation domains. With support for over 75 signal standards and modulation types, you'll be ready to analyze radar and communications signals, modulations ranging from 2 FSK to 1024QAM, and standards ranging from RFID to LTE-Advanced.

Do more with built-in capabilities; optimize connectivity and control

For power and noise-figure measurements, the PXA includes built-in support for USB power sensors and Agilent smart noise sources (SNS Series). As a system controller, the PXA can also control other instruments through its GPIB, LAN, and USB ports, and the Windows XP Pro operating system. In controller mode, the PXA can replace the test-system PC, potentially simplifying system architecture as well as security procedures in classified military ATE applications. In addition, external mixing allows you to measure signals up to 325 GHz and beyond.

89600 VSA software


On the leading edge of wireless design, signal interactions can cause the unexpected. Recognizing there is a problem is relatively easy—achieving the clarity to find the root cause is the real challenge.

Agilent 89600 VSA software is your window into what's happening inside complex wireless devices.


www.agilent.com/find/89600_VSA

Explore evolving standards

If you're analyzing evolving signals and standards, built-in drivers make it easy to integrate the PXA into your MATLAB environment. To help you get started, we provide several example programs and an application note that explains how to develop your own programs or applications in MATLAB.



LTE modulation analysis (N9080A)



MATLAB application (N6171A)

PXA Front and Rear Panels

Soft keys provide tactile feedback to allow quicker navigation of menus and retain a clear display.

Use six traces and three different detectors simultaneously.

Mark the frequency or position of a trace with up to 12 markers that enable easy viewing of measurement results.

Save files fast with the quick-save feature.

Extend frequency to 325 GHz and beyond with external mixing.

Two USB 2.0 ports conveniently located on the front of the instrument.

Ensure analog baseband signal quality with embedded 16-bit ADC.

Identify signals quickly and view information easily on the 21.4-cm, high-resolution XGA display.

Get answers quickly with the comprehensive, context-sensitive embedded help system.

Navigate the interface and help system using the front-panel keys, or a mouse and keyboard.

Send and receive SCPI commands over the GPIB interface.

Acquire IQ waveform data quickly or control the PXA remotely from an external PC over the USB 2.0 (type-B port) interface.

Connect external peripherals and transfer data via the USB 2.0 (type-A port) interface.

View the display on an external monitor by connecting to the VGA video output.

Control the PXA remotely over 1000Base-T LAN.

Removable CPU enables processor, memory, and I/O upgrades.

Removable solid-state drive. Additional solid-state drive available for instrument security.

Evaluate noise figure using SNS or 346 Series noise sources and the N9069A measurement application.

Start measurements based on a specific incident using an external trigger input signal.

Synchronize other test equipment with the analyzer using the external trigger output signals.

Digital bus for future applications.

Related Literature

Agilent PXA Signal Analyzers

Data Sheet 5990-3952EN

Configuration Guide 5990-3953EN

X-Series Measurement Applications Brochure 5989-8019EN

X-Series Signal Analysis Brochure 5990-7998EN



Agilent Email Updates

www.agilent.com/find/emailupdates

Get the latest information on the products and applications you select.



www.lxistandard.org

LAN eXtensions for Instruments puts the power of Ethernet and the Web inside your test systems. Agilent is a founding member of the LXI consortium.

Agilent Channel Partners

www.agilent.com/find/channelpartners

Get the best of both worlds: Agilent's measurement expertise and product breadth, combined with channel partner convenience.

Microsoft and Windows are U.S. registered trademarks of Microsoft Corporation.

WiMAX is a trademark of the WiMAX Forum.



Agilent Advantage Services is committed to your success throughout your equipment's lifetime. To keep you competitive, we continually invest in tools and processes that speed up calibration and repair and reduce your cost of ownership. You can also use Infoline Web Services to manage equipment and services more effectively. By sharing our measurement and service expertise, we help you create the products that change our world.

www.agilent.com/find/advantageservices



www.agilent.com/quality

www.agilent.com
www.agilent.com/find/pxa

For more information on Agilent Technologies' products, applications or services, please contact your local Agilent office. The complete list is available at:

www.agilent.com/find/contactus

Americas

Canada	(877) 894 4414
Brazil	(11) 4197 3600
Mexico	01800 5064 800
United States	(800) 829 4444

Asia Pacific

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 112 929
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Other AP Countries	(65) 375 8100

Europe & Middle East

Belgium	32 (0) 2 404 93 40
Denmark	45 45 80 12 15
Finland	358 (0) 10 855 2100
France	0825 010 700*
	*0.125 €/minute
Germany	49 (0) 7031 464 6333
Ireland	1890 924 204
Israel	972-3-9288-504/544
Italy	39 02 92 60 8484
Netherlands	31 (0) 20 547 2111
Spain	34 (91) 631 3300
Sweden	0200-88 22 55
United Kingdom	44 (0) 118 927 6201

For other unlisted countries:

www.agilent.com/find/contactus

Revised: January 6, 2012

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 2011-2012
Published in USA, January 24, 2012
5990-3951EN



Agilent Technologies