

## In this Chapter...

- [General Instructions](#), 9-2
- [Replacing or Adding a Hard Drive](#), 9-3
- [The LP Spooler](#), 9-4

## Introduction

3070 systems are shipped with their peripherals fully configured.

Use this chapter to replace, install, configure, or manage 3070 peripherals.

## For Help

### HP-UX Reference

HP-UX reference information is available on the Internet at:

<http://docs.hp.com/index.html>

### System Administrator Manager (SAM)

To start SAM, enter: `/usr/sbin/sam` at a shell window prompt.

For help inside of SAM:

- From the dialog, click **Help**.
- Press F1 for context-sensitive help on a specific field.

### 3070 Reference

3070 User and Service manuals are located on 3070 system controllers and on factory-supplied updates.

### More Help

See [In Case of Difficulty](#) on page 10-1.

---

## General Instructions

### To Connect a Peripheral to the 3070

Follow the instructions that accompany the hardware.

### To Configure the Peripheral

- 
- 1 From the 3070 system to use the peripheral, start SAM
  - 2 Click **Printers and Plotters** or **Peripheral Devices** as appropriate.  
Make the appropriate selections.

---

## Replacing or Adding a Hard Drive

HP-UX-specific reference information pertaining to adding or replacing a hard drive can be found on the Internet at:

<http://docs.hp.com/index.html>

---

## The LP Spooler

This section contains:

- [Introduction](#), 9-4
- [Stop and Restart the LP Spooler](#), 9-4
- [Control LP Spooler Jobs](#), 9-4
- [Monitor the LP Spooler Status](#), 9-4

### Introduction

The HP-UX line printer spooling system (LP spooler) is a set of programs, shell scripts, and directories that control the data flow of system printers and plotters.

### Stop and Restart the LP Spooler

The LP spooler is started during the boot process.

Follow these steps to stop the LP spooler when adding and removing a printer or plotter.

---

**1 Login as `root`.**

---

**2 Start SAM.**

At a shell window prompt, enter:

```
/usr/sbin/sam
```

---

**3 Click Printers and Plotters > LP Spooler**

## Control LP Spooler Jobs

To cancel print requests or stop the printer spooler:

---

**1 Start SAM.**

---

**2 Click Printers and Plotters > LP Spooler > Print Requests**

---

**3 Select the print job, then use the Actions menu.**

## Monitor the LP Spooler Status

To check the status of a printer, add or remove a printer from the spooler, disable a printer, or set a printer as the system default:

- Click **Printers and Plotters > LP Spooler > Printers and Plotters**, then use the **Actions** menu.