# MODIFICATION ONLY - DOES NOT COMMUNICATE A MODIFICATION OR SAFETY COMMUNICATE

3499A-06

## <u>SERVICE NOTE</u>

Supersedes: NONE

3499A/B/C

Serial Numbers: [0000A00000 / 9999Z99999]

Firmware revision: 4.02.00

3499A/B/C hangs with CLOS:STAT? or OPEN ALL

**Parts Required:** 

P/N Description Qty.

**NONE** 

### ADMINISTRATIVE INFORMATION

SERVICE NOTE CLASSIFICATION:

### **INFORMATION ONLY**

AUTHOR: woh PRODUCT LINE: PLAR

ADDITIONAL INFORMATION:

© AGILENT TECHNOLOGIES, INC. 2003 PRINTED IN U.S.A.

October 16, 2003



Page 2 of 2 3499A-06

#### **Situation:**

When sending a sequence of commands containing OPEN ALL and CLOS::STAT the instrument may hang.

This is a bug in revision 4.0 of the 3499 firmware.

### **Resolution Workaround**

- 1. Use the command SYST:CPON ALL instead of OPEN ALL
- 2. Use the command CLOS? Instead of CLOS:STAT?

These two program snippets demonstrate the problem, and show the workaround.

```
Program 1:
CLOS (@100)
CLOS:STAT? - system hang
Work around solution:
CLOS (@100)
CLOS? (@100)

Program 2:
CLOS (@100)
OPEN ALL - system hang

Work around solution:
CLOS (@100)
SYST: CPON ALL
```

Check this Service Note for future updates.