
Agilent E4438C ESG Vector Signal Generator

Configuration Guide





E4438C ESG Vector Signal Generator

To add options to a Model, use the following ordering scheme:

	Example
Model #	E4438C
Model #-option #	E4438C-001
Model #-option #	E4438C-400

Step 1 Choose a frequency range (Mandatory)

Ordering #	Description	Requires	Not Compatible	For more information
E4438C-501	250 kHz to 1 GHz frequency range			
E4438C-502	250 kHz to 2 GHz frequency range			
E4438C-503	250 kHz to 3 GHz frequency range			
E4438C-504	250 kHz to 4 GHz frequency range			
E4438C-506	250 kHz to 6 GHz frequency range *(Mechanical attenuator only— Do not need to order Option UNB)	UNJ	UNB*, 300	

Step 2 Choose phase noise performance (NOT mandatory)

Ordering #	Description	Requires	Not Compatible	For more information
Standard	Standard phase noise performance			Data Sheet: 5988-4039EN or www.agilent.com/find/esg
E4438C-UNJ	Enhanced phase noise performance: Up to 20 dB Single Sideband (SSB) improvement over standard performance. (Option 1E5 performance is included)		300, 1E5	Data Sheet: 5988-4039EN or www.agilent.com/find/esg

Step 3 Choose a frequency reference (NOT mandatory)

op o	onocco a moquement reference (aaaco.	11	
Ordering #	Description	Requires	Not Compatible	For more information
Standard	Standard stability time base			Data Sheet: 5988-4039EN or www.agilent.com/find/esg
E4438C-1E5	High-stability time base: Provides improved frequency accuracy over		UNJ	Data Sheet: 5988-4039EN or www.agilent.com/find/esg
	time and with temperature variation. (Option performance is included with Option UNJ)	1E5		
	32 Msample memory; extra memory for when longer waveform playback is desired. Used to produce arbitrary and real-time I/Q			www.agilent.com/find/esg
	waveforms. A variety of standard compliant firmware and software personalities are available. Option 001 is NOT required.			

E4438C ESG Vector Signal Generator (continued)

Step 4 Choose an attenuator (NOT mandatory)

Ordering #	Description	Requires	Not Compatible	For more information
Standard with Options 501,502,503,504	State-of-the-art electronic attenuator: Includes excellent adjacent channel performance(ACP) for CDMA application (previously Option H99). Also provides alternate timeslot power control ideal for GSM receiver and transmitter designs (previously Option UNA).		506	Data Sheet: 5988-4039EN or www.agilent.com/find/esg
E4438C-UNB	High output power with mechanical attenuator Increase the output power up to 6 dB for higher power applications. (Option UNB performance is included with Option 506)	;	300, 506	Data Sheet: 5988-4039EN or www.agilent.com/find/esg

Step 5 Choose baseband generator with memory (NOT mandatory)

op o	Onocoo bacobana gonorator with	(, i illulluutoi i i	
Ordering #	Description	Requires	Not Compatible	For more information
E4438C-001	Internal baseband generator with 8 Msample memory; used to produce arbitrary and real-time I/Q waveforms. A variety of standard compliant firmware and software personalities are available.			Data Sheet: 5988-4039EN or www.agilent.com/find/esg
E4438C-002	Internal baseband generator with 32 Msample memory; extra memory for when longer waveform playback is desired. Used to produce arbitrary and real-time I/Q waveforms. A variety of standard compliant firmware and software personalities are available. Option 001 is NOT required.			Data Sheet: 5988-4039EN or www.agilent.com/find/esg
E4438C-005	6G Byte hard drive for non-volatile waveform storage	001 (or 002)		Data Sheet: 5988-4039EN or www.agilent.com/find/esg

Step 6 Choose a firmware personality for your internal baseband generator (NOT mandatory)

Ordering #	Description	Requires	Not Compatible	For more information
E4438C-400	3GPP W-CDMA (FDD) personalities	001 (or 002)		Product Overview: 5988-4449EN www.agilent.com/find/esg
E4438C-401	cdma2000 and IS-95-A personalities	001 (or 002)		Product Overview: 5988-4430EN www.agilent.com/find/esg
E4438C-402	TDMA personalities Includes GSM, EDGE, NADC, PDC, PHS, DECT, TETRA.	001 (or 002)		Product Overview: 5988-4431EN www.agilent.com/find/esg
E4438C-403	Calibrated noise personality: Provides settable Eb/No used for sensitivity testing in cdma2000 and W-CDMA applications	001 (or 002)		
E4438C-409	GPS personality	001 (or 002)		Product Overview: 5988-6256EN www.agilent.com/find/esg

E4438C ESG Vector Signal Generator (continued)

Step 7	Choose a Signal Studio softwar	e with your interna	l baseband gene	rator (NOT mandatory)
Ordering #	Description	Requires	Not Compatible	For more information
E4438C-404	1xEV-DO Signal Studio software	001 (or 002) and a PC		Product Note: 5988-5416EN Product Overview: 5988-5459EN www.agilent.com/find/signalstudio
E4438C-405	802.11b WLAN Signal Studio software software	001 (or 002) and a PC		Product Note: 5988-5415EN Product Overview: 5988-5766EN www.agilent.com/find/signalstudio
E4438C-406	<i>Bluetooth</i> [™] Signal Studio software	001 (or 002) and a PC		Product Note: 5988-5417EN Product Overview: 5988-5458EN www.agilent.com/find/signalstudio
E4438C-408	Enhanced Multitone Signal Studio software	001 (or 002) and a PC		Product Overview: 5988-5639EN www.agilent.com/find/signalstudio
E4438C-410	802.11a WLAN Signal Studio software	001 (or 002) and a PC		Product Note: 5988-5414EN Product Overview: 5988-5765EN www.agilent.com/find/signalstudio
E4438C-411	TD-SCDMA (TSM) Signal Studio software	001 (or 002) and a PC		Product Overview: 5988-6552EN www.agilent.com/find/signalstudio

Step 8	NOT mandatory)
--------	---------------	---

Ordering #	Description	Requires	Not Compatible	For more information
E4438C-UN7	Internal bit-error-rate analyzer			
E4438C-300	GSM/EDGE basestation loopback BER test capability	001 (or 002), 402, UN7	UNJ, UNB, 506	

ο. ο	ΛΙ			f	/RIOT I . \
Step 9	I honed arrae	enride or inetr	IIMANT CANNACTAR I	rantialiratian	(NOT mandatory)
OLGD J	บแบบจับ สับบัน	วงบาเธอ บา เมอนา	unicht Comicció	communation .	livo i illalluatoi v <i>i</i>

				<u> </u>
Ordering #	Description	Requires	Not Compatible	For more information
E4438C-1EM	Moves all front panel connectors to rear panel			
E4438C-1CP	Rack mount kit with handles			Catalog: 5980-0450E
E4438C-1CN	Handle kit			Catalog: 5980-0450E

Step 10 Choose a warranty plan (Mandatory)

Ordering #	Standard warranty is 36 months.
	For warranty and service of 5 years, please order 60 months of R-51B (quantity = 60).
R-51B	Return-to-Agilent warranty and service plan

Step 11 Choose a calibration plan¹ (Mandatory)

Ordering #	For 3 years, order 36 months of the appropriate calibration plan shown below.
	For 5 years, specify 60 months.
R-50C-001	Standard calibration
R-50C-002	Standards compliant calibration

¹ Options not available in all countries.

E4438C ESG Vector Signal Generator (continued)

Step 12 Choose any documentation (NOT mandatory)

Ordering #	Description Re	equires	Not Compatible	For more information			
E4438C-CD1 (Standard)	CD-ROM - English Documentation Set						
E4438C-0BW	Service documentation, assembly level (Hardcopy)						
E4438C-0BV	Service documentation, component level (Hardcopy)						
E4438C-UK6	Commercial calibration certificate with test data (Hardcopy)						
E4438C-ABA	United States - English documentation set (Hardco	oy)					
E4438C-AB0	Taiwan - Chinese localization (Hardcopy)						
E4438C-AB1	Korean - Korean localization (Hardcopy)						
E4438C-AB2	China - Chinese localization (Hardcopy)						
E4438C-ABF	French - French localization (Hardcopy)						
E4438C-ABJ	Japanese - Japenese localization (Hardcopy)						

Additional Agilent literature

E4438C ESG Vector Signal Generator, Brochure, literature number 5988-3935EN.

RF Source Basics, a self-based tutorial (CD ROM),

literature number 5980-2060E.

Digital Modulation in Communications Systems — An Introduction,

Application Note 1298, literature number 5965-7160E.

Using Vector Modulation Analysis in the Integration, Troubleshooting and Design of Digital RF Communications Systems, Product Note 89400-8, literature number 5091-8687E.

Testing CDMA Base Station Amplifiers,

Application Note 1307, literature number 5967-5486E.

Understanding GSM Transmitter Measurements for Base Transceiver Stations and Their Components, Application Note 1312,

literature number 5968-2320E.

Understanding CDMA
Measurements for Base Stations
and their Components,

Application Note 1311, literature number 5968-0953E.

Testing and Troubleshooting Digital RF Communications Receiver Designs,

Application Note 1314, literature number 5968-3579E.

BluetoothTM RF Measurements Fundamentals,

Application Note 1333-1, literature number 5988-3760EN.

Designing and Testing 3GPP W-CDMA Base Stations,

Application Note 1355, literature number 5980-1239E.

Designing and Testing 3GPP W-CDMA User Equipment,

Application Note 1356, literature number 5980-1238E.

Designing and Testing cdma2000 Base Stations,

Application Note 1357, literature number 5980-1303E.

Designing and Testing cdma2000 Mobile Stations,

Application Note 1358, literature number 5980-1237E.

Additional Agilent literature (continued)

Product literature

E4438C ESG Vector Signal Generator, Brochure, literature number 5988-3935EN.

E4438C ESG Vector Signal Generator, Data Sheet, literature number 5988-4039EN.

RF and Microwave Signal Generators, Catalog, literature number 5965-3094E.

IntuiLink Software, Data Sheet, literature number 5980-3115EN.

See the ESG Web page

Get the latest news, product and support information, application literature and more. The Agilent Technologies Internet address for the ESG family is: http://www.agilent.com/find/esg

New trade-up program

Ask your local sales representative about instrument trade-up opportunities for all ESG models.

IntuiLink PC software

Transfer screen data and images easily into Microsoft® Excel and Microsoft® Word. Save and restore instrument states. Download arbitrary waveform files. For more information visit our website at: http://www.agilent.com/find/IntuiLink



www.agilent.com/find/emailupdates

Get the latest information on the products and applications you select.

Bluetooth™ and the Bluetooth logos are trademarks owned by Bluetooth SIG, Inc., U.S.A. and licensed to Agilent Technologies, Inc.

 $Microsoft^{\circledR}$ is a U.S. registered trademark of Microsoft Corp.

Agilent Technologies' Test and Measurement Support, Services, and Assistance

Agilent Technologies aims to maximize the value you receive, while minimizing your risk and problems. We strive to ensure that you get the test and measurement capabilities you paid for and obtain the support you need. Our extensive support resources and services can help you choose the right Agilent products for your applications and apply them successfully. Every instrument and system we sell has a global warranty. Support is available for at least five years beyond the production life of the product. Two concepts underlie Agilent's overall support policy: "Our Promise" and "Your Advantage."

Our Promise

Our Promise means your Agilent test and measurement equipment will meet its advertised performance and functionality. When you are choosing new equipment, we will help you with product information, including realistic performance specifications and practical recommendations from experienced test engineers. When you use Agilent equipment, we can verify that it works properly, help with product operation, and provide basic measurement assistance for the use of specified capabilities, at no extra cost upon request. Many self-help tools are available.

Your Advantage

Your Advantage means that Agilent offers a wide range of additional expert test and measurement services, which you can purchase according to your unique technical and business needs. Solve problems efficiently and gain a competitive edge by contracting with us for calibration, extra-cost upgrades, out-of-warranty repairs, and on-site education and training, as well as design, system integration, project management, and other professional engineering services. Experienced Agilent engineers and technicians worldwide can help you maximize your productivity, optimize the return on investment of your Agilent instruments and systems, and obtain dependable measurement accuracy for the life of those products.

Get the latest information on the products and applications you select.

By internet, phone, or fax, get assistance with all your test & measurement needs

Online assistance: www.agilent.com/find/assist

Phone or Fax

United States: (tel) 800 452 4844

(tel) (82 2) 2004 5004 (fax) (82 2) 2004 5115 Canada:

(tel) 877 894 4414 (fax) 905 282 6495 Latin America:

China:

(tel) (305) 269 7500 (fax) (305) 269 7599

(tel) 800 810 0189

(fax) 800 820 2816

(tel) 0800 047 866

(fax) 0800 286 331 (tel) (31 20) 547 2323

Other Asia Pacific Countries: (fax) (31 20) 547 2390 (tel) (65) 6375 8100 (fax) (65) 6836 0252

Japan: (tel) (81) 426 56 7832 Email: tm_asia@agilent.com

(fax) (81) 426 56 7840

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 2002 Printed in USA, June 20, 2002 5988-4085EN

