

PDH / DSn
Operating Manual

HP 37717C
Communications
Performance Analyzer

© Copyright Hewlett-Packard Ltd.1997

All rights reserved.
Reproduction, adaption, or translation without prior written permission is prohibited, except as allowed under the copyright laws.

Information in this document may apply to modules which use the VxWORKS TM software. The VxWORKS TM software was developed by Wind River Systems, Inc., which has copyright to it.

HP Part No. 37717-90283

First edition, September 97

Printed in U.K.

Warranty

The information contained in this document is subject to change without notice.

Hewlett-Packard makes no warranty of any kind with regard to this material, including, but not limited to, the implied warranties or merchantability and fitness for a particular purpose.


Hewlett-Packard shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this material.

WARNING

Warning Symbols Used on the Product



The product is marked with this symbol when the user should refer to the instruction manual in order to protect the apparatus against damage.



The product is marked with this symbol to indicate that hazardous voltages are present



EN 60825 1991

The product is marked with this symbol to indicate that a laser is fitted. The user should refer to the laser safety information in the Calibration Manual.

HP 37717C Communications Performance Analyzer

About This Book

The HP 37717C PDH /DSn Operating Manual explains the following:

- How to select and use the PDH / DSn features provided with the PDH /DSn options
- How to make PDH / DSn measurements

For some operations and measurements, information from one of the following associated books may be required:

“The HP 37717C Mainframe Operating Manual” explains how to obtain the required display, how to use the front panel keys, how to interpret the status indicators, how to connect to external equipment and how to perform instrument tasks associated with the HP 37717C irrespective of the option configuration.

“The HP 37717C SDH / SONET Operating Manual” describes the selection of SDH / SONET features and how to perform SDH / SONET tests with the HP 37717C Communications Performance Analyzer.

“The HP 37717C Jitter Operating Manual” describes the selection of Jitter features and how to perform Jitter tests with the HP 37717C Communications Performance Analyzer.

“The HP 37717C ATM and LAN Operating Manual” describes the selection of ATM and LAN testing features and how to perform ATM and LAN tests with the HP 37717C Communications Performance Analyzer.

1 HP 37717C PDH / DS_n Features

Introduction to PDH / DS_n 2

Options With PDH / DS_n Capability 3

Unstructured PDH Generation and Measurement. Option UKK (USB) 3

Structured PDH Generation and Measurement. Options UKJ (USA) and UKN (USE) 4

DS1, DS3, E1 and E3 Transmit and Receive Interfaces for ATM Payloads. Option UKZ 5

E1, E3 and E4 Transmit and Receive Interfaces for ATM Payloads. Option UKN (USE) 6

Binary Interfaces. Option UH3 (US7) 7

Multiple PDH Outputs. Option UHC (US6) 8

PDH / DS_n Display Reference 9

Unstructured PDH Generation and Measurement. Option UKK (USB) 9

Structured PDH Generation and Measurement. Options UKJ (USA) or UKN (USE) 11

DS1, DS3, E1 and E3 Transmit and Receive Interfaces for ATM Payloads.

Option UKZ 15

E1, E3 and E4 Transmit and Receive Interfaces for ATM Payloads. Option UKN (USE) 19

Binary Interfaces. Option UH3 (US7) 22

2 PDH / DS_n Testing With The HP 37717C

Alarm Monitoring 26

Analysis of N X 64 kb/s 29

BERT Testing 33

Cross Multiplexer Testing 38

FAS Monitoring 44

Frequency Measurement 48

Frequency Offset Tolerance 51

Multiplexer Testing 55

Round Trip Delay 60

M2100, M2110, M2120 Analysis 63

Monitoring DS3 with ATM Payloads 67

1

Introduction to PDH / DSn page 2

Options With PDH / DSn Capability page 3

Unstructured PDH Generation and Measurement. Option UKK (USB) page 3

Structured PDH Generation and Measurement. Options UKJ (USA) and UKN (USE) page 4

DS1, DS3, E1 and E3 Transmit and Receive Interfaces for ATM Payloads. Option UKZ
page 5

E1, E3 and E4 Transmit and Receive Interfaces for ATM Payloads. Option UKN (USE)
page 6

Binary Interfaces. Option UH3 (US7) page 7

Multiple PDH Outputs. Option UHC (US6) page 8

PDH / DSn Display Reference page 9

Unstructured PDH Generation and Measurement. Option UKK (USB) page 9

Structured PDH Generation and Measurement. Options UKJ (USA) or UKN (USE) page 11

DS1, DS3, E1 and E3 Transmit and Receive Interfaces for ATM Payloads. Option UKZ
page 15

E1, E3 and E4 Transmit and Receive Interfaces for ATM Payloads. Option UKN (USE)
page 19

Binary Interfaces. Option UH3 (US7) page 22

HP 37717C PDH / DSn Features

Information on the optional modules including
selection of the features available.

Introduction to PDH / DSn

The Plesiochronous Digital Hierarchy (PDH / DSn) is still the dominant technology in most existing telecommunications networks throughout the world, although it is being replaced in many networks by Synchronous Digital Hierarchy (SDH) or SONET networks. PDH / DSn networks were developed at a time when point-to-point transmission was the predominant network requirement. To support this requirement, the standard approach to network management and maintenance was to use manual distribution frames for access to individual signals. This is now considered out of date and consequently SDH / SONET is now the preferred network topology for new installations.

However PDH / DSn networks will exist for a long time to come even in networks where SDH /SONET is the preferred technology. PDH is the ETSI international standard, based on 2 Mb/s, defined by the ITU-T, and covers the hierarchal transmission rates of 2 Mb/s, 8 Mb/s, 34 Mb/s and 140 Mb/s. DSn is the ANSI standard covering transmission rates of 1.544 Mb/s (DS1) and 44.736 Mb/s (DS3). PDH is asynchronous at 8 Mb/s, 34 Mb/s and 140 Mb/s. In order to access a signal, for rerouting or test purposes, the whole line signal structure must be demultiplexed step by step down to the 2 Mb/s level, because of the asynchronous nature of the multiplexing.


At each multiplexing step, the bit rate of the individual tributary signals is controlled within specified limits and is not synchronized with the multiplex equipment. Because the bit rates of the individual tributaries are controlled within specific limits this type of multiplexing is referred to as Plesiochronous i.e. nearly synchronous. The individual tributaries are synchronized with the equipment at each multiplex step by the process of positive bit stuffing justification.

In new SDH / SONET networks, PDH / DSn signals are mapped into virtual containers / tributaries before being transported as part of the SDH / SONET payload. The SDH / SONET payload must then be demapped into a PDH / DSn tributary signal.

Therefore all PDH / DSn, SDH / SONET and mixed PDH/SDH DSn / SONET networks require test sets which have PDH / DSn interfaces and PDH / DSn test capability.

Options With PDH / DS_n Capability

Unstructured PDH Generation and Measurement. Option UKK (USB)



Option UKK (USB), Unstructured PDH, provides generation and measurement of unstructured PDH at interface rates of 704 kb/s, 2.048 Mb/s, 8.448 Mb/s, 34.368 Mb/s and 139.264 Mb/s.

Allows the addition of Frequency Offset to the PDH signal

Provides 75 Ω unbalanced or 120 Ω balanced input and output interfaces.


Allows selection of PRBS, WORD or USER patterns

Allows selection of Line Code AMI, HDB3 or CMI

Provides an ECL pulse each time an error occurs (Error Out)

Structured PDH Generation and Measurement. Options UKJ (USA) and UKN (USE)

Structured PDH Generation and Measurement. Options UKJ (USA) and UKN (USE)



Options UKJ (USA) and UKN (USE), provide generation and measurement of Structured or Unstructured PDH at interface rates of 2.048 Mb/s (E1), 8.448 Mb/s (E2), 34.368 Mb/s (E3) and 139.264 Mb/s (E4).

Structured test signal rates of 64 kb/s, 2.048 Mb/s, 8.448 Mb/s and 34.368 Mb/s are provided.

Frequency Offset can be added at the interface rates.

Line rate frequency can be measured.

Provides 75 Ω unbalanced or 120 Ω balanced input and output interfaces.

Allows selection of PRBS, WORD or USER patterns

Allows selection of Line Code AMI, HDB3 or CMI

Interface and test signal rates can be Framed or Unframed

MUX connector allows a 2 Mb/s signal from external equipment to be inserted into the HP 37717C test signal.

DEMUX connector allows a 2 Mb/s signal from the HP 37717C to be Dropped to external equipment.


Option UKN (USE) also provides generation and measurement of PDH signals with ATM payloads. Option UKN (USE) therefore provides all of the PDH facilities described here with the additional facilities described on page 6.

Information on the ATM capabilities of the UKN (USE) module is given in “The ATM Operating Manual”

Option UKJ (USA)

DS1, DS3, E1 and E3 Transmit and Receive Interfaces for ATM Payloads. Option UKZ

DS1, DS3, E1 and E3 Transmit and Receive Interfaces for ATM Payloads. Option UKZ



Option UKZ, provides generation and measurement of PDH /DSn signals with ATM payloads at interface rates of: 1.544 Mb/s (DS1), 44.736 Mb/s (DS3), 2.048 Mb/s (E1), and 34.368 Mb/s (E3).

Frequency Offset can be added at the interface rates.

Line rate frequency can be measured.

Provides the following RZ input and output interfaces:
DS3 and E3: 75 Ω unbalanced
E1: 75 Ω unbalanced, 120 Ω balanced.
DS1: 100 Ω balanced.

Allows selection of Line Code as AMI, HDB3, B3ZS or B8ZS

Provides Input sensitivity level selection.

Provides output level control for DS1 and DS3.


Allows error and alarm injection at the physical and ATM layers.

Allows selection of PCLP or Direct mapping at DS3.

Information on the ATM capabilities of this module is given in "The ATM Operating Manual"

**E1, E3 and E4 Transmit and Receive Interfaces for ATM Payloads.
Option UKN (USE)**

**E1, E3 and E4 Transmit and Receive Interfaces for ATM Payloads.
Option UKN (USE)**



Option UKN (USE) provides generation and measurement of PDH signals with ATM payloads at rates of 2.048 (E1), 34.368 (E3) and 139.264 (E4) Mb/s.

Frequency Offset can be added at the interface rates.

Line rate frequency can be measured.

Provides the following input and output interfaces:

E1: RZ, 75 Ω unbalanced and 120 Ω balanced.

E3: RZ, 75 Ω unbalanced.

E4: CMI 75 Ω unbalanced.

Allows selection of E1 Line Code AMI, HDB3.

Allows selection of CRC-4 Multiframe at E1.

Information on the ATM capabilities of this module is given in “The ATM Operating Manual”

Binary Interfaces. Option UH3 (US7)



Option UH3 (US7) provides binary NRZ interfaces for the structured PDH module option UKJ (USA), and the unstructured PDH module option UKK (USB).

The interfaces can operate at any of the standard rates ± 100 ppm.

When used with option UKK (USB), with an external binary clock input, the interfaces can operate at any rate in the range 700 kb/s to 170 Mb/s.

TTL signal levels, at data and clock ports, and external clock port, are valid from 700 kb/s to 50 Mb/s, 75Ω to ground.

ECL signals, at data and clock ports, and external clock port, are valid from 700 kb/s to 170 Mb/s, 75Ω to -2V.


The external clock input may be used to clock **coded** data from the PDH / DS_n transmitter at standard rates. In addition if Option UKK (USB), Unstructured PDH, is fitted can clock **coded** data in the range 700 kb/s to 170 Mb/s.

Simultaneous jitter of binary clock and binary data outputs is possible (2, 8, 34 & 140 Mb/s) if Option UHK (USB) or A3K, Jitter Generator, is fitted.

Jitter measurement on the binary clock input is possible (2, 8, 34 & 140 Mb/s ± 100 ppm) if Option UHN, A1M, A1N or A1P, Jitter Measurement, is fitted.

Frequency measurement of the external clock input and binary clock input is provided.

Multiple PDH Outputs. Option UHC (US6)



Option UHC (US6), Multiple PDH Outputs, provides three additional 75Ω PDH outputs.

OUT 1 is delayed by 4 bits relative to the main PDH OUT.

OUT 2 is delayed by 8 bits relative to the main PDH OUT.

OUT 3 is delayed by 12 bits relative to the main PDH OUT.

NOTE: When used with Option UKZ, multiple outputs are available at the 2 and 34 Mb/s E1 and E3 rates.

PDH / DS_n Display Reference

Unstructured PDH Generation and Measurement. Option UKK (USB)

A choice of 5 SIGNAL rates is available.

The clock is normally synchronized to an internal clock.

When 2 Mb/s is selected the clock RECOVERED by the Receiver can be used as the synchronization source.

TRANSMITTER OUTPUT		[PDH]
PDH	JITTER	TEST FUNCTION
SIGNAL	CLOCK SYNC	[2 Mb/s]
FREQUENCY OFFSET		[OFF]
CODE		[HDB3]
PATTERN		[2 ⁿ 15-1]
TERMINATION		75Ω UNBAL

STATUS:

140 Mb/s	84 Mb/s	8 Mb/s	2 Mb/s	904 kb/s	MULTIPLE WINDOW
----------	---------	--------	--------	----------	-----------------

FREQUENCY OFFSET can be added at preset CCITT values or as User defined values in the range ± 100 ppm.

The preset value will change according to the PDH signal rate selected.

TRANSMITTER OUTPUT		[PDH]
PDH	JITTER	TEST FUNCTION
SIGNAL	CLOCK SYNC	[140 Mb/s]
FREQUENCY OFFSET		[OFF]
CODE		[CM1]
PATTERN		[2 ⁿ 23-1]
TERMINATION		75Ω UNBAL

STATUS:

OFF	+15 ppm	-15 ppm	USER OFFSET	MULTIPLE WINDOW
-----	---------	---------	-------------	-----------------

Unstructured PDH Generation and Measurement. Option UKK (USB)

PATTERN allows a choice of PRBS and WORD patterns.

Line CODE and TERMINATION can be selected to match the requirements of network equipment.

Errors of the type selected on the TEST FUNCTION display can be added to the PATTERN singly by pressing **SINGLE** or at a selectable RATE.

TEST MODE allows Bit Error measurements to be made with the network equipment Out Of Service or Frame error measurements to be made with the network equipment In Service.

TRANSMITTER OUTPUT		[PDH]
PDH	JITTER	TEST FUNCTION
SIGNAL	CLOCK SYNC	[2 Mb/s]
	FREQUENCY OFFSET	[INTERNAL]
		[OFF]
CODE		[HDB3]
PATTERN		[2 ¹⁵ -1]
TERMINATION		[75Ω UNBAL]

STATUS: 2¹⁵-1 ALL ZEROS ALL ONES MORE MULTIPLE WINDOW

RECEIVER INPUT		[PDH]
PDH	JITTER	
SIGNAL	LEVEL	[2 Mb/s]
TEST MODE		[TERMINATE]
		[OUT OF SRVC]
CODE		[HDB3]
PATTERN		[2 ¹⁵ -1]
TERMINATION		[75Ω UNBAL]

STATUS: OUT OF SERVICE IN SERVICE MULTIPLE WINDOW

When In Service is selected the only PATTERN available is LIVE TRAFFIC.

If 2 Mb/s is selected as the SIGNAL rate, a choice of 2 Mb/s FRAMING type is provided.

RECEIVER INPUT		[PDH]
PDH	JITTER	
SIGNAL	LEVEL	[2 Mb/s]
TEST MODE		[TERMINATE]
		[IN SERVICE]
FRAMING		[PCM30]
CODE		[HDB3]
PATTERN		[LIVE TRAFFIC]
TERMINATION		[75Ω UNBAL]

STATUS: PCM30 PCM31 PCM31CRC PCM30CRC MULTIPLE WINDOW


Structured PDH Generation and Measurement. Options UKJ (USA) or UKN (USE)

Structured PDH Generation and Measurement. Options UKJ (USA) or UKN (USE)

A choice of four SIGNAL rates is available.


The clock is synchronized to an internal clock.

TERMINATION and Line CODE selections should match the requirements of the network equipment.



FREQUENCY OFFSET can be added at preset CCITT values or as User defined values in the range ± 100 ppm


The preset value will change according to the PDH signal rate selected.



PAYLOAD TYPE determines whether the PDH signal is Unframed (Unstructured), Framed or Structured.


PATTERN allows a choice of PRBS and WORD patterns.

PRBS POLARITY allows a choice between Inverted (CCITT recommended) and Normal.



Structured PDH Generation and Measurement. Options UKJ (USA) or UKN (USE)

If 2Mb/s SIGNAL rate is selected the choice of Framing type is included in the PAYLOAD TYPE menu.




If STRUCTURED is selected a new display of **STRUCTURED SETTINGS** is obtained.

TEST SIGNAL allows a choice of rates (sub interface rate) at which testing is performed.

The example shown is for a 140 Mb/s main signal rate.


If 2Mb/s TEST SIGNAL rate is selected the choice of Framing type is included in the 2M PAYLOAD menu.



The 2M PAYLOAD menu includes a choice of INSERT 2Mb/s which allows an external 2 Mb/s Test Signal, presented at the MUX port, to be inserted into the structured PDH signal.

The capability to DROP the 2 Mb/s Test Signal to external equipment, via the DEMUX connector, is provided on the

RECEIVE STRUCTURED SETTINGS display 2M PAYLOAD menu.




Structured PDH Generation and Measurement. Options UKJ (USA) or UKN (USE)

34Mb, 8Mb and 2Mb allow selection of the tributary of interest.

PATTERN allows a choice of PRBS and WORD patterns.

PRBS POLARITY allows a choice between Inverted (CCITT recommended) and Normal.


B/G PATTERN selection determines the pattern inserted in the non test tributaries.



If Transmit and Receive TEST SIGNAL 64 kb/s is selected the 2 Mb/s Framing choice is made from the 2M PAYLOAD menu.

A telephone HANDSET can be connected to the 64 kb/s channel and used to LISTEN or TALK and LISTEN.


The B/G PATTERN in the non test 64 kb/s channels is always NUMBERED.



When N X 64kb/s is selected a test pattern can be inserted across a number of Timeslots even if the selected Timeslots are non contiguous.

The required Timeslots are selected using **DESELECT ALL**, **DESELECT**, **SELECT**, [←] and [→].

In this example timeslots 3, 5, 9, 25, 26 and 27 are selected.




Structured PDH Generation and Measurement. Options UKJ (USA) or UKN (USE)

If the receiver input is derived from the network equipment monitor point then **SIGNAL IN** is pressed until the MONITOR indicator is lit.

The received signal will be 20 to 30 dB below the normal level. To return the received signal to normal GAIN is required at the receiver input.


The received signal may also require equalization to compensate for cable losses.



The **TRANSMIT TEST FUNCTION** allows the addition of errors.

Bit, Code or FAS (Frame) errors can be added dependent upon the SIGNAL and PAYLOAD TYPE selections.

Errors of the type selected on the TEST FUNCTION display can be added to the PATTERN singly by pressing **SINGLE**, or at a selectable RATE.



DS1, DS3, E1 and E3 Transmit and Receive Interfaces for ATM Payloads. Option UKZ

DS1, DS3, E1 and E3 Transmit and Receive Interfaces for ATM Payloads. Option UKZ

A choice of four PDH / DSn SIGNAL rates is available

The clock may be synchronized to an internal clock or the received clock.

TERMINATION and Line CODE selections should match the requirements of the network equipment.

For DS1 and DS3 signal rates, the OUTPUT LEVEL can be selected. At DS3 the CONVERGENCE LAYER can be configured

When SDH / SONET modules are fitted, additional transmission and reception rates are available. For example STM-1 and OC-3c transmission and reception is available via the SDH Overhead / Stress module A1T plus an optical module such as UH1.

FREQUENCY OFFSET can be added at preset values or as User defined values in the range ± 100 ppm

The preset value will change according to the PDH / DSn signal rate selected.

TRANSMITTER OUTPUT			[ATM]
PHYSICAL LAYER	ATM LAYER	TEST FUNCTION	
SIGNAL	DS3	[INTERNAL]	
CLOCK SYNC		[INTERNAL]	
OUTPUT LEVEL		[DSX-3]	
TERMINATION		[75 Ω UNBAL]	
LINE CODE		[B3Z5]	
FREQUENCY OFFSET		[OFF]	
CONVERGENCE SUB-LAYER		[DIRECT]	
SCRAMBLING			[ON]
STATUS:			
DS3	34 Mb/s	2 Mb/s	DS1 MULTIPLE WINDOW

TRANSMITTER OUTPUT			[ATM]
PHYSICAL LAYER	ATM LAYER	TEST FUNCTION	
SIGNAL	DS3	[INTERNAL]	
CLOCK SYNC		[INTERNAL]	
OUTPUT LEVEL		[DS3-HI]	
TERMINATION		[75 Ω UNBAL]	
LINE CODE		[B3Z5]	
FREQUENCY OFFSET		[OFF]	
CONVERGENCE SUB-LAYER		[DIRECT]	
SCRAMBLING			[ON]
STATUS:			
STS-3c	STM-1	DS3	34 Mb/s MORE MULTIPLE WINDOW

TRANSMITTER OUTPUT			[ATM]
PHYSICAL LAYER	ATM LAYER	TEST FUNCTION	
SIGNAL	[34 Mb/s]	[INTERNAL]	
CLOCK SYNC		[INTERNAL]	
TERMINATION		[75 Ω UNBAL]	
LINE CODE		[HDB3]	
FREQUENCY OFFSET		[OFF]	
TRAIL TRACE		[TEST HP37717C]	
SCRAMBLING			[ON]
STATUS:			
OFF	+20 ppm	-20 ppm	USER OFFSET MULTIPLE WINDOW

DS1, DS3, E1 and E3 Transmit and Receive Interfaces for ATM Payloads. Option UKZ

At the 34Mb/s SIGNAL rate a TRAIL TRACE facility is available. The default signal, HP37717C, may be replaced with a selectable message.

TRANSMITTER OUTPUT		[ATM]
PHYSICAL LAYER	ATM LAYER	TEST FUNCTION
SIGNAL	[34 Mb/s]	[INTERNAL]
CLOCK SYNC		[INTERNAL]
TERMINATION		[75% UNBAL]
LINE CODE		[HDB3]
FREQUENCY OFFSET		[OFF]
TRAIL TRACE		[YES]
		HP37717C
SCRAMBLING		[ON]

STATUS:

If the DS3 SIGNAL rate is selected the choice of CONVERGENCE SUB-LAYER is provided (Direct or PLCP mapping).

TRANSMITTER OUTPUT		[ATM]
PHYSICAL LAYER	ATM LAYER	TEST FUNCTION
SIGNAL	[DS3]	[INTERNAL]
CLOCK SYNC		[INTERNAL]
OUTPUT LEVEL		[DS3-HI]
TERMINATION		[75% UNBAL]
LINE CODE		[B3Z]
FREQUENCY OFFSET		[OFF]
CONVERGENCE SUB-LAYER		[PLCP]
LINE SIGNAL STATUS(G1)		[000]
CYCLIC/STUFF COUNT		[NOMINAL]
GROWTH BYTES	[21]	[11111111]
SCRAMBLING		[ON]

STATUS:

If the 2Mb/s SIGNAL rate is selected, CRC-4 Multiframe may be selected. SCRAMBLING may be selected ON or OFF at any of the SIGNAL rates.

TRANSMITTER OUTPUT		[ATM]
PHYSICAL LAYER	ATM LAYER	TEST FUNCTION
SIGNAL	[2 Mb/s]	[INTERNAL]
CLOCK SYNC		[INTERNAL]
TERMINATION		[75% UNBAL]
LINE CODE		[HDB3]
FREQUENCY OFFSET		[OFF]
CRC-4 MULTIFRAME		[OFF]
SCRAMBLING		[ON]

STATUS:

DS1, DS3, E1 and E3 Transmit and Receive Interfaces for ATM Payloads. Option UKZ

The **TRANSMIT TEST FUNCTION** allows the addition of errors and alarms at the physical and ATM layers.

The types of error available for selection will depend on the SIGNAL rate selected. The example shown is for DS1 which includes excess zeros (EXZ).

TRANSMITTER OUTPUT		[ATM]
PHYSICAL LAYER	ATM LAYER	TEST FUNCTION
TEST FUNCTION [PDH]		ERR & ALARM
ERROR ADD TYPE	[FAS (LINE)]	
RATE	[OFF]	
PRESS SIGNAL KEY TO ERROR	[1 FRAME]	
ALARM TYPE	[OFF]	

STATUS:	FAS (LINE)	CODE	CRC	EXZ	MULTIPLE WINDOW
---------	------------	------	-----	-----	-----------------

The alarms which may be generated also depend on the SIGNAL rate selected.

The example shown here is for DS3.

The Far End Alarm and Control (FEAC) function allows alarm conditions and control codewords to be transmitted.

TRANSMITTER OUTPUT		[ATM]
PHYSICAL LAYER	ATM LAYER	TEST FUNCTION
TEST FUNCTION [PDH]		ERR & ALARM
ERROR ADD TYPE	[FAS (LINE)]	
RATE	[OFF]	
PRESS SIGNAL KEY TO ERROR	[1 FRAME]	
ALARM TYPE	[FEAC]	
FEAC CODE TYPE	[LOOPBACK]	
MESSAGE	[DEACTIVATE DS1 JC 1]	
REPEAT (TIMES)	[10 LOOP, 10 MESS.]	
TRANSMIT NEW CODE	[OFF]	

STATUS:	RAT	FEAC	IDLE	MORE	MULTIPLE WINDOW
---------	-----	------	------	------------	-----------------

To make measurements on PDH / DSn signals with ATM payloads, set the **RECEIVE PHYSICAL LAYER** to the interface SIGNAL RATE. MONITOR and TERMINATE LEVELS should be set to match the signal level.


RECEIVER INPUT		ATM
PHYSICAL LAYER	ATM LAYER	
SIGNAL	[DS1]	
TERMINATION	[100% BAL]	
LINE CODE	[B2S]	
LEVEL	[TERMINATE]	
CELL SCRAMBLING	[OFF]	

ttion	DS3	34 Mb/s	2 Mb/s	DS1	MULTIPLE WINDOW
-------	-----	---------	--------	-----	-----------------


HP 37717C PDH / DSn Features

**DS1, DS3, E1 and E3 Transmit and Receive Interfaces for ATM
Payloads. Option UKZ**

Select **RESULTS** **PDH RESULTS**



Then select the type of result required.



Information on the ATM features of this module is given in “The ATM Operating Manual”

**E1, E3 and E4 Transmit and Receive Interfaces for ATM Payloads.
Option UKN (USE)**

**E1, E3 and E4 Transmit and Receive Interfaces for ATM Payloads.
Option UKN (USE)**

A choice of three PDH SIGNAL rates is available

The clock may be synchronized to an internal clock or the received clock.

FREQUENCY OFFSET can be added at preset values or as User defined values in the range ± 100 ppm. The preset value will change according to the PDH signal rate selected.

A Trail Trace facility is available at the 140 and 34 Mb/s rates.

TERMINATION and Line CODE are preset at 140 and 34 Mb/s. at the 2 Mb/s rate the Termination and line code selections should match the requirements of the network equipment.

At the 2 Mb/s rate CRC-4 Multiframe can be selected.

TRANSMITTER OUTPUT		[ATM]
PHYSICAL LAYER	ATM LAYER	TEST FUNCTION
SIGNAL	140 Mb/s	[INTERNAL]
CLOCK SYNC		INTERNAL
TERMINATION		75% UNBAL
LINE CODE		CMI
FREQUENCY OFFSET		[OFF]
TRAIL TRACE		[TEST HP37717C]
STATUS:		
140 Mb/s	34 Mb/s	2 Mb/s
		MULTIPLE WINDOW

TRANSMITTER OUTPUT		[ATM]
PHYSICAL LAYER	ATM LAYER	TEST FUNCTION
SIGNAL	[2 Mb/s]	[INTERNAL]
CLOCK SYNC		INTERNAL
TERMINATION		[75% UNBAL]
LINE CODE		[B1B3]
FREQUENCY OFFSET		[OFF]
CRC-4 MULTIFRAME		[OFF]
STATUS:		
H0B3	AMI	
		MULTIPLE WINDOW

HP 37717C PDH / DS_n Features

**E1, E3 and E4 Transmit and Receive Interfaces for ATM Payloads.
Option UKN (USE)**

When SDH / SONET modules are fitted, additional transmission and reception rates are available. For example STM-1 OPTICAL and STM-1 (ELECTRICAL) transmission and reception is available via the SDH Overhead / Stress module A1T plus an optical module such as UH1.

TRANSMITTER OUTPUT		[ATM]
PHYSICAL LAYER	ATM LAYER	TEST FUNCTION
SIGNAL	[2 Mb/s]	[INTERNAL]
CLOCK SYNC		[INTERNAL]
TERMINATION		[75Ω UNBAL]
LINE CODE		[HDB3]
FREQUENCY OFFSET		[OFF]
CRC-4 MULTIFRAME		[OFF]

STATUS: **STM-1** 140 Mb/s 8x Mb/s 2 Mb/s MULTIPLE WINDOW

To make measurements on PDH signals with ATM payloads, set **RECEIVE** to **ATM** and select the interface SIGNAL RATE. MONITOR and TERMINATE LEVELS are available.

RECEIVER INPUT		[ATM]
PHYSICAL LAYER	ATM LAYER	
SIGNAL		[140 Mb/s]
TERMINATION		[75Ω UNBAL]
LINE CODE		[CMI]
LEVEL		[TERMINATE]

STATUS: **PDH** **ATM** MULTIPLE WINDOW

Select **RESULTS** **PDH RESULTS**


RESULTS	[PDH]	[SHORT TERM]
		[EM BIP]
EM BIP EC		
EM BIP ER		
ELAPSED TIME		

STATUS: **PROBLE SCAN** **LINKS CONTROL** **PDH RESULTS** **ATM RESULTS** MULTIPLE WINDOW

HP 37717C PDH / DSn Features

E1, E3 and E4 Transmit and Receive Interfaces for ATM Payloads. Option UKN (USE)

Then select the type of result required.



NOTE

When DS3 frame errors are being measured, errors in either FAS or MFAS bits are included.

Information on the ATM features of this module is given in “The ATM Operating Manual”.

Binary Interfaces. Option UH3 (US7)

To enable the **TRANSMIT** selection of NRZ binary interfaces, select, **PDH**, MAIN SETTINGS, INTERFACE, **BINARY**

The CLOCK SYNC for the transmitted signal may be selected as either the internal source or from an external binary (NRZ) input.

TRANSMITTER OUTPUT	[PDH]
MAIN STRUCT'D TEST BINARY	
SETTINGS: SETTINGS: FUNCTION:	
SIGNAL	[2 Mb/s]
INTERFACE	[BINARY]
CLOCK SYNC	[INTERNAL]
FREQUENCY OFFSET	[OFF]
PAYLOAD TYPE	[UNFRAMED]
PATTERN	[2 ¹⁵ -1 PRBS]
PRBS POLARITY	[INU] CCITT

STATUS: **CODED** **BINARY** **MULTIPLE WINDOW**

The binary clock and data output thresholds and polarity are selectable. Thresholds may be ECL (75 Ω to ground) or TTL (75 Ω to -2V), polarity may be normal or inverted.

TRANSMITTER OUTPUT	[PDH]
MAIN STRUCT'D TEST BINARY	
SETTINGS: SETTINGS: FUNCTION:	
SIGNAL	[2 Mb/s]
INTERFACE	[BINARY]
CLOCK SYNC	[INTERNAL]
THRESHOLDS: CLOCK OUT	[ECL]
DATA OUT	[ECL]
POLARITY: CLOCK OUT	[NORMAL]
DATA OUT	[NORMAL]

STATUS: **CODED** **BINARY** **MULTIPLE WINDOW**

To enable the **RECEIVE** selection of binary interfaces, select, **PDH**, MAIN SETTINGS, INTERFACE, **BINARY**

RECEIVER INPUT	[PDH]
MAIN STRUCT'D TEST BINARY	
SETTINGS: SETTINGS:	
SIGNAL	[2 Mb/s]
INTERFACE	[BINARY]
PAYLOAD TYPE	[UNFRAMED]
PATTERN	[2 ¹⁵ -1 PRBS]
PRBS POLARITY	[INU] CCITT

STATUS: **CODED** **BINARY** **MULTIPLE WINDOW**

HP 37717C PDH / DS_n Features Binary Interfaces. Option UH3 (US7)

The binary clock and data input thresholds and polarity are selectable.

RECEIVER INPUT		[PDH]
MAIN SETTINGS	STRUCTURE	BINARY
SIGNAL INTERFACE		2 Mb/s BINARY
THRESHOLDS:	CLOCK IN	[ECL]
	DATA IN	[ECL]
POLARITY:	CLOCK IN	[NORMAL]
	DATA IN	[NORMAL]
STATUS:		
MULTIPLE WINDOWS		

The DATA threshold selections are:

TTL (1.5V), ECL (-1.3V) and GND (0V)

The CLOCK thresholds are as for data plus AUTO (mean signal level).

The CLOCK and DATA polarity may be normal or inverted.

RECEIVER INPUT		[PDH]		
MAIN SETTINGS	STRUCTURE	BINARY		
SIGNAL INTERFACE		2 Mb/s BINARY		
THRESHOLDS:	CLOCK IN	[ECL]		
	DATA IN	[ECL]		
POLARITY:	CLOCK IN	[NORMAL]		
	DATA IN	[NORMAL]		
STATUS:				
ECL	TTL	GND	AUTO	MULTIPLE WINDOWS

2

Alarm Monitoring	page 26
Analysis of N X 64 kb/s	page 29
BERT Testing	page 33
Cross Multiplexer Testing	page 38
FAS Monitoring	page 44
Frequency Measurement	page 48
Frequency Offset Tolerance	page 51
Multiplexer Testing	page 55
Round Trip Delay	page 60
M2100, M2110, M2120 Analysis	page 63
Monitoring DS3 with ATM Payloads	page 67

PDH / DS_n Testing With The HP 37717C

Alarm Monitoring

Alarm Monitoring

Options Required Structured PDH UKJ (USA) or UKN (USE)

Application

Problems in the network at all levels in the hierarchy can be detected by the occurrence of alarms in each tributary of structured PDH systems.

Using the HP 37717C in a *receive only* mode, each tributary can be scanned and the state of Frame Loss, Remote (RAI) and AIS alarms viewed on the **RESULTS** display.

Default (Known State) Settings

It can be advisable to set the HP 37717C to a known state prior to setting up to make a measurement. This clears all previous settings and provides a clearly defined instrument state. For a list of Default Settings and the procedure for accessing them see *Stored Settings*.


Test Setup Procedure (Alarm Monitoring)

This setup procedure is based on Structured PDH 140 Mb/s line traffic interfaced at the line equipment 75 Ω protected Monitor point. If a protected Monitor Point is not available then an HP 15510A Protective Probe may be used at an unprotected Monitor point.

When 120 Ω Balanced alarm monitoring is desired at an unprotected Monitor point use an HP 15511A Protective Monitor Probe. The instrument is used in a *receive only* mode to monitor Frame Loss, AIS and Remote alarms.


PDH / DS_n Testing With The HP 37717C

Alarm Monitoring




- 1 Connect the HP 37717C to the line terminal equipment protected Monitor point and set up the **RECEIVE** display **MAIN SETTINGS** as shown opposite.

The GAIN and EQUALIZER settings should be set to optimize the received signal.



- 2 Set up the **RECEIVE** display **STRUCTURED SETTINGS** as shown opposite.

2M PAYLOAD determines the Framing and selection which should match that of the network equipment.




Alarm Monitoring

Start the Test (Alarm Monitoring)

- 1 . Set up the **RESULTS** display as shown opposite and select **PDH ALM SCAN ON** .


If any of the three alarms, Frame Loss, RAI or AIS has occurred the appropriate point in the hierarchy will be highlighted.

The test can be halted at any time by selecting **OFF** on the **RESULTS PDH ALM SCAN** display.




- 2 To determine which alarm has occurred set the PDH ALM SCAN **OFF** and then set the **RECEIVE STRUCTURED SETTINGS** display to the tributary highlighted as shown opposite and press **RUN/STOP** .

Example 2Mb number 2 of 8Mb number 1 of 34 Mb number 1 is highlighted.



- 3 Now view the Alarm Seconds results on the **RESULTS** display to determine which alarms have occurred.



Analysis of N X 64 kb/s

Options Required Structured PDH UKJ (USA) or UKN (USE)

Application

Many customer premises receive subrate signals for example 128 Kb/s or 384 kb/s. The timeslots which make up these services may or may not be contiguous. Testing these services requires that the test set to be able to insert a pattern across the required timeslots.


Testing N X 64 kb/s channels structured within a 2 Mb/s signal can be carried out on an End to End basis using two test sets.

Default (Known State) Settings

It can be advisable to set the HP 37717C to a known state prior to setting up to make a measurement. This clears all previous settings and provides a clearly defined instrument state. For a list of Default Settings and the procedure for accessing them see *Stored Settings in the Mainframe Operating Manual*.

Test Setup Procedure (N X 64 kb/s Analysis)

This setup procedure is interfaced at 2 Mb/s, with a test signal of 6 X 64 kb/s non-contiguous timeslots. A PRBS test pattern is transmitted across the 6 timeslots. A BER measurement is performed on the received test pattern.




PDH / DS_n Testing With The HP 37717C

Analysis of N X 64 kb/s

HP 37717C #1


1. Set up the **OTHER SETTINGS CONTROL** display as shown opposite.

Any settings change made on the **TRANSMIT** or **RECEIVE** displays will automatically occur on the other.



2. Connect the HP 37717C to the line equipment and set up the **TRANSMIT MAIN SETTINGS** display as shown opposite.


The settings of SIGNAL rate and LINE CODE must match those of the network equipment.



3. Set up the **TRANSMIT STRUCTURED SETTINGS** display as shown opposite.

In this example timeslots 3, 5, 9, 25, 26 and 27 are selected.

2M PAYLOAD selects the Framing which must match that of the network equipment.




PDH / DSn Testing With The HP 37717C

Analysis of N X 64 kb/s

4. Set up the **RESULTS** display as shown opposite.


The RESULTS type may be changed during the measurement without interrupting the test.



HP 37717C #2


1. Set up the **OTHER SETTINGS CONTROL** display as shown opposite.

Any settings change made on the **TRANSMIT** or **RECEIVE** displays will automatically occur on the other.



2. Set up the **RECEIVE MAIN SETTINGS** display as shown opposite.

The settings of SIGNAL rate and LINE CODE must match those of the network equipment.



BERT Testing

BERT Testing

Options Required Structured PDH UKJ (USA) or UKN (USE), or Unstructured PDH UKK (USB)

Application


A transmission system must be specified for its overall error performance, measured over a period of time. Conformance to these specifications ensures that an installed system will meet the requirements of an Integrated Digital Network (IDN).

After troubleshooting, or during installation or commissioning, it is necessary to check that the transmission link meets this error performance.

This can be performed in two ways:

- End To End - Error performance measurements are made on an end-to-end basis testing the Go and Return paths separately but simultaneously. The measurements are often performed unattended and the results and other events, alarms for example, logged on a printer or disc and timed by a real time clock facility.


Two HP 37717C's are required for this measurement, one at each end of the link.



End-to End Test

BERT Testing

- Loopback - Error performance measurements are made via a loopback at the remote end of the system testing the combined Go and Return paths. The measurements are often performed unattended and the results and other events, alarms for example, logged on a printer or disc and timed by a real time clock.



Loopback Test

Default (Known State) Settings

It can be advisable to set the HP 37717C to a known state prior to setting up to make a measurement. This clears all previous settings and provides a clearly defined instrument state. For a list of Default Settings and the procedure for accessing them see *Stored Settings*.

Test Setup Procedure (BERT Testing)


This setup procedure is based on 140 Mb/s, CMI, PRBS test data terminated in 75Ω . A SINGLE test period of 24 HOURS is used and use of the a printer or disc for recording of results and alarms is included. A graphical record of the results can be viewed on the HP 37717C **GRAPH** display at the end of the test period.

PDH / DSn Testing With The HP 37717C


BERT Testing

1. Set up the **OTHER SETTINGS CONTROL** display as shown opposite (on both HP 37717C's if end to end).

Any settings change made on the **TRANSMIT** or **RECEIVE** displays will automatically occur on the other.



2. Connect the HP 37717C to the line equipment and set up the **TRANSMIT** display as shown opposite (on both HP 37717C's if end to end).




3. Select the **LOGGING** function as shown opposite (on both HP 37717C's if end to end).

A LOGGING PERIOD selection of [USER PROGRAM] [10 MIN] provides the following:

A complete set of period and a complete set of cumulative results logged on the printer or disc every 10 minutes.

A complete set of cumulative results logged on the printer or to disc at the end of the test period.




PDH / DSn Testing With The HP 37717C

BERT Testing

4. Set up the **RESULTS** display as shown opposite (on both HP 37717C's if end to end).

The RESULTS type can be changed during the test period without interrupting the test.

The RESULTS **TIMING CONTROL** STORAGE selection enables the graphics. To disable graphics select STORAGE [OFF].



Start the Test (BERT Testing)

1. Press **RUN/STOP** (on both HP 37717C's if end to end).

The measurement results and alarms are available on the **RESULTS** display during the test period.

The graphical measurement results and alarms are stored in non volatile memory for viewing later on the **GRAPH** display.

The test can be halted at any time by pressing **RUN/STOP**.

At the End of the Test (BERT Testing)

- The Date and Time the test started and the instrument setup are logged on the selected logging device.
- All results are logged on the selected logging device at 10 minute intervals.
- Any alarms which occur during the test period will be logged on a printer or disc.
- At the end of the test period a complete set of cumulative results are logged on the printer or disc.
- A graphical record of the results during the test period can be viewed on the **GRAPH** display. If Remote Control option A3B or A3D is fitted the graph results can be logged to an external printer, at a later date. See *Graphics* and *External HP 550C DeskJet Printer in the Mainframe Operating Manua*.
- Results and Alarm summaries can be viewed on the **GRAPH** display.

BERT Testing

The total graphics store capacity is normally 20,000 events. If GRAPH STORAGE RESOLUTION [FULL] is selected on the **OTHER** **MISCELLANEOUS** display the capacity reduces to 10,000 events.

The resolution, determined by the selection made under STORAGE on the **RESULTS** **TIMING CONTROL** display, affects the ZOOM capability when viewing the bar graphs. If 1 SECOND is selected all resolutions are available under ZOOM. If 1 MIN is selected only 1 MIN/BAR, 15 MINS/BAR and 60 MINS/BAR are available. If 15 MINS is selected only 15 MINS/BAR and 60 MINS/BAR are available. If 1 HOUR is selected only 60 MINS/BAR is available.

Up to 10 sets of graphical results can be stored. If an attempt is made to store more than 10 sets of results, then a first in first out policy is operated and the oldest set of results will be lost. If graphics are enabled and a test is run which exceeds the remaining storage capacity, then some previously stored graphical results will be lost.

To prevent accidental overwriting of previously stored results the graphics capability should be disabled, when graphical results are not required, by selecting STORAGE [OFF] on the **RESULTS** **TIMING CONTROL** display.

Cross Multiplexer Testing

Cross Multiplexer Testing

Options Required Structured PDH UKJ (USA) or UKN (USE)

Application

For comprehensive testing of network equipment it is essential that the test equipment can multiplex/demultiplex the test signal.

The insertion of tributary signals into the PDH multiplexer, which are then multiplexed into the 140 Mb/s PDH structure should take place without introducing errors. The insertion and structuring process is tested by adding a test pattern to the tributary inserted at the tributary insert port. At the high rate side of the PDH multiplexer the tributary is destructured and a BER test performed.

By using a protected monitor point at the high rate side of the PDH multiplexer the mux/demux need not be taken out of service.

Default (Known State) Settings

It is advisable to set the HP 37717C to a known state before setting up a measurement. This clears all previous settings and provides a clearly defined instrument state. For a list of Default Settings and the procedure for accessing them see *Stored Settings in the Mainframe Operating Manua*.

Cross Multiplexer Testing Test Setup Procedure


In this setup a 2 Mb/s Framed tributary, containing a test pattern, is inserted at the tributary insert port of the PDH multiplexer. The 140 Mb/s structured PDH signal is obtained from a protected monitor point. The 2 Mb/s tributary is destructured by the HP 37717C test set and an Error measurement is performed on the 2 Mb/s tributary test pattern.

A SINGLE test period of 24 HOURS is used and the printer is enabled to record results and alarms.

The HP 37717C PDH/SDH test set GRAPHICS function is enabled. The graphical results can be viewed on the **GRAPH** display.


PDH / DSn Testing With The HP 37717C

Cross Multiplexer Testing



Cross Multiplexer Testing

1. Connect the HP 37717C to the network equipment and set up the **OTHER** **SETTINGS CONTROL** display as shown opposite.



Cross Multiplexer Testing

2. Set up the **TRANSMIT** display as shown opposite.

The PAYLOAD TYPE determines the Framing, which is selected from the softkey menu.

Selections of Framing and Code must match those of the network equipment.

TRANSMITTER OUTPUT [PDH]	
MAIN	STRUCT'D
SETTINGS	FUNCTION
SIGNAL	[2 Mb/s]
CLOCK SYNC	[INTERNAL]
TERMINATION	[75% UNBAL]
LINE CODE	[HDDBS]
FREQUENCY OFFSET	[OFF]
PAYLOAD TYPE	[PCHS1CRC]
PATTERN	[2 ¹¹ -1 PRBS]
PRBS POLARITY	[NORM] CCITT

STATUS: **PCHS1CRC** **STRUCT'D** **MORE** **MULTIPLE WINDOW**

3. Set up the **RECEIVE** display **MAIN SETTINGS** as shown opposite.

The GAIN and EQUALIZER settings should be set to optimize the received signal.

RECEIVER INPUT [PDH]	
MAIN	STRUCT'D
SETTINGS	SETTINGS
SIGNAL	[140 Mb/s]
TERMINATION	[75% UNBAL]
LINE CODE	[CH1]
LEVEL	[MONITOR]
EQUALIZER	[OFF] GAIN [20 dB]
PAYLOAD TYPE	[STRUCTURED]

TO SET TEST SIGNAL, FIRST SELECT THE 'STRUCT'D SETTINGS' FOLDER ABOVE

STATUS: **MULTIPLE WINDOW**

4. Set up the **RECEIVE** display **STRUCTURED SETTINGS** as shown opposite.

The required 2 Mb/s test signal is selected under 34Mb: 8Mb: 2Mb

2M Payload determines the test signal framing and must match that of the network equipment.


RECEIVER INPUT [PDH]	
MAIN	STRUCT'D
SETTINGS	SETTINGS
TEST SIGNAL	[2 Mb/s]
2M PAYLOAD	[PCHS1CRC]
34Mb	[2]
8Mb	[4]
2Mb	[4]
PATTERN	[2 ¹¹ -1 PRBS]
PRBS POLARITY	[NORM] CCITT

STATUS: **1** **2** **3** **4** **MULTIPLE WINDOW**

Cross Multiplexer Testing

5. Select the logging device and set up the **OTHER** display, **LOGGING** function, as shown opposite.


WHEN [PERIOD EC>0] ensures results are not logged on the selected logging device when a print period is error free.



Continuity Check

Before running the test carry out a continuity test to verify the measurement path.


1. Set up the **RESULTS** display as shown opposite.
2. Press **RUN/STOP** to start a measurement.
3. Press error add **SINGLE** three times and check that the errors are recorded on the **RESULTS** display.
4. Press **RUN/STOP** to stop the measurement.



Start the Cross Multiplexer Test

1. Set up the **RESULTS** display as shown opposite.

G.821 Analysis results are displayed but any of the other results can be viewed without affecting the measurement.




Cross Multiplexer Testing

If you do not require stored graphics results select STORAGE [OFF] on the

RESULTS **TIMING CONTROL**

display.

2. Press **RUN/STOP** to start the measurement.



The following error results are available on the **RESULTS** display during the test period:

- 2 Mb/s - FAS, CRC, REBE and BIT
- 8, 34 and 140 Mb/s - FAS

The graphical measurement results and alarms are stored in non volatile memory for viewing later on the **GRAPH** display.

The test can be halted at any time by pressing **RUN/STOP**.

At the End of the Test (Cross Multiplexer Testing)

- The Date and Time the test started and the instrument set-up are logged on the logging device selected.
- Results are logged on the selected logging device at 1 hour intervals if the error count is greater than 0.
- Any alarms which occur during the test period will be logged on the selected logging device.
- At the end of the test period a complete set of cumulative results are logged on the selected logging device.
- A graphical record of the results during the test period can be viewed on the **GRAPH** display. If Remote Control option A3B or A3D is fitted the graph results can be logged to an external printer, at a later date. See *Graphics* and *External HP 550C DeskJet Printer in the Mainframe Operating Manua*.
- Results and Alarm summaries can be viewed on the **GRAPH** display.

Cross Multiplexer Testing

The total graphics store capacity is normally 20,000 events. If GRAPH STORAGE RESOLUTION [FULL] is selected on the **OTHER** **MISCELLANEOUS** display the capacity reduces to 10,000 events.

The resolution, determined by the selection made under STORAGE on the **RESULTS** **TIMING CONTROL** display, affects the ZOOM capability when viewing the bar graphs. If 1 SECOND is selected all resolutions are available under ZOOM. If 1 MIN is selected only 1 MIN/BAR, 15 MINS/BAR and 60 MINS/BAR are available. If 15 MINS is selected only 15 MINS/BAR and 60 MINS/BAR are available. If 1 HOUR is selected only 60 MINS/BAR is available.

Up to 10 sets of graphical results can be stored. If an attempt is made to store more than 10 sets of results, then a first in first out policy is operated and the oldest set of results will be lost. If graphics are enabled and a test is run which exceeds the remaining storage capacity, then some previously stored graphical results will be lost.

To prevent accidental overwriting of previously stored results the graphics capability should be disabled, when graphical results are not required, by selecting STORAGE [OFF] on the **RESULTS** **TIMING CONTROL** display.

FAS Monitoring

Options Required Structured PDH **UKJ (USA)** or **UKN (USE)**, or Unstructured PDH **UKK (USB)**

Alternatively for PDH / DSn with ATM payloads Option **UKZ**.

NOTE

Option UKK (USB) - Unstructured PDH allows FAS Monitoring to be carried out at 2, 8, 34 and 140 Mb/s.

Option UKZ - allows FAS Monitoring to be carried out at DS1 and DS3 (Incorrect F and M framing sequence) rates as well as at 2 and 34 Mb/s ETSI rates.

Application

Degradation in error performance can be detected by the occurrence of Frame Alignment Signal (FAS) errors in PDH /DSn systems.

Using the HP 37717C in a *receive only* mode, FAS errors can be measured and viewed on the **RESULTS** display. In addition, the results can be logged on the selected logging device for examination later.

Default (Known State) Settings

It can be advisable to set the HP 37717C to a known state prior to setting up to make a measurement. This clears all previous settings and provides a clearly defined instrument state. For a list of Default Settings and the procedure for accessing them see *Stored Settings*.

Test Setup Procedure (FAS Monitoring)

This setup procedure is based on Structured PDH 140 Mb/s line traffic interfaced at the line equipment protected Monitor point. If a protected Monitor Point is not available then an HP 15510A Protective Probe may be used at an unprotected Monitor point.


The instrument is used in a *receive only* mode to measure FAS Errors. A Timed Start test period is used which allows the measurement to be started at a time when the user would not normally be available.

All Error Ratio and Analysis results are logged on the selected logging device at 2 hour intervals and at the end of the test period. Occurrences of error seconds and

PDH / DSn Testing With The HP 37717C

FAS Monitoring

alarms are logged on the selected logging device in real time.




FAS Monitoring

1. Connect the HP 37717C to the line terminal equipment protected Monitor point and set up the **RECEIVE** display **MAIN SETTINGS** as shown opposite.

When Balanced FAS monitoring is desired at an unprotected Monitor point use an HP 15511A Protective Monitor Probe.

The GAIN and EQUALIZER settings should be set to optimize the received signal.



PDH / DSn Testing With The HP 37717C

FAS Monitoring

2. Set up the **RECEIVE** display **STRUCTURED SETTINGS** as shown opposite.

2M PAYLOAD Framing selection should match that of the network equipment.

RECEIVER INPUT	[PDH]
MAIN SETTINGS	STRUCTURED SETTINGS
TEST SIGNAL	[2 Mb/s]
2M PAYLOAD	[PCS0CRC]
	[34Mb] [8Mb] [2Mb] [4]
PATTERN	[LIVE TRAFFIC]
STATUS:	
MULTIPLE WINDOW	

3. Set up the **OTHER LOGGING** display as shown opposite.

FUNCTION	[LOGGING]
LOGGING SETUP	[CONTROL]
LOGGING PERIOD	[1 HOUR]
RESULTS LOGGED WHEN	[SELECTED]
CONTENT	PERIOD EC > 0
	[ER & ANAL]
LOG ERROR SECONDS	[PER & CUMUL]
LOG AT END OF TEST	[OFF]
LOG ON DEMAND	RESULTS
STATUS:	
ALWAYS	PERIOD EC > 0
MULTIPLE WINDOW	

Start the Test (FAS Monitoring)

Set up the **RESULTS** display as shown opposite.

The test period will begin at the START time selected on the **RESULTS** display.

RESULTS [PDH]	[CUMULATIVE]			
FAS	FAS	FAS	FAS	MORE
140 Mb/s	34 Mb/s	8 Mb/s	2 Mb/s	
FAS 140M EC				
FAS 140M ER				
ELAPSED TIME				
STATUS:				
MULTIPLE WINDOW				

The following error types can be monitored:

140 Mb/s - FAS (Short Term, Cumulative and G.821 Analysis) 4 Mb/s- FAS

PDH / DSn Testing With The HP 37717C

FAS Monitoring

(Short Term, Cumulative and G.821 Analysis)

8 Mb/s - FAS (Short Term, Cumulative and G.821 Analysis)

2 Mb/s - FAS, CRC and REBE (Short Term, Cumulative and G.821 Analysis)

- Any occurrence of Alarms or Error Seconds during the test period are logged on the selected logging device.
- Cumulative and Period versions of Error Results and Analysis Results are logged on the selected logging device at 1 hour intervals.
- The test can be halted at any time by pressing **RUN/STOP**.

At the End of the Test

Cumulative and Period versions of Error Results and Analysis Results are logged on the selected logging device.

Frequency Measurement

Options Required Structured PDH **UKJ (USA)** or **UKN (USE)**, or Unstructured PDH **UKK (USB)**

Alternatively for PDH / DS_n with ATM payloads Option **UKZ**.

Application

The clock frequency and the amount of offset from the ITU standard rate can be measured to give an indication of probability of errors. The measurement can be made in out of service or monitor mode and is generally of short duration.

Default (Known State) Settings

It can be advisable to set the HP 37717C to a known state prior to setting up to make a measurement. This clears all previous settings and provides a clearly defined instrument state. For a list of Default Settings and the procedure for accessing them see *Stored Settings*.

Test Setup Procedure (Frequency Measurement)

If measuring frequency at PDH rates one of the following options is required.

- UKJ (USA), UKN (USE), UKK (USB) or UKL - Modules with PDH capability.
- UKZ - Module with PDH / DS_n capability

If measuring frequency at SDH rates the following options must be fitted:

- US1 (US5) or A1T (A1U) - SDH Module (STM-1 electrical)
- UH1 or UH2 or URU (STM-1 or STM-4 optical)

If measuring on live traffic the measurement is interfaced at the line terminal equipment Monitor point.

The HP 37717C is used in a *receive only* mode to measure the PDH / DS_n frequency. The PDH / DS_n frequency is measured and compared with the internal ITU standard frequency selected

PDH / DS_n Testing With The HP 37717C

Frequency Measurement






Figure 1 Frequency Measurement

1. Select SIGNAL [8 Mb/s] on the **RECEIVE** display.

For frequency measurement PATTERN; TERMINATION and CODE are not relevant.



2. Select **RESULTS PDH FREQUENCY**.



PDH / DSn Testing With The HP 37717C


Frequency Measurement

Run the Test (Frequency Measurement)

Connect the PDH / DSn IN port to the line terminal equipment monitor point.

The measured frequency and amount of offset from the internal standard is displayed.

If the PDH / DSn frequency is different from the selected BIT RATE the error message **Unable to recover clock** appears on the display. A **FREQ** reading is displayed but this should be ignored.



At the End of the Test (Frequency Measurement)

Disconnect the HP 37717C from the line terminal equipment.

Frequency Offset Tolerance

Application

The capability of the network equipment to reliably recover the clock is tested by varying the clock rate of the generated data and checking for the occurrence of transmission errors.

The measurement can be made via a loopback or in a cross-multiplexer configuration, and is generally of short duration.

The ITU G.703 Recommendation for Clock Tolerance is:

- DS1 1.544 Mb/s \pm 32 ppm
- E1 2.048 Mb/s \pm 50 ppm
- E2 8.448 Mb/s \pm 30 ppm
- E3 34.368 Mb/s \pm 20 ppm
- DS3 44.736 Mb/s \pm 20 ppm
- E4 139.264 Mb/s \pm 15 ppm

In SDH systems if the master timing reference is lost a standby reference within 20 ppm can be used for a limited time:

- STM-1 155.520 Mb/s \pm 20 ppm
- STM-4 622.080 Mb/s \pm 20 ppm.

Default (Known State) Settings

It can be advisable to set the HP 37717C to a known state prior to setting up to make a measurement. This clears all previous settings and provides a clearly defined instrument state. For a list of Default Settings and the procedure for accessing them see *Stored Settings in the Mainframe Operating Manual*.

Test Setup Procedure (Frequency Offset Tolerance)

If checking frequency offset tolerance at PDH /DS_n rates one of the following options is required.

- UKJ (USA) UKN (USE), or UKK (USB) - Modules with PDH capability
- UKZ - Module with PDH / DS_n capability.

Frequency Offset Tolerance

If checking frequency offset tolerance at SDH rates one of the following options must be fitted:

- US1 (US5) or A1T (A1U) - SDH Module (STM-1 electrical)
- UH1 or UH2 or URU (STM-1 or STM-4 optical)

This setup procedure tests the clock recovery capability of the line terminal equipment at 34 Mb/s using a PRBS pattern connected to the 75Ω interface. The frequency of the generated data is offset and the data is looped back and monitored for errors.





Figure 2

Frequency Offset Tolerance Test

1. Set up the **OTHER SETTINGS CONTROL** display as shown below.


Any settings change made on the **TRANSMIT** or **RECEIVE** displays will automatically occur on the other.



PDH / DSn Testing With The HP 37717C Frequency Offset Tolerance


2. Set up the **RECEIVE** display as shown opposite.

Select the PATTERN required from the menu.



3. Set up the **RESULTS** display as shown opposite.

Any of the other results can be selected without affecting the measurement.



Continuity Check

Before running the test carry out a continuity test to verify the measurement path.

1. Connect a loopback at the desired point on the line terminal or cross-multiplexer equipment.
2. Press **RUN/STOP** to start a measurement.
3. Press error add **SINGLE** three times and check that the errors are recorded on the **RESULTS** display.
4. Press **RUN/STOP** to stop the measurement.

PDH / DS_n Testing With The HP 37717C

Frequency Offset Tolerance

Run the Test (Frequency Offset Tolerance)

1. Connect the HP 37717C to the 75 Ω interface of the multiplexer and set up the **TRANSMIT** display as shown opposite.

2. Press **RUN/STOP** to start the measurement.

TRANSMITTER OUTPUT	[PDH]
PDH	STRUCT'D TEST
	SETTINGS FUNCTION
SIGNAL	[34 Mb/s]
CLOCK SYNC	INTERNAL
FREQUENCY OFFSET	OFF
CODE	HDB3
PATTERN	[2 ¹⁵ -1]
TERMINATION	75 Ω UNBAL

STATUS:
OFF +20 ppm -20 ppm USER OFFSET MULTIPLE WINDOW

3. Select TX CLOCK OFFSET [+20ppm] and check that the Error Count and Error Ratio results are unchanged.

4. Select TX CLOCK OFFSET [-20ppm] and check that the Error Count and Error Ratio results are unchanged.

NOTE

The OFFSET values used above conform to ITU, G.703 Recommendation. If different values are required selection of [USER OFFSET] allows offsets of up to 100 ppm to be used.

At the End of the Test

1. Halt the test by pressing **RUN/STOP**, and disconnect the HP 37717C.
2. Remove the loopback from the line terminal or cross-multiplexer equipment.

Multiplexer Testing

Multiplexer Testing

Application

PDH multiplexers combine four lower rate signals into a higher rate signal for transmission or further multiplexing. It is important that each multiplexer port operates error free and no "crosstalk" occurs between ports.

Multiplexing of the tributaries can be verified by performing a BER test at each of the four ports. However a more rigorous test involves loading all four ports to simulate live traffic conditions. This verifies the individual ports and detects any crosstalk problems between the ports.

Default (Known State) Settings

It is advisable to set the HP 37717C to a known state before setting up a measurement. This clears all previous settings and provides a clearly defined instrument state. For a list of Default Settings and the procedure for accessing them see *Stored Settings*.

Multiplexer Test Setup Procedure

The following Options must be fitted to the HP 37717C to perform this test:

- UHC (US6) - Multiple Outputs
- UKJ (USA) or UKK (USB) - PDH Module

In this setup the PDH OUT signal and the three additional data outputs, from the Multiple Outputs option, load the 34 Mb/s input ports of the multiplexer. The HP 37717C (Structured PDH Option UKJ (USA)) destructures the 140 Mb/s signal and a BER test is performed on each of the 34 Mb/s signals in turn.

A SINGLE test period of 15 Minutes is used and the selected logging device is enabled to record results and alarms.

PDH / DSn Testing With The HP 37717C

Multiplexer Testing




Figure 3 Structured PDH Multiplexer Test

NOTE

This test can be performed using the Unstructured PDH Option UKK (USB) but the equipment configuration is slightly different as shown below.





Figure 4 Unstructured PDH Multiplexer Test

PDH / DSn Testing With The HP 37717C


Multiplexer Testing

1. Connect the HP 37717C to the network equipment and set up the **OTHER** **SETTINGS CONTROL** display as shown opposite.




2. Set up the **TRANSMIT** **MAIN SETTINGS** display as shown opposite.

PAYLOAD TYPE, PATTERN and PRBS POLARITY selections should meet the requirements of the network equipment.



3. Set up the **RECEIVE** **MAIN SETTINGS** display as shown below.


PAYLOAD TYPE [STRUCTURED] ensures the 140 Mb/s signal is destructured into the four 34 Mb/s test signals




Multiplexer Testing

4. Set up the **RECEIVE** display
STRUCTURED SETTINGS as shown
 opposite.

The required 34 Mb/s test signal is
 selected under 34Mb.



5. Select the logging output required with
 the **OTHER** display, **LOGGING**
 function, LOGGING SETUP **DEVICE**
 then select LOGGING SETUP
CONTROL and set up the display as
 shown opposite.




Start the Multiplexer Test

1. Set up the **RESULTS** display as shown
 opposite.

2. Press **RUN/STOP** to start the
 measurement.

3. Repeat the test for the other three 34
 Mb/s signals, selectable on the **RECEIVE**
STRUCTURED SETTINGS display.

G.821 ANALYSIS is selected but any of
 the other results can be selected from the
 softkey menu without affecting the
 measurement.



- The measurement results and alarms are available on the **RESULTS** display

Multiplexer Testing

during the test period.

- The test can be halted at any time by pressing **RUN/STOP**.

At the End of the Multiplexer Test

- The Date and Time the test started and the instrument setup are logged on the selected logging device.
- All results are logged on the selected logging device at the end of the test.
- Any alarms which occur during the test period will be logged on the selected logging device.

Round Trip Delay

Round Trip Delay

Application

In certain applications the time taken for a signal to pass through the network can be very important for example Voice Traffic where excessive delay can make speech difficult to understand. The Round Trip delay feature of the HP 37717C allows measurement of the delay at any interface or test signal rate.

Default (Known State) Settings


It can be advisable to set the HP 37717C to a known state prior to setting up to make a measurement. This clears all previous settings and provides a clearly defined instrument state. For a list of Default Settings and the procedure for accessing them see *Stored Settings in the Mainframe Operating Manual*.

Test Setup Procedure (Round Trip Delay)

The following Option must be fitted to the HP 37717C to perform this test:

- UKJ (USA) - Structured PDH Module

This setup is interfaced at 140 Mb/s with a test signal of 64 kb/s. A test pattern is transmitted in the 64 kb/s slot and a timer is set running. A loopback is applied to the network equipment to return the test signal. The received pattern stops the timer and the Round Trip Delay is calculated.




Round Trip Delay

PDH / DSn Testing With The HP 37717C

Round Trip Delay

1. Connect the HP 37717C to the network equipment as shown and set up the **OTHER SETTINGS CONTROL** display as shown opposite.


Any settings change made on the **TRANSMIT** or **RECEIVE** displays will automatically occur on the other.



2. Set up the **TRANSMIT MAIN SETTINGS** display as shown opposite.

The SIGNAL rate and LINE CODE settings must match those of the network equipment.


Ensure that the **TRANSMIT TEST FUNCTION** display is set for bit errors.



3. Set up the **TRANSMIT STRUCTURED SETTINGS** display as shown opposite.

The 2M PAYLOAD selection determines the Framing which should match that of the network equipment.

The test 64 kb/s slot is selected under 34Mb; 8Mb; 2Mb; 64kb.




Continuity Check

Before running the test carry out a continuity test to verify the measurement path.

PDH / DS_n Testing With The HP 37717C

Round Trip Delay

1. Connect a loopback at the desired point on the line terminal equipment and set up the **RESULTS** display as shown opposite.
2. Press **RUN/STOP** to start a measurement.
3. Press error add **SINGLE** three times and check that the errors are recorded on the **RESULTS** display.
4. Press **RUN/STOP** to stop the measurement.




Start the Test (Round Trip Delay)

1. Set up the **RESULTS** display as shown opposite.

Select ACTION **ON** to start the test.

The Round Trip Delay result is displayed in milliseconds.



The delay measurement range is up to 2 seconds. The Resolution varies according to the received rate:

- 2 Mb/s - 1 μ s
- 8, 34, 140 Mb/s - 10 μ s
- STM-1 - 0.5 ms

M2100, M2110, M2120 Analysis

Application


Previously ITU-T G.821 was the only international recommendation available to measure the quality of a communications link. ITU-T G.821 was originally an “Out of Service” measurement and analysis for commissioning a link and troubleshooting during severe disruption. The commissioning test was a one month “Out of Service” test based on errored and severely errored seconds. A one month test with the subsequent loss of revenue is clearly unacceptable.

Due to demand ITU-T G.821 also evolved into proprietary methods for “In Service” testing based on FAS and code errors. Demand for high quality leased lines meant an “In Service” performance standard, closer to real conditions and allowing comparisons between providers, was required.

The ITU-T M.2100 series was specifically defined to provide a clear indication of link quality, for service providers using long term performance analysis. “Bringing into Service” and “repair criteria” analysis were also included.

M.2100 analysis is based on frame errors and provides Error Seconds (anomaly), Severely Errored Seconds (defect) and Unavailability results for receive and transmit directions. Transmit results are only available for 2 Mb/s signals with CRC framing. “Out of Service” testing is only available for the receive direction. M.2110 is an “Out of Service” measurement for “bringing into service” testing of paths. A 15 minute BER test (G.821) is performed and if this is error free a 24 hour M.2110 test is performed. If the 24 hour M.2110 test displays PASS (S1 limit not reached) the path can be returned to service. If FAIL is displayed (S2 limit reached or exceeded) the 15 minute BER test should be repeated, If m-d;- (UNCERTAIN) is displayed (result between the S1 and S2 limits) run the 7 day BIS test.

The PASS FAIL and UNCERTAIN parameters are determined by the S1 and S2 limits which are user selectable.



M2100, M2110, M2120 Analysis

Default (Known State) Settings

It can be advisable to set the HP 37717C to a known state prior to setting up to make a measurement. This clears all previous settings and provides a clearly defined instrument state. For a list of Default Settings and the procedure for accessing them see *Stored Settings in the Mainframe Operating Manual*.

Test Setup Procedure M2110 Analysis


The following Option must be fitted to the HP 37717C to perform this test:

- UKJ - Structured PDH Module

This setup procedure is interfaced at 140 Mb/s, with a test signal of 2 Mb/s with PCM30CRC framing.


1. Set up the **OTHER SETTINGS CONTROL** display as shown opposite.

Any settings change made on the **TRANSMIT** or **RECEIVE** displays will automatically occur on the other.



2. Connect the HP 37717C to the line equipment and set up the **TRANSMIT MAIN SETTINGS** display as shown opposite.

The settings of SIGNAL rate and LINE CODE must match those of the network equipment.




PDH / DSn Testing With The HP 37717C


M2100, M2110, M2120 Analysis

3. Set up the **TRANSMIT** display
STRUCTURED SETTINGS as shown
 opposite.

2M PAYLOAD selects the Framing which
 must match that of the network equipment.




4. Set up the **RESULTS** display as shown
 opposite.



5. Press **RUN/STOP** to start the
 measurement.

At the end of the test period check that the
 G.821 results are error free.




PDH / DSn Testing With The HP 37717C

M2100, M2110, M2120 Analysis

6. Set up the **RESULTS** display as shown opposite


Select the Path Allocation value required in the range 0.5% to 40%.

The Path Allocation value determines the S1 and S2 limits and these will change on the display as the Path Allocation value is changed.



7. Set up the **RESULTS** display as shown opposite.

Press **RUN/STOP** to start the measurement.




8. View the M.2110 results.

BIS Results of PASS, FAIL and m-d;- (uncertain) are possible.

If PASS is displayed (S1 limit not reached) the path may be returned to service immediately.

If FAIL is displayed (S2 limit reached or exceeded) repeat the BER (G.821) test.

If m-d;- is displayed (result between the S1 and S2 limits) run the 7 day BIS test.



Monitoring DS3 with ATM Payloads

Monitoring DS3 with ATM Payloads

Option Required DS1, DS3, E1 and E3 Transmit and Receive Interfaces for ATM Payloads. **Option UKZ**

Connect the HP 37717C RECEIVE DS3 IN to the network monitor point, select the **RECEIVE** display and DS3 rate.

RECEIVER INPUT		ATM
PHYSICAL LAYER	ATM LAYER	
SIGNAL	DS3	
TERMINATION LINE CODE LEVEL	752 UNBAL B32S	[TERMINATE]
CONVERGENCE SUB-LAYER	[DIRECT]	
CELL SCRAMBLING	[ON]	

STATUS: DS3 34 Mb/s 2 Mb/s DS1 MULTIPLE WINDOW

Select the convergence layer, Direct or PLCP.

RECEIVER INPUT		ATM
PHYSICAL LAYER	ATM LAYER	
SIGNAL	[DS3]	
TERMINATION LINE CODE LEVEL	752 UNBAL B32S	[TERMINATE]
CONVERGENCE SUB-LAYER	[PLCP]	
CELL SCRAMBLING	[ON]	

STATUS: DIRECT PLCP MULTIPLE WINDOW


Select **RESULTS PDH** for the physical and convergence layer results.

RESULTS [PDH]	[CUMULATIVE]
FEBE	PLCP BIP
PLCP FEBE	PLCP MISMATCHES
MORE	
PLCP TRAILER-MISMATCHES	
ELAPSED TIME	

STATUS: MULTIPLE WINDOW

PDH / DS_n Testing With The HP 37717C Monitoring DS₃ with ATM Payloads

Select **RESULTS** **PDH** ALARM
SECONDS to display the physical and
convergence layer alarms.



Information on cell level testing is given in “The ATM Operating Manual”.

Index

A

Alarm generation selection, 17
Alarm Monitoring, 26
Alarm scan display, 28
Alarm seconds display, 28
Analysis of N X 64 kb/s, 29

B

B/G Pattern, 13
BERT Testing, 33
Binary Interfaces, Option UH3 (US7)
 Display Selections, 22
 Module Information, 7

C

Code, 10, 11, 15, 19
Convergence sub-layer selection, 16
Coupled Settings, 64
Cross Multiplexer Testing, 38

D

Default Settings, 64
Drop 2Mb/s, 12
DS1, DS3, E1 and E3 Interfaces for ATM
 Payloads, Option UKZ
 Display Selections, 15
 Module Information, 5

E

E1, E3 and E4 Interfaces for ATM Pay-
 loads, Option UKN
 Display Selections, 19
E1, E3 and E4 Interfaces for ATM Pay-
 loads, Option UKN
 Module Information, 6
E1, E3 and E4 Tx and Rx Interfaces for
 ATM Payloads, Option UKN
 Module Information, 6
End to End BERT Testing, 33
Error add selection, 17
Error Add Test Function, 14

F

FAS Monitoring, 44
Framing 2Mb/s, 10
Frequency Measurement, 48
Frequency Offset, 9, 11, 15, 19
Frequency Offset Tolerance, 51

G

Graph
 Storage resolution selection, 37

H

Handset, 13

I

In Service., 10
Insert 2Mb/s, 12
Introduction to PDH, 2

L

Live Traffic., 10
Loopback BERT Testing, 34

M

M2100, M2110, M2120 Analysis, 63
Monitor Equalizer, 14
Monitor Gain, 14
Multiple PDH Outputs, Option UHC
 Module Information, 8
Multiplexer Testing, 55

N

N X 64kb/s, 13
Numbered, 13

O

Out Of Service, 10

P

Pattern, 10, 11, 13
Payload Type, 11
Payload Type 2Mb/s Framing, 12
Payload Type Framed, 11
Payload Type Structured, 12, 16
Payload Type Unframed, 11
PRBS Polarity, 11, 13

R

Receive and transmit settings linked, 30
Round Trip Delay, 60

S

Scrambling selection, 16
Settings Coupled, 64
Storage resolution selection, 37

Structured PDH, 11

Structured PDH , Options UKJ or UKN
 Display Selections, 11
 Module Information, 11
Structured PDH Multiplexer Test, 56

T

Termination, 10, 11, 15, 19
Test Function, 14, 17
Test Mode, 10
Test Signal, 12
Timeslot selection, 30
Trail trace selection, 16
Transmit and receive settings linked, 30

U

Unstructured PDH Multiplexer Test, 56
Unstructured PDH, Option UKK
 Display Selections, 9
 Module Information, 3

Index

Hewlett-Packard Sales and Service Offices

United States:

Hewlett-Packard Company
2101 Gaither Road
Rockville
MD 20850
(301) 258-2000

Hewlett-Packard Company
5201 Tollview Drive
Rolling Meadows
IL 60008
(708) 255-9800

Hewlett-Packard Company
1421 S. Manhattan Avenue
Fullerton
CA 92631
(714) 999-6700

Hewlett-Packard Company
2000 South Park Place
Atlanta
GA 30339
(404) 955-1500

Canada:

Hewlett-Packard Canada Ltd.
5150 Spectrum Way
Mississauga
Ontario
L4W 5G1
(416) 206-4725

Europe:

Hewlett-Packard
European Marketing Centre
PO Box 999
1180 AZ Amstelveen
The Netherlands

Japan:

Yokogawa-Hewlett-Packard Ltd.
Measurement Assistance Center
9-1, Takakura-Cho
Hachioji-Shi
Tokyo 192
Japan
(81) 426 48 0722

Latin America:

Hewlett-Packard
Latin America Region Headquarters
5200 Blue Lagoon Drive
9th Floor
Miami
Florida 33126
USA
(305) 267 4245/4220

Australia/New Zealand:

Hewlett-Packard Australia Ltd.
31-41 Joseph Street
Blackburn
Victoria 3130
Australia
Melbourne Caller 272 2555
(008) 13 1347

Far East:

Hewlett-Packard Pacific Ltd.
22-30/F Peregrine Tower
Lippo Centre
89 Queensway
Central
Hong Kong
(852) 848 7070

Learning Products Map

All of the learning products which apply to the HP 37717C Communications Performance Analyzer with ATM Services and LAN testing capability are shown below:

The HP 37717C Mainframe Operating Manual- 37717-90282

General operating information irrespective of option.

The HP 37717C PDH / DS_n Operating Manual - 37717-90283

Information about the PDH / DS_n modules, how to select the features available and measurement examples.

The HP 37717C SDH / SONET Operating Manual - 37717-90284

Information about the SDH / SONET modules, how to select the features available and measurement examples. This book also contains a table of ANSI / ETSI equivalent terms.

The HP 37717C Jitter Operating Manual - 37717-90285

Information about the Jitter modules, how to select the features available and measurement examples.

The HP 37717C ATM + LAN Operating Manual - 37717-90286

Information about the ATM and LAN modules, how to select the features available and measurement examples. This book also contains tutorial information on some ATM and LAN measurements, Information on pre-stored sequences and a glossary of ATM and LAN terms.

Calibration Manual - 37717-90287:

Provides specifications and methods of testing that the instrument meets its specifications.

Remote Control Manual - 37717-90288:

Provides remote control information for instruments fitted with the RS232 and HP-IB remote control option modules.

About This Edition

This is the 1st edition of
the 37717-90283 manual.
It documents the product
as of September 1997.
Edition dates are as
follows:

1st Edition, September
1997

© Copyright Hewlett-
Packard Ltd. 1997.
All rights reserved.
Reproduction, adaption,
or translation without prior
written permission is
prohibited, except as
allowed under the
copyright laws.

In This Book

This book provides information on HP 37717C modules with PDH / DS_n capability when used with instruments which have ATM Services and LAN testing capability. It also provides applications associated with these modules.

The individual applications contain techniques which may be of value for purposes other than those shown.

