8922S-05

S	Е	R	V	Ι	С	Е	Ν	0	Т	Ε
							SUPERSEDE	S: NON	E	
Agi	lent 892	22 GS	M Test	: Sets						
Seria	al Numbe	ers: See	Below							
				ied to	correct	interm	ittent			
GSN	/I signal	powe	er loss.							
Dupl	licate Ser	vice No	otes:							
8922	M-10	Serial	Number	s: 0000/	400000 / -	4006U99	9999			
8922		Serial Numbers: 0000A00000 / 4006U99999 Serial Numbers: 0000A00000 / 9999Z99999								
8922		Serial Numbers: 0000A00000 / 9999Z99999								
8922	P-07	Serial Numbers: 0000A00000 / 4006U99999								
8922	R-04	Serial Numbers: 0000A00000 / 4006U99999								
8922	S-05	Serial Numbers: 0000A00000 / 4006U99999								
8922	X-07	Serial	Number	s: 00004	400000 / -	4006U99	9999			
To B	e Perfori	ned By	: Agilent-	Qualifi	ed Person	nel				
Parts	s Require	ed:								
Agile	ent P/N	De	scription	l		Quar	ntity			
0892	2-69897	Refu	irbished A	A23 Inp	ut Module	e 1				
									Continue	ed
							DATE: April 2	000		

ADMINISTRATIVE INFORMATION

SERVICE NOTE CLASSIFICATION: MODIFICATION RECOMMENDED								
ACTION CATEGORY:	 IMMEDIATELY ON SPECIFIED FAILURE AGREEABLE TIME 	STANDARDS: LABOR 4.0 Hours						
LOCATION CATEGORY:	 ☐ CUSTOMER INSTALLABLE ■ ON-SITE ☐ SERVICE CENTER 	SERVICE ■ RETURN USED ■ RETURN INVENTORY: □ SCRAP PARTS: □ SCRAP □ SEE TEXT □ SEE TEXT						
AVAILABILITY:	PRODUCT'S SUPPORT LIFE	AGILENT RESPONSIBLE UNTIL: April 2002						
AUTHOR: FH	ENTITY: E600-6423	ADDITIONAL INFORMATION:						

© 2000 AGILENT TECHNOLOGIES PRINTED IN U.S.A.



Situation:

Intermittent loss of signal power (typically 10 to 30 dB) in the GSM band reported in the field. The problem has been traced to two failure mechanisms on the A23 Input Module:-

- 1. Failure of a relay in the output path.
- 2. Solder process problem producing poor electrical connection between the relay contacts and the circuit board.

Solution / Action:

The fault can be verified by Agilent service personnel running the test software "Pwr_chk". To obtain the test software, access the following web URL:

```
http://www.sqf.hp.com/QMD_Mktg/prodsup/8922/index.htm
```

Click on "verification" then "Software Tools". Go to PWR_CHK:Version A.02.02 and download the program version you want, ie, "Pwr chk.bas", "Pwr chk.asc", or "Pwr chk.txt".

Perform the following procedure.

Equipment Required:

Agilent 8902A Measuring Receiver Agilent 11722A Power sensor Agilent 8657A/B Signal Generator PC or Controller with GPIB card HP Basic GPIB cables BNC co-axial cables Test software - Pwr_chk (as above)

Procedure

- 1. Connect the PC (or controller), 8922, 8902A, and 8657A/B GPIB interfaces together using GPIB cables.
- 2. Connect a high stability 10 MHz reference to the 8922 REF IN port. Connect the 10 MHz OUT port on the 8922 to the 10 MHz REFERENCE IN port on the 8657A/B. Connect the 10 MHz REFERENCE OUT port on the 8657A/B to the 10 MHz REFERENCE IN port on the 8902A Measuring Receiver.
- 3. Open an HP Basic window on the PC (or controller).
- 4. Change the directory path to the one that contains the test software (Pwr_chk) using the MSI "yyyy" command, where yyyy is the directory path.
- 5. Load the test software using the command GET "pwr_chk.asc", GET "pwr_chk.txt", or LOAD "pwr_chk.bas".
- 6. Type RUN or press F3 to start the program.
- 7. Follow the instructions given on the screen and all testing will be performed automatically.

The program stops when an out-of-limits error is encountered - follow the instructions on the screen and check that the power reading on the 8922 AUX RF OUT port is -85 dBm, indicating that the relay has failed.

Note:

Due to the intermittent nature of the fault, it may be necessary to leave the program running for several hours (typically 2-10 hrs) before a relay failure is detected.

Halt the Pwr_chk program by pressing Control/Break.

The results will be stored in a file named RESxxxx.txt where xxxx is the last four digits of the serial number entered at the beginning of the Pwr_chk program.

Note:

The modification recommended in this service note will only be implimented free of charge if a valid printed set of results or customer data showing the failure is returned with the faulty A23 Input Module.

If the A23 Input Module proves to be faulty, replace it with refurbished part 08922-69897 using the exchange program.