
V743/64 VXI Embedded Controller HP E1497A

Technical Specifications

- **Direct VXI Access with PA-RISC technology**
- **Compatibility with Series 700 workstations/controllers**
- **C-SCPI and HP VEE support**
- **Includes SICL and VISA with special enhancements**
- **VXI plug&play-compatible with HP-UX**



Description

The HP V743/64 and V743/100 embedded controllers are **C-size, 1-slot, VXI modules**. These high-performance message-based controllers use HP's PA-RISC technology to deliver extraordinary performance and direct VXI access at a very competitive price.

Developed specifically as an embedded HP-UX (UNIX) controller for VXI, the V743 controller provides the high I/O performance of direct VXI backplane support, the space savings of an embedded controller, and the high power and speed of HP PA-RISC-All in an HP-UX environment! The V743 supports all VXI addressing modes (A16, A24, and A32), programmable interrupt handler, single channel DMA for VXI extended memory devices, and a 1-MB dual-ported memory buffer for high-speed data acquisition. Note: You may use only one embedded controller in a system.

The V743/100, with its high speed- 100 MHz 7100LC PA-RISC processor, is ideal for development of run-time applications. The V743/64, with its 64 MHz, 7100LC PA-RISC processor, provides the performance you need for run-time applications at a lower cost than the V743/100.

Both models are completely compatible with other HP 9000 Series 700 workstations and controllers. However, both require HP-UX releases 9.05 and later. With HP-UX, you can set up industry-standard networking, windowing systems, and languages. Databases and a full range of VXI-related software are available for automated test applications.

Refer to the HP Website for instrument driver availability and downloading instructions.

Software Support

- SICL and VISA are included when you order the V743.
- C-SCPI is supported on HP-UX with C language.
- HP VEE is supported, including special enhancements for direct VXIbus support.
- HP-UX *VXIplug&play* Framework.

Operating System

HP-UX 9.05 and later

Note: You may use only one embedded controller in a system.

Specifications

Processor:	PA 7100LC
Clock speed:	64 or 100 MHz

Performance

MIPS:	77.7/121.6
MFLOPS:	24.3/37.8
SPECmark 89:	—
SPEC int92:	66.6/100.1
SPEC fp92:	96.5/137.0
X11 Xmark 93:	6.55/8.63
SPECrate int92:	1497.8/1237.3
SPECrate fp92:	281.4/3225.9
Main memory:	16-64 MB (64 MHz), 32-128 MB (100 MHz)
Built-in interfaces:	HP-IB, 2 RS-232, 1 SCSI-II, LAN, AUI
Additional interfaces:	SE Keyboard and Mouse Speaker Out Trigger I/O, Clock I/O
Optional interfaces:	none
Available slots:	none
Supported expanders:	none
Display resolution:	Color 1024x768 1280x1024
Internal mass storage:	Optional External: 600 MB CD-ROM 2 GB DDS Tape 4-8 GB DDS w/ comp
O.S. (earliest supported):	HP-UX 9.05

VXI Characteristics

VXI device type:	Message-based Controller
Size:	C
Slots:	1
Connectors:	P1/2
Shared memory:	n/a
VXI busses:	TTL Trigger Bus ECL Trigger Bus
C-size compatibility:	Yes

Instrument Drivers

See the HP Website (http://www.hp.com/go/inst_drivers) for driver availability and downloading.

Command module firmware:	n/a
Command module firmware rev:	n/a
I-SCPI Win 3.1:	n/a
I-SCPI Series 700:	n/a
C-SCPI LynxOS:	n/a
C-SCPI Series 700:	n/a
HP VEE Drivers:	n/a
VXIplug&play Win Framework:	n/a
VXIplug&play Win95/NT Framework:	n/a
VXIplug&play HP-UX Framework:	Yes

Module Current

	I _{PM}	I _{DM}
+5 V:	10	0.1
+12 V:	0.25	0
-12 V:	0.08	0.6
+24 V:	0.04	0
-24 V:	0	0
-5.2 V:	0.56	0
-2 V:	0.48	0

Cooling/Slot

Watts/slot:	59.00
ΔP mm H ₂ O:	0.30
Air Flow liter/s:	4.70

Ordering Information

Description	Product No.
V743/64 VXI embedded controller module	HP E1497A
Delete converter cable set	HP E1497A 001
Delete SICL media and manuals	HP E1497A 002
32 MB total RAM	HP E1497A ANC
64 MB total RAM	HP E1497A ANE
3 yr. retn. to HP to 1 yr. OnSite warr.	HP E1497A W01

Data Subject to Change
Copyright © June 1997
Hewlett Packard Co.
HP Publication No.: 5965-5509E