

HZ200 Probe 10:1



Attenuation ratio:	10:1
Bandwidth:	250 MHz
Rise time:	< 1.4 ns
Input impedance:	10MΩ 12 pF
Max. Voltage:	400V (DC + peak AC)
LF compensation:	1
RF compensation:	2
Cable length:	1.2 m
Probe factor identification	
Measuring category:	CAT I

HZ51 Probe 10:1



Attenuation ratio:	10:1
Bandwidth:	150 MHz
Rise time:	< 2.4 ns
Input impedance:	10MΩ 12 pF
Max. Voltage:	600V (DC + peak AC)
LF compensation:	1
RF compensation:	1
Cable length:	1.2 m
Measuring category:	CAT I

HZ52 Probe 10:1



Attenuation ratio:	10:1
Bandwidth:	250 MHz
Rise time:	< 1.4 ns
Input impedance:	10MΩ 10 pF
Max. Voltage:	600V (DC + peak AC)
LF compensation:	1
RF compensation:	2
Cable length:	1.2 m
Measuring category:	CAT I

HZ53 Probe 100:1



Attenuation ratio:	100:1
Bandwidth:	100 MHz
Rise time:	< 3.5 ns
Input impedance:	100MΩ 4.5 pF
Max. Voltage:	1200V (DC + peak AC)
LF compensation:	1
Cable length:	1.2 m
Measuring category:	CAT I

HZ154 Probe 1:1 / 10:1



Attenuation ratio:	1:1
Switchable:	10:1
Bandwidth:	10/150 MHz
Rise time :	< 35/3.5 ns
Input impedance:	1/10 MΩ 82/12 pF
Max. voltage:	(10:1) 600V (DC + peak AC)
LF compensation:	1 at 10:1
RF compensation:	2 at 10:1
Cable length:	1.2 m
Measuring category:	CAT I

HZ100 Differential Probe 20:1/200:1 Technical specifications at 23 °C ± 2 °C



Differential input voltage (DC + peak AC) max.:	±700 V
Max. input voltage per input:	±700 V
Attenuation ratio:	20:1
Switchable:	200:1
Bandwidth:	30/40 MHz
Rise time:	12/9 ns
Input impedance:	8 MΩ 1.2 pF
Output impedance:	50 Ω
Max. output voltage:	±3.5 V at 1 MΩ
Max. noise:	2 mV
Accuracy after 1min:	±3 % (18 °C – 30 °C)
Common mode rejection DC/AC 1MHz:	70 dB / > 50 dB
Inputs (CAT III):	2 safety connectors
Input leads:	2 test leads 50 cm with spring hooks
Battery operation:	9 V battery 6LR61
Input for an external power supply:	9...16 V DC/30 mA

HZ109 Differential Probe 1:1 / 10:1 Technical specifications at 23 °C ± 2 °C



Differential input voltage (DC + peak AC) max.:	±35 V
Max. input voltage per input:	±100 V
Attenuation ratio:	1:1
Switchable:	10:1
Bandwidth:	20/30 MHz
Rise time:	17/12 ns
Input impedance:	20 MΩ 5 pF
Output impedance:	50 Ω
Max. output voltage:	±3.5 V at 1 MΩ
Max. background noise:	2 mV
Accuracy after 1min:	±3 % (18 °C – 30 °C)
Common mode rejection DC/AC 1MHz:	70 dB / > 50 dB
Inputs (CAT III):	2 safety connectors
Input leads:	2 test leads 50 cm with spring hooks
Battery operation:	9 V battery 6LR61
Input for an external power supply:	9...16 V DC/30 mA

HZ115 Differential Probe 100:1/1000:1 Technical specifications at 23 °C ± 2 °C



Differential input voltage (DC + peak AC) max.:	± 1500V
Max. input voltage per input:	± 1500V
Attenuation ratio:	100:1
Switchable:	1000:1
Bandwidth:	20/30 MHz
Rise time:	17/12 ns
Input impedance:	60 MΩ 1.5 pF
Output impedance:	50 Ω
Max. output voltage:	± 1.5 V an 1 MΩ
Max. background noise:	2 mV
Accuracy after 1 min:	± 3 % (18 °C - 30 °C)
Common mode rejection DC/AC 1 MHz:	70 dB / > 50 dB
Inputs (CAT III):	2 safety connectors
Input leads:	2 test leads 75 cm with safety test clips
Battery operation:	9 V battery 6LR61
Input for an external power supply:	9...16 V DC/30 mA

www.hameg.com