



TOTAL SOLUTIONS™

TSS-450

TSS-750

TSS-1100

 **Infinity**®

TECHNOLOGY • PERFORMANCE • DESIGN

The system is the solution.





The TSS-750.

TECHNOLOGY, PERFORMANCE, DESIGN.

Groundbreaking new technologies, revolutionary new materials and advanced manufacturing techniques – for 35 years, Infinity has set new standards for performance, simplicity and style. Now, Infinity's unchallenged leadership in loudspeaker design extends from our critically acclaimed Prelude™ MTS Series to the stylish new Total Solutions™ loudspeaker systems inspired by the award-winning Prelude MTS.



Infinity's flagship
Prelude MTS
loudspeaker system.

TSS — COMPLETE 6-PIECE MOVIE AND MUSIC LOUDSPEAKER SYSTEMS WITH POWERED SUBWOOFERS

Realistic surround sound, deep, powerful bass and clean dialogue reproduction will entice you into enjoying your favorite movies and music again and again — or even contending with your adversaries in your favorite video game! TSS systems are designed for almost any size space, so filling your room with great sound is easy.

The most demanding digital media are handled with ease through the voice-matched center channel, wall-mountable satellite speakers and powerful, amplified subwoofer. With attention to detail, a sleek, subtle design and the choice of a charcoal or platinum finish, TSS systems will blend seamlessly with today's flat-panel televisions and your décor.

NEW METAL MATRIX DIAPHRAGM™ (MMD™) DRIVER TECHNOLOGY

Derived from our patented CMMD™ technology, the TSS-750 and TSS-1100 employ Infinity's new Metal Matrix Diaphragms.™ MMD™ continues the Infinity tradition of using advanced materials to improve cone performance, with significantly less distortion, outperforming commonly used cones made of paper, polypropylene and Kevlar.®



ROOM-FRIENDLY

All Total Solutions speaker systems utilize an acoustical waveguide to deliver a wider, more even high-frequency response. This ensures that no matter where in the room you sit, you won't miss any of the action.



And remember, unlike many systems, the TSS-450, TSS-750 and TSS-1100 are engineered to sound as exceptional with music as they do with your favorite movies.



TSS-450



TSS-450

A Most Dramatic Improvement in Television Sound

- Four 2-way satellites with 2-1/2" woofer and 1/2" tweeter
- 2-Way center channel with dual 2-1/2" woofers and 1/2" tweeter
- 8", 100-Watt powered sub
- High-impact polystyrene enclosures
- Satellites and center are magnetically shielded
- Includes four adjustable satellite wall brackets
- Adjustable foot on center channel
- Available in platinum or charcoal



TSS-750



TSS-750

Exceptional Home Theater and Music Reproduction

- Extruded- and brushed-aluminum satellites and center channel enclosures
- MMD™ drivers
- Four 2-way satellites with 3-1/2" woofer and 3/4" tweeter
- 2-Way center channel with dual 3-1/2" woofers and 3/4" tweeter
- 10", 150-Watt powered sub
- Satellites and center are magnetically shielded
- Includes four adjustable satellite wall brackets
- Includes center channel base
- Gold-plated binding posts
- Available in platinum or charcoal



All TSS models are also available in charcoal.

TSS-1100



TSS-1100

**Capable of Filling Even
the Largest Spaces With
Great Sound**

- Extruded- and brushed-aluminum satellites and center channel enclosures
- MMD™ drivers
- Four 2-way satellites and a 2-way center channel with dual 3-1/2" woofers and 3/4" tweeter
- 12," 250-Watt powered sub
- Satellites and center are magnetically shielded
- Includes four adjustable satellite wall brackets
- Includes center channel base
- Gold-plated binding posts
- Available in platinum or charcoal

 **Infinity**®

TECHNOLOGY • PERFORMANCE • DESIGN

TOTAL SOLUTIONS™ SPECIFICATIONS



Satellite wall-mounting brackets included.

TSS-450

	Satellites	Center Channel		Powered Subwoofer
Frequency Range (± 3 dB)	150Hz – 20,000Hz	150Hz – 20,000Hz	Frequency Range (± 3 dB)	39Hz – 150Hz
Recommended Amplifier Power Range	10 – 100 watts	10 – 100 watts	Amplifier Output	100 watts RMS
Sensitivity (2.83V @ 1 meter)	86dB	87dB	Low-Frequency Driver	8"
Nominal Impedance	8 ohms	8 ohms	Crossover Frequency	120Hz, 24dB/octave (LFE/Normal switch in Normal position)
Crossover Frequency	7000Hz	7000Hz	Dimensions (H x W x D)	16-1/4" x 10-1/4" x 15-1/2" (413mm x 262mm x 394mm)
Midrange Driver(s)	2-1/2", magnetically shielded	Dual 2-1/2", magnetically shielded	Weight	28.3 lb (12.9kg)
High-Frequency Driver	1/2", magnetically shielded	1/2", magnetically shielded		
Dimensions (H x W x D)	5" x 3-1/2" x 3-1/2" (127mm x 88mm x 88mm)	3-1/2" x 8" x 3-1/2" (88mm x 203mm x 88mm)		
Weight	1.2 lb (0.5kg)	1.9 lb (0.9kg)		



Satellite wall-mounting brackets included.

TSS-750

	Satellites	Center Channel		Powered Subwoofer
Frequency Range (± 3 dB)	120Hz – 20,000Hz	120Hz – 20,000Hz	Frequency Range (± 3 dB)	34Hz – 150Hz
Recommended Amplifier Power Range	10 – 100 watts	10 – 125 watts	Amplifier Output	150 watts RMS
Sensitivity (2.83V @ 1 meter)	88dB	89dB	Low-Frequency Driver	10" (250mm)
Nominal Impedance	8 ohms	8 ohms	Crossover Frequency	50Hz – 150Hz, 24dB/octave, continuously variable
Crossover Frequency	3500Hz, 24dB/octave	3500Hz, 24dB/octave	Dimensions (H x W x D)	16-3/4" x 10-3/4" x 15-3/4" (425mm x 273mm x 400mm)
Midrange Driver(s)	3-1/2" (87mm) MMD™, magnetically shielded	Dual 3-1/2" (87mm) MMD™, magnetically shielded	Weight	33 lb (15.0kg)
High-Frequency Driver	3/4" (19mm) MMD, magnetically shielded	3/4" (19mm) MMD, magnetically shielded		
Dimensions (H x W x D)	6" x 4-1/8" x 4-3/8" (152mm x 105mm x 111mm)	4-1/8" x 9-1/4" x 4-3/8" (105mm x 235mm x 111mm)		
Weight	2.8 lb (1.3kg)	4.5 lb (2.0kg)		



Satellite wall-mounting brackets included.

TSS-1100

	Satellites	Center Channel		Powered Subwoofer
Frequency Range (± 3 dB)	120Hz – 20,000Hz	120Hz – 20,000Hz	Frequency Range (± 3 dB)	29Hz – 150Hz
Recommended Amplifier Power Range	10 – 125 watts	10 – 125 watts	Amplifier Output	250 watts RMS
Sensitivity (2.83V @ 1 meter)	89dB	89dB	Low-Frequency Driver	12" (300mm) MMD™
Nominal Impedance	8 ohms	8 ohms	Crossover Frequency	50Hz – 150Hz, 24dB/octave, continuously variable
Crossover Frequency	3500Hz, 24dB/octave	3500Hz, 24dB/octave	Dimensions (H x W x D)	17-3/4" x 12" x 16-1/8" (451mm x 305mm x 410mm)
Midrange Driver(s)	Dual 3-1/2" (87mm) MMD™, magnetically shielded	Dual 3-1/2" (87mm) MMD™, magnetically shielded	Weight	44 lb (20kg)
High-Frequency Driver	3/4" (19mm) MMD, magnetically shielded	3/4" (19mm) MMD, magnetically shielded		
Dimensions (H x W x D)	9-1/4" x 4-1/8" x 4-3/8" (235mm x 105mm x 111mm)	4-1/8" x 9-1/4" x 4-3/8" (105mm x 235mm x 111mm)		
Weight	4.5 lb (2.0kg)	4.5 lb (2.0kg)		



Optional satellite stand available.

250 Crossways Park Drive, Woodbury, NY 11797 USA 516.674.4INF (4463) Fax 516.682.3523 www.infinitysystems.com
H A Harman International Company © 2003 Harman International Industries, Incorporated. Printed 12/03 Part No. TSSLIT12/03
 Designed, edited and digitally produced by Harman Consumer Group Marketing & Design Center, Woodbury, NY

Infinity
 TECHNOLOGY • PERFORMANCE • DESIGN

Infinity is a registered trademark, and Total Solutions, Prelude, Metal Matrix Diaphragm, MMD and CMMD are trademarks, of Harman International Industries, Incorporated. Ceramic Metal Matrix Diaphragm (CMMD) patent nos. 6,327,372 and 6,404,897. Kevlar is a registered trademark of E.I. du Pont de Nemours and Company. Infinity continually strives to update and improve existing products, as well as create new ones. The specifications and construction details herein are therefore subject to change without notice.