

## Tactical Radio Products

*RF-3045B* **REMOTE CONTROL** SYSTEM - AUDIO



The RF-3045B Remote Control System provides remote transmitter keying, audio modulation, and reception of received audio signals. Intercom (order wire) with ring-down signaling is also provided between the local and remote operators. The RF-3045B permits two-wire remote audio control of most HF and VHF tactical transceivers up to a distance of 5 km (3.1 miles).

Visual and audio signals alert the operators. When an operator is not immediately available, the call light remains on until the handset push-to-talk button is depressed.

A single BA-5590, BB-390, or BB-590 battery supplies power, while a built-in amplifier and speaker provide three watts of au-



## General

**Remote Audio Control Functions** Transmitter keying

Receiver audio

Intercom (order wire) Ring down signaling Call light/tone Volume control Speaker ON/OFF 3-Watt audio

2-wire circuit test

Low battery voltage level check

**Control Distance** Up to 5 km (3.1 miles)

Power Supply 12 VDC, from BA-5590, BB-390, BB-590 battery (not included)

Temperature Range -40° to +70° C
Shock/Vibration) MIL-STD-810B
Immersion 3 ft. of water
Humidity MIL-STD-810B

**Size** 3.25H x 8.625W x 10.2D in


8.125H x 21.56W x 25.7D cm

**Weight** Single unit with handset and w/o battery: 4.25 lb (1.9 kg)

**Consists of** RF-3045B Remote Control Unit includes battery box, handset, interconnecting cable to radio, carrying bag, instruction card, and

instruction manual

## **Typical RF-3045B Remote Extension Applications**



FALCON is a registered trademark of Harris Corporation. Specifications are subject to change without notice.

