


# Hitachi Multi-Standard Camera SK-3300 Series

HITACHI






## Features-1

- **Full HDTV & SDTV Performance Multi format (without replacement of Unit)**

1080i HDTV Camera	Standard 1080i and 480i
	Optional 1080i/720P and 480i
- **New 12 bit A/D DSP**
  - High performance
  - High picture quality
  - Low Power consumption
- **Independent Controls for HDTV & SDTV Functions**
  - Main signal processing DSP & SDTV signal process DSP, DTL & Masking




## Features-2


- **High quality Down/Up Converter**  
High speed signal processing prevents moiré & waveform distortion
- **Support Full Digital system**  
Monitoring output signal
- **Same HD and SD signal Phase output from CCU**  
Same phase for HD-SDI: 1080i/720p, D1, VBS  
Delay time is less than 600us
- **Built-in frame sync**  
Trouble free for return video switching
- **Freely selectable for any return video signal format**



## Features-3

- **Reliable & Serviceable CCU design**  
HD signal processing, SD signal processing  
and Power circuit are separated by built-in individual  
modules.





# Camera-man friendly Design


- **SK-3300P**

**Light & Compact Approx. 4.7kg including VF**

**Balance of Camera: Front/Back, right/left**

**4 input return signal selection available**

Function	SK-3000P	SK-3300P
Optical Filter	2 wheel/4	2 wheel/5
DSP	0.35u	0.18u L/ Power
A/D	10 bit	12 bit
HD-SDI OUT	Optional	Standard
Size	135x250x390	118x210x374
Width		Slim body
VF		Compact
Mass(kg)	6.3	4.7




# SK-3300P/SK-3300



SK-3300



SK-3100P/SK-3300P



# Compact CCU Design

- **Compact & Lightweight CU-3300**  
Full rack & 2 units ,Built-in Down/UP converter  
,Digital Encoder for NTSC signal  
Independent control both HDTV & SDTV for DTL/ Masking
- **Comparison of Current & New CCU**

Function	CU-3000	CU-3300
Height(rack unit)	3	2
Mass(kg)	25	15
Plug in unit	11	3
Power consumption	300VA	150VA
Format exchange	Unit replacement	Menu
NTSC Encoder	Analog	Digital



# Accessory



Studio adapter



Set Up Unit




Remote Unit




Portable LCD VF

# Composition

## SK-3300/SK-3300P System Configuration





# Worldwide Customer List

HDTV Camera	Qty	Broadcast Station
<b>SK-3000P</b>	<b>11</b>	TAO(1), NTV(2), CHUKYO TV(2), AOMORI TV(2), NHK(1), TV ASAHI(2), BS ASAHI(1)
<b>SK-3000</b>	<b>9</b>	NTV(4), CHUKYO(3), AOMORI TV(2)
<b>SK-3300P</b>	<b>29</b>	NTV(5), TAIWAN(8), SIZUOKA(4), EHIME(6), NTV(4), YAMAGATA TV(2),
<b>SK-3300</b>	<b>12</b>	TAIWAN TV(7), NTV(2), YAMANASHI(3),
<b>TTL 2/11/02</b>	<b>61</b>	

# HDTV Comparison

Comparison HDTV camera

	Ikegami		Sony		Hitachi	
	HDK-79E		HDC-950		SK-3300P	
CCD 1080i	2.2M pixel FIT -CCD	○	2.2M pixel FIT -CCD	○	2.2M pixel FIT -CCD	○
1080i	2.2M pixel IT -CCD	◎	—	△	2.2M pixel IT -CCD	◎
Sensitivity (2000 lx)	F8	○	F10	◎	F8	○
S/N(dB)	56	○	56	○	56	◎
Resolution(TV-L)	1000	○	1000	○	1000	○
Mod. Depth at 27MHz %	45	◎	40	○	45	○
Head Power(VA)	42 (at VTR rec.)	○	45	○	45(w/Optical cable operation	○
Size (W x H x D) mm	105 x 222 x 375	△	133 x 276 x 360	△	<b>115 x 209 x 348</b>	◎
Mass kg	6	△	5.1	△	<b>4.7</b>	◎
<b>Side Panel extension for Heat ventilation</b>	yes	△	yes	△	<b>NO</b>	◎
Optical Cable connector location	right	△	right	△	<b>Center 150 degree adjustable</b>	◎
CCU Height mm	133	△	133	△	<b>88</b>	◎
Mass kg	30	△	20	△	<b>15</b>	◎
Power VA	500	△	540	△	<b>150 + 50</b>	○