

# METAL CASED MONITORS

## CPX1402MS & CPX2102MS

### CPX-1402MS

#### Product Features

450 TVL Resolution  
PAL/NTSC Auto Sensing  
Y/C Input for S-VHS Playback  
Robust Metal Casing  
Video & Audio Inputs with Loophthrough  
Built In Speaker  
2 Year Warranty



#### Technical Specifications

<b>CRT Size</b>	14"
<b>Colour System</b>	PAL & NTSC (3.58/4.43) Auto Detect
<b>Resolution</b>	450 TV Lines
<b>Connectors</b>	BNC x 1 - Composite video in/out (1V p-p at 75 Ohm) Phono x 1 - mono audio in/out, Mini-Din 4 Pin S-Video in
<b>Controls</b>	Power On/Off, power on LED, Tint, Sharpness, Colour, Brightness, Contrast, Volume.
<b>Speaker</b>	1.0 +/-0.2W, 8 Ohm
<b>Power/Consumption</b>	110 - 240V AC (50/60Hz) / 68W
<b>Dimensions</b>	350mm x 332mm x 370mm (WxHxD)
<b>Weight</b>	14Kg

### CPX-2102MS

#### Product Features

450 TVL Resolution  
PAL/NTSC Auto Sensing  
Y/C Input for S-VHS Playback  
Robust Metal Casing  
2 x Video & Audio Inputs with Loophthrough  
Built In Speaker  
2 Year Warranty



#### Technical Specifications

<b>CRT Size</b>	21"
<b>Colour System</b>	PAL & NTSC (3.58/4.43) Auto Detect
<b>Resolution</b>	450 TV Lines
<b>Connectors</b>	BNC x 2 - Composite video in/out (1V p-p at 75 Ohm) Phono x 2 - mono audio in/out, Mini-Din 4 Pin S-Video in
<b>Controls</b>	Power On/Off, power on LED, Input Selection (Video 1, 2, S-video) Tint, Sharpness, Colour, Brightness, Contrast, Volume.
<b>Speaker</b>	1.0 +/-0.2W, 8 Ohm
<b>Power/Consumption</b>	110 - 240V AC (50/60Hz) / 67W
<b>Dimensions</b>	476mm x 432mm x 468mm (WxHxD)
<b>Weight</b>	26Kg